DesignLights Consortium

Model Number	ALI-BPL-2X2-15/20/30/40/50W-6CCT-S1
Classification	Premium
Primary Use	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	50 W
Reported Light Output	6250 lm
Reported CCT	3000 K
Reported CRI (Ra)	80
Product ID	S-SXSVXR
DLC Family Code	SLFHFS
Listing Status	Listed
Date Qualified	2025-01-07

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-SXSVXR
Manufacturer	American lighting industry corp
Brand	Astrelights Inc
Model Number	ALI-BPL-2X2-15/20/30/40/50W-6CCT-S1
Parent	Yes
Classification	Premium
DLC Family Code	SLFHFS
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	Sensor Receptacle
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	6250 lm
Reported Efficacy (AC)	125 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	17
Reported IES Rf	81
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Minimum Light Output	1875 lm
Reported Maximum Light Output	6250 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	6500 K
Reported Default Light Output	6250 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	50 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	15 W
Reported Maximum Input Wattage	50
Reported Default Input Wattage	50 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120

Tested Light Output	6286 lm
Tested Efficacy (AC)	132.1 lm/W
Tested CCT	3046 K
Tested CRI (Ra)	81
Tested R9	20
Tested IES Rf	81
Tested IES Rg	99
Tested IES Rcs,h1	-10 %
Tested Duv	0.0022

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	47.59 W
Tested Total Harmonic Distortion	11.6 %
Tested Power Factor	0.959

VERSION HISTORY VIEW DETAILS

2025-01-07	Listed	5.1	Premium