# DesignLights Consortium

| | |
|---|---|
| Model Number | ALI-BPL-2X4-20/30/40/50/75W-6CCT-S1 |
| Classification | Premium |
| Primary Use | 2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces |
| Reported Input Wattage | 75 W |
| Reported Light Output | 9375 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 80 |
| Product ID | S-SN9PRY |
| DLC Family Code | SLFHFS |
| Listing Status | Listed |
| Date Qualified | 2025-01-07 |

## PRODUCT INFORMATION VIEW DETAILS

| | |
|---|---|
| Qualified Product List | Solid State Lighting |
| Technical Requirements Version | 5.1 |
| Product ID | S-SN9PRY |
| Manufacturer | American lighting industry corp |
| Brand | Astrelights Inc |
| Model Number | ALI-BPL-2X4-20/30/40/50/75W-6CCT-S1 |
| Parent | Yes |
| Classification | Premium |
| DLC Family Code | SLFHFS |
| Input Power Type | AC |

## PRODUCT CATEGORIZATION VIEW DETAILS

| | |
|---|---|
| Category | Indoor Luminaires |
| General Application | Troffer |
| Primary Use Designation | 2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces |

## CONTROL FEATURES VIEW DETAILS

| | |
|---|---|
| Integral Controls | Yes |
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No |
| Sensor Type | Sensor Receptacle |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No |
| Field Adjustable Light Output | Yes |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|---|---|
| Reported Light Output | 9375 lm |
| Reported Efficacy (AC) | 125 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 80 |
| Reported R9 | 17 |
| Reported IES Rf | 81 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -13 |
| Reported Minimum Light Output | 2500 lm |
| Reported Maximum Light Output | 9375 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 6500 K |
| Reported Default Light Output | 9375 lm |

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|---|---|
| Reported Input Wattage | 75 W |
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 20 W |
| Reported Maximum Input Wattage | 75 |
| Reported Default Input Wattage | 75 W |
| Voltage Range | 120-277 V |

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|---|---|
| Tested Voltage for Minimum Efficacy | 120 |

| | |
|---|---|
| Tested Light Output | 9422 lm |
| Tested Efficacy (AC) | 133.1 lm/W |
| Tested CCT | 3029 K |
| Tested CRI (Ra) | 80 |
| Tested R9 | 17 |
| Tested IES Rf | 81 |
| Tested IES Rg | 99 |
| Tested IES Rcs,h1 | -10 % |
| Tested Duv | 0.0026 |

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|---|---|
| Tested Input Wattage | 70.79 W |
| Tested Total Harmonic Distortion | 8.9 % |
| Tested Power Factor | 0.98 |

## VERSION HISTORY VIEW DETAILS

| | | | |
|---|---|---|---|
| 2025-01-07 | Listed | 5.1 | Premium |