

API Specification

Endpoints

Rooms

Retrieves a list of all rooms.

Method	GET
Path	/rooms
Query Parameters	pageIndex

Example Response:

```
{
  "rooms": [
    {
      "id": 1,
      "title": "Technikum Standard Room",
      "description": "A cozy room for business travelers.",
      "capacity": 2,
      "pricePerNight": 89.00,
      "image": "images/rooms/1.jpg",
      "extras": [
        {
          "id": "1",
          "name": "Highspeed WiFi",
          "icon": "bi-wifi"
        },
        {
          "id": "2",
          "name": "Workspace",
          "icon": "bi-laptop"
        }
      ]
    },
    {
      "id": 2,
      "title": "Boutique Deluxe Suite",
      "description": "Premium comfort with a view of the city.",
      "capacity": 3,
      "pricePerNight": 139.00,
    }
  ]
}
```

```
{
  "image": "images/rooms/2.jpg",
  "extras": [
    {
      "id": "1",
      "name": "Highspeed WiFi",
      "icon": "bi-wifi"
    },
    {
      "id": "3",
      "name": "King Size Bed",
      "icon": "bi-bed"
    },
    {
      "id": "4",
      "name": "Mini-Bar",
      "icon": "bi-cup-straw"
    }
  ]
}
```

Rooms/{id}

Retrieves a single room.

Method	GET
Path	/rooms/{id}

Example Response:

```
{
  "id": 1,
  "title": "Technikum Standard Room",
  "description": "A cozy room for business travelers.",
  "capacity": 2,
  "pricePerNight": 89.00,
  "image": "images/rooms/1.jpg",
  "extras": [
    {
      "id": "1",
      "name": "Highspeed WiFi",
      "icon": "bi-wifi"
    },
  ],
}
```

```
{
  "id": "2",
  "name": "Workspace",
  "icon": "bi-laptop"
}
```

Availability

Checks if a specific room is available for a selected period.

Method	GET
Path	/rooms/{id}/availability
Query Parameters	startDate, endDate (yyyy-MM-dd)

Example Response:

```
{
  "id": 1,
  "available": true
}
```

Bookings

Processes a room booking request.

Method	POST
Path	/bookings

Example Request:

```
{
  "roomId": 1,
  "startDate": "2026-06-15",
  "endDate": "2026-06-20",
  "firstName": "Max",
  "lastName": "Mustermann",
  "email": "max.mustermann@example.at",
  "breakfast": true,
}
```

```
    "guestCount": 2
}
```

Example Response:

```
{
  "bookingId": "202601",
  "confirmationDate": "2026-05-04T20:15:00Z",
  "personalData": {
    "firstName": "Max",
    "lastName": "Mustermann",
    "email": "max.m@example.at"
  },
  "bookingDetails": {
    "period": {
      "start": "2026-06-15",
      "end": "2026-06-20"
    },
    "guestCount": 2,
    "breakfastIncluded": true,
    "totalPrice": 445.00
  },
  "room": {
    "id": 1,
    "name": "Technikum Standard Room",
    "image": "images/rooms/1.jpg",
    "description": "A cozy room for business travelers.",
    "extras": [
      {"id": 1, "name": "Highspeed WiFi", "icon": "bi-wifi"},
      {"id": 5, "name": "Workspace", "icon": "bi-laptop"}
    ]
  },
  "arrivalInfo": {
    "directions": "Take the U6 to Technikum Wien. The hotel is a  
5-minute walk from the station.",
    "trainConnections": "S-Bahn S1, S2, S3, S7, S45",
    "contact": "Phone: +43 13334077 | Email: welcome@hotel-technikum.at"
  }
}
```

HTTP Codes

The API uses standard HTTP status codes:

- 200 OK: Success response
- 400 Bad Request: Validation errors (e.g. mismatched emails)
- 404 Not Found: Room not found
- 409 Conflict: Room is no longer available
- 500 Internal Server Error: Backend processing issues

With this specification, we reach Level 2 in maturity (per the Richardson Maturity Model).