

TOULBAR2 User documentation

The TOULBAR2 developer team

May 11, 2018

1 What is toulbar2

TOULBAR2 is an exact black box discrete optimization solver targeted at solving cost function networks (CFN), thus solving the so-called “weighted Constraint Satisfaction Problem” or WCSP. Cost function networks can be simply described by a set of discrete variables each having a specific finite domain and a set of integer cost functions, each involving some of the variables. The WCSP is to find an assignment of all variables such that the sum of all cost functions is minimum and less than a given upper bound often denoted as k or \top . Functions can be typically specified by sparse or full tables but also more concisely as specific functions called “global cost functions” [3].

Using on the fly translation, TOULBAR2 can also directly solve optimization problems on other graphical models such as Maximum probability Explanation (MPE) on Bayesian networks [16], and Maximum A Posteriori (MAP) on Markov random field [16]. It can also read partial weighted MaxSAT problems, Quadratic Pseudo Boolean problems (MAXCUT) as well as Linkage `.pre` pedigree files for genotyping error detection and correction.

TOULBAR2 is exact. It will only report an optimal solution when it has both identified the solution and proved its optimality. Because it relies only on integer operations, addition and subtraction, it does not suffer from rounding errors. In the general case, the WCSP, MPE/BN, MAP/MRF, PWMaxSAT, QPBO or MAXCUT being all NP-hard problems and thus TOULBAR2 may take exponential time to prove optimality. This is however a worst-case behavior and TOULBAR2 has been shown to be able to solve to optimality problems with half a million non Boolean variables defining a search space as large as $2^{829,440}$. It may also fail to solve in reasonable time problems with a search space smaller than 2^{264} .

TOULBAR2 provides and uses by default an “anytime” algorithm [2] that tries to quickly provide good solutions together with an upper bound on the gap between the cost of each solution and the (unknown) optimal cost. Thus, even if it is unable to prove optimality, it will bound the quality of the solution provided. It can also apply a variable neighborhood search algorithm exploiting a problem decomposition [25]. This algorithm is complete (if enough CPU-time is given) and it can be run in parallel using OpenMPI.

Beyond the service of providing optimal solutions, TOULBAR2 can also exhaustively enumerate solutions below a cost threshold and perform guaranteed approximate weighted counting of solutions. For stochastic graphical models, this means that TOULBAR2 will compute the partition function (or the normalizing constant Z). These problems being $\#P$ -complete, TOULBAR2 runtimes can quickly increase on such problems.

2 How do I install it ?

TOULBAR2 is an open source solver distributed under the MIT license as a set of C++ sources managed with git at <http://github.com/toulbar2/toulbar2>. If you want to use a released version, then you can download there source archives of a specific release that should be easy to compile on most Linux systems.

If you want to compile the latest sources yourself, you will need a modern C++ compiler, CMake, Gnu MP Bignum library, a recent version of boost libraries and optionally the jemalloc memory management and OpenMPI libraries. You can then clone TOULBAR2 on your machine and compile it by executing:

```
git clone https://github.com/toulbar2/toulbar2.git
cd toulbar2
mkdir build
cd build
# cmake ..
cmake ..
make
```

Finally, TOULBAR2 is available in the debian-science section of the unstable/sid Debian version. It should therefore be directly installable using:

```
sudo apt-get install toulbar2
```

If you want to try TOULBAR2 on crafted, random, or real problems, please look for benchmarks in the Cost Function benchmark Section. Other benchmarks coming from various discrete optimization languages are available at Genotoul EvalGM [15].

3 Using it as a black box

Using TOULBAR2 is just a matter of having a properly formatted input file describing the cost function network, graphical model, PWMaxSAT, PBO or Linkage `.pre` file and executing:

```
toulbar2 [option parameters] <file>
```

and TOULBAR2 will start solving the optimization problem described in its file argument. By default, the extension of the file (either `.wcsp`, `.wcnf`, `.cnf`, `.qpbo`, `.uai`, `.LG`, `.pre` or `.bep`) is used to determine the nature of the file (see section 6). There is no specific order for the options or problem file. TOULBAR2 comes with decently optimized default option parameters. It is however often possible to set it up for different target than pure optimization or tune it for faster action using specific command line options.

4 Quick start

1. Download a binary weighted constraint satisfaction problem (WCSP) file *example.wcsp* from the toulbar2's Documentation Web page. Solve it with default options:

```
toulbar2 EXAMPLES/example.wcsp

Read 25 variables, with 5 values at most, and 63 cost functions, with maximum arity 2.
Cost function decomposition time : 7e-06 seconds.
Reverse DAC lower bound: 20 (+10%)
Reverse DAC lower bound: 22 (+9.09091%)
Preprocessing time: 0.000934 seconds.
24 unassigned variables, 117 values in all current domains (med. size:5, max size:5) and 62 non-unary cost functions (med. degree:5)
Initial lower and upper bounds: [22,64[ 65.625%
New solution: 29 (0 backtracks, 8 nodes, depth 9)
Optimality gap: [ 23 , 29 ] 20.6897 % (8 backtracks, 16 nodes)
New solution: 27 (8 backtracks, 24 nodes, depth 8)
Optimality gap: [ 24 , 27 ] 11.1111 % (14 backtracks, 30 nodes)
Optimality gap: [ 25 , 27 ] 7.40741 % (44 backtracks, 113 nodes)
Optimality gap: [ 26 , 27 ] 3.7037 % (54 backtracks, 151 nodes)
Optimality gap: [ 27 , 27 ] 0 % (54 backtracks, 157 nodes)
Node redundancy during HBFS: 30.5732 %
Optimum: 27 in 54 backtracks and 157 nodes ( 205 removals by DEE) and 0.004154 seconds.
end.
```

2. Solve a WCSP using INCOP, a local search method [24] applied just after preprocessing, in order to find a good upper bound before a complete search:

```
toulbar2 EXAMPLES/example.wcsp -i

Read 25 variables, with 5 values at most, and 63 cost functions, with maximum arity 2.
Cost function decomposition time : 7e-06 seconds.
Reverse DAC lower bound: 20 (+10%)
Reverse DAC lower bound: 22 (+9.09091%)
Preprocessing time: 0.000898 seconds.
New solution: 27 (0 backtracks, 0 nodes, depth 1)
INCOP solving time: 0.200984 seconds.
24 unassigned variables, 117 values in all current domains (med. size:5, max size:5) and 62 non-unary cost functions (med. degree:5)
Initial lower and upper bounds: [22,27[ 18.5185%
Optimality gap: [ 23 , 27 ] 14.8148 % (34 backtracks, 87 nodes)
Optimality gap: [ 24 , 27 ] 11.1111 % (49 backtracks, 122 nodes)
Optimality gap: [ 25 , 27 ] 7.40741 % (77 backtracks, 198 nodes)
Optimality gap: [ 27 , 27 ] 0 % (84 backtracks, 226 nodes)
Node redundancy during HBFS: 25.6637 %
Optimum: 27 in 84 backtracks and 226 nodes ( 226 removals by DEE) and 0.206461 seconds.
end.
```

3. Solve a WCSP with an initial upper bound and save its (first) optimal solution in filename "example.sol":

```
toulbar2 EXAMPLES/example.wcsp -ub=28 -w=example.sol
```

```

Read 25 variables, with 5 values at most, and 63 cost functions, with maximum arity 2.
Cost function decomposition time : 7e-06 seconds.
Reverse DAC lower bound: 20 (+10%)
Reverse DAC lower bound: 22 (+9.09091%)
Preprocessing time: 0.000922 seconds.
24 unassigned variables, 117 values in all current domains (med. size:5, max size:5) and 62 non-unary cost functions (med. degree:5)
Initial lower and upper bounds: [22,28[ 21.4286%
Optimality gap: [ 23 , 28 ] 17.8571 % (7 backtracks, 14 nodes)
New solution: 27 (7 backtracks, 20 nodes, depth 6)
Optimality gap: [ 23 , 27 ] 14.8148 % (12 backtracks, 25 nodes)
Optimality gap: [ 24 , 27 ] 11.1111 % (26 backtracks, 67 nodes)
Optimality gap: [ 25 , 27 ] 7.40741 % (58 backtracks, 163 nodes)
Optimality gap: [ 27 , 27 ] 0 % (70 backtracks, 217 nodes)
Node redundancy during HBFS: 35.4839 %
Optimum: 27 in 70 backtracks and 217 nodes ( 158 removals by DEE) and 0.005575 seconds.
end.

cat example.sol
# each value corresponds to one variable assignment in problem file order

1 0 1 2 3 4 0 4 2 0 3 1 0 2 3 0 1 3 2 4 2 1 0 4 4

```

4. Download a larger WCSP file *scen06.wcsp* from the toulbar2's Documentation Web page. Solve it using a limited discrepancy search strategy [14] in order to speed-up the search for finding good upper bounds first¹:

```

toulbar2 EXAMPLES/scen06.wcsp -l

Read 100 variables, with 44 values at most, and 1222 cost functions, with maximum arity 2.
Cost function decomposition time : 4.7e-05 seconds.
Preprocessing time: 0.156179 seconds.
82 unassigned variables, 3273 values in all current domains (med. size:44, max size:44) and 327 non-unary cost functions (med. degree:6)
Initial lower and upper bounds: [0,248338[ 100%
--- [0] LDS 0 --- (0 nodes)
c 2097152 Bytes allocated for long long stack.
c 4194304 Bytes allocated for long long stack.
c 8388608 Bytes allocated for long long stack.
New solution: 8451 (0 backtracks, 110 nodes, depth 1)
--- [0] LDS 1 --- (110 nodes)
New solution: 6134 (2 backtracks, 386 nodes, depth 2)
New solution: 5795 (4 backtracks, 527 nodes, depth 2)
New solution: 5711 (5 backtracks, 590 nodes, depth 2)
New solution: 5444 (6 backtracks, 676 nodes, depth 2)
New solution: 4828 (7 backtracks, 747 nodes, depth 2)
New solution: 4507 (9 backtracks, 853 nodes, depth 2)
New solution: 4408 (10 backtracks, 910 nodes, depth 2)
New solution: 4145 (15 backtracks, 1047 nodes, depth 2)
New solution: 3730 (18 backtracks, 1112 nodes, depth 2)
--- [0] LDS 2 --- (1132 nodes)
New solution: 3635 (64 backtracks, 1606 nodes, depth 3)
New solution: 3585 (150 backtracks, 2169 nodes, depth 3)
New solution: 3493 (168 backtracks, 2283 nodes, depth 3)
New solution: 3472 (171 backtracks, 2312 nodes, depth 3)
--- [0] LDS 4 --- (2420 nodes)
New solution: 3463 (988 backtracks, 5683 nodes, depth 5)
New solution: 3441 (990 backtracks, 5711 nodes, depth 5)
New solution: 3401 (1101 backtracks, 6178 nodes, depth 5)
--- [0] Search with no discrepancy limit --- (8111 nodes)
Optimality gap: [ 349 , 3401 ] 89.7383 % (44869 backtracks, 94455 nodes)
New solution: 3400 (56746 backtracks, 118233 nodes, depth 24)
New solution: 3399 (56747 backtracks, 118235 nodes, depth 23)
New solution: 3389 (56749 backtracks, 118248 nodes, depth 29)
Optimality gap: [ 1023 , 3389 ] 69.8141 % (90007 backtracks, 184743 nodes)
Optimality gap: [ 1306 , 3389 ] 61.4636 % (91295 backtracks, 187319 nodes)
Optimality gap: [ 1818 , 3389 ] 46.3559 % (93973 backtracks, 192675 nodes)
Optimality gap: [ 2261 , 3389 ] 33.2842 % (94054 backtracks, 192837 nodes)
Optimality gap: [ 2777 , 3389 ] 18.0584 % (94060 backtracks, 192849 nodes)
Optimum: 3389 in 94062 backtracks and 192853 nodes ( 375927 removals by DEE) and 52.2443 seconds.
end.

```

5. Download a cluster decomposition file *scen06.dec* (each line corresponds to a cluster of variables, clusters may overlap). Solve the previous WCSP using a variable neighborhood search algorithm (UDGVNS) [25] during 5 seconds:

¹By default, toulbar2 uses another diversification strategy based on hybrid best-first search [2].

```
toulbar2 EXAMPLES/scen06.wcsp EXAMPLES/scen06.dec -vns -time=5
```

```
Read 100 variables, with 44 values at most, and 1222 cost functions, with maximum arity 2.
Cost function decomposition time : 4.8e-05 seconds.
Preprocessing time: 0.15041 seconds.
82 unassigned variables, 3273 values in all current domains (med. size:44, max size:44) and 327 non-unary cost functions (med. degree:6)
Initial lower and upper bounds: [0,248338[ 100%
c 2097152 Bytes allocated for long long stack.
c 4194304 Bytes allocated for long long stack.
c 8388608 Bytes allocated for long long stack.
New solution: 8451 (0 backtracks, 110 nodes, depth 111)
Problem decomposition in 55 clusters with size distribution: min: 1 median: 5 mean: 4.78182 max: 12
***** Restart 1 with 1 discrepancies and UB=8451 ***** (110 nodes)
New solution: 8440 (0 backtracks, 110 nodes, depth 1)
New solution: 7474 (0 backtracks, 112 nodes, depth 2)
New solution: 6481 (0 backtracks, 117 nodes, depth 2)
New solution: 6358 (0 backtracks, 117 nodes, depth 1)
New solution: 6252 (0 backtracks, 120 nodes, depth 2)
New solution: 6250 (0 backtracks, 120 nodes, depth 1)
New solution: 6248 (0 backtracks, 120 nodes, depth 1)
New solution: 6223 (0 backtracks, 120 nodes, depth 1)
New solution: 6131 (0 backtracks, 123 nodes, depth 2)
New solution: 6121 (0 backtracks, 123 nodes, depth 1)
New solution: 6022 (0 backtracks, 123 nodes, depth 1)
New solution: 5098 (2 backtracks, 141 nodes, depth 2)
New solution: 5096 (2 backtracks, 141 nodes, depth 1)
New solution: 5095 (2 backtracks, 141 nodes, depth 1)
New solution: 5094 (2 backtracks, 141 nodes, depth 1)
New solution: 4887 (5 backtracks, 205 nodes, depth 2)
New solution: 4630 (10 backtracks, 232 nodes, depth 2)
New solution: 4629 (10 backtracks, 234 nodes, depth 2)
New solution: 4557 (30 backtracks, 366 nodes, depth 2)
New solution: 4556 (35 backtracks, 383 nodes, depth 1)
New solution: 4544 (37 backtracks, 395 nodes, depth 2)
New solution: 4388 (48 backtracks, 549 nodes, depth 2)
New solution: 4220 (68 backtracks, 706 nodes, depth 2)
New solution: 4218 (68 backtracks, 706 nodes, depth 1)
New solution: 4216 (68 backtracks, 706 nodes, depth 1)
New solution: 4208 (70 backtracks, 713 nodes, depth 1)
New solution: 4133 (71 backtracks, 715 nodes, depth 1)
New solution: 4127 (72 backtracks, 724 nodes, depth 2)
New solution: 4125 (75 backtracks, 733 nodes, depth 1)
New solution: 3709 (97 backtracks, 898 nodes, depth 2)
New solution: 3703 (240 backtracks, 2276 nodes, depth 2)
New solution: 3700 (240 backtracks, 2276 nodes, depth 1)
New solution: 3598 (278 backtracks, 2540 nodes, depth 2)
New solution: 3588 (279 backtracks, 2543 nodes, depth 1)
New solution: 3562 (280 backtracks, 2546 nodes, depth 2)
New solution: 3542 (280 backtracks, 2549 nodes, depth 2)
New solution: 3523 (283 backtracks, 2564 nodes, depth 2)
New solution: 3473 (384 backtracks, 3243 nodes, depth 2)
New solution: 3472 (386 backtracks, 3251 nodes, depth 2)
New solution: 3471 (388 backtracks, 3256 nodes, depth 1)
New solution: 3470 (388 backtracks, 3256 nodes, depth 1)
New solution: 3469 (391 backtracks, 3264 nodes, depth 1)
New solution: 3447 (409 backtracks, 3344 nodes, depth 2)
New solution: 3437 (414 backtracks, 3377 nodes, depth 2)
New solution: 3430 (439 backtracks, 3517 nodes, depth 2)
New solution: 3420 (439 backtracks, 3517 nodes, depth 1)
New solution: 3412 (468 backtracks, 3664 nodes, depth 2)
New solution: 3389 (517 backtracks, 4099 nodes, depth 2)
***** Restart 2 with 2 discrepancies and UB=3389 ***** (5528 nodes)

Time limit expired... Aborting...
```

6. Download another difficult instance *scen07.wcsp*. Solve it using a variable neighborhood search algorithm (UDGVNS) with maximum cardinality search cluster decomposition and absorption [25] during 5 seconds:

```
toulbar2 EXAMPLES/scen07.wcsp -vns -D=1 -E -time=5
```

```
Read 200 variables, with 44 values at most, and 2665 cost functions, with maximum arity 2.
Cost function decomposition time : 0.00014 seconds.
Reverse DAC lower bound: 10001 (+0.009999%)
Preprocessing time: 0.358369 seconds.
162 unassigned variables, 6481 values in all current domains (med. size:44, max size:44) and 764 non-unary cost functions (med. degree:8)
Initial lower and upper bounds: [10001,436523359[ 99.9977%
c 2097152 Bytes allocated for long long stack.
c 4194304 Bytes allocated for long long stack.
c 8388608 Bytes allocated for long long stack.
New solution: 1504818 (0 backtracks, 232 nodes, depth 233)
Tree decomposition time: 0.002884 seconds.
Problem decomposition in 25 clusters with size distribution: min: 3 median: 10 mean: 10.36 max: 38
```

```

***** Restart 1 with 1 discrepancies and UB=1504818 ***** (232 nodes)
New solution: 1485420 (0 backtracks, 232 nodes, depth 1)
New solution: 1485419 (0 backtracks, 232 nodes, depth 1)
New solution: 1485417 (0 backtracks, 232 nodes, depth 1)
New solution: 1485217 (0 backtracks, 232 nodes, depth 1)
New solution: 1445515 (0 backtracks, 232 nodes, depth 1)
New solution: 1445514 (0 backtracks, 232 nodes, depth 1)
New solution: 1425615 (0 backtracks, 233 nodes, depth 2)
New solution: 1425514 (0 backtracks, 233 nodes, depth 1)
New solution: 1425411 (0 backtracks, 233 nodes, depth 1)
New solution: 1415410 (0 backtracks, 233 nodes, depth 1)
New solution: 1415409 (0 backtracks, 233 nodes, depth 1)
New solution: 1405209 (0 backtracks, 233 nodes, depth 1)
New solution: 405311 (0 backtracks, 235 nodes, depth 2)
New solution: 405209 (0 backtracks, 235 nodes, depth 1)
New solution: 405207 (0 backtracks, 235 nodes, depth 1)
New solution: 395207 (1 backtracks, 241 nodes, depth 2)
New solution: 385207 (2 backtracks, 247 nodes, depth 2)
New solution: 384907 (2 backtracks, 247 nodes, depth 1)
New solution: 384506 (3 backtracks, 254 nodes, depth 2)
New solution: 374405 (3 backtracks, 256 nodes, depth 2)
New solution: 374404 (4 backtracks, 259 nodes, depth 1)
New solution: 374303 (6 backtracks, 266 nodes, depth 1)
New solution: 374104 (14 backtracks, 309 nodes, depth 2)
New solution: 354104 (16 backtracks, 318 nodes, depth 1)
New solution: 354103 (18 backtracks, 325 nodes, depth 1)
New solution: 353906 (26 backtracks, 370 nodes, depth 2)
New solution: 343903 (26 backtracks, 370 nodes, depth 1)
New solution: 343902 (41 backtracks, 431 nodes, depth 2)
New solution: 343803 (68 backtracks, 564 nodes, depth 1)
New solution: 343801 (85 backtracks, 675 nodes, depth 1)
New solution: 343800 (106 backtracks, 801 nodes, depth 2)
New solution: 343796 (106 backtracks, 801 nodes, depth 1)
New solution: 343595 (110 backtracks, 813 nodes, depth 1)
New solution: 343593 (126 backtracks, 867 nodes, depth 1)
New solution: 343592 (151 backtracks, 971 nodes, depth 2)
***** Restart 2 with 2 discrepancies and UB=343592 ***** (2649 nodes)

Time limit expired... Aborting...

```

- Download file *404.wcsp*. Solve it using Depth-First Branch and Bound with Tree Decomposition and HBFS (BTD-HBFS) [10] based on a min-fill variable ordering:

```

toulbar2 EXAMPLES/404.wcsp -0=-3 -B=1

Read 100 variables, with 4 values at most, and 710 cost functions, with maximum arity 3.
Cost function decomposition time : 5.3e-05 seconds.
Reverse DAC lower bound: 64 (+26.5625%)
Reverse DAC lower bound: 67 (+4.47761%)
Preprocessing time: 0.006246 seconds.
88 unassigned variables, 226 values in all current domains (med. size:2, max size:4) and 591 non-unary cost functions (med. degree:13)
Initial lower and upper bounds: [67,153] 56.2092%
Tree decomposition width : 19
Tree decomposition height : 43
Number of clusters : 47
Tree decomposition time: 0.002262 seconds.
New solution: 123 (24 backtracks, 44 nodes, depth 2)
Optimality gap: [ 68 , 123 ] 44.7154 % (24 backtracks, 44 nodes)
New solution: 122 (38 backtracks, 73 nodes, depth 2)
Optimality gap: [ 75 , 122 ] 38.5246 % (38 backtracks, 73 nodes)
New solution: 117 (170 backtracks, 341 nodes, depth 2)
Optimality gap: [ 89 , 117 ] 23.9316 % (170 backtracks, 341 nodes)
Optimality gap: [ 91 , 117 ] 22.2222 % (236 backtracks, 518 nodes)
Optimality gap: [ 93 , 117 ] 20.5128 % (302 backtracks, 703 nodes)
New solution: 116 (324 backtracks, 800 nodes, depth 2)
Optimality gap: [ 97 , 116 ] 16.3793 % (324 backtracks, 800 nodes)
New solution: 115 (386 backtracks, 973 nodes, depth 2)
Optimality gap: [ 99 , 115 ] 13.913 % (386 backtracks, 973 nodes)
New solution: 114 (408 backtracks, 1027 nodes, depth 2)
Optimality gap: [ 99 , 114 ] 13.1579 % (408 backtracks, 1027 nodes)
Optimality gap: [ 100 , 114 ] 12.2807 % (436 backtracks, 1117 nodes)
Optimality gap: [ 101 , 114 ] 11.4035 % (437 backtracks, 1137 nodes)
Optimality gap: [ 102 , 114 ] 10.5263 % (444 backtracks, 1205 nodes)
Optimality gap: [ 103 , 114 ] 9.64912 % (463 backtracks, 1256 nodes)
Optimality gap: [ 104 , 114 ] 8.77193 % (464 backtracks, 1262 nodes)
Optimality gap: [ 105 , 114 ] 7.89474 % (510 backtracks, 1384 nodes)
Optimality gap: [ 106 , 114 ] 7.01754 % (510 backtracks, 1449 nodes)
Optimality gap: [ 107 , 114 ] 6.14035 % (513 backtracks, 1476 nodes)
Optimality gap: [ 108 , 114 ] 5.26316 % (523 backtracks, 1510 nodes)
Optimality gap: [ 109 , 114 ] 4.38596 % (523 backtracks, 1516 nodes)
Optimality gap: [ 110 , 114 ] 3.50877 % (523 backtracks, 1532 nodes)
Optimality gap: [ 112 , 114 ] 1.75439 % (534 backtracks, 1568 nodes)
Optimality gap: [ 113 , 114 ] 0.877193 % (535 backtracks, 1603 nodes)

```

```

Optimality gap: [ 114 , 114 ] 0 % (535 backtracks, 1620 nodes)
HBFS open list restarts: 0 % and reuse: 12.7371 % of 369
Node redundancy during HBFS: 35.679 %
Optimum: 114 in 535 backtracks and 1620 nodes ( 46 removals by DEE) and 0.028496 seconds.
end.

```

8. Solve the same problem using Russian Doll Search exploiting BTD [26]:

```

toulbar2 EXAMPLES/404.wcsp -0=-3 -B=2

Read 100 variables, with 4 values at most, and 710 cost functions, with maximum arity 3.
Cost function decomposition time : 4.2e-05 seconds.
Reverse DAC lower bound: 64 (+26.5625%)
Reverse DAC lower bound: 67 (+4.47761%)
Preprocessing time: 0.006214 seconds.
88 unassigned variables, 226 values in all current domains (med. size:2, max size:4) and 591 non-unary cost functions (med. degree:13)
Initial lower and upper bounds: [67,153] 56.2092%
Tree decomposition width : 19
Tree decomposition height : 43
Number of clusters : 47
Tree decomposition time: 0.002272 seconds.
--- Solving cluster subtree 5 ...
New solution: 0 (0 backtracks, 0 nodes, depth 1)
--- done cost = [0,0] (0 backtracks, 0 nodes, depth 1)

--- Solving cluster subtree 6 ...
New solution: 0 (0 backtracks, 0 nodes, depth 1)
--- done cost = [0,0] (0 backtracks, 0 nodes, depth 1)

--- Solving cluster subtree 7 ...

...

--- Solving cluster subtree 44 ...
New solution: 40 (326 backtracks, 563 nodes, depth 7)
New solution: 39 (334 backtracks, 574 nodes, depth 7)
New solution: 35 (344 backtracks, 605 nodes, depth 21)
--- done cost = [35,35] (434 backtracks, 748 nodes, depth 1)

--- Solving cluster subtree 46 ...
New solution: 114 (434 backtracks, 748 nodes, depth 1)
--- done cost = [114,114] (434 backtracks, 748 nodes, depth 1)

Optimum: 114 in 434 backtracks and 748 nodes ( 45 removals by DEE) and 0.02135 seconds.
end.

```

9. Solve another WCSP using the original Russian Doll Search method [28] with static variable ordering (following problem file) and soft arc consistency:

```

toulbar2 EXAMPLES/505.wcsp -B=3 -j=1 -svo -k=1

Read 240 variables, with 4 values at most, and 2242 cost functions, with maximum arity 3.
Cost function decomposition time : 0.000659 seconds.
Preprocessing time: 0.013853 seconds.
233 unassigned variables, 666 values in all current domains (med. size:2, max size:4) and 1966 non-unary cost functions (med. degree:16)
Initial lower and upper bounds: [2,34347] 99.9942%
Tree decomposition width : 89
Tree decomposition height : 233
Number of clusters : 239
Tree decomposition time: 0.014871 seconds.
--- Solving cluster subtree 0 ...
New solution: 0 (0 backtracks, 0 nodes, depth 1)
--- done cost = [0,0] (0 backtracks, 0 nodes, depth 1)

--- Solving cluster subtree 1 ...
New solution: 0 (0 backtracks, 0 nodes, depth 1)
--- done cost = [0,0] (0 backtracks, 0 nodes, depth 1)

--- Solving cluster subtree 2 ...

...

--- Solving cluster subtree 3 ...
New solution: 21253 (26963 backtracks, 48851 nodes, depth 2)
New solution: 21251 (26991 backtracks, 48883 nodes, depth 3)
--- done cost = [21251,21251] (26992 backtracks, 48883 nodes, depth 1)

--- Solving cluster subtree 238 ...
New solution: 21253 (26992 backtracks, 48883 nodes, depth 1)

```

```

--- done cost = [21253,21253] (26992 backtracks, 48883 nodes, depth 1)

Optimum: 21253 in 26992 backtracks and 48883 nodes ( 0 removals by DEE) and 5.59561 seconds.
end.

```

10. Solve the same WCSP using a parallel variable neighborhood search algorithm (UPDGVNS) with min-fill cluster decomposition [25] using 4 cores during 5 seconds:

```

mpirun -n 4 toulbar2 EXAMPLES/505.wcsp -vns -O=-3 -time=5

Read 240 variables, with 4 values at most, and 2242 cost functions, with maximum arity 3.
Cost function decomposition time : 0.001757 seconds.
Reverse DAC lower bound: 11113 (+27.3553%)
Reverse DAC lower bound: 11120 (+0.0629496%)
Preprocessing time: 0.070685 seconds.
233 unassigned variables, 666 values in all current domains (med. size:2, max size:4) and 1970 non-unary cost functions (med. degree:16)
Initial lower and upper bounds: [11120,34354[ 67.6311%
Tree decomposition time: 0.01732 seconds.
Problem decomposition in 89 clusters with size distribution: min: 4 median: 11 mean: 11.8315 max: 23
New solution: 26264 (0 backtracks, 56 nodes, depth 57)
New solution: 26263 in 0.0327849 seconds.
New solution: 26262 in 0.036654 seconds.
New solution: 26261 in 0.0400689 seconds.
New solution: 25263 in 0.0407119 seconds.
New solution: 25262 in 0.050138 seconds.
New solution: 25261 in 0.061362 seconds.
New solution: 25260 in 0.0637269 seconds.
New solution: 24263 in 0.0679278 seconds.
New solution: 24260 in 0.068089 seconds.
New solution: 24259 in 0.077704 seconds.
New solution: 23260 in 0.0918329 seconds.
New solution: 23258 in 0.0964508 seconds.
New solution: 23257 in 0.102036 seconds.
New solution: 23256 in 0.105563 seconds.
New solution: 22256 in 0.118236 seconds.
New solution: 21259 in 0.152582 seconds.
New solution: 21258 in 0.154594 seconds.
New solution: 21256 in 0.156728 seconds.
New solution: 21254 in 0.239868 seconds.
New solution: 21253 in 0.703341 seconds.
-----
MPI_ABORT was invoked on rank 1 in communicator MPI_COMM_WORLD
with errorcode 0.

NOTE: invoking MPI_ABORT causes Open MPI to kill all MPI processes.
You may or may not see output from other processes, depending on
exactly when Open MPI kills them.
-----

Time limit expired... Aborting...

```

11. Download file *example.dec*. Solve a WCSP using a variable neighborhood search algorithm (UDGVNS) with a given cluster decomposition:

```

toulbar2 EXAMPLES/example.wcsp EXAMPLES/example.dec -vns

Read 25 variables, with 5 values at most, and 63 cost functions, with maximum arity 2.
Cost function decomposition time : 6e-06 seconds.
Reverse DAC lower bound: 20 (+10%)
Reverse DAC lower bound: 22 (+9.09091%)
Preprocessing time: 0.00088 seconds.
24 unassigned variables, 117 values in all current domains (med. size:5, max size:5) and 62 non-unary cost functions (med. degree:5)
Initial lower and upper bounds: [22,64[ 65.625%
New solution: 29 (0 backtracks, 8 nodes, depth 9)
Problem decomposition in 7 clusters with size distribution: min: 11 median: 15 mean: 15.1429 max: 17
***** Restart 1 with 1 discrepancies and UB=29 ***** (8 nodes)
New solution: 28 (0 backtracks, 8 nodes, depth 1)
New solution: 27 (0 backtracks, 8 nodes, depth 1)
***** Restart 2 with 2 discrepancies and UB=27 ***** (61 nodes)
***** Restart 3 with 4 discrepancies and UB=27 ***** (133 nodes)
***** Restart 4 with 8 discrepancies and UB=27 ***** (280 nodes)
***** Restart 5 with 16 discrepancies and UB=27 ***** (636 nodes)
Optimum: 27 in 343 backtracks and 770 nodes ( 950 removals by DEE) and 0.024371 seconds.
end.

```

12. Solve a WCSP using a parallel variable neighborhood search algorithm (UPDGVNS) with the same cluster decomposition:


```
mpirun -n 4 toulbar2 EXAMPLES/example.wcsp EXAMPLES/example.dec -vns
```

```
Read 25 variables, with 5 values at most, and 63 cost functions, with maximum arity 2.
Cost function decomposition time : 1.3e-05 seconds.
Reverse DAC lower bound: 20 (+10%)
Reverse DAC lower bound: 22 (+9.09091%)
Preprocessing time: 0.001489 seconds.
24 unassigned variables, 117 values in all current domains (med. size:5, max size:5) and 62 non-unary cost functions (med. degree:5)
Initial lower and upper bounds: [22,64[ 65.625%
Problem decomposition in 7 clusters with size distribution: min: 11 median: 15 mean: 15.1429 max: 17
New solution: 29 (0 backtracks, 7 nodes, depth 8)
New solution: 28 in 0.00155497 seconds.
New solution: 27 in 0.0021801 seconds.
Optimum: 27 in 0 backtracks and 7 nodes ( 35 removals by DEE) and 0.044263 seconds.
Total CPU time = 0.192932 seconds
Solving real-time = 0.046993 seconds (not including preprocessing time)
end.
```

13. Download file *example.order*. Solve a WCSP using BT-D-HBFS based on a given (min-fill) reverse variable elimination ordering:

```
toulbar2 EXAMPLES/example.wcsp EXAMPLES/example.order -B=1
```

```
Read 25 variables, with 5 values at most, and 63 cost functions, with maximum arity 2.
Cost function decomposition time : 8e-06 seconds.
Reverse DAC lower bound: 19 (+10.5263%)
Preprocessing time: 0.000803 seconds.
24 unassigned variables, 115 values in all current domains (med. size:5, max size:5) and 62 non-unary cost functions (med. degree:5)
Initial lower and upper bounds: [19,64[ 70.3125%
Tree decomposition width : 8
Tree decomposition height : 16
Number of clusters : 18
Tree decomposition time: 0.00026 seconds.
New solution: 29 (19 backtracks, 34 nodes, depth 2)
Optimality gap: [ 20 , 29 ] 31.0345 % (19 backtracks, 34 nodes)
Optimality gap: [ 22 , 29 ] 24.1379 % (43 backtracks, 92 nodes)
New solution: 28 (71 backtracks, 157 nodes, depth 2)
Optimality gap: [ 22 , 28 ] 21.4286 % (71 backtracks, 157 nodes)
New solution: 27 (94 backtracks, 204 nodes, depth 2)
Optimality gap: [ 22 , 27 ] 18.5185 % (94 backtracks, 204 nodes)
Optimality gap: [ 23 , 27 ] 14.8148 % (115 backtracks, 249 nodes)
Optimality gap: [ 24 , 27 ] 11.1111 % (159 backtracks, 363 nodes)
Optimality gap: [ 25 , 27 ] 7.40741 % (176 backtracks, 414 nodes)
Optimality gap: [ 26 , 27 ] 3.7037 % (177 backtracks, 441 nodes)
Optimality gap: [ 27 , 27 ] 0 % (181 backtracks, 537 nodes)
HBFS open list restarts: 0 % and reuse: 11.4286 % of 70
Node redundancy during HBFS: 34.2644 %
Optimum: 27 in 181 backtracks and 537 nodes ( 94 removals by DEE) and 0.009692 seconds.
end.
```

14. Download file *example.cov*. Solve a WCSP using BT-D-HBFS based on a given explicit (min-fill path-) tree-decomposition:

```
toulbar2 EXAMPLES/example.wcsp EXAMPLES/example.cov -B=1
```

```
Read 25 variables, with 5 values at most, and 63 cost functions, with maximum arity 2.
Warning! Cannot apply variable elimination during search with a given tree decomposition file.
Warning! Cannot apply functional variable elimination with a given tree decomposition file.
Cost function decomposition time : 7e-06 seconds.
Reverse DAC lower bound: 20 (+10%)
Reverse DAC lower bound: 21 (+4.7619%)
Preprocessing time: 0.00093 seconds.
25 unassigned variables, 120 values in all current domains (med. size:5, max size:5) and 63 non-unary cost functions (med. degree:5)
Initial lower and upper bounds: [21,64[ 67.1875%
Tree decomposition width : 16
Tree decomposition height : 24
Number of clusters : 9
Tree decomposition time: 0.000218 seconds.
New solution: 29 (23 backtracks, 29 nodes, depth 2)
Optimality gap: [ 22 , 29 ] 24.1379 % (33 backtracks, 52 nodes)
New solution: 28 (128 backtracks, 273 nodes, depth 2)
Optimality gap: [ 22 , 28 ] 21.4286 % (128 backtracks, 273 nodes)
New solution: 27 (161 backtracks, 340 nodes, depth 2)
Optimality gap: [ 23 , 27 ] 14.8148 % (161 backtracks, 340 nodes)
Optimality gap: [ 24 , 27 ] 11.1111 % (217 backtracks, 469 nodes)
Optimality gap: [ 25 , 27 ] 7.40741 % (261 backtracks, 590 nodes)
Optimality gap: [ 26 , 27 ] 3.7037 % (271 backtracks, 681 nodes)
Optimality gap: [ 27 , 27 ] 0 % (276 backtracks, 739 nodes)
HBFS open list restarts: 0 % and reuse: 26.9231 % of 26
Node redundancy during HBFS: 28.4168 %
Optimum: 27 in 276 backtracks and 739 nodes ( 95 removals by DEE) and 0.012753 seconds.
end.
```

15. Download a Markov Random Field (MRF) file *pedigree9.uai* in UAI format from the toulbar2's Documentation Web page. Solve it using bounded (of degree at most 8) variable elimination enhanced by cost function decomposition in preprocessing [13] followed by BTD-HBFS exploiting only small-size (less than four variables) separators:

```
toulbar2 EXAMPLES/pedigree9.uai -O=-3 -p=-8 -B=1 -r=4

Read 1118 variables, with 7 values at most, and 1118 cost functions, with maximum arity 4.
No evidence file specified. Trying EXAMPLES/pedigree9.uai.evid
No evidence file.
Generic variable elimination of degree 4
Maximum degree of generic variable elimination: 4
Cost function decomposition time : 0.003853 seconds.
Preprocessing time: 0.06838 seconds.
232 unassigned variables, 517 values in all current domains (med. size:2, max size:7) and 417 non-unary cost functions (med. degree:6)
Initial lower and upper bounds: [553902779,13246577453[ 95.8185%
Tree decomposition width : 227
Tree decomposition height : 230
Number of clusters : 890
Tree decomposition time: 0.044444 seconds.
New solution: 864780591 energy: 298.356 prob: 2.66419e-130 (73 backtracks, 142 nodes, depth 2)
New solution: 842808347 energy: 296.159 prob: 2.39777e-129 (297 backtracks, 620 nodes, depth 2)
New solution: 833705902 energy: 295.249 prob: 5.95829e-129 (728 backtracks, 1583 nodes, depth 2)
New solution: 823002032 energy: 294.178 prob: 1.73774e-128 (895 backtracks, 2001 nodes, depth 2)
New solution: 781808575 energy: 290.059 prob: 1.06904e-126 (943 backtracks, 2103 nodes, depth 2)
New solution: 753290137 energy: 287.207 prob: 1.85154e-125 (1076 backtracks, 2380 nodes, depth 2)
New solution: 711184893 energy: 282.997 prob: 1.24779e-123 (2112 backtracks, 4459 nodes, depth 2)
HBFS open list restarts: 0 % and reuse: 44.7548 % of 1611
Node redundancy during HBFS: 18.4077 %
Optimum: 711184893 energy: 282.997 prob: 1.24779e-123 in 29934 backtracks and 73355 nodes ( 24686 removals by DEE) and 5.28419 seconds.
end.
```

16. Download another MRF file *GeomSurf-7-gm256.uai*. Solve it using Virtual Arc Consistency (VAC) in preprocessing [6] and exploit a VAC-based value ordering heuristic [7]:

```
toulbar2 EXAMPLES/GeomSurf-7-gm256.uai -A -V

Read 787 variables, with 7 values at most, and 3527 cost functions, with maximum arity 3.
No evidence file specified. Trying EXAMPLES/GeomSurf-7-gm256.uai.evid
No evidence file.
Lb before VAC: 4506326046
Cost function decomposition time : 0.000862 seconds.
Reverse DAC lower bound: 5853428901 (+0.0694528%)
Preprocessing VAC mean lb/incr: 2.8643e+06 total increments: 463 cyclesize: 22.2419 k: 1.29806 (mean), 4 (max)
Lb after VAC: 5905811708
Preprocessing time: 2.18214 seconds.
730 unassigned variables, 4828 values in all current domains (med. size:7, max size:7) and 3131 non-unary cost functions (med. degree:6)
Initial lower and upper bounds: [5905811708,111615200815[ 94.7088%
c 2097152 Bytes allocated for long long stack.
c 4194304 Bytes allocated for long long stack.
New solution: 6135086360 energy: 1099.69 prob: 2.57374e-478 (0 backtracks, 116 nodes, depth 117)
Optimality gap: [ 5908760056 , 6135086360 ] 3.68905 % (104 backtracks, 220 nodes)
New solution: 5922481881 energy: 1078.43 prob: 4.40413e-469 (104 backtracks, 331 nodes, depth 109)
Optimality gap: [ 5909173184 , 5922481881 ] 0.224715 % (191 backtracks, 418 nodes)
Optimality gap: [ 5922481881 , 5922481881 ] 0 % (191 backtracks, 420 nodes)
VAC mean lb/incr: -nan total increments: 0 cyclesize: -nan k: -nan (mean), 0 (max)
Node redundancy during HBFS: 1.19048 %
Optimum: 5922481881 energy: 1078.43 prob: 4.40413e-469 in 191 backtracks and 420 nodes ( 18060 removals by DEE) and 2.55928 seconds.
end.
```

17. Download another MRF file *1CM1.uai*. Solve it by applying first a strong dominance pruning test in preprocessing, and secondly, a modified variable ordering heuristic during search [4]:

```
toulbar2 EXAMPLES/1CM1.uai -dee=2 -m=2

Read 37 variables, with 350 values at most, and 703 cost functions, with maximum arity 2.
No evidence file specified. Trying EXAMPLES/1CM1.uai.evid
No evidence file.
```

```

Cost function decomposition time : 0.000225 seconds.
Reverse DAC lower bound: 102868791154 (+0.010277%)
Preprocessing time: 10.9057 seconds.
37 unassigned variables, 1679 values in all current domains (med. size:33, max size:350) and 624 non-unary cost functions (med. degree:35)
Initial lower and upper bounds: [102868791154,239074057808[ 56.972%
c 2097152 Bytes allocated for long long stack.
c 4194304 Bytes allocated for long long stack.
c 8388608 Bytes allocated for long long stack.
c 16777216 Bytes allocated for long long stack.
c 33654432 Bytes allocated for long long stack.
c 67108864 Bytes allocated for long long stack.
New solution: 104206588216 energy: -12464.3 prob: inf (0 backtracks, 48 nodes, depth 49)
Optimality gap: [ 103905905484 , 104206588216 ] 0.288545 % (22 backtracks, 70 nodes)
New solution: 104174014744 energy: -12467.6 prob: inf (22 backtracks, 82 nodes, depth 3)
Optimality gap: [ 103963607615 , 104174014744 ] 0.201977 % (23 backtracks, 83 nodes)
Optimality gap: [ 104010471712 , 104174014744 ] 0.15699 % (24 backtracks, 93 nodes)
Optimality gap: [ 104174014744 , 104174014744 ] 0 % (25 backtracks, 96 nodes)
Node redundancy during HBFS: 19.7917 %
Optimum: 104174014744 energy: -12467.6 prob: inf in 25 backtracks and 96 nodes ( 3803 removals by DEE) and 11.4979 seconds.
end.

```

18. Download a weighted Max-SAT file *brock200_4.clq.wcnf* in wcnf format from the toulbar2's Documentation Web page. Solve it using a modified variable ordering heuristic [4]:

```

toulbar2 EXAMPLES/brock200_4.clq.wcnf -m=1

c Read 200 variables, with 2 values at most, and 7011 clauses, with maximum arity 2.
Cost function decomposition time : 0.000277 seconds.
Reverse DAC lower bound: 91 (+86.8132%)
Reverse DAC lower bound: 92 (+1.08696%)
Preprocessing time: 0.034145 seconds.
200 unassigned variables, 400 values in all current domains (med. size:2, max size:2) and 6811 non-unary cost functions (med. degree:68)
Initial lower and upper bounds: [92,200[ 54%
New solution: 189 (0 backtracks, 9 nodes, depth 10)
New solution: 188 (20 backtracks, 55 nodes, depth 10)
New solution: 187 (113 backtracks, 326 nodes, depth 20)
New solution: 186 (428 backtracks, 1013 nodes, depth 21)
New solution: 185 (8011 backtracks, 17396 nodes, depth 14)
New solution: 184 (13807 backtracks, 29658 nodes, depth 11)
New solution: 183 (13821 backtracks, 29682 nodes, depth 7)
Node redundancy during HBFS: 26.313 %
Optimum: 183 in 299378 backtracks and 812567 nodes ( 3362 removals by DEE) and 21.3244 seconds.
end.

```

19. Download another WCSP file *latin4.wcsp*. Count the number of feasible solutions:

```

toulbar2 EXAMPLES/latin4.wcsp -a

Read 16 variables, with 4 values at most, and 24 cost functions, with maximum arity 4.
Cost function decomposition time : 0 seconds.
Reverse DAC lower bound: 48 (+2.08333%)
Preprocessing time: 0.006302 seconds.
16 unassigned variables, 64 values in all current domains (med. size:4, max size:4) and 8 non-unary cost functions (med. degree:6)
Initial lower and upper bounds: [48,1000[ 95.2%
Optimality gap: [ 49 , 1000 ] 95.1 % (12 backtracks, 26 nodes)
Optimality gap: [ 58 , 1000 ] 94.2 % (353 backtracks, 813 nodes)
Optimality gap: [ 72 , 1000 ] 92.8 % (575 backtracks, 1360 nodes)
Optimality gap: [ 1000 , 1000 ] 0 % (575 backtracks, 1369 nodes)
Number of solutions      : = 576
Time                    : 0.300726 seconds
... in 575 backtracks and 1369 nodes
end.

```

20. Download a crisp CSP file *GEOM40_6.wcsp* (initial upper bound equal to 1). Count the number of solutions using #BTD [12] using a min-fill variable ordering²:

```

toulbar2 EXAMPLES/GEOM40_6.wcsp -0=-3 -a -B=1

```

²Warning, cannot use BTD to find all solutions in optimization.

```

Read 40 variables, with 6 values at most, and 78 cost functions, with maximum arity 2.
Cost function decomposition time : 4e-06 seconds.
Preprocessing time: 0.000908 seconds.
40 unassigned variables, 240 values in all current domains (med. size:6, max size:6) and 78 non-unary cost functions (med. degree:4)
Initial lower and upper bounds: [0,1[ 100%
Tree decomposition width : 5
Tree decomposition height : 20
Number of clusters : 29
Tree decomposition time: 0.000336 seconds.
Number of solutions : = 4.11111e+23
Number of #goods : 3993
Number of used #goods : 17190
Size of sep : 4
Time : 0.051852 seconds
... in 13689 backtracks and 27378 nodes
end.

```

21. Get a quick approximation of the number of solutions of a CSP with Approx#BTD [12]:

```

toulbar2 EXAMPLES/GEOM40_6.wcsp -O=-3 -a -B=1 -D

Read 40 variables, with 6 values at most, and 78 cost functions, with maximum arity 2.
Cost function decomposition time : 5e-06 seconds.
Preprocessing time: 0.000888 seconds.
40 unassigned variables, 240 values in all current domains (med. size:6, max size:6) and 78 non-unary cost functions (med. degree:4)
Initial lower and upper bounds: [0,1[ 100%

part 1 : 40 variables and 71 constraints (really added)
part 2 : 10 variables and 7 constraints (really added)
--> number of parts : 2
--> time : 0.000341 seconds.

Tree decomposition width : 5
Tree decomposition height : 17
Number of clusters : 33
Tree decomposition time: 0.000629 seconds.

Cartesian product : 1.33675e+31
Upper bound of number of solutions : <= 1.71993e+24
Number of solutions : ~= 4.8e+23
Number of #goods : 468
Number of used #goods : 4788
Size of sep : 3
Time : 0.011165 seconds
... in 3738 backtracks and 7476 nodes
end.

```

5 Command line options

If you just execute:

```
toulbar2
```

TOULBAR2 will give you its (long) list of optional parameter which we now describe in more detail.

To deactivate a default command line option, just use the command-line option followed by “:”. For example:

```
toulbar2 -dee: <file>
```

will disable the default Dead End Elimination [9] (aka Soft Neighborhood Substitutability) preprocessing.

5.1 General control

- a=[integer]** finds at most a given number of solutions with a cost strictly lower than the initial upper bound and stops, or if no integer is given, finds all solutions (or counts the number of zero-cost satisfiable solutions in conjunction with BTD)
- D** approximate satisfiable solution count with BTD
- logz** computes log of probability of evidence (i.e. log partition function or $\log(Z)$ or PR task) for graphical models only (problem file extension .uai)
- timer=[integer]** give a CPU time limit in seconds. TOULBAR2 will stop after the specified CPU time has been consumed. The time limit is a CPU user time limit, not wall clock time limit.
- seed=[integer]** random seed non-negative value or use current time if a negative value is given (default value is 1)

5.2 Preprocessing

- nopre** deactivates all preprocessing options (equivalent to -e: -p: -t: -f: -dec: -n: -mst: -dec:)
- p=[integer]** preprocessing only: general variable elimination of degree less than or equal to the given value (default value is -1)
- t=[integer]** preprocessing only: simulates restricted path consistency by adding ternary cost functions on triangles of binary cost functions within a given maximum space limit (in MB)
- f=[integer]** preprocessing only: variable elimination of functional (f=1) (resp. bijective (f=2)) variables (default value is 1)
- dec** preprocessing only: pairwise decomposition [13] of cost functions with arity ≥ 3 into smaller arity cost functions (default option)
- n=[integer]** preprocessing only: projects n-ary cost functions on all binary cost functions if n is lower than the given value (default value is 10). See [13].
- mst** find a maximum spanning tree ordering for DAC
- M=[integer]** apply the Min Sum Diffusion algorithm (default is inactivated, with a number of iterations of 0). See [7].

5.3 Initial upper bounding

- l=[integer]** limited discrepancy search [14], use a negative value to stop the search after the given absolute number of discrepancies has been explored (discrepancy bound = 4 by default)
- L=[integer]** randomized (quasi-random variable ordering) search with restart (maximum number of nodes/VNS restarts = 10000 by default)
- i=["string"]** initial upper bound found by INCOP local search solver [24]. The string parameter is optional, using "0 1 3 idwa 100000 cv v 0 200 1 0 0" by default with the following meaning: *stoppinglowerbound randomseed nbiterations method nbmoves neighborhoodchoice neighborhoodchoice2 minnbneighbors maxnbneighbors neighborhoodchoice3 autotuning tracemode*.
- x=[(,i=a)*]** assigns variable of index i to value a (multiple assignments are separated by a comma and no space) (without any argument, a complete assignment – used as initial upper bound and as a value heuristic – read from default file "sol" taken as a certificate or given directly as an additional input filename with ".sol" extension and without **-x**)

5.4 Tree search algorithms and tree decomposition selection

- hbfs=[integer]** hybrid best-first search [2], restarting from the root after a given number of backtracks (default value is 10000)
- open=[integer]** hybrid best-first search limit on the number of stored open nodes (default value is -1)
- B=[integer]** (0) DFBB, (1) BTD [10], (2) RDS-BTD [26], (3) RDS-BTD with path decomposition instead of tree decomposition [26] (default value is 0)
- O=[filename]** reads either a reverse variable elimination order (given by a list of variable indexes) from a file in order to build a tree decomposition (if BTD-like and/or variable elimination methods are used) or reads a valid tree decomposition directly (given by a list of clusters in topological order of a rooted forest, each line contains a cluster number, followed by a cluster parent number with -1 for the first/root(s) cluster(s), followed by a list of variable indexes). It is also used as a DAC ordering.
- O=[negative integer]** build a tree decomposition (if BTD-like and/or variable elimination methods are used) and also a compatible DAC ordering using
 - (-1) maximum cardinality search ordering,
 - (-2) minimum degree ordering,

- (-3) minimum fill-in ordering,
- (-4) maximum spanning tree ordering (see -mst),
- (-5) reverse Cuthill-McKee ordering,
- (-6) approximate minimum degree ordering,
- (-7) default file ordering

If not specified, then use the variable order in which variables appear in the problem file.

- j=[integer]** splits large clusters into a chain of smaller embedded clusters with a number of proper variables less than this number (use options "-B=3 -j=1 -svo -k=1" for pure RDS, use value 0 for no splitting) (default value is 0).
- r=[integer]** limit on the maximum cluster separator size (merge cluster with its father otherwise, use a negative value for no limit) (default value is -1)
- X=[integer]** limit on the minimum number of proper variables in a cluster (merge cluster with its father otherwise, use a zero for no limit) (default value is 0)
- E=[float]** merges leaf clusters with their fathers if small local treewidth (in conjunction with option "-e" and positive threshold value) or ratio of number of separator variables by number of cluster variables above a given threshold (in conjunction with option -vns) (default value is 0)
- R=[integer]** choice for a specific root cluster number
- I=[integer]** choice for solving only a particular rooted cluster subtree (with RDS-BTD only)

5.5 Variable neighborhood search algorithms

- vns** unified decomposition guided variable neighborhood search [25] (UDGVNS).
A problem decomposition into clusters can be given as *.dec, *.cov, or *.order input files or using tree decomposition options such as -O. For a parallel version (UPDGVNS), use "mpirun -n [NbOfProcess] toulbar2 -vns problem.wcsp".
- vnsini=[integer]** initial solution for VNS-like methods found: (-1) at random, (-2) min domain values, (-3) max domain values, (-4) first solution found by a complete method, (k=0 or more) tree search with k discrepancy max (-4 by default)
- ldsmin=[integer]** minimum discrepancy for VNS-like methods (1 by default)
- ldsmax=[integer]** maximum discrepancy for VNS-like methods (number of problem variables multiplied by maximum domain size -1 by default)

- ldsinc=[integer]** discrepancy increment strategy for VNS-like methods using (1) Add1, (2) Mult2, (3) Luby operator (2 by default)
- kmin=[integer]** minimum neighborhood size for VNS-like methods (4 by default)
- kmax=[integer]** maximum neighborhood size for VNS-like methods (number of problem variables by default)
- kinc=[integer]** neighborhood size increment strategy for VNS-like methods using: (1) Add1, (2) Mult2, (3) Luby operator (4) Add1/Jump (4 by default)
- best=[integer]** stop VNS-like methods if a better solution is found (default value is 0)

5.6 Node processing & bounding options

- e=[integer]** performs “on the fly” variable elimination of variable with small degree (less than or equal to a specified value, default is 3 creating a maximum of ternary cost functions). See [17].
- k=[integer]** soft local consistency level (NC [18] with Strong NIC for global cost functions=0 [21], (G)AC=1 [27, 18], D(G)AC=2 [8], FD(G)AC=3 [19], (weak) ED(G)AC=4 [11, 22]) (default value is 4). See also [7, 23].
- A=[integer]** enforces VAC [6] at each search node with a search depth less than a given value (default value is 0)
- V** VAC-based value ordering heuristic (default option)
- dee=[integer]** restricted dead-end elimination [9] (value pruning by dominance rule from EAC value ($dee \geq 1$ and $dee \leq 3$)) and soft neighborhood substitutability (in preprocessing ($dee=2$ or $dee=4$) or during search ($dee=3$)) (default value is 1)
- o** ensures an optimal worst-case time complexity of DAC and EAC (can be slower in practice)

5.7 Branching, variable and value ordering

- svo** searches using a static variable ordering heuristic. The variable order value used will be the same order as the DAC order.
- b** searches using binary branching (by default) instead of n-ary branching. Uses binary branching for interval domains and small domains and dichotomic branching for large enumerated domains (see option -d).
- c** searches using binary branching with last conflict backjumping variable ordering heuristic [20].

- q=[integer]** use weighted degree variable ordering heuristic [5] if the number of cost functions is less than the given value (default value is 1000000).
- var=[integer]** searches by branching only on the first [given value] decision variables, assuming the remaining variables are intermediate variables that will be completely assigned by the decision variables (use a zero if all variables are decision variables, default value is 0)
- m=[integer]** use a variable ordering heuristic that selects first variables such that the sum of the mean (m=1) or median (m=2) cost of all incident cost functions is maximum [4] (in conjunction with weighted degree heuristic -q) (default value is 0: unused).
- d=[integer]** searches using dichotomic branching. The default d=1 splits domains in the middle of domain range while d=2 splits domains in the middle of the sorted domain based on unary costs.
- sortd** sorts domains in preprocessing based on increasing unary costs (works only for binary WCSPs).

5.8 Console output

- help** shows the default help message that TOULBAR2 prints when it gets no argument.
- v=[integer]** sets the verbosity level (default 0).
- Z=[integer]** debug mode (save problem at each node if verbosity option -v=num >= 1 and -Z=num >= 3)
- s** shows each solution found during search. The solution is printed on one line, giving the value (integer) of each variable successively in increasing file order.

5.9 File output

- w=[filename]** writes last/all solutions found in the specified filename (or "sol" if no parameter is given). The current directory is used as a relative path.
- z=[filename]** saves problem in wvsp format in filename (or "problem.wvsp" if no parameter is given) writes also the graphviz dot file and the degree distribution of the input problem
- z=[integer]** 1: saves original instance (by default), 2: saves after preprocessing (this option can be used in combination with -z=filename)
- x=[(,i=a)*]** assigns variable of index i to value a (multiple assignments are separated by a comma and no space) (without any argument, a complete assignment – used as initial upper bound and as value heuristic – read from default file "sol" or given as input filename with ".sol" extension)

5.10 Probability representation and numerical control

- precision**=[integer] probability/real precision is a conversion factor (a power of ten) for representing fixed point numbers (default value is 7)
- epsilon**=[float] approximation factor for computing the partition function (greater than 1, default value is infinity)

5.11 Random problem generation

-**random**=[bench profile] bench profile must be specified as follows.

- n and d are respectively the number of variable and the maximum domain size of the random problem.

bin-n-d-t1-p2-seed

- t1 is the tightness in percentage % of random binary cost functions
- p2 is the number of binary cost functions to include
- the seed parameter is optional

binsub-n-d-t1-p2-p3-seed binary random & submodular cost functions

- t1 is the tightness in percentage % of random cost functions
- p2 is the number of binary cost functions to include
- p3 is the percentage % of submodular cost functions among p2 cost functions (plus 10 permutations of two randomly-chosen values for each domain)

tern-n-d-t1-p2-p3-seed

- p3 is the number of ternary cost functions

nary-n-d-t1-p2-p3...-pn-seed

- pn is the number of n-ary cost functions

salldiff-n-d-t1-p2-p3...-pn-seed

- pn is the number of salldiff global cost functions (p2 and p3 still being used for the number of random binary and ternary cost functions). *salldiff* can be replaced by *gcc* or *regular* keywords with three possible forms (*e.g.*, *sgcc*, *sgccdp*, *wgcc*).

6 Input File formats

Notice that by default TOULBAR2 distinguishes file formats based on their extension.

6.1 wcsp format (.wcsp file extension)

It is a text format composed of a list of numerical and string terms separated by spaces. Instead of using names for making reference to variables, variable indexes are employed. The same for domain values. All indexes start at zero.

Cost functions can be defined in intention (see below) or in extension, by their list of tuples. A default cost value is defined per function in order to reduce the size of the list. Only tuples with a different cost value should be given (not mandatory). All the cost values must be positive. The arity of a cost function in extension may be equal to zero. In this case, there is no tuples and the default cost value is added to the cost of any solution. This can be used to represent a global lower bound constant of the problem.

The wcsp file format is composed of three parts: a problem header, the list of variable domain sizes, and the list of cost functions.

- Header definition for a given problem:

```
<Problem name>
<Number of variables (N)>
<Maximum domain size>
<Number of cost functions>
<Initial global upper bound of the problem (UB)>
```

The goal is to find an assignment of all the variables with minimum total cost, strictly lower than UB. Tuples with a cost greater than or equal to UB are forbidden (hard constraint).

- Definition of domain sizes

```
<Domain size of variable with index 0>
...
<Domain size of variable with index N - 1>
```

Note

domain values range from zero to *size-1*
a negative domain size is interpreted as a variable with an interval domain in $[0, -size - 1]$

Warning

variables with interval domains are restricted to arithmetic and disjunctive cost functions in intention (see below)

- General definition of cost functions
 - Definition of a cost function in extension

```
<Arity of the cost function>
<Index of the first variable in the scope of the cost function>
...
<Index of the last variable in the scope of the cost function>
<Default cost value>
<Number of tuples with a cost different than the default cost>
```

followed by for every tuple with a cost different than the default cost:

```
<Index of the value assigned to the first variable in the scope>
...
<Index of the value assigned to the last variable in the scope>
<Cost of the tuple>
```

Note

Shared cost function: A cost function in extension can be shared by several cost functions with the same arity (and same domain sizes) but different scopes. In order to do that, the cost function to be shared must start by a negative scope size. Each shared cost function implicitly receives an occurrence number starting from 1 and incremented at each new shared definition. New cost functions in extension can reuse some previously defined shared cost functions in extension by using a negative number of tuples representing the occurrence number of the desired shared cost function. Note that default costs should be the same in the shared and new cost functions. Here is an example of 4 variables with domain size 4 and one AllDifferent hard constraint decomposed into 6 binary constraints.

- Shared CF used inside a small example in wcsp format:

```
AllDifferentDecomposedIntoBinaryConstraints 4 4 6 1
4 4 4 4
-2 0 1 0 4
0 0 1
1 1 1
2 2 1
3 3 1
2 0 2 0 -1
2 0 3 0 -1
2 1 2 0 -1
2 1 3 0 -1
2 2 3 0 -1
```

- Definition of a cost function in intension by replacing the default cost value by -1 and by giving its keyword name and its K parameters

```
<Arity of the cost function>
<Index of the first variable in the scope of the cost function>
...
<Index of the last variable in the scope of the cost function>
-1
<keyword>
<parameter1>
...
<parameterK>
```

Possible keywords of cost functions defined in intension followed by their specific parameters:

- $\geq cst\ delta$ to express soft binary constraint $x \geq y + cst$ with associated cost function $max((y + cst - x \leq delta)?(y + cst - x) : UB, 0)$
- $> cst\ delta$ to express soft binary constraint $x > y + cst$ with associated cost function $max((y + cst + 1 - x \leq delta)?(y + cst + 1 - x) : UB, 0)$

- $\leq cst\ delta$ to express soft binary constraint $x \leq y + cst$ with associated cost function $max((x - cst - y \leq delta)?(x - cst - y) : UB, 0)$
- $< cst\ delta$ to express soft binary constraint $x < y + cst$ with associated cost function $max((x - cst + 1 - y \leq delta)?(x - cst + 1 - y) : UB, 0)$
- $= cst\ delta$ to express soft binary constraint $x = y + cst$ with associated cost function $(|y + cst - x| \leq delta)?|y + cst - x| : UB$
- $disj\ cstx\ csty\ penalty$ to express soft binary disjunctive constraint $x \geq y + csty \vee y \geq x + cstx$ with associated cost function $(x \geq y + csty \vee y \geq x + cstx)?0 : penalty$
- $sdisj\ cstx\ csty\ xinfy\ yinfy\ costx\ costy$ to express a special disjunctive constraint with three implicit hard constraints $x \leq xinfy$ and $y \leq yinfy$ and $x < xinfy \wedge y < yinfy \Rightarrow (x \geq y + csty \vee y \geq x + cstx)$ and an additional cost function $((x = xinfy)?costx : 0) + ((y = yinfy)?costy : 0)$
- Global cost functions using a flow-based propagator:
 - $salldiff\ var|dec|decbi\ cost$ to express a soft alldifferent constraint with either variable-based (*var* keyword) or decomposition-based (*dec* and *decbi* keywords) cost semantic with a given *cost* per violation (*decbi* decomposes into a binary cost function complete network)
 - $sgcc\ var|dec|wdec\ cost\ nb_values\ (value\ lower_bound\ upper_bound\ (shortage_weight\ excess_weight)?)*$ to express a soft global cardinality constraint with either variable-based (*var* keyword) or decomposition-based (*dec* keyword) cost semantic with a given *cost* per violation and for each value its lower and upper bound (if *wdec* then violation cost depends on each value shortage or excess weights)
 - $ssame\ cost\ list_size1\ list_Size2\ (variable_index)*\ (variable_index)*$ to express a permutation constraint on two lists of variables of equal size (implicit variable-based cost semantic)
 - $sregular\ var|edit\ cost\ nb_states\ nb_initial_states\ (state)*\ nb_final_states\ (state)*\ nb_transitions\ (start_state\ symbol_value\ end_state)*$ to express a soft regular constraint with either variable-based (*var* keyword) or edit distance-based (*edit* keyword) cost semantic with a given *cost* per violation followed by the definition of a deterministic finite automaton with number of states, list of initial and final states, and list of state transitions where symbols are domain values
- Global cost functions using a dynamic programming DAG-based propagator:
 - $sregulardp\ var\ cost\ nb_states\ nb_initial_states\ (state)*\ nb_final_states\ (state)*\ nb_transitions\ (start_state\ symbol_value\ end_state)*$ to express a soft regular constraint with a variable-based (*var* keyword)

cost semantic with a given *cost* per violation followed by the definition of a deterministic finite automaton with number of states, list of initial and final states, and list of state transitions where symbols are domain values

- sgrammar|sgrammardp var|weight *cost nb_symbols nb_values start_symbol nb_rules* ((0 *terminal_symbol value*)|(1 *nonterminal_in nonterminal_out_left nonterminal_out_right*)|(2 *terminal_symbol value weight*)|(3 *nonterminal_in nonterminal_out_left nonterminal_out_right weight*))* to express a soft/weighted grammar in Chomsky normal form
- samong|samongdp var *cost lower_bound upper_bound nb_values (value)** to express a soft among constraint to restrict the number of variables taking their value into a given set of values
- salldifdp var *cost* to express a soft alldifferent constraint with variable-based (*var* keyword) cost semantic with a given *cost* per violation (decomposes into samongdp cost functions)
- sgccdp var *cost nb_values (value lower_bound upper_bound)** to express a soft global cardinality constraint with variable-based (*var* keyword) cost semantic with a given *cost* per violation and for each value its lower and upper bound (decomposes into samongdp cost functions)
- max|smaxdp *defCost nbtuples (variable value cost)** to express a weighted max cost function to find the maximum cost over a set of unary cost functions associated to a set of variables (by default, *defCost* if unspecified)
- MST|smstdp to express a spanning tree hard constraint where each variable is assigned to its parent variable index in order to build a spanning tree (the root being assigned to itself)
- Global cost functions using a cost function network-based propagator [1]:
 - wregular *nb_states nb_initial_states (state and cost)* nb_final_states (state and cost)* nb_transitions (start_state symbol_value end_state cost)** to express a weighted regular constraint with weights on initial states, final states, and transitions, followed by the definition of a deterministic finite automaton with number of states, list of initial and final states with their costs, and list of weighted state transitions where symbols are domain values
 - walldiff hard|lin|quad *cost* to express a soft alldifferent constraint as a set of wamong hard constraint (*hard* keyword) or decomposition-based (*lin* and *quad* keywords) cost semantic with a given *cost* per violation
 - wgcc hard|lin|quad *cost nb_values (value lower_bound upper_bound)** to express a soft global cardinality constraint as either a hard constraint (*hard* keyword) or with decomposition-based (*lin* and *quad* keyword) cost semantic with a given *cost* per violation and for each value its lower and upper bound

- `wsame hard|lin|quad cost` to express a permutation constraint on two lists of variables of equal size (implicitly concatenated in the scope) using implicit decomposition-based cost semantic
- `wsamegcc hard|lin|quad cost nb_values (value lower_bound upper_bound)*` to express the combination of a soft global cardinality constraint and a permutation constraint
- `wamong hard|lin|quad cost nb_values (value)* lower_bound upper_bound` to express a soft among constraint to restrict the number of variables taking their value into a given set of values
- `wvamong hard cost nb_values (value)*` to express a hard among constraint to restrict the number of variables taking their value into a given set of values to be equal to the last variable in the scope
- `woverlap hard|lin|quad cost comparator righthandside` overlaps between two sequences of variables X, Y (i.e. set the fact that Xi and Yi take the same value (not equal to zero))
- `wsum hard|lin|quad cost comparator righthandside` to express a soft sum constraint with unit coefficients to test if the sum of a set of variables matches with a given comparator and right-hand-side value
- `wvarsum hard cost comparator` to express a hard sum constraint to restrict the sum to be *comparator* to the value of the last variable in the scope

Let us note $\langle \rangle$ the comparator, K the right-hand-side value associated to the comparator, and Sum the result of the sum over the variables. For each comparator, the gap is defined according to the distance as follows:

- * if $\langle \rangle$ is `==` : $\text{gap} = \text{abs}(K - \text{Sum})$
- * if $\langle \rangle$ is `<=` : $\text{gap} = \max(0, \text{Sum} - K)$
- * if $\langle \rangle$ is `<` : $\text{gap} = \max(0, \text{Sum} - K - 1)$
- * if $\langle \rangle$ is `!=` : $\text{gap} = 1$ if $\text{Sum} \neq K$ and $\text{gap} = 0$ otherwise
- * if $\langle \rangle$ is `>` : $\text{gap} = \max(0, K - \text{Sum} + 1)$;
- * if $\langle \rangle$ is `>=` : $\text{gap} = \max(0, K - \text{Sum})$;

Warning

The decomposition of `wsum` and `wvarsum` may use an exponential size (sum of domain sizes).

list_size1 and *list_size2* must be equal in *ssame*.

Cost functions defined in intention cannot be shared.

Note

More about network-based global cost functions can be found here <https://metivier.users.greyc.fr/decomposable/>

Examples:

- quadratic cost function $x_0 * x_1$ in extension with variable domains $\{0, 1\}$ (equivalent to a soft clause $\neg x_0 \vee \neg x_1$):

```
2 0 1 0 1 1 1 1
```

- simple arithmetic hard constraint $x_1 < x_2$:

```
2 1 2 -1 < 0 0
```

- hard temporal disjunction $x_1 \geq x_2 + 2 \vee x_2 \geq x_1 + 1$:

```
2 1 2 -1 disj 1 2 UB
```

- `soft_alldifferent`($\{x_0, x_1, x_2, x_3\}$):

```
4 0 1 2 3 -1 salldiff var 1
```

- `soft_gcc`($\{x_1, x_2, x_3, x_4\}$) with each value v from 1 to 4 only appearing at least $v-1$ and at most $v+1$ times:

```
4 1 2 3 4 -1 sgcc var 1 4 1 0 2 2 1 3 3 2 4 4 3 5
```

- `soft_same`($\{x_0, x_1, x_2, x_3\}, \{x_4, x_5, x_6, x_7\}$):

```
8 0 1 2 3 4 5 6 7 -1 ssame 1 4 4 0 1 2 3 4 5 6 7
```

- `soft_regular`($\{x_1, x_2, x_3, x_4\}$) with DFA $(3^*) + (4^*)$:

```
4 1 2 3 4 -1 sregular var 1 2 1 0 2 0 1 3 0 3 0 0 4 1 1 4 1
```

- `soft_grammar`($\{x_0, x_1, x_2, x_3\}$) with hard cost (1000) producing well-formed parenthesis expressions:

```
4 0 1 2 3 -1 sgrammardp var 1000 4 2 0 6 1 0 0 0 1 0 1 2 1 0 1 3 1 2 0 3 0 1 0 0 3 1
```

- `soft_among`($\{x_1, x_2, x_3, x_4\}$) with hard cost (1000) if $\sum_{i=1}^4 (x_i \in \{1, 2\}) < 1$ or $\sum_{i=1}^4 (x_i \in \{1, 2\}) > 3$:

```
4 1 2 3 4 -1 samongdp var 1000 1 3 2 1 2
```

- `soft_max`($\{x_0, x_1, x_2, x_3\}$) with cost equal to $\max_{i=0}^3 ((x_i! = i)?1000 : (4 - i))$:


```
4 0 1 2 3 -1 smaxdp 1000 4 0 0 4 1 1 3 2 2 2 3 3 1
```

- wregular($\{x_0, x_1, x_2, x_3\}$) with DFA $(0(10)^*2^*)$:

```
4 0 1 2 3 -1 wregular 3 1 0 0 1 2 0 9 0 0 1 0 0 1 1 1 0 2 1 1 1 1 0 0 1 0 0 1 1 2 0 1 1 2 2 0 1 0 2 1 1 1 2
1
```

- wamong ($\{x_1, x_2, x_3, x_4\}$) with hard cost (1000) if $\sum_{i=1}^4 (x_i \in \{1, 2\}) < 1$ or $\sum_{i=1}^4 (x_i \in \{1, 2\}) > 3$:

```
4 1 2 3 4 -1 wamong hard 1000 2 1 2 1 3
```

- wvamong ($\{x_1, x_2, x_3, x_4\}$) with hard cost (1000) if $\sum_{i=1}^3 (x_i \in \{1, 2\}) \neq x_4$:

```
4 1 2 3 4 -1 wvamong hard 1000 2 1 2
```

- woverlap($\{x_1, x_2, x_3, x_4\}$) with hard cost (1000) if $\sum_{i=1}^2 (x_i = x_{i+2}) \geq 1$:

```
4 1 2 3 4 -1 woverlap hard 1000 < 1
```

- wsum ($\{x_1, x_2, x_3, x_4\}$) with hard cost (1000) if $\sum_{i=1}^4 (x_i) \neq 4$:

```
4 1 2 3 4 -1 wsum hard 1000 == 4
```

- wvarsum ($\{x_1, x_2, x_3, x_4\}$) with hard cost (1000) if $\sum_{i=1}^3 (x_i) \neq x_4$:

```
4 1 2 3 4 -1 wvarsum hard 1000 ==
```

Latin Square 4 x 4 crisp CSP example in wcsp format:

```
latin4 16 4 8 1
4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
4 0 1 2 3 -1 salldiff var 1
4 4 5 6 7 -1 salldiff var 1
4 8 9 10 11 -1 salldiff var 1
4 12 13 14 15 -1 salldiff var 1
4 0 4 8 12 -1 salldiff var 1
4 1 5 9 13 -1 salldiff var 1
4 2 6 10 14 -1 salldiff var 1
4 3 7 11 15 -1 salldiff var 1
```

4-queens binary weighted CSP example with random unary costs in wcsp format:

```
4-4QUEENS 4 4 10 5
4 4 4 4
2 0 1 0 10
0 0 5
0 1 5
1 0 5
1 1 5
1 2 5
2 1 5
2 2 5
2 3 5
3 2 5
3 3 5
2 0 2 0 8
0 0 5
0 2 5
1 1 5
```

```

1 3 5
2 0 5
2 2 5
3 1 5
3 3 5
2 0 3 0 6
0 0 5
0 3 5
1 1 5
2 2 5
3 0 5
3 3 5
2 1 2 0 10
0 0 5
0 1 5
1 0 5
1 1 5
1 2 5
2 1 5
2 2 5
2 3 5
3 2 5
3 3 5
2 1 3 0 8
0 0 5
0 2 5
1 1 5
1 3 5
2 0 5
2 2 5
3 1 5
3 3 5
2 2 3 0 10
0 0 5
0 1 5
1 0 5
1 1 5
1 2 5
2 1 5
2 2 5
2 3 5
3 2 5
3 3 5
1 0 0 2
1 1
3 1
1 1 0 2
1 1
2 1
1 2 0 2
1 1
2 1
1 3 0 2
0 1
2 1

```

6.2 UAI and LG formats (.uai, .LG)

It is a simple text file format specified below to describe probabilistic graphical model instances. The format is a generalization of the Ergo file format initially developed by Noetic Systems Inc. for their Ergo software.

- **Structure**

A file in the UAI format consists of the following two parts, in that order:

<Preamble>

<Function tables>

The contents of each section (denoted < ... > above) are described in the following:

- **Preamble**

The preamble starts with one line denoting the type of network. This will be either BAYES (if the network is a Bayesian network) or MARKOV (in case of a Markov network). This is followed by a line containing the number of variables. The next line specifies each variable's domain size, one at a time, separated by whitespace (note that this implies an order on the variables which will be used throughout the file).

The fourth line contains only one integer, denoting the number of functions in the problem (conditional probability tables for Bayesian networks, general factors for Markov networks). Then, one function per line, the scope of each function is given as follows: The first integer in each line specifies the size of the function's scope, followed by the actual indexes of the variables in the scope. The order of this list is not restricted, except when specifying a conditional probability table (CPT) in a Bayesian network, where the child variable has to come last. Also note that variables are indexed starting with 0.

For instance, a general function over variables 0, 5 and 11 would have this entry:

```
3 0 5 11
```

A simple Markov network preamble with three variables and two functions might for instance look like this:

```
MARKOV
3
2 2 3
2
2 0 1
3 0 1 2
```

The first line denotes the Markov network, the second line tells us the problem consists of three variables, let's refer to them as X, Y, and Z. Their domain size is 2, 2, and 3 respectively (from the third line). Line four specifies that there are 2 functions. The scope of the first function is X,Y, while the second function is defined over X,Y,Z.

An example preamble for a Belief network over three variables (and therefore with three functions) might be:

```
BAYES
3
2 2 3
3
1 0
2 0 1
2 1 2
```

The first line signals a Bayesian network. This example has three variables, let's call them X, Y, and Z, with domain size 2, 2, and 3, respectively (from lines two and three). Line four says that there are 3 functions (CPTs in

this case). The scope of the first function is given in line five as just X (the probability $P(X)$), the second one is defined over X and Y (this is $(Y \mid X)$). The third function, from line seven, is the CPT $P(Z \mid Y)$. We can therefore deduce that the joint probability for this problem factors as $P(X,Y,Z) = P(X).P(Y \mid X).P(Z \mid Y)$.

- **Function tables**

In this section each function is specified by giving its full table (i.e, specifying the function value for each tuple). The order of the functions is identical to the one in which they were introduced in the preamble.

For each function table, first the number of entries is given (this should be equal to the product of the domain sizes of the variables in the scope). Then, one by one, separated by whitespace, the values for each assignment to the variables in the function's scope are enumerated. Tuples are implicitly assumed in ascending order, with the last variable in the scope as the 'least significant'.

To illustrate, we continue with our Bayesian network example from above, let's assume the following conditional probability tables:

X	$P(X)$	
0	0.436	
1	0.564	

X	Y	$P(Y X)$
0	0	0.128
0	1	0.872
1	0	0.920
1	1	0.080

Y	Z	$P(Z Y)$
0	0	0.210
0	1	0.333
0	2	0.457
1	0	0.811
1	1	0.000
1	2	0.189

The corresponding function tables in the file would then look like this:

```

2
0.436 0.564

4
0.128 0.872
0.920 0.080

6
0.210 0.333 0.457
0.811 0.000 0.189

```

(Note that line breaks and empty lines are effectively just whitespace, exactly like plain spaces " ". They are used here to improve readability.)

In the LG format, probabilities are replaced by their logarithm.

- **Summary**

To sum up, a problem file consists of 2 sections: the preamble and the full the function tables, the names and the labels.

For our Markov network example above, the full file could be:

```

MARKOV
3
2 2 3
2
2 0 1
3 0 1 2

4
4.000 2.400
1.000 0.000

12
2.2500 3.2500 3.7500
0.0000 0.0000 10.0000
1.8750 4.0000 3.3330
2.0000 2.0000 3.4000

```

Here is the full Bayesian network example from above:

```

BAYES
3
2 2 3
3
1 0
2 0 1
2 1 2

2
0.436 0.564

4
0.128 0.872
0.920 0.080

6
0.210 0.333 0.457
0.811 0.000 0.189

```

- **Expressing evidence**

Evidence is specified in a separate file. This file has the same name as the original problems file but an added .evid extension at the end. For instance, problem.uai will have evidence in problem.uai.evid.

The file simply starts with a line specifying the number of evidence variables. This is followed by the pairs of variable and value indexes for each

observed variable, one pair per line. The indexes correspond to the ones implied by the original problem file.

If, for our above example, we want to specify that variable Y has been observed as having its first value and Z with its second value, the file example.uai.evid would contain the following:

```
2
1 0
2 1
```

6.3 Partial Weighted MaxSAT format

Max-SAT input format (.cnf)

The input file format for Max-SAT will be in DIMACS format:

```
c
c comments Max-SAT
c
p cnf 3 4
1 -2 0
-1 2 -3 0
-3 2 0
1 3 0
```

- The file can start with comments, that is lines beginning with the character 'c'.
- Right after the comments, there is the line "p cnf nbvar nbclauses" indicating that the instance is in CNF format; nbvar is the number of variables appearing in the file; nbclauses is the exact number of clauses contained in the file.
- Then the clauses follow. Each clause is a sequence of distinct non-null numbers between -nbvar and nbvar ending with 0 on the same line. Positive numbers denote the corresponding variables. Negative numbers denote the negations of the corresponding variables.

Weighted Max-SAT input format (.wcnf)

In Weighted Max-SAT, the parameters line is "p wcnf nbvar nbclauses". The weights of each clause will be identified by the first integer in each clause line. The weight of each clause is an integer greater than or equal to 1.

Example of Weighted Max-SAT formula:

```
c
c comments Weighted Max-SAT
c
p wcnf 3 4
10 1 -2 0
3 -1 2 -3 0
8 -3 2 0
5 1 3 0
```

Partial Max-SAT input format (.wcnf)

In Partial Max-SAT, the parameters line is "p wcnf nbvar nbclauses top". We associate a weight with each clause, which is the first integer in the clause. Weights must be greater than or equal to 1. Hard clauses have weight top and soft clauses have weight 1. We assume that top is a weight always greater than the sum of the weights of violated soft clauses.

Example of Partial Max-SAT formula:

```
c
c comments Partial Max-SAT
c
p wcnf 4 5 15
15 1 -2 4 0
15 -1 -2 3 0
1 -2 -4 0
1 -3 2 0
1 1 3 0
```

Weighted Partial Max-SAT input format (.wcnf)

In Weighted Partial Max-SAT, the parameters line is "p wcnf nbvar nbclauses top". We associate a weight with each clause, which is the first integer in the clause. Weights must be greater than or equal to 1. Hard clauses have weight top and soft clauses have a weight smaller than top. We assume that top is a weight always greater than the sum of the weights of violated soft clauses.

Example of Weighted Partial Max-SAT formula:

```
c
c comments Weighted Partial Max-SAT
c
p wcnf 4 5 16
16 1 -2 4 0
16 -1 -2 3 0
8 -2 -4 0
4 -3 2 0
3 1 3 0
```

6.4 QPBO format (.qpbo)

In the quadratic pseudo-Boolean optimization (unconstrained quadratic programming) format, the goal is to minimize or maximize the quadratic function:

$$X' * W * X = \sum_{i=1}^N \sum_{j=1}^N W_{ij} * X_i * X_j$$

where W is a symmetric squared $N \times N$ matrix expressed by all its non-zero half ($i \leq j$) squared matrix coefficients, X is a vector of N binary variables with domain values in $\{0, 1\}$ or $\{1, -1\}$, and X' is the transposed vector of X .

Note that for two indices $i \neq j$, coefficient $W_{ij} = W_{ji}$ (symmetric matrix) and it appears twice in the previous sum. Note also that coefficients can be positive or negative and are real float numbers. They are converted to fixed-point real numbers by multiplying them by $10^{\text{precision}}$ (see option *-precision* to modify it, default value is 7). Infinite coefficients are forbidden.

Notice that depending on the sign of the number of variables in the first text line, the domain of all variables is either $\{0, 1\}$ or $\{1, -1\}$.

Warning! The encoding in Weighted CSP of variable domain $\{1, -1\}$ associates for each variable value the following index: value 1 has index 0 and value -1 has index 1 in the solutions found by `toulbar2`. The encoding of variable domain $\{0, 1\}$ is direct.

Qpbo is a file text format:

- First line contains the number of variables N and the number of non-zero coefficients M .

If N is negative then domain values are in $\{1, -1\}$, otherwise $\{0, 1\}$. If M is negative then it will maximize the quadratic function, otherwise it will minimize it.

- Followed by $|M|$ lines where each text line contains three values separated by spaces: position index i (integer belonging to $[1, |N|]$), position index j (integer belonging to $[1, |N|]$), coefficient W_{ij} (float number) such that $i \leq j$ and $W_{ij} \neq 0$

6.5 Linkage format (.pre)

See `mendelsoft` companion software at <http://www.inra.fr/mia/T/MendelSoft> for pedigree correction. See also <https://carlit.toulouse.inra.fr/cgi-bin/awki.cgi/HaplotypeInference> for haplotype inference in half-sib families.

7 Using it as a library

See `TOULBAR2` reference manual which describes the `libtb2.so` C++ library API.

8 Using it from Python/Numberjack

See <http://numberjack.ucc.ie>.

References

- [1] D Allouche, C Bessiere, P Boizumault, S de Givry, P Gutierrez, S Loudni, JP Métivier, and T Schiex. Decomposing global cost functions. In *Proc. of AAAI-12*, Toronto, Canada, 2012. <http://www.inra.fr/mia/T/degivry/Ficolof2012poster.pdf> (poster).
- [2] D Allouche, S de Givry, G Katsirelos, T Schiex, and M Zytnicki. Anytime Hybrid Best-First Search with Tree Decomposition for Weighted CSP. In *Proc. of CP-15*, pages 12–28, Cork, Ireland, 2015.

- [3] David Allouche, Christian Bessière, Patrice Boizumault, Simon de Givry, Patricia Gutierrez, Jimmy H.M. Lee, Ka Lun Leung, Samir Loudni, Jean-Philippe Métivier, Thomas Schiex, and Yi Wu. Tractability-preserving transformations of global cost functions. *Artificial Intelligence*, 238:166–189, 2016.
- [4] David Allouche, Jessica Davies, Simon de Givry, George Katsirelos, Thomas Schiex, Seydou Traoré, Isabelle André, Sophie Barbe, Steve Prestwich, and Barry O’Sullivan. Computational protein design as an optimization problem. *Artificial Intelligence*, 212:59–79, 2014.
- [5] Frédéric Boussemart, Fred Hemery, Christophe Lecoutre, and Lakhdar Sais. Boosting systematic search by weighting constraints. In *ECAI*, volume 16, page 146, 2004.
- [6] M. Cooper, S. de Givry, M. Sanchez, T. Schiex, and M. Zytnicki. Virtual arc consistency for weighted csp. In *Proc. of AAAI-08*, Chicago, IL, 2008.
- [7] M. Cooper, S. de Givry, M. Sanchez, T. Schiex, M. Zytnicki, and T. Werner. Soft arc consistency revisited. *Artificial Intelligence*, 174(7–8):449–478, 2010.
- [8] M C. Cooper. Reduction operations in fuzzy or valued constraint satisfaction. *Fuzzy Sets and Systems*, 134(3):311–342, 2003.
- [9] S de Givry, S Prestwich, and B O’Sullivan. Dead-End Elimination for Weighted CSP. In *Proc. of CP-13*, pages 263–272, Uppsala, Sweden, 2013.
- [10] S. de Givry, T. Schiex, and G. Verfaillie. Exploiting Tree Decomposition and Soft Local Consistency in Weighted CSP. In *Proc. of AAAI-06*, Boston, MA, 2006.
- [11] S. de Givry, M. Zytnicki, F. Heras, and J. Larrosa. Existential arc consistency: Getting closer to full arc consistency in weighted CSPs. In *Proc. of IJCAI-05*, pages 84–89, Edinburgh, Scotland, 2005.
- [12] A. Favier, S. de Givry, and P. Jégou. Exploiting problem structure for solution counting. In *Proc. of CP-09*, pages 335–343, Lisbon, Portugal, 2009.
- [13] A Favier, S de Givry, A Legarra, and T Schiex. Pairwise decomposition for combinatorial optimization in graphical models. In *Proc. of IJCAI-11*, Barcelona, Spain, 2011. Video demonstration at <http://www.inra.fr/mia/T/degivry/Favier11.mov>.
- [14] W. D. Harvey and M. L. Ginsberg. Limited discrepancy search. In *Proc. of IJCAI-95*, Montréal, Canada, 1995.
- [15] B Hurley, B O’Sullivan, D Allouche, G Katsirelos, T Schiex, M Zytnicki, and S de Givry. Multi-Language Evaluation of Exact Solvers in Graphical Model Discrete Optimization. *Constraints*, 21(3):413–434, 2016.

- [16] D Koller and N Friedman. *Probabilistic graphical models: principles and techniques*. The MIT Press, 2009.
- [17] J. Larrosa. Boosting search with variable elimination. In *Principles and Practice of Constraint Programming - CP 2000*, volume 1894 of *LNCS*, pages 291–305, Singapore, September 2000.
- [18] J. Larrosa. On arc and node consistency in weighted CSP. In *Proc. AAAI’02*, pages 48–53, Edmondston, (CA), 2002.
- [19] J. Larrosa and T. Schiex. In the quest of the best form of local consistency for weighted CSP. In *Proc. of the 18th IJCAI*, pages 239–244, Acapulco, Mexico, August 2003.
- [20] C. Lecoutre, L Saïs, S. Tabary, and V. Vidal. Reasoning from last conflict(s) in constraint programming. *Artificial Intelligence*, 173:1592,1614, 2009.
- [21] J. H. M. Lee and K. L. Leung. Towards Efficient Consistency Enforcement for Global Constraints in Weighted Constraint Satisfaction. In *Proceedings of IJCAI’09*, pages 559–565, 2009.
- [22] J. H. M. Lee and K. L. Leung. A Stronger Consistency for Soft Global Constraints in Weighted Constraint Satisfaction. In *Proceedings of AAAI’10*, pages 121–127, 2010.
- [23] J. H. M. Lee and K. L. Leung. Consistency Techniques for Global Cost Functions in Weighted Constraint Satisfaction. *Journal of Artificial Intelligence Research*, 43:257–292, 2012.
- [24] Bertrand Neveu, Gilles Trombettoni, and Fred Glover. Id walk: A candidate list strategy with a simple diversification device. In *Proc. of CP*, pages 423–437, Toronto, Canada, 2004.
- [25] Abdelkader Ouali, David Allouche, Simon de Givry, Samir Loudni, Yahia Lebbah, Francisco Eckhardt, and Lakhdar Loukil. Iterative Decomposition Guided Variable Neighborhood Search for Graphical Model Energy Minimization. In *Proc. of UAI-17*, pages 550–559, Sydney, Australia, 2017.
- [26] M Sanchez, D Allouche, S de Givry, and T Schiex. Russian doll search with tree decomposition. In *Proc. of IJCAI’09*, Pasadena (CA), USA, 2009. http://www.inra.fr/mia/T/degivry/rdsbtd_ijcai09_sdg.ppt.
- [27] T. Schiex. Arc consistency for soft constraints. In *Principles and Practice of Constraint Programming - CP 2000*, volume 1894 of *LNCS*, pages 411–424, Singapore, September 2000.
- [28] G. Verfaillie, M. Lemaître, and T. Schiex. Russian doll search. In *Proc. of AAAI-96*, pages 181–187, Portland, OR, 1996.