



ANSI E1.37-2 – 2015
Entertainment Technology—
Additional Message Sets for ANSI E1.20 (RDM) –
Part 2, IPv4 & DNS Configuration Messages

Document number CP/2012-1001r7

This standard was approved as an American National Standard by ANSI's Board of Standards Review on 25 September 2015.

This standard was originally published when the Entertainment Services and Technology Association was operating under the name of PLASA North America. ESTA has reverted to its original name, and this document has been rebranded with the current corporate name and logo. No changes have been made to the contents of the standard.

Copyright © 2017 ESTA
630 Ninth Avenue, Suite 609
New York, NY 10036, USA.
All rights reserved.

NOTICE and DISCLAIMER

ESTA does not approve, inspect, or certify any installations, procedures, equipment or materials for compliance with codes, recommended practices or standards. Compliance with a ESTA standard or an American National Standard developed by ESTA is the sole and exclusive responsibility of the manufacturer or provider and is entirely within their control and discretion. Any markings, identification or other claims of compliance do not constitute certification or approval of any type or nature whatsoever by ESTA.

ESTA neither guarantees nor warrants the accuracy or completeness of any information published herein and disclaims liability for any personal injury, property or other damage or injury of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document. In issuing and distributing this document.

In issuing this document, ESTA does not either (a) undertake to render professional or other services for or on behalf of any person or entity, or (b) undertake any duty to any person or entity with respect to this document or its contents. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstance.

Published by:

Entertainment Services and Technology Association
630 Ninth Avenue, Suite 609
New York, NY 10036
USA
Phone: 1-212-244-1505
Fax: 1-212-244-1502
standards@esta.org

The ESTA Technical Standards Program

The ESTA Technical Standards Program was created to serve the ESTA membership and the entertainment industry in technical standards related matters. The goal of the Program is to take a leading role regarding technology within the entertainment industry by creating recommended practices and standards, monitoring standards issues around the world on behalf of our members, and improving communications and safety within the industry. ESTA works closely with the technical standards efforts of other organizations within our industry, including USITT and VPLT, as well as representing the interests of ESTA members to ANSI, UL, and the NFPA. The Technical Standards Program is accredited by the American National Standards Institute.

The Technical Standards Council (TSC) was established to oversee and coordinate the Technical Standards Program. Made up of individuals experienced in standards-making work from throughout our industry, the Council approves all projects undertaken and assigns them to the appropriate working group. The Technical Standards Council employs a Technical Standards Manager to coordinate the work of the Council and its working groups as well as maintain a “Standards Watch” on behalf of members. Working groups include: Control Protocols, Electrical Power, Event Safety, Floors, Fog and Smoke, Followspot Position, Photometrics, Rigging, and Stage Lifts.

ESTA encourages active participation in the Technical Standards Program. There are several ways to become involved. If you would like to become a member of an existing working group, as have over four hundred people, you must complete an application which is available from the ESTA office. Your application is subject to approval by the working group and you will be required to actively participate in the work of the group. This includes responding to letter ballots and attending meetings. Membership in ESTA is not a requirement. You can also become involved by requesting that the TSC develop a standard or a recommended practice in an area of concern to you.

The Control Protocols Working Group, which authored this Standard, consists of a cross section of entertainment industry professionals representing a diversity of interests. ESTA is committed to developing consensus-based standards and recommended practices in an open setting.

Investors in Innovation**VISIONARY**

Altman Lighting, Inc.
Boston Illumination group
Candela Controls Inc.
Clark-Reder Engineering
LDI
John T. McGraw

ProSight Specialty Insurance
Alan M. Rowe
Theatre Safety Programs
United States Institute for Theatre
Technology
View One, Inc.
Steve A. Walker & Associates*
Ralph Weber

INVESTOR

Barbizon Electric
Louis Bradfield*
EGI Event Production Services*
ETC
Indianapolis Stage Sales & Rentals, Inc.*

H&H Specialties, Inc.
Ken Production Services Inc.
McLaren Engineering Group
Mountain Productions Inc.
Texas Scenic Company

SUPPORTER

AC Power Distribution
American Society of Theatre Consultants
Arjan van Vught
Roy Bickel
Bigger Hammer Production Services
ELS / Entertainment Lighting Services
Entertainment Structures Group
Tony Giovannetti
IATSE Local 514
IATSE Local 728
InCord
Jones-Phillips Associates, LLC
The Kentucky Center for the Performing
Arts

Eddie Kramer
Lightstream Design, LLC
Musique Xpress Lights, Inc.*
Oasis Stage Werks
See Factor Industry
Stage Equipment and Lighting
Stage Labor of the Ozarks
Strohmeier Lighting, Inc.
TOMCAT
Total Structures*
Stephen Vanciel
Vincent Lighting Systems*

*Investor for over 15 years

All donations to the TSP support the Technical Standards Program in general and are not directed to or for the benefit of any particular technical standard project or any Working Group working on any particular standard or project.

Contact Information**Technical Standards Manager**

Karl G. Ruling
Entertainment Services and Technology Association
630 Ninth Avenue, Suite 609
New York, NY 10036
USA
1-212-244-1505
karl.ruling@esta.org

Assistant Technical Standards Manager

Erin Grabe
Entertainment Services and Technology Association
630 Ninth Avenue, Suite 609
New York, NY 10036
USA
1-212-244-1505
erin.grabe@esta.org

Technical Standards Council Chairpersons

Mike Garl
Mike Garl Consulting LLC
1-865-389-4371
mike@mikegarlconsulting.com

Mike Wood
Mike Wood Consulting LLC
1-512-288-4916
mike@mikewoodconsulting.com

Control Protocols Working Group Chairperson

Michael Lay
Philips Color Kinetics
3 Burlington Woods Drive
Burlington, MA 01803
USA
1-781-418-9145
michael.lay@philips.com

Acknowledgments

The Control Protocols Working Group members when this document was approved by the working group on 25 September 2015 are shown below.

Voting members:

Daniel W. Antonuk; Electronic Theatre Controls, Inc.; MP
Paul Beasley; Walt Disney Company; U
Robert Bell; Acuity Brands Inc.; MP
Marcus Bengtsson; LumenRadio AB; MP
Scott M. Blair; Full Throttle Films/ VER; DR
Ian Campbell; Doug Fleenor Design, Inc.; MP
Milton Davis; Doug Fleenor Design, Inc.; MP
Casey Diers; DesignLab Chicago, Inc.; DR
Gary Douglas; Acuity Brands Inc.; MP
Bill Ellis; Candela Controls, Inc.; DE
Doug Fleenor; Doug Fleenor Design, Inc.; MP
Randy L. Fox; Walt Disney Company; U
Andrew Frazer; Stellasclapes.com; MP
Robert Goddard; Goddard Design Co.; MP
Dennis Grow; I.A.T.S.E. Local 728; U
Mitch Hefter; USITT; U
Jeremy Hochman; Full Throttle Films/ VER; DR
Harrison Hohnholt; City Theatrical, Inc.; MP
Maurits van der Hoorn; Acuity Brands Inc.; MP
John Huntington; I.A.T.S.E. Local 1; U
Michael Karlsson; LumenRadio AB; MP
Paul Kleissler; City Theatrical, Inc.; MP
Edwin S. Kramer; I.A.T.S.E. Local 1; U
Ulrich Kunkel; E3 Engineering & Education for Entertainment GmbH; U
Roger Lattin; I.A.T.S.E. Local 728; U
Hans Lau; LumenRadio AB; MP
Michael Lay; Royal Philips; MP
Joshua Liposky; Lex Products Corp.; CP
Dan Lisowski; University of Wisconsin - Madison; DE
Kevin Loewen; Acuity Brands Inc.; MP
Tyrone Mellon, Jr.; Lex Products Corp.; CP
Joshua Moyerman; Stellasclapes.com; MP
Peter Newman; Open Lighting Project; G

Downloaded from TSP.ESTA.ORG - Free download courtesy of ProSight Specialty Insurance

Simon Newton; Open Lighting Project; G
Maya Nigrosh; Electronic Theatre Controls, Inc.; MP
Andrew Nikel; City Theatrical, Inc.; MP
Kimberly Corbett Oates; Schuler Shook; DE
Claude Ostyn; Full Throttle Films/ VER; DR
Edward A. (Ted) Paget; Electronic Theatre Controls, Inc.; MP
Jason Potterf; Cisco; MP
Alan M. Rowe; I.A.T.S.E. Local 728; U
Larry Schoeneman; DesignLab Chicago, Inc.; DR
Dane Styczynski; University of Wisconsin - Madison; DE
Steve Terry; Electronic Theatre Controls, Inc.; MP
Ken Vannice; Ken Vannice LLC; G
Peter Willis; Howard Eaton Lighting Ltd.; CP

Observer members:

Christian Allabauer; Lighting Innovations, Hermann Sorger GmbH; CP
Simon Alpert; Lighttech Event Technologies; CP
Klaus Amling; Licht-Technik; MP
Matthew Ardine; IATSE Local 728; U
Robert Barbagallo; Solotech Inc.; U
Adam Bennette; Electronic Theatre Controls, Inc.; MP
David Bertenshaw; David Bertenshaw; G
Stephen Bickford; T. Kondos Associates; U
Torrey Bievenour; Vision Quest Lighting; G
Lee J. Bloch; Bloch Design Group, Inc.; G
David A. Boller; Organic Machines LLC; CP
Ron Bonner; PLASA EU; G
Stef Bressers; MagicFX B.V.; MP
André Broucke; André Broucke; G
Ken Bruns; Lumenpulse Lighting Inc.; MP
Justyn Butler; JBOTS; CP
Jean-Francois Canuel; A.C. Lighting Ltd.; CP
Steve Carlson; High Speed Design, Inc.; MP
Sang-Il Choi; Kyungpook National University; G
Jon Chuchla; Audio Visual Systems, Inc.; G
Soo-Myong Chung; Bloch Design Group, Inc.; G
Paul J. Clark; HxDx; CP
Edward R. Condit; Edward R. Condit; G
Fraser Connolly; Artistic Licence Holdings; DE
Eric Cornwell; West Side Systems; U

Stuart Cotts; Oregon Shakespeare Festival; U
Klas Dalbjorn; TC Group; MP
Ben Darrington; Wireless Solutions Sweden AB; MP
Jeremy Day; Lumenpulse Lighting Inc.; MP
Gilray Densham; CAST Group Inc; MP
Larry Dew; W.A. Benjamin Electric Co.; DE
Gary Dove; Dove Systems; MP
Tucker Downs; Tucker Downs; U
Yongshun Duan; Macostar International Ltd.; CP
Hamish Dumbreck; James Embedded Systems Engineering; MP
Lauren E. Dunn; Lauren E. Dunn (Larry); DE
Jerry Durand; Durand Interstellar, Inc.; CP
James Eade; ABTT; G
Andrew Eales; Rhodes University ; U
Matthew Earnshaw; acdc LED Ltd.; MP
Paul K. Ericson; Sparling & IES; DE
Jon R. Farley; Sixteenth Avenue Systems; CP
Martin Farnik; Robe Show Lighting s.r.o.; MP
Derek R. Flickinger; Interactive Homes, Inc.; U
Trevor Forrest; Helvar Lighting Control; MP
Howard Forryan; Harting KGAA; G
Steve Friedlander; Auerbach Pollock Friedlander; U
Ed Garstkiewicz; Harting KGAA; G
Jerry Gorrell; Theatre Safety Programs; G
Tom Grimes; Barco; MP
Rob Halliday; Rob Halliday; U
Sean Harding; High Output, Inc.; G
Douglas Heriot; Douglas Heriot; MP
Bill Hewlett; Hewlett Electronics; CP
Jim Holladay; Luxence; G
Wayne David Howell; Artistic Licence Holdings; DE
Il Soon Jang; Electronics and Telecommunications Research Institute; G
Sierk Janszen; Ground Zero; U
Eric Johnson; Eric Johnson; G
Rob Johnston; Interactive Technologies, Inc.; MP
Jussi Kallioinen; Eastway Sound & Lighting; U
Tae Gyu Kang; Electronics and Telecommunications Research Institute; G
Hyun Jong Kim; Electronics and Telecommunications Research Institute; G
Peter Kirkup; Peter Kirkup; G
Hiroshi Kita; Marumo Electric Co., Ltd.; MP

Phil Klapwyk; IATSE Local 891; U
Mark T. Kraft; Lehigh Electric Products Co.; MP
Kristen Kuipers; Newcomb & Boyd; DE
Jason Kyle; JPK Systems Ltd.; MP
Rick Leinen; Leviton Manufacturing Co., Inc.; MP
Hans Leiter; Electronic Theatre Controls, Inc.; MP
Jon Lenard; Applied Electronics; MP
Maarten Lepelaars; eldoLED; MP
Sang-Kyu Lim; Electronics and Telecommunications Research Institute; G
Mark Manthei; Shure Inc.; G
Paul F. Mardon; Pulsar Ltd.; MP
Mick Martin; ShowCAD Control Systems; MP
Paul Kenneth McEwan; Cooper Controls Ltd.; MP
Brian McKelvey; Brian McKelvey; G
John Mehlretter; Lehigh Electric Products Co.; MP
Jeff T. Miller; Walt Disney Company; U
Avraham "Avi" Mendall Mor; Lightswitch; U
John Musarra; John Musarra; U
Tobin Neis; Barbizon Companies; DR
Dan T. Nguyen; LynTec; MP
Lars F. Paape; Scientific Algorithms and Embedded Systems; U
Ben Peoples; Pittsburgh Hoist & Sandbag Company; CP
Gary Pritchard; LSC Lighting Systems PTY Ltd; MP
Torben Kaas Rasmussen; Martin Professional A/S; G
Charles Reese; Production Resource Group; DR
Charlie Richmond; Richmond Sound Design Ltd.; CP
Bernardo Benito Rico; Ben-Ri Electronica S.A.; MP
Steve Roberts; Carr & Angier; G
Erwin Rol; Erwin Rol; G
Dietmar Rottinghaus; Connex GmbH; MP
Richard Salzedo; Avolites Ltd.; MP
Yngve Sandboe; Sand Network Systems, Inc.; MP
Nicolai Gubi Schmidt; Gobo & Highlight A/S; DR
Martin Searancke; Dream Solutions Ltd.; MP
Ford Sellers; Chauvet Lighting; MP
John Sellers; AIM Northwest; G
Andrew Sherar; Lightmoves PLC; MP
Sean Sill; Open Lighting Project; G
Ashley Simper; TMB; DR
Storm K. Staley; Stormwerx; U

Eckart Steffens; Soundlight, the DMX Company; CP
Ralph Stillinger; Royal Philips; MP
Bart Swinnen; Luminex LCE; MP
Arnold Tang; Arnold Tang Productions; U
Geoffrey O. Thompson; IEEE 802.3/Nortel Networks; G
Christopher Tilton; Westlake Reed Leskosky; DE
Robert Timmerman; Royal Philips; MP
David Timmins; Jands Electronics; MP
Victoria Tisdale; Google Summer of Code 2013; G
J. B. Toby; Avolites Ltd.; MP
James Tomlinson; James Tomlinson; G
Bob Toms; Catalyst Microsystems LLC; G
Robert Tooker; Robert Tooker; U
Tad Trylski; Tad Trylski; U
Stephen J. Tyrrell; Quantum Logic; MP
Tracy Underhill; 4U Consulting; G
Steve Unwin; Pulsar Ltd.; MP
Samuli Valo; Picturall Ltd.; MP
Carlo Venturati; Clay Paky S.P.A.; MP
Will Wagner; Carallon Ltd.; MP
Oliver Waits; Avolites Ltd.; MP
John Warwick; Royal Philips; MP
Colin Waters; TMB; DR
Ralph Weber; ENDL Texas; G
Lars Wernlund; Capture Visualisation AB; MP
Michael (Mike) Whetstone; Integrated Theatre, Inc.; CP
Loren Wilton; Showman Systems; CP
C. S. Wong; Macostar International Ltd.; CP
Jiantong Wu; Beijing Special Engineering Design & Research Institute; G
Kehang Wu; Shure Inc.; G
David Yellin; LightMinded Industries, Inc.; MP
Larry Zoll; Zoll Design & Consulting, LLC; U

Interest category codes:

CP = Custom-market Producer
DE = Designer
DR = Dealer or Rental company
G = General interest
MP = Mass-market Producer
U = User

Downloaded from TSP.ESTA.ORG - Free download courtesy of ProSight Specialty Insurance

Table of Contents

NOTICE and DISCLAIMER.....	i
Contact Information.....	iv
Acknowledgments.....	v
1 Introduction.....	1
1.1 E1.20 Basic Features.....	1
1.2 Overview & Scope.....	1
2 Normative References.....	3
3 General.....	5
3.1 General.....	5
3.2 Sub-Device Handling.....	5
3.3 Text Field Handling.....	5
3.4 Byte Ordering.....	5
3.5 IP Addressing Modes.....	5
4 Parameter Messages.....	7
4.1 Get Interface List (LIST_INTERFACES).....	7
4.2 Get Interface Name (INTERFACE_LABEL).....	8
4.3 Get Hardware Address (INTERFACE_HARDWARE_ADDRESS_TYPE1).....	9
4.4 Get/Set DHCP (IPV4_DHCP_MODE).....	10
4.5 Get/Set Zeroconf Mode (IPV4_ZEROCONF_MODE).....	13
4.6 Get IPv4 Address / Netmask (IPV4_CURRENT_ADDRESS).....	15
4.7 Get/Set IPv4 Static Address (IPV4_STATIC_ADDRESS).....	17
4.8 Apply Interface Configuration (INTERFACE_APPLY_CONFIGURATION).....	20
4.9 Renew DHCP Lease (INTERFACE_RENEW_DHCP).....	21
4.10 Release DHCP Lease (INTERFACE_RELEASE_DHCP).....	23
4.11 Get/Set Default Route (IPV4_DEFAULT_ROUTE).....	24
4.12 Get/Set Name Servers (DNS_IPV4_NAME_SERVER).....	27
4.13 Get/Set Host Name (DNS_HOSTNAME).....	29
4.14 Get/Set Domain Name (DNS_DOMAIN_NAME).....	30
Appendix A: Defined Parameters (Normative).....	33
Appendix B: Example Message Exchange.....	35
Reading the Current State.....	35
Enabling DHCP.....	37
Static Configuration.....	38

Index of Tables

Table A-1: RDM Parameter ID Defines.....	33
Table A-2: Additional NACK Reason Codes*.....	34
Table A-3: DHCP Mode Defines.....	34

1 Introduction

1.1 E1.20 Basic Features

The ANSI E1.20 Remote Device Management Protocol (RDM) [RDM] permits intelligent bi-directional communication between devices from multiple manufacturers using a modified DMX512 data link. RDM is an EF 1.0 implementation of ANSI E1.11 (DMX512-A).

RDM permits a console or other controlling device to discover and then configure, monitor, and manage intermediate and end-devices connected through a DMX512 network. RDM provides intelligent control of devices on a DMX512 network.

RDM commands may also be sent over transports other than DMX512-A., for example, IPv4. The specification for sending RDM commands over non-DMX512-A transports is outside the scope of this standard.

1.2 Overview & Scope

This document provides additional Get/Set parameter messages (PIDs) for use with the ANSI E1.20 Remote Device Management protocol. Messages in this document are intended for configuring network interfaces, routing information and Domain Name System [DNS] settings on devices with IPv4 [IPv4] addresses.

The messages in this standard enable a controller to retrieve a list of network interfaces on a device, and for each interface, do the following:

- If appropriate, determine the EUI-48 hardware address [EUI]. Such addresses are commonly referred to as MAC addresses. Hardware addresses in a format other than EUI-48 are not covered by this standard.
- Retrieve and configure the IPv4 address & subnet mask. Addressing schemes other than IPv4 are outside the scope of this standard.
- Enable / disable DHCP [DHCPv4].
- Renew and release the DHCP lease.
- Enable and disable Zeroconf [IPv4LL].

Commands are also provided to:

- Set the hostname of the device.
- Set the DNS domain of the device.
- Set the DNS name servers of the device.
- Set the default IPv4 route of the device.

2 Normative References

[ARP-PARAMS] - Address Resolution Protocol (ARP) Parameters

[<http://www.iana.org/assignments/arp-parameters/arp-parameters.xhtml>]

This registry is maintained by:

Internet Engineering Task Force (IETF) Secretariat
c/o Association Management Solutions, LLC (AMS)
48377 Fremont Blvd., Suite 117
Fremont, California 94538
USA
+1-510-492-4080
<http://www.ietf.org>

[DHCPv4] RFC 2131 - Dynamic Host Configuration Protocol. 1997.

[<http://tools.ietf.org/html/rfc2131>]

This standard is maintained by the IETF.

[DNS] RFC 1035 - Domain Names – Implementation and Specification. 1987.

[<http://tools.ietf.org/html/rfc1035>].

This standard is maintained by the IETF. This standard has been updated, please see the link for the relevant updates.

[DNS-CLARIFICATIONS] RFC 2181 - Clarifications to the DNS Specification. 1997.

[<http://tools.ietf.org/html/rfc2181>]

This standard is maintained by the IETF.

[EUI] Guidelines for use of a 48-bit Extended Unique Identifier (EUI-48™) [<http://standards.ieee.org/develop/regauth/tut/eui48.pdf>]

This document is maintained by:

IEEE Operations Center
445 Hoes Lane
Piscataway, NJ 08854-4141
USA
+1-732-981-0060
<http://standards.ieee.org/>

[HOST—NAME] RFC 1123 - Requirements for Internet Hosts -Application and Support. 1989.
[<http://tools.ietf.org/html/rfc1123>]

This standard is maintained by the IETF.

[IDNA] RFC 3490 - Internationalizing Domain Names in Applications. 2003.
[<http://tools.ietf.org/html/rfc3490>]

This standard is maintained by the IETF.

[IPv4] RFC 791– Internet Protocol. 1999.
[<http://tools.ietf.org/html/rfc791>]

This standard is maintained by the IETF. This standard is commonly referred to as Internet Protocol Version 4.

[IPv4LL] RFC 3927– Dynamic Configuration of IPv4 Link-Local Addresses. 2005.
[<http://tools.ietf.org/html/rfc3927>]

This standard is maintained by the IETF.

[RDM] ANSI E1.20 Entertainment Technology – Remote Device Management over DMX512 networks.

This standard is maintained by ESTA.

3 General

3.1 General

These parameter messages are intended for configuring IPv4 network interfaces, the default IPv4 route, the Domain Name System [DNS] servers, the device's hostname, and the device's domain name.

They are for general purpose use across any type of device and not limited to any specific class of products.

3.2 Sub-Device Handling

Refer to ANSI E1.20 Section 9 for information on Sub-Device usage. This document does not change or modify the requirements stated in ANSI E1.20. Requirements stated in this document are in addition to the stated ANSI E1.20 requirements.

3.3 Text Field Handling

Text field encoding shall conform to Section 10.1 in [RDM]. Where the parameter data contains both a text field and one or more fixed length fields, the parameter data length shall be the sum of the size of the fixed length fields as well as the actual size of the text string being sent.

3.4 Byte Ordering

All multi-byte data shall be transmitted as specified in Section 6.1 of [RDM]. This includes IPv4 Addresses.

3.5 IP Addressing Modes

Three IPv4 address configuration modes are provided: static configuration, DHCP [DHCPv4] and Zeroconf [IPv4LL]. The IP Addresses used for an interface shall be determined by:

- If a static address is configured, it shall be used.
- If no static address is configured, and DHCP mode is enabled, the device shall attempt to acquire an address for the interface using DHCP.

- If no static address is configured, and DHCP failed to provide an address (or was disabled / unsupported) a link local address shall be used if Zeroconf mode is enabled.
- If none of the above provided an address, the interface shall remain unconfigured.

If DHCP mode is enabled and no address was obtained using DHCP, the device shall retry the DHCP process again at a later time. Devices should retry no more than once every 5 minutes.

Per Section 4.4.5 of [DHCPv4], if a DHCP lease expires before the device receives a positive acknowledgment of renewal (DHCPACK) it must stop using the previous address. If Zeroconf mode is enabled the device shall switch to a link local address, and retry DHCP requests as described above.

4 Parameter Messages

4.1 Get Interface List (LIST_INTERFACES)

This parameter returns a packed list of network interface descriptors, representing the IPv4 network interfaces on the device.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) LIST_INTERFACES	(PDL) 0x00
(PD) Not Present		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RES PONSE	(PID) LIST_INTERFACES	Variable (0x00 – 0xE6)
(PD) Packed group of repeated interface descriptors (48 bits per interface) <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: fit-content;"> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px; width: 100%;">Interface Identifier (32-bit)</div> <div style="border: 1px solid black; padding: 5px; width: 100%;">Interface Hardware Type (16-bit)</div> </div>		

Data Description:

The data returned is a packed list of network interface descriptors. Each interface descriptor contains two fields, the *Interface Identifier* and the *Interface Hardware Type*.

The Interface Identifier is a 32-bit value which the controller will use to refer to the interface in other commands. The interface identifiers returned shall range from 1 to 0xFFFFFFFF00. Interface identifiers are not required to be contiguous.

The Interface Hardware Type field identifies the underlying hardware of the interface. The values are defined in [ARP-PARAMETERS] under the 'Hardware Types' section.

Devices may queue a GET LIST_INTERFACES response if the set of interfaces changes.

4.2 Get Interface Name (INTERFACE_LABEL)

This parameter is used to retrieve the label for a network interface.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) INTERFACE_LABEL	(PDL) 0x04
(PD) <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 80%;"> Interface Identifier (32-bit) </div>		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD	
(CC) GET_COMMAND_RESPONSE	(PID) INTERFACE_LABEL		Variable (0x04 – 0x24)
<div>(PD)</div> <div><div>Interface Identifier (32-bit)</div><div>ASCII text label. Up to 32 characters.</div></div>			

Data Description:

The data returned is an ASCII string of up to 32 characters, conforming to Section 3.3.

4.3 Get Hardware Address (INTERFACE_HARDWARE_ADDRESS_TYPE1)

This parameter is used to fetch the EUI-48 [EUI] hardware address of an interface.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

Requests for the hardware address of an interface that does not have an EUI-48 hardware address shall return NR_DATA_OUT_OF_RANGE.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) INTERFACE_HARDWARE_ADDRESS_TYPE1	(PDL) 0x04
(PD) <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 60%;">Interface Identifier (32-bit)</div>		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RESPONSE	(PID) INTERFACE_HARDWARE_ADDRESS_TYPE1	(PDL) 0x0a
(PD) <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 60%;"> <div style="border-bottom: 1px solid black; padding-bottom: 5px;">Interface Identifier (32-bit)</div> <div style="padding-top: 5px;">Hardware Address (48-bit)</div> </div>		

Data Description:

The data returned is the EUI-48 hardware address, commonly known as the MAC address, in big endian format.

4.4 Get/Set DHCP (IPV4_DHCP_MODE)

This parameter is used to retrieve or change the Dynamic Host Configuration Protocol [DHCPv4] mode for an interface. Changes to the DHCP mode shall not take effect until INTERFACE_APPLY_CONFIGURATION SET request is received.

The GET command shall return the configured DHCP mode for the interface, which may not reflect the actual state. To retrieve the actual state controllers can use IPV4_CURRENT_ADDRESS.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

If the interface does not support DHCP then GET requests shall always return a value of 0 (disabled) and SET requests shall return NR_ACTION_NOT_SUPPORTED.

As described in Section 3.5, DHCP mode shall only take effect when the configured IPv4 address (see Section 4.6) is set to IPV4_UNCONFIGURED and the DHCP mode option is enabled.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200	
(CC) GET_COMMAND	(PID) IPV4_DHCP_MODE		(PDL) 0x04
<div>(PD)<div>Interface Identifier (32-bit)</div></div>			

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_DHCP_MODE	(PDL) 0x05
(PD)		
Interface Identifier (32-bit)		
Disabled/Enabled (0/1)		

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) IPV4_DHCP_MODE	(PDL) 0x05
(PD)		
Interface Identifier (32-bit)		
Disabled/Enabled (0/1)		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) IPV4_DHCP_MODE	(PDL) 0x00
(PD)		

Downloaded from TSP.ESTA.ORG - Free download courtesy of ProSight Specialty Insurance

Not Present

4.5 Get/Set Zeroconf Mode (IPV4_ZEROCONF_MODE)

This parameter is used to retrieve or change the IPv4 Link Local Addressing (Zeroconf) [IPv4LL] mode on an interface. Changes to the Zeroconf mode shall not take effect until an INTERFACE_APPLY_CONFIGURATION SET request is received.

Zeroconf allows IPv4 addresses to be assigned to an interface, without configuration servers (such as DHCP servers) or operator intervention.

When Zeroconf is enabled, the algorithm described in [IPv4LL] shall be used to assign an IPv4 address to an interface when all of the following conditions are true:

- No static address is configured.
- DHCP mode is disabled or no DHCP lease has been received.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

If the interface does not support Zeroconf then GET requests shall always return a value of 0 (disabled) and SET requests shall return NR_ACTION_NOT_SUPPORTED.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) IPV4_ZEROCONF_MODE	(PDL) 0x04
(PD) <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 60%;">Interface Identifier (32-bit)</div>		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_ZEROCONF_MODE	(PDL) 0x05
(PD)		
<div>Interface Identifier (32-bit)</div>		
<div>Disabled/Enabled (0/1)</div>		

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) IPV4_ZEROCONF_MODE	(PDL) 0x05
(PD) Interface Identifier (32-bit)		
Disabled/Enabled (0/1)		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RES PONSE	(PID) IPV4_ZEROCONF_MODE	(PDL) 0x00
(PD) Not Present		

4.6 Get IPv4 Address / Netmask (IPV4_CURRENT_ADDRESS)

This parameter is used to retrieve the current IPv4 Address and Netmask information for an interface.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) IPV4_CURRENT_ADDRESS	(PDL) 0x04
(PD) <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 80%;"> Interface Identifier (32-bit) </div>		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_CURRENT_ADDRESS	(PDL) 0x0a
(PD) <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 80%;"> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px; text-align: center;">Interface Identifier (32-bit)</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px; text-align: center;">IPv4 Address (32-bit)</div> <div style="display: flex; justify-content: space-between; border: 1px solid black; padding: 5px;"> Netmask DHCP Status (0/1/2) </div> </div>		

Data Description:

The data returned is the current IPv4 address (as determined in Section 3.5) and current network mask. Interfaces without a configured IPv4 Address shall return IPV4_UNCONFIGURED.

The netmask is the number of bits in the network portion of the address. The valid range is from 0-32.

The DHCP Status field values are enumerated in Table A-3. Some devices may not be able to determine if the current address was obtained via DHCP. If the device does not support this feature, the value of the DHCP Status field shall be DHCP_STATUS_UNKNOWN.

If the feature is supported:

- If the current address was obtained via DHCP the value shall be set to DHCP_STATUS_ACTIVE.
- If the current address was not obtained via DHCP (i.e. either statically assigned or a zeroconf address) the value shall be set to DHCP_STATUS_INACTIVE.

Interaction with DHCP and Zeroconf Mode

Devices under DHCP control shall respond to a GET IPV4_CURRENT_ADDRESS with the current IPv4 address assigned by the DHCP server or IPV4_UNCONFIGURED if no address has been assigned and Zeroconf mode is disabled.

Devices may queue a GET IPV4_CURRENT_ADDRESS response when the address changes either via DHCP or any other mechanism.

4.7 Get/Set IPv4 Static Address (IPV4_STATIC_ADDRESS)

This parameter is used to statically configure the IPv4 address and network mask on an interface. Changes made to an interface's configuration shall not take effect until a SET INTERFACE_APPLY_CONFIGURATION request is received.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200	
(CC) GET_COMMAND	(PID) IPV4_STATIC_ADDRESS		(PDL) 0x04
(PD) <div>Interface Identifier (32-bit)</div>			

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD	
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_STATIC_ADDRESS	(PDL) 0x09	
<div>(PD)<div><div>Interface Identifier (32-bit)</div><div>IPv4 Address (32-bit)</div><div>Netmask</div></div></div>			

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF	
(CC) SET_COMMAND	(PID) IPV4_STATIC_ADDRESS		(PDL) 0x09
<div>(PD)<div><div>Interface Identifier (32-bit)</div><div>IPv4 Address (32-bit)</div><div>Netmask</div></div></div>			

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) IPV4_STATIC_ADDRESS	(PDL) 0x00
(PD) Not Present		

Data Description:

The netmask is the number of bits in the network portion of the address. The valid range is from 0-32.

4.8 Apply Interface Configuration (INTERFACE_APPLY_CONFIGURATION)

This parameter applies the stored configuration to an interface. The configuration of an interface shall include, but is not limited to, the settings in IPV4_STATIC_ADDRESS, IPV4_DHCP_MODE (if supported) and IPV4_ZEROCONF_MODE (if supported).

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

Controllers should be aware that some devices may reboot after applying the interface configuration.

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) INTERFACE_APPLY_CONFIGURATION	(PDL) 0x04
(PD) Interface Identifier (32-bit)		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) INTERFACE_APPLY_CONFIGURATION	(PDL) 0x00
(PD) Not Present		

Response Behavior

Controllers are advised that if the underlying transport relies on IPv4 connectivity using the interface specified in the request, no response may be received.

Following a SET INTERFACE_APPLY_CONFIGURATION request, controllers may send a GET IPV4_CURRENT_ADDRESS to read the new address.

4.9 Renew DHCP Lease (INTERFACE_RENEW_DHCP)

This parameter causes the device to attempt to renew its DHCP address.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

Upon receiving a SET INTERFACE_RENEW_DHCP, the device shall do one of the following:

- If the specified interface has a static address configured, NR_ACTION_NOT_SUPPORTED shall be returned.
- If no static address is configured, DHCP mode is enabled, and the interface is currently configured with an IPv4 address, the interface shall enter the RENEWING state as described in Section 4.4.5 of [DHCPv4].
- If no static address is configured, DHCP mode is enabled, and the interface does not have a DHCP-assigned IPv4 address, the interface shall enter the INIT state as described in Section 4.4.1 of [DHCPv4].
- If no static address is configured and DHCP mode was not enabled, NR_ACTION_NOT_SUPPORTED shall be returned.

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) INTERFACE_RENEW_DHCP	(PDL) 0x04
(PD) Interface Identifier (32-bit)		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) INTERFACE_RENEW_DHCP	(PDL) 0x00
(PD) Not Present		

Response Behavior

Controllers are advised that if the underlying transport relies on IPv4 connectivity using the interface specified in the request, no response may be sent.

Following a SET INTERFACE_RENEW_DHCP request, controllers may send a GET IPV4_CURRENT_ADDRESS to read the new address.

4.10 Release DHCP Lease (INTERFACE_RELEASE_DHCP)

This parameter causes the device to release its DHCP address.

Responders shall return NR_DATA_OUT_OF_RANGE if the interface identifier refers to an interface that would not be listed in the LIST_INTERFACES response.

Upon receiving a SET INTERFACE_RELEASE_DHCP, the device shall do one of the following:

- If no static address is configured, DHCP mode is enabled, and the interface is currently configured with an IPv4 address, the device shall send a DHCPRELEASE message in accordance with item 6 of section 3.1 in [DHCPv4] and remove the address from the interface. If Zeroconf mode is enabled the device shall generate a link local address.
- Otherwise NR_ACTION_NOT_SUPPORTED shall be returned.

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) INTERFACE_RELEASE_DHCP	(PDL) 0x04
(PD) Interface Identifier (32-bit)		

--

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) INTERFACE_RELEASE_DHCP	(PDL) 0x00
(PD) Not Present		

Response Behavior

Controllers are advised that if the underlying transport relies on IPv4 connectivity using the interface specified in the request, no response may be sent.

4.11 Get/Set Default Route (IPV4_DEFAULT_ROUTE)

This parameter is used to get and set the default IPv4 route for a device. The default route is a global property of a device.

If a default route exists, it may point to a gateway or, in the case of a point-to-point link, to an interface without a gateway. If a gateway is used, the device may be able to provide the interface the gateway is reachable on. This is extra information which may facilitate debugging, but devices are not required to provide it.

Controllers should be aware that some devices may reboot after changing the default route.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) IPV4_DEFAULT_ROUTE	(PDL) 0x00
(PD) Not Present		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD			
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_DEFAULT_ROUTE	(PDL) 0x08			
(PD)					
<table><tr><td>Interface Identifier (32-bit)</td></tr><tr><td>IPv4 Default Route (32-bit)</td></tr></table>				Interface Identifier (32-bit)	IPv4 Default Route (32-bit)
Interface Identifier (32-bit)					
IPv4 Default Route (32-bit)					

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF			
(CC) SET_COMMAND	(PID) IPV4_DEFAULT_ROUTE		(PDL) 0x08		
(PD)					
<table><tr><td>Interface Identifier (32-bit)</td></tr><tr><td>IPv4 Default Route (32-bit)</td></tr></table>				Interface Identifier (32-bit)	IPv4 Default Route (32-bit)
Interface Identifier (32-bit)					
IPv4 Default Route (32-bit)					

Downloaded from TSP.ETA.ORG - Free download courtesy of ProSight Specialty Insurance

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) IPV4_DEFAULT_ROUTE	(PDL) 0x00
(PD) Not Present		

Get Behavior:

If the device is not configured with a default route, both the IPv4 Default Route and Interface Identifier fields shall be NO_DEFAULT_ROUTE.

If a point-to-point link is used, the Interface Identifier field represents the interface used for the default route. The IPv4 Default Route field shall be set to NO_DEFAULT_ROUTE.

If a gateway is used, the IPv4 Default Route field shall contain the IPv4 address of the gateway. The Interface Identifier field may contain the interface used to reach the gateway if the device can provide this information. If the device cannot provide this information the Interface Identifier field shall be set to NO_DEFAULT_ROUTE.

Set Behavior:

To remove the default route, the IPv4 Default Route and Interface Identifier fields shall be set to NO_DEFAULT_ROUTE.

To use a point-to-point link as the default route, the IPv4 Default Route field shall be set to NO_DEFAULT_ROUTE. The Interface Identifier field shall contain the interface to use as the default route.

If a gateway is to be used as the default route, the IPv4 Default Route field shall contain the IPv4 address of the gateway to use. The Interface Identifier field shall be set to NO_DEFAULT_ROUTE.

4.12 Get/Set Name Servers (DNS_IPV4_NAME_SERVER)

This parameter is used to set the IPv4 DNS name servers for a device. Up to three IPv4 name servers may be configured.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) DNS_IPV4_NAME_SERVER	(PDL) 0x01
(PD) Name Server Index (8-bit)		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RESPONSE	(PID) DNS_IPV4_NAME_SERVER	(PDL) 0x05
(PD) Name Server Index (8-bit) Name Server Address (32-bit)		

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) DNS_IPV4_NAME_SERVER	(PDL) 0x05
<div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: fit-content;"> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px; width: 150px; text-align: center;">Name Server Index (8-bit)</div> <div style="border: 1px solid black; padding: 5px; margin: 0 auto; width: 350px; text-align: center;">Name Server Address (32-bit)</div> </div>		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) DNS_IPV4_NAME_SERVER	(PDL) 0x00
(PD) Not Present		

Data Description:

The valid IPv4 Name Server Index values are 0 to 2 inclusive. Requests outside this range shall be NACKed with NR_DATA_OUT_OF_RANGE.

If a device supports fewer than 3 IPv4 name servers, it shall use the name server index values starting from 0 and incrementing by one for each name server. Requests for all other values shall return NR_DATA_OUT_OF_RANGE.

The Name Server value is an IPv4 Address. It shall be set to IPV4_UNCONFIGURED if no name server is configured.

Downloaded from TSP.ESTA.ORG - Free download courtesy of ProSight Specialty Insurance

4.13 Get/Set Host Name (DNS_HOSTNAME)

This parameter is used to get and set the unqualified host name for a device. The hostname shall conform to the requirements in Section 2.1 of [HOST-NAME].

Devices shall not truncate the hostname. Upon receiving a SET, if the device has insufficient storage capacity to store the entire hostname, a NR_BUFFER_FULL shall be returned.

If the system hostname does not fit within 63 bytes a NR_HARDWARE_FAULT shall be returned.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) DNS_HOSTNAME	(PDL) 0x00
(PD) Not Present		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RESPONSE	(PID) DNS_HOSTNAME	(PDL) (0x01 - 0x3F)
(PD) <div style="border: 1px solid black; padding: 5px; display: inline-block;"> ASCII text. 1 to 63 characters. </div>		

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) DNS_HOSTNAME	(PDL) (0x01 - 0x3F)
(PD) <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">ASCII text. 1 to 63 characters.</div>		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) DNS_HOSTNAME	(PDL) 0x00
(PD) Not Present		

4.14 Get/Set Domain Name (DNS_DOMAIN_NAME)

This parameter is used to get and set the DNS domain name for a device. Domain names shall conform to Section 11 of [DNS-CLARIFICATIONS].

Furthermore, domain names for RDM devices shall be a maximum of 231 characters. This ensures the domain name fits in a single SET command.

Internationalized domain names may be supported by encoding with Punycode [IDNA].

An empty domain name implies there is no domain name configured. Setting the domain name to an empty string shall remove any existing domain name.

Devices shall not truncate the domain name. If the device has insufficient storage capacity to store the entire domain name, a NR_BUFFER_FULL shall be returned.

If the system domain name does not fit within 231 bytes a NR_HARDWARE_FAULT shall be returned.

Controller: (GET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200
(CC) GET_COMMAND	(PID) DNS_DOMAIN_NAME	(PDL) 0x00
(PD) Not Present		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) GET_COMMAND_RES PONSE	(PID) DNS_DOMAIN_NAME	(PDL) (0x00 - 0xE7)
(PD) <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;"> ASCII text. Up to 231 characters. </div>		

Controller: (SET)

(Port Id) 0x01 - 0xFF	(Message Count) 0x00	(Sub-Device) 0x0000 (Root) or 0x0001-0x0200 or 0xFFFF
(CC) SET_COMMAND	(PID) DNS_DOMAIN_NAME	(PDL) (0x00 - 0xE7)
(PD) <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;"> ASCII text. Up to 231 characters. </div>		

Response:

(Response Type) ACK	(Message Count) 0x00 - 0xFF	(Sub-Device) Copy of Controller SD
(CC) SET_COMMAND_RESPONSE	(PID) DNS_DOMAIN_NAME	(PDL) 0x00
(PD) Not Present		

Appendix A: Defined Parameters (Normative)

IPV4_UNCONFIGURED 0x00000000

NO_DEFAULT_ROUTE 0x00000000

Table A-1: RDM Parameter ID Defines

GET Allowed	SET Allowed	RDM Parameter ID's (Slot 21-22)	Value	Comment	Required
		Category – IP & DNS Configuration			
✓		LIST_INTERFACES	0x0700	*Support required only if any other PID in Table A-1 is supported	✓☒
✓		INTERFACE_LABEL	0x0701		
✓		INTERFACE_HARDWARE_ADDRESS_TYPE1	0x0702		
✓	✓	IPV4_DHCP_MODE	0x0703		
✓	✓	IPV4_ZEROCONF_MODE	0x0704		
✓		IPV4_CURRENT_ADDRESS	0x0705		
✓	✓	IPV4_STATIC_ADDRESS	0x0706		
	✓	INTERFACE_RENEW_DHCP	0x0707		
	✓	INTERFACE_RELEASE_DHCP	0x0708		
	✓	INTERFACE_APPLY_CONFIGURATION	0x0709	*Support required only if the SET command for any of IPV4_DHCP_MODE, IPV4_ZEROCONF_MODE or IPV4_STATIC_ADDRESS are supported	✓*

Downloaded from TSP.ESTA.ORG - Free download courtesy of ProSight Specialty Insurance

GET Allowed	SET Allowed	RDM Parameter ID's (Slot 21-22)	Value	Comment	Required
✓	✓	IPV4_DEFAULT_ROUTE	0x070A		
✓	✓	DNS_IPV4_NAME_SERVER	0x070B		
✓	✓	DNS_HOSTNAME	0x070C		
✓	✓	DNS_DOMAIN_NAME	0x070D		

Table A-2: Additional NACK Reason Codes*

Response NACK Reason Codes	Value	Description
NR_ACTION_NOT_SUPPORTED	0x000B	The parameter data is valid but the SET operation cannot be performed with the current configuration.

*These are in addition to NACK Reason Codes defined in Table A-17 of E1.20

Table A-3: DHCP Mode Defines

DHCP Mode Defines	Value	Description
DHCP_STATUS_INACTIVE	0x00	The IP address was not obtained via DHCP.
DHCP_STATUS_ACTIVE	0x01	The IP address was obtained via DHCP.
DHCP_STATUS_UNKNOWN	0x02	The system cannot determine if the address was obtained via DHCP.

Appendix B: Example Message Exchange

The following examples are for a device which has two interfaces:

- eth0, the first interface, with a hardware type of 0x0001 (Ethernet) and an address of 192.168.0.1
- eth1, the second interface, also with a hardware type of 0x0001.

Reading the Current State

Controller sends GET: LIST_INTERFACES:

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) GET_COMMAND	(PID) LIST_INTERFACES	(PDL) 0x00
(PD) Not Present		

Responder returns the packed list of interfaces:

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000					
(CC) GET_COMMAND_RESPONSE	(PID) LIST_INTERFACES		(PDL) 0x0c				
(PD)							
<table><tr><td>0x00000001</td></tr><tr><td>0x0001</td></tr><tr><td>0x00000002</td></tr><tr><td>0x0001</td></tr></table>				0x00000001	0x0001	0x00000002	0x0001
0x00000001							
0x0001							
0x00000002							
0x0001							

Downloaded from TSP.ESTA.ORG - Free download courtesy of ProSight Specialty Insurance

Controller sends GET: INTERFACE_LABEL for the first interface:

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) GET_COMMAND	(PID) INTERFACE_LABEL	(PDL) 0x04
(PD) 0x00000001		

Responder returns the interface name:

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) GET_COMMAND_RESPONSE	(PID) INTERFACE_LABEL	Variable 0x08
(PD) 0x00000001 "eth0"		

Controller sends GET: IPV4_CURRENT_ADDRESS for the first interface:

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) GET_COMMAND	(PID) IPV4_CURRENT_ADDRESS	(PDL) 0x04
(PD) 0x00000001		

Responder returns the interface's IPv4 address, network mask and DHCP mode. This response indicates the responder has a statically configured address of 192.168.0.1/24.

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000							
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_CURRENT_ADDRESS		(PDL) 0x0c						
(PD)									
<table><tr><td colspan="2">0x00000001</td></tr><tr><td colspan="2">0xc0a80001</td></tr><tr><td>24</td><td>0</td></tr></table>				0x00000001		0xc0a80001		24	0
0x00000001									
0xc0a80001									
24	0								

Enabling DHCP

Controller sends SET: IPV4_DHCP_MODE to enable DHCP for the first interface:

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000	
(CC) SET_COMMAND	(PID) IPV4_DHCP_MODE		(PDL) 0x05
(PD)			
<div>0x00000001</div>			
<div>1</div>			

Responder acknowledges:

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000	
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_DHCP_MODE		(PDL) 0x00
(PD)			

Not Present

At this point the changes have yet to be applied.

Controller sends SET: INTERFACE_APPLY_CONFIGURATION for the first interface:

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) SET_COMMAND	(PID) INTERFACE_APPLY_CONFIGURATION	(PDL) 0x04
(PD) 0x00000001		

Responder acknowledges:

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) GET_COMMAND_RESPONSE	(PID) INTERFACE_APPLY_CONFIGURATION	(PDL) 0x00
(PD) Not Present		

Static Configuration

Following on from the previous example, the Controller sends SET: IPV4_DHCP_MODE to disable DHCP for the first interface:

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) SET_COMMAND	(PID) IPV4_DHCP_MODE	(PDL) 0x05
(PD)		

Downloaded from TSP.ESTA.ORG - Free download courtesy of ProSight Specialty Insurance

0x00000001	
0	

Responder acknowledges:

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) GET_COMMAND_RESPONSE	(PID) IPV4_DHCP_MODE	(PDL) 0x00
(PD) Not Present		

At this point the changes have yet to be applied.

Controller sends SET: IPV4_STATIC_ADDRESS for the first interface to set the address to 10.0.0.32/8

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) SET_COMMAND	(PID) IPV4_STATIC_ADDRESS	(PDL) 0x09
(PD)		
0x00000001		
0x0a000020		
8		

Response:

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) SET_COMMAND_RESPONSE	(PID) IPV4_STATIC_ADDRESS	(PDL) 0x00

(PD) Not Present

At this point the changes have still yet to be applied.

Controller sends SET: INTERFACE_APPLY_CONFIGURATION for the first interface:

(Port Id) 0x01	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) SET_COMMAND	(PID) INTERFACE_APPLY_CONFIGURATION	(PDL) 0x04
(PD) 0x00000001		

Responder acknowledges:

(Response Type) ACK	(Message Count) 0x00	(Sub-Device) 0x0000
(CC) GET_COMMAND_RESPONSE	(PID) INTERFACE_APPLY_CONFIGURATION	(PDL) 0x00
(PD) Not Present		