

DSC_0035 (29 控制点)

指标	DLT (无畸变)	DLT + K1	后方交会
sigma0 (mm)	0.013068	0.012136	0.002056
sigma0 (px)	3.01	2.79	0.47
f (mm)	51.9625	51.9602	51.9819
x0 (mm)	0.0125	0.0091	0.0142
y0 (mm)	-0.2637	-0.2633	-0.2515
K1	—	7.07e-06	-2.71e-06
K2	—	0.00e+00	3.87e-09
P1	—	0.00e+00	6.29e-07
P2	—	0.00e+00	4.11e-07
Xs (mm)	4019.83	—	4019.72
Ys (mm)	1369.81	—	1369.88
Zs (mm)	-69.27	—	-69.45
omega (deg)	-89.3208	—	-89.3368
phi (deg)	-9.0839	—	-9.0809
kappa (deg)	-0.8722	—	-0.8702
迭代次数	1	4	14
DLT畸变校正提升	7.1%		
DLT+K1/后方交会 sigma0	5.90x		
焦距差 (mm)	0.0218		

DSC_0037 (32 控制点)

指标	DLT (无畸变)	DLT + K1	后方交会
sigma0 (mm)	0.005198	0.005194	0.001432
sigma0 (px)	1.20	1.19	0.33
f (mm)	51.9685	51.9645	51.9719
x0 (mm)	-0.1016	-0.0999	-0.0816
y0 (mm)	-0.0403	-0.0394	-0.0705
K1	—	-8.83e-07	-2.61e-06
K2	—	0.00e+00	5.81e-09
P1	—	0.00e+00	2.57e-06
P2	—	0.00e+00	-6.41e-06
Xs (mm)	1491.59	—	1491.90
Ys (mm)	1272.29	—	1273.00
Zs (mm)	-166.80	—	-166.60
omega (deg)	-89.6523	—	-89.6138
phi (deg)	17.3871	—	17.4085
kappa (deg)	0.0313	—	0.0432
迭代次数	1	2	14
DLT畸变校正提升	0.1%		
DLT+K1/后方交会 sigma0	3.63x		
焦距差 (mm)	0.0074		