

MDB-sheet

Basics of grid system

header

nav

main

sections id="main-features"

container container-fluid

row

col col-md-12

footer

.page-footer

.blue .indigo

.center-on-small-only

.footer-copyright container-fluid

Spacing

`{property}{sides}-{size}` for **xs**

`{property}{sides}-{breakpoint}-{size}` for **sm, md, lg, and xl**

property `-m` `-p`

sides `-t` `-b` `-l` `-r` `-x` `-y`

breakpoint `sm` `md` `lg` `xl`

sizes

0 - 0

1 - (by default) `$spacer-x * .25` or `$spacer-y * .25`

2 - (by default) `$spacer-x * .5` or `$spacer-y * .5`

3 - (by default) `$spacer-x` or `$spacer-y`

4 - (by default) `$spacer-x * 1.5` or `$spacer-y * 1.5`

5 - (by default) `$spacer-x * 3` or `$spacer-y * 3`

```
.mt-0 { margin-top: 0 !important; }
```

```
.ml-1 { margin-left: ($spacer-x * .25) !important; }
```

```
.px-2 { padding-left: ($spacer-x * .5) !important; padding-right: ($spacer-x * .5) !important; }
```

```
.p-3 { padding: $spacer-y $spacer-x !important; }
```

Responsive spacing

Screen Size

Appears on all

Appears only on xs

Appears only on sm

Appears only on md

Appears only on lg

Appears only on xl

Class

`.ml-3`

`.ml-3 .ml-sm-0`

`.ml-sm-3 .ml-md-0`

`.ml-md-3 .ml-lg-0`

`.ml-lg-3 .d-xl-0`

`.ml-xl-3`

Horizontal centering

`.mx-auto`

```
<div class="mx-auto" style="width: 200px;">
```

Centered element

```
</div>
```

Centered element

Images

`.img-fluid`

view

overlay

hm-white-ligth

z-depht-1-half

Full page background image

```
<div id="intro" class="view hm-black-strong">
  <div class="container-fluid full-bg-img d-flex align-items-center justify-content-center">
    <div class="row d-flex justify-content-center">
      <div class="col-md-10 text-center">
        <h2 class="display-3 font-weight-bold white-text mb-2">Title</h2>
        <hr class="hr-light">
        <h4 class="white-text my-4">Lorem ipsum dolor sit amet, consectetur adipisicing elit.
Doloribus, asperiores numquam enim exercitationem officiis voluptatum.</h4>
        <button type="button" class="btn btn-outline-white">Read more<i class="fa fa-book
ml-2"></i></button>
      </div>
    </div>
  </div>
</div>
```

```
<!-- STYLES FOR FULL BACKGROUND IMAGE -->
<style>
  html, body, header, #intro {
    height: 100%;
  }
  #intro {
    background: url("img/img-togas-lp/02-header.jpg") no-repeat center center fixed;
    -webkit-background-size: cover;
    -moz-background-size: cover;
    -o-background-size: cover;
    background-size: cover;
  }
</style>
```

Masks Overlays*

Usage















































.view **.mask** **.pattern-[1-9]**

```
<div class="view hm-black-strong"> // strong overlay: previous version
  
  <div class="mask pattern-1 flex-center [rgba-black-strong]*">
    <p class="white-text">.pattern-1</p>
  </div>
```

.mask div after img

hm-black-strong // strong overlay //slight // light: **previous version**

Overlay colors and intensity

	.rgba-blue-light		.rgba-blue-strong		.rgba-blue-slight
	.rgba-red-light		.rgba-red-strong		.rgba-red-slight
	.rgba-pink-light		.rgba-pink-strong		.rgba-pink-slight
	.rgba-purple-light		.rgba-purple-strong		.rgba-purple-slight
	.rgba-indigo-light		.rgba-indigo-strong		.rgba-indigo-slight
	.rgba-cyan-light		.rgba-cyan-strong		.rgba-cyan-slight
	.rgba-teal-light		.rgba-teal-strong		.rgba-teal-slight
	.rgba-green-light		.rgba-green-strong		.rgba-green-slight
	.rgba-lime-light		.rgba-lime-strong		.rgba-lime-slight
	.rgba-yellow-light		.rgba-yellow-strong		.rgba-yellow-slight
	.rgba-orange-light		.rgba-orange-strong		.rgba-orange-slight
	.rgba-brown-light		.rgba-brown-strong		.rgba-brown-slight
	.rgba-grey-light		.rgba-grey-strong		.rgba-grey-slight
	.rgba-blue-grey-light		.rgba-blue-grey-strong		.rgba-blue-grey-slight
	.rgba-black-light		.rgba-black-strong		.rgba-black-slight
	.rgba-stylish-light		.rgba-stylish-strong		.rgba-stylish-slight
	.rgba-white-light		.rgba-white-strong		.rgba-white-slight

Masks Overlays*

```
.view { position: relative; overflow: hidden; cursor: default; }  
.view .full-bg-img { height: 100%; }  
.view .full-bg-img { background-repeat: no-repeat; background-position: center center;  
  -webkit-background-size: cover; background-size: cover; }  
.view .mask { position: absolute; top: 0; overflow: hidden; width: 100%; height: 100%;  
  background-attachment: fixed; }  
  
.overlay .mask { opacity: 0; -webkit-transition: all 0.4s ease-in-out; -o-transition: all 0.4s ease-in-out;  
  transition: all 0.4s ease-in-out; }  
.overlay .mask:hover { opacity: 1; }
```

Hover Effects

Overlay effect

```
<div class="view overlay"> // . zoom
  
  <div class="mask flex-center rgba-blue-light">
    <p class="white-text">Light overlay</p>
  </div>
</div>
```

Zoom effect

```
<div class="view zoom"> ...
```

Shadow effect

```

```

Buttons

```
<button type="button" class="btn btn-primary">Primary</button>
```



Additional buttons

`.btn-elegant .btn-unique .btn-indigo .btn-light-gree .btn-amber .btn-mdb-color`

Outline buttons

`.btn-outline-* [primary] .waves-effect .btn-rounded`

"Back to the top" button



```
<div class="fixed-action-btn smooth-scroll" style="bottom: 45px; right: 24px;">
  <a href="#top-section" class="btn-floating btn-large red">
    <i class="fa fa-arrow-up"></i>
  </a>
</div>
```

Buttons with icons

```
<button class="btn btn-primary"><i class="fa fa-magic mr-1"></i> Left</button>
```

Button tags

```
<a class="btn btn-primary" href="#" role="button">Link</a>
<button class="btn btn-primary" type="submit">Button</button>
<input class="btn btn-primary my-3" type="button" value="Input">
<input class="btn btn-primary my-3" type="submit" value="Submit">
<input class="btn btn-primary my-3" type="reset" value="Reset">
```



Sizes `.btn-lg` `.btn-sm` `.btn-block`

Disabled state `.disabled`

Button plugin

Toggle states `data-toggle="button" aria-pressed="false" autocomplete="off"`

Checkbox and radio buttons

```
<div class="btn-group" data-toggle="buttons">
  <label class="btn btn-primary active"><input type="radio" name="options" id="option1" autocomplete="off" checked>
    Radio 1 (preselected) </label>
  <label class="btn btn-primary"><input type="radio" name="options" id="option2" autocomplete="off"> Radio 2 </label>
</div>
```

Methods

`$().button('dispose')` `$().button('dispose')`

Flexbox


Cards

Icons

```
<i class="fa fa-android fa-2x grey" aria-hidden="true"></i>
```



Larger icons Colors Margins Buttons



Why is it so great?

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam.



International

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Reprehenderit maiores nam, aperiam minima assumenda deleniti hic.




Experimental

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Reprehenderit maiores nam, aperiam minima assumenda deleniti hic.



Relaxing

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Reprehenderit maiores nam, aperiam minima assumenda deleniti hic.



Beloved

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Reprehenderit maiores nam, aperiam minima assumenda deleniti hic.



Rapid

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Reprehenderit maiores nam, aperiam minima assumenda deleniti hic.



Magical

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Reprehenderit maiores nam, aperiam minima assumenda deleniti hic.

Nav

wrapper

optional containers to limit their horizontal width

```
<div class="container">
  <nav class="navbar navbar-expand-lg navbar-dark indigo">
    <a class="navbar-brand" href="#">Navbar</a>
  </nav>
</div>
```

```
<nav class="navbar navbar-expand-lg navbar-dark indigo">
  <div class="container">
    <a class="navbar-brand" href="#">Navbar</a>
  </div>
</nav>
```

- `.navbar` with `.navbar-expand{-sm|-md|-lg|-xl}`
- `spacing` and `flex` utility classes for controlling spacing and alignment within navbars
- Navbars are responsive by default, but you can easily modify them to change that. Responsive behavior depends on our Collapse JavaScript plugin.
- Navbars are hidden by default when printing. Force them to be printed by adding `.d-print` to the `.navbar`. See the [display utility class](#).
- Ensure accessibility by using a `<nav>` element or, if using a more generic element such as a `<div>`, add a `role="navigation"` to every navbar to explicitly identify it as a landmark region for users of assistive technologies.
- `color scheme` classes

`navbar-dark danger-color` `secondary-color indigo`

`navbar-light bg-faded`

`navbar-light default-color lighten-4`

`navbar-light warning-color lighten-5`

Supported content

`.navbar-brand` for your company, product, or project name **+img**.

`.navbar-nav` for a full-height and lightweight navigation (including support for dropdowns).

`.navbar-toggler` for use with our collapse plugin and other [navigation toggling](#) behaviors.

`.form-inline` for any form controls and actions.

`.navbar-text` for adding vertically centered strings of text.

`.collapse.navbar-collapse` for grouping and hiding navbar contents by a parent breakpoint.

toggler classes

```
<nav class="navbar navbar-expand-lg navbar-dark primary-color">
  <a class="navbar-brand" href="#">Navbar</a>
  <button class="navbar-toggler" type="button" data-toggle="collapse" data-target="#navbarNav"
aria-controls="navbarNav" aria-expanded="false" aria-label="Toggle navigation">
  <span class="navbar-toggler-icon"></span>
</button>
<div class="collapse navbar-collapse" id="navbarNav">
  <ul class="navbar-nav">
    <li class="nav-item active">
      <a class="nav-link" href="#">Home <span class="sr-only">(current)</span></a>
    </li>
    <li class="nav-item">
      <a class="nav-link disabled" href="#">Disabled</a>
    </li>
  </ul>
</div>
</nav>
```

Forms


.form-inline.

Heading

Text

.navbar-text

.white-text



Placement

.fixed-top

.fixed-bottom

.sticky-top uses position: sticky, which isn't fully supported in every browser

Responsive behaviors

.navbar-toggler

.navbar-collapse

.navbar-expand{-sm|-md|-lg|-xl}

For navbars that never collapse, add the `.navbar-expand` class on the navbar. For navbars that always collapse, don't add any `.navbar-expand` class.


Toggler



Navbar togglers are left-aligned by default, but should they follow a sibling element like a `.navbar-brand`, they'll automatically be aligned to the far right. Reversing your markup will reverse the placement of the toggler. Below are examples of different toggle styles.



External content



```
<div class="pos-f-t">
  <div class="collapse" id="navbarToggleExternalContent">
    <div class="bg-dark p-4">
      <h4 class="text-white">Collapsed content</h4>
      <span class="text-muted">Toggleable via the navbar brand.</span>
    </div>
  </div>
  <nav class="navbar navbar-dark bg-dark">
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-target="#navbarToggleExternalContent" aria-controls="navbarToggleExternalContent" aria-expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>
  </nav>
</div>
```

Scrolling navbar

By adding `.scrolling-navbar` class to your fixed-top navbar, you can give it a smooth animation on a scroll.

Advanced navigation

MDB PRO COMPONENT

MDB provides you multiple useful, ready-to-use page layouts with various predefined navigation types.



Navigation layouts

READ MORE



Skins

READ MORE

Typography

```
<h1>h1. heading</h1>
<h2>h2. heading</h2>
<h3>h3. heading</h3>
<h4>h4. heading</h4>
<h5>h5. heading</h5>
<h6>h6. heading</h6>
<p class="h1">h1. Bootstrap heading</p>
<p class="h2">h2. Bootstrap heading</p>
<p class="h3">h3. Bootstrap heading</p>
<p class="h4">h4. Bootstrap heading</p>
<p class="h5">h5. Bootstrap heading</p>
<p class="h6">h6. Bootstrap heading</p>
```

h1. heading

h2. heading

h3. heading

h4. heading

h5. heading

h6. heading

h1. Bootstrap heading

h2. Bootstrap heading

h3. Bootstrap heading

h4. Bootstrap heading

h5. Bootstrap heading

h6. Bootstrap heading

h1. heading

h2. heading

h3. heading

h4. heading

h5. heading

h1. heading

h2. heading

h3. heading

h4. heading

h5. heading

Responsive headings

```
<h1 class="h1-responsive">h1. heading</h1>
<h2 class="h2-responsive">h2. heading</h2>
<h3 class="h3-responsive">h3. heading</h3>
<h4 class="h4-responsive">h4. heading</h4>
<h5 class="h5-responsive">h5. heading</h5>
```

Customizing headings

```
<h3> <strong>Fancy display heading</strong>
    <small class="text-muted">With faded secondary text</small> </h3>
```

Fancy display heading With faded secondary text

Display headings

```
<h1 class="display-1">Display 1</h1>
<h1 class="display-2">Display 2</h1>
<h1 class="display-3">Display 3</h1>
<h1 class="display-4">Display 4</h1>
```

Display 1

Display 2

Display 3

Display 4

Lead

Make a paragraph stand out by adding **.lead**

Inline text elements

```
<p>You can use the mark tag to <mark>highlight</mark> text.</p>
<p><del>This line of text is meant to be treated as deleted text</del></p>
<p><s>This line of text is meant to be treated as no longer accurate.</s></p>
<p><ins>This line of text is meant to be treated as an addition to the document.</ins></p>
<p><u>This line of text will render as underlined</u></p>
<p><small>This line of text is meant to be treated as fine print.</small></p>
<p><strong>This line rendered as bold text.</strong></p>
<p><em>This line rendered as italicized text.</em></p>
```

You can use the mark tag to highlight text.

This line of text is meant to be treated as deleted text.

This line of text is meant to be treated as no longer accurate.

This line of text is meant to be treated as an addition to the document.

This line of text will render as underlined

This line of text is meant to be treated as fine print.

This line rendered as bold text.

This line rendered as italicized text.

Abbreviations

```
<p><abbr title="attribute">attr</abbr></p>
```

attr

```
<p><abbr title="HyperText Markup Language" class="initialism">HTML</abbr></p>
```

HTML

Blockquotes

Naming a source*

Alignment**

```
<blockquote class="blockquote text-center**">
```

```
<p class="mb-0**">Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer posuere erat a ante.</p>
```

```
<footer class="blockquote-footer">*Someone famous in <cite title="Source Title">Source Title</cite></footer>
</blockquote>
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer posuere erat a ante.

— Someone famous in *Source Title*

Success notification

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Maiores quibusdam dignissimos itaque harum illor! Quidem, corporis at quae tempore nisi impedit cupiditate perferendis nesciunt, ex dolores doloremque! Sit, rem, in?

Text notifications

```
<blockquote class="blockquote bq-success"> // .bq-danger .bq-warning .bq-primary
```

Lists

```
<ul class="list-unstyled">
```

```
<ul class="list-inline">
```

```
<li class="list-inline-item">Item 1</li>
```

Responsive typography

```
html { font-size: 14px; }
```

```
@include media-breakpoint-up(sm) { html { font-size: 16px; } }
```

```
@include media-breakpoint-up(md) { html { font-size: 20px; } }
```

```
@include media-breakpoint-up(lg) { html { font-size: 28px; } }
```

Text colors

Lorem ipsum dolor sit amet, cr

Impedit architecto, totam hic s

Similique ex, expedita minus a

Veritatis eum libero nam, adipi

Sapiente, ea. Molestias sunt ni

Sapiente sit, possimus maiore

Corrupti adipisci, praesentium

Odio autem veritatis aliquam c

Similique, adipisci ea, sequi m

Eos et vitae, odit deserunt digr

red-text

pink-text

purple-text

deep-purple-text

indigo-text

blue-text

light-blue-text

cyan-text

teal-text

green-text

Fugit nihil numquam inve

Sed odit inventore illum e

At odio animi distinctio, a

Quo at accusamus vel ea

Iusto odit eos distinctio te

Quas fugit fuga assumen

Excepturi iusto amet suni

Non sint nulla incidunt, or

Eius, provident. Quo simil

light-green-text"

lime-text

yellow-text

amber-text

orange-text

deep-orange-text

brown-text

grey-text

blue-grey-text

white-text

Bootstrap text utilities

Text alignment

.text-justify

.text-left

.text-right

.text-center

.text-[sm/md/lg/xl]-left

.text-nowrap

For longer content, you can add a **.text-truncate** class to truncate the text with an *ellipsis*. Requires **display: inline-block** or **display: block**.

```
<!-- Block level -->
```

```
<div class="row">
```

```
  <div class="col-2 text-truncate">
```

```
    Praeterea iter est quasdam res quas ex communi.
```

```
  </div>
```

```
</div>
```

```
<!-- Inline level -->
```

```
<span class="d-inline-block text-truncate" style="max-width: 150px;">
```

```
  Praeterea iter est quasdam res quas ex communi.
```

```
</span>
```

Text transform

.text-lowercase

.text-uppercase

.text-capitalize

Font weight and italics

.font-weight-bold

.font-weight-normal

.font-italic

MDB-sheet

MDB-sheet

MDB-sheet

MDB-sheet

MDB-sheet

MDB-sheet

MDB-sheet

MDB-sheet

MDB-sheet

MDB-sheet

