

THE UNDERUSED WALL

Make room for a second service channel.

A laundry locker wall gives customers a place to leave and collect service orders while the operator keeps washing, folding, quality control and scheduling in its own hands.



THE FIVE-CHAIR WALL STUDY

Rework the right wall as an indoor drop-off and pickup point. Preserve the machines and principal aisles. Size the compartments around the actual wash-and-fold bags and finished orders before choosing the door mix.

Illustrative proposed placement. "Heritage Suds" is a working name; final brand, site dimensions and equipment remain open.

OPERATOR OPPORTUNITY

A service window beyond the counter.

Offer controlled drop-off and pickup around the hours your site permits. Process laundry on a schedule your staff can sustain. Confirm the bag size, operator dashboard and handoff rules before selecting hardware.

01 DROP OFF

Customer places a labeled bag in an assigned compartment.

02 ACCEPT

Operator confirms contents, service, price and any exceptions.

03 PROCESS

Staff wash, dry, fold or route work under the chosen service policy.

04 RETURN

Finished order goes into an assigned compartment; customer is notified.

05 PICK UP

Authorized customer retrieves it; an exception path handles missed pickup.

SALES CASE

Turn a wall into an additional order handoff point. Sell convenience and a repeatable service routine - then model capacity from your own demand, labor and compartment turnover.

UNDERWRITE WITH YOUR NUMBERS

Monthly orders x contribution per order
minus service labor, software, utilities, support and occupancy cost
minus monthly equipment or financing cost
= estimated operating contribution

DECISIONS BEFORE LAUNCH

Service menu & pricing / full-bag fit test / intake inspection & disputes / dashboard needs / payment and notifications / pickup deadline & recovery / staff custody handoffs

BUILDABLE SERVICE WALL

Plan the wall as part of the room.

Treat the locker as a coordinated equipment and casework package. This working-site study illustrates an indoor retrofit; a repeatable bay system is the alternate path for a portfolio.

01 / SITE-MEASURED FIT

Match the selected wall, finishes and access route. Confirm clearances, accessible approach and reach, egress, anchorage, service opening and room circulation before a final elevation.

02 / REPEATABLE BAYS

Use one screen/control bay with added capacity in measured increments. Test a full 15-30 lb wash-and-fold bag and finished-order package in the clear opening; then define the joint and service path.

COORDINATE THESE INTERFACES

SPACE Survey wall, aisle, bag dimensions, door swing and accessible approach.

POWER + DATA Confirm feed, Ethernet or Wi-Fi, and property network policy.

OPERATIONS Define customer and staff handoffs, dashboard access and exceptions.

SECURITY Scope optional camera monitoring, credentials and response owner.

SERVICE Allow access to controls, locks, ventilation and cleaning surfaces.

DISCUSS A SITE / Mike@Monetize-that.com / Configuration and pricing by site.