REFERENCED DRAWING: I-RM-3A00.00-1519-291-PZ9-005 R0

Baker Hughes

CBS Nº .: 4600641834 PCS Nº .: 4511254834

REVISIONS										
REV	DESCRIPTION	APPROVED	DATE							
6	According to ECR WS00077208.	RMs	9/16/2022							
7	DRAFT									

**BMS-11 FIELD DEVELOPMENT** 

N/A

COMPOSITION DRAWING - Gas Injection - -/IG-14 - SMP03

TOP CONFIGURATION:

1/2

REV.:

DRAWING NUMBER:

C2891.2 UN-03

		(2) - IN ACCO	RDANCE WITH MTL-6	J4U.					(4) - Items from pipe C2891 A-08. (5) - Pipe C2891 A-08 at C2891.2 UN-29.				
NOTES	8:				NGE), BICHROME	OVER CADMIUM	4. 1 1/2" - 8 UN NUTS (24 PER FLA	ANGE), E	<u>-</u>				
LEGEN	ID:	N/A : ME	ANS NOT APPLI	CABLE.	TBD: ME	ANS TO BE	DEFINED.	ITEMS	TO BE ASSEMBLED OFFSHORE. ITEMS TO BE PARTIAL ASSEMBLED OFFSHORE. ITEMS TO BE DELIVERED WIT	H OFFSHORE O	NES		
ITE	ЕМ	PCS ITEM	CBS ITEM	NEW QTY.	SPARE QTY.	SUPPLIED BY CLIENT	DOCUMENT Nº	REV Nº	DESCRIPTION	NOTES	C		
1	1	10	370	2300 m	-	1000 m	WSI 152.2553-RD-4042-6	-	" ID Gas Injection Flexible Flowline				
2	2	20	390	6	-	-	CB-EF1522540-00-05	-	d Fitting 6" ID Gas Injection Flowline 7 1/16" API 6BX Flange, 10000 psi, BX 156 With N2 Seal Port - Single Barrier - Full Protection				
<b>7</b> 3	3	30	440	1	-	-	CB-BR1522553-00-01	-	nd Restrictor, 6" ID Gas Injection Flowline 72 Degrees (Splited)				
4	4	40	550	3	-	-	CB-TH152XXXX-00-01	-	ndling Test Head, 7 1/16" API 6BX Flange, 10000 psi, BX 156 (SWL= 55 tf)				
- 5	5	50	540	3	_	-	CB-TH152XXXX-00-02	_	allation Test Head, 7 1/16" API 6BX Flange, 10000 psi, BX 156 (SWL= 500 tf)				
7 6	6	60	490	4	_	-	N/A		Seal Ring BX 156 Inconel 625 (For Installation)		_		
	7	120	480	6	<u> </u>		N/A		Ring BX 156 AISI 316L (For transports and tests)				
<u> </u>	8	70	520	3	-	-	N/A		of Studs and Bolts, 7 1/16" API 6BX Flange, 10000 psi, BX 156 , For Tensioner Hydratight HL (For Installation)				
	9	90 80	500 510	6	-	-	N/A N/A		of Studs and Bolts, 7 1/16" API 6BX Rotative Flange, 10000 psi, BX 156, For Tensioner Hydratight HL (For Installation) of Studs and Bolts, 7 1/16" API 6BX Flange, 10000 psi, BX 156, For Tensioner Hydratight HL (For transport and tests)				
	1	140	470	162 kg	-	-	CB-TDC2891XX-00-01		ode Collar for Service Life 27 Kg (3 per EndFitting, Drawing Number CB-TDXXXXXXX-00-01.14AD) + Neoprene Blanket				
1 1	2	150	470	216 kg	-	-	CB-TDC2891XX-00-01	-	ode Collar for Service Life 27 Kg (4 per EndFitting, Drawing Number CB-TDXXXXXXX-00-01.14AC) + Neoprene Blanket				
_	3	160	470	162 kg	-	-	CB-TDC2891XX-00-01	-	de Collar for Service Life 27 Kg (6 per EndFitting, Drawing Number CB-TDXXXXXXX-00-01.14AA) + Neoprene Blanket				
<b>7</b> 1	4	100	380	3	-	-	ENG-R-3121	-	pair Kit to WSI 152.2553-RD-4042-6				
1	5	170	410	1	-	-	CB-AC1522553-00-01	-	chor Collar, 6" ID Gas Injection Flexible Flowline (SWL= 80tf)				
י וב	0	110	430	1	-	-	PT-PRT-379021	-	Abrasion Protection (3 meters)	(4)			

16/12/2021

20/12/2021

21/12/2021

DATE:

DATE:

TITLE:

CLIENT:

**Petrobras** 

ENGINEERED BY:

CHECKED BY:


APPROVED BY:

**Tobias Campos** 

Filipe Alvarenga

João Lima

## ← LAUNCHING SEQUENCE



WELL

Somente os tramos C2891 A-10 e C2891 A-11 serão utilizados nesta operação

	ENGINEERED BY: Tobias Campos	DATE: 16/12/2021	REV:	TITLE: BMS-11 FIELD DEVELOPMENT			SHEET.:
	CHECKED BY:	DATE: 20/12/2021		COMPOSITION DRAWING - Gas Injection/IG-14 - SMP03			2/2
	Filipe Alvarenga	20/12/2021		CLIENT:	TOP CONFIGURATION:	DRAWING NUMBER:	REV.:
<b>Baker Hughes</b>	APPROVED BY:	DATE:					
	João Lima	21/12/2021		Petrobras	N/A	C2891.2 UN-03	