REFER

CBS N° :: 4600440586	

Page 16 4 4 4 4 4 4 4 4 4	CBS N° .: 46	;00440586 ;05988271									TION ECN B067/15 3S Item - ECN B656/15	APPROVED MBa	2/2/201 12/30/2(15
	DCC No . 4F	05988271								$\overline{\Box}$	ECN B067/15	MBa	2/2/201 12/30/2C	5)15
12 12 12 12 12 13 13 13	2									\vdash	.'S Item - ECN B656/15	МВа	12/30/20	115
1 12 12 12 12 12 12 12														
Ø 13 - 6 ERCR-1312 - Repair Kit to WSI 152.2510-DR-40414 Anode Collar for Service Life 20.1 Kg (4 per End Fitting, Drawing Number CB-TDC647XXXX-00-01.3A) + Neopene Blanket Anode Collar for Service Life 20.1 Kg (4 per End Fitting, Drawing Number CB-TDC647XXXX-00-01.2A) + Neopene Blanket Anode Collar for Service Life 20.1 Kg (3 per End Fitting, Drawing Number CB-TDC647XXXX-00-01.2A) + Neopene Blanket (1) (2) Ø 10 2410 6 - - N/A 4 Anode Collar for Service Life 20.1 Kg (3 per End Fitting, Drawing Number CB-TDC647XXXX-00-01.2A) + Neopene Blanket (1) (2) Ø 11 100 2410 6 - N/A - Set of Studs and Bols, 71/16" API GBX Fange, 10000 psi, BX 156. For Tensioner Hydraight HL (For Installation) (1) (2) Ø 80 1520 4 - N/A - Set of Studs and Bols, 71/16" API GBX Fange, 10000 psi, BX 156. For Tensioner Hydraight HL (For Installation) (1) (2) Ø 150 1520 4 - N/A - Seal Ring BX 156 Incore [625] (For Installation) (1) (2) Ø 1520 4 - N/A - Seal Ring BX 156 Incore [625] (For Installation) (1) (2)														
Include the control of the	_		3040	0					oair Kit to WSI 152.2510-DR-4041-4					
Include Collar for Service Life 20.1 Kg of Service Lif		100	2410	8	,				ode Collar for Service Life 20.1 Kg (4 per EndFitting, Drawing Num	ber CB-TDC647XXXX-00-01.3A) + Neop	orene Blanket			
Include and Bolts of 10 in 10		100	2410	9	-	-			ode Collar for Service Life 20.1 Kg (3 per EndFitting, Drawing Num	ber CB-TDC647XXXX-00-01.2A) + Neop	orene Blanket			
2 8 8 1620 4 - N/A - Set of Studs and Bolls, 7 11/6" API 6BX Flange, 10000 psi, BX 156, For Tensioner Hydratight HL (For Installation) (1)(2) 2 3 3 4 - - N/A - Set of Studs and Bolls, 7 11/6" API 6BX Flange, 10000 psi, BX 156, For Tensioner Hydratight HL (For Installation) (1)(2) 4 5 6 5 - N/A - Set Ring BX 156 inchall BRX 156 inchallation) Aminor Ami		110	1610	1	-	-			of Studs and Bolts, 7 1/16" API 6BX Flange, 10000 psi, BX 156 , i	or Tensioner Hydratight HL (For Installa	ation)		(1) (2)	
Ø 0 1630 2 - N/A - Set of Studs and Bolts, 7 1/16° APT 6BX Rotative Flange, 10000 psi, BX 156, For Tensioner Hydratight HL (For Installation) (1) (2) Ø 7 60 1570 4 - - N/A - Seal Ring BX 156 Incomed 625 (For Installation) Page 1876 (SWL=400 tf) Page 1876 (SWL=400	6	80	1620	4					of Studs and Bolts, 7 1/16" API 6BX Flange, 10000 psi, BX 156 , I	or Tensioner Hydratight HL (For transpc	ort and tests)		(1)(2)	
4 5 6 1570 4 - - N/A - Seal Ring BX 156 (For Installation) - - Seal Ring BX 156 (For Installation) - <th></th> <td>70</td> <td>1630</td> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td>of Studs and Bolts, 7 1/16" API 6BX Rotative Flange, 10000 psi, E</td> <td>X 156 , For Tensioner Hydratight HL (Fc</td> <td>or Installation)</td> <td></td> <td>(1) (2)</td> <td></td>		70	1630	2					of Studs and Bolts, 7 1/16" API 6BX Rotative Flange, 10000 psi, E	X 156 , For Tensioner Hydratight HL (Fc	or Installation)		(1) (2)	
Image: Size bit	7	09	1570	4					al Ring BX 156 AISI 316L (For transports and tests)					
6 91 3250 2 - <th></th> <th>20</th> <th>1580</th> <th>3</th> <th></th> <th></th> <th></th> <th></th> <th>al Ring BX 156 Inconel 625 (For Installation)</th> <th></th> <th></th> <th></th> <th></th> <th></th>		20	1580	3					al Ring BX 156 Inconel 625 (For Installation)					
4 31 3230 2 - <th>2</th> <th>91</th> <th>3250</th> <th>2</th> <th></th> <th></th> <th></th> <th></th> <th>tallation/Test Head, 7 1/16" API 6BX Flange, 10000 psi, BX 156 (S</th> <th>WL= 400 tf)</th> <th></th> <th></th> <th></th> <th></th>	2	91	3250	2					tallation/Test Head, 7 1/16" API 6BX Flange, 10000 psi, BX 156 (S	WL= 400 tf)				
■ 3 40 3240 2 - - - CB-BR1522510-00-05 2 Bend Restriction, €"ID Water Injection Flowline 71/16" API 6BX Flange, 10000 psi, BX 156 With N2 Seal Port Post Instance <th< th=""><th>4</th><td>31</td><td>3230</td><td>2</td><td></td><td></td><td></td><td></td><td>ndling/Test Head, 7 1/16" API 6BX Flange, 10000 psi, BX 156 (SW</td><td>L= 40 tf)</td><td></td><td></td><td></td><td></td></th<>	4	31	3230	2					ndling/Test Head, 7 1/16" API 6BX Flange, 10000 psi, BX 156 (SW	L= 40 tf)				
2 20 3120 4 - - - - CB-EF1222310-00-09 2 End Fitting 6" ID Water Injection Flowline 7 1/16" API 6BX Flange, 10000 psi, BX 156 With N2 Seal Port Paragram 152, 2510-DR-4041-4 1 6" ID Water Injection Flexible Flowline Paragram 152 Paragram 152, 2510-DR-4041-4 1 6" ID Water Injection Flexible Flowline Paragram 152 Paragram 152 Paragram 152, 2510-DR-4041-4 1 6" ID Water Injection Flexible Flowline Paragram 152		40	3240	2					nd Restrictor, 6" ID Water Injection Flowline 120 Degrees (Splited)					
1 10 3100 1335 m 2 2 2 2 2 2 2 2 2	2	20	3120	4		,			3 Fitting 6" ID Water Injection Flowline 7 1/16" API 6BX Flange, 10	000 psi, BX 156 With N2 Seal Port				
PCS TEM CESTEM NEW OTT: STATE SUPPLIED DOCUMENT Nº NOTES TEM NEW DOCUMENT Nº NOTES TEM NEW DECEMBRITION DESCRIPTION DESCRIPTIO	-	10	3100	1335 m			152,2510-DR-4041-4		D Water Injection Flexible Flowline					
NIA : MEANS NOT APPLICABLE. TBD: MEANS TO BE DEFINED.			BS ITEM			SUPPLIED BY CLIENT		N° V		SSCRIPTION				CHECK
	LEGEND:	N/A: MEANS	VOT APPLICA	BLE.	TBD: N	MEANS TO		ITEM	ASSEMBLED OFFSHORE.	TIAL ASSEMBLED OFFSHORE.		RED WITH OFFS	HORE ONES	

	THE DESIGN WAS ORIGINALED BY AND IS THE EXCLOSIVE FROPER FOUNDED SPECIFIC IN WELLS TRAMMING THAT IN OFFICIAL OF WELLS TRAMMING SPECIFIC IN WELLS TRAMMING THAT IN OFFICIAL OF WELLS TRAMMING SPECIFIC IN WELLS TRAMMING THAT IN OFFICIAL OF WELLS TRAMMING THAT IN OFFICIAL OFFI		-				
	ENGINEERED BY:	DATE:	REV:	те:	IRACEMA NORTE FIELD DEVELOPMENT	E	SHET.:
	Marco Araujo	10/07/2014	MBa	THE COURT		CHAILMIN AND A TH	15
	CHECKED BY:	DATE:		COMPOSITION DRAWI	COMPOSITION DRAWING - Water Injection - FPSO CIDADE DE LI AGUAI/IW-IN 13	I I AGUAI/IW-IN IS	7.1
Wellstream	Celi Nogueira	10/07/2014	TCs	CLIENT:	TOP CONFIGURATION:	DRAWING NUMBER:	REV.:
	APPROVED BY:	DATE:			****	!	
	Orlando Borges	10/07/2014	r So	Petrobras	K/N	C647 UN-15	9

