

PC-2: Rush Hour - Ernest Landrito

Generated by Doxygen 1.8.5

Tue Oct 15 2013 14:33:15



# Contents

<b>1</b>	<b>Class Index</b>	<b>1</b>
1.1	Class List . . . . .	1
<b>2</b>	<b>File Index</b>	<b>3</b>
2.1	File List . . . . .	3
<b>3</b>	<b>Class Documentation</b>	<b>5</b>
3.1	traffic Class Reference . . . . .	5
3.1.1	Constructor & Destructor Documentation . . . . .	5
3.1.1.1	traffic . . . . .	5
3.1.2	Member Function Documentation . . . . .	6
3.1.2.1	canMoveBack . . . . .	6
3.1.2.2	canMoveForward . . . . .	6
3.1.2.3	getData . . . . .	6
3.1.2.4	moveBackward . . . . .	7
3.1.2.5	moveForward . . . . .	7
3.1.2.6	printMoves . . . . .	8
3.1.2.7	recSolve . . . . .	8
3.1.2.8	setDefault . . . . .	8
3.2	vehicle Class Reference . . . . .	9
3.2.1	Constructor & Destructor Documentation . . . . .	9
3.2.1.1	vehicle . . . . .	9
3.2.1.2	vehicle . . . . .	9
3.2.2	Member Data Documentation . . . . .	10
3.2.2.1	id . . . . .	10
3.2.2.2	justMovedBackward . . . . .	10
3.2.2.3	justMovedForward . . . . .	10
3.2.2.4	leftX . . . . .	10
3.2.2.5	orientation . . . . .	10
3.2.2.6	size . . . . .	10
3.2.2.7	topY . . . . .	10

<b>4 File Documentation</b>	<b>11</b>
4.1 rushHour.cpp File Reference . . . . .	11
4.1.1 Function Documentation . . . . .	11
4.1.1.1 main . . . . .	11
4.2 rushHour.h File Reference . . . . .	11
4.2.1 Variable Documentation . . . . .	11
4.2.1.1 EMPTY_VAL . . . . .	11
 <b>Index</b>	 <b>12</b>

# Chapter 1

## Class Index

### 1.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">traffic</a>	.....	5
<a href="#">vehicle</a>	.....	9



## Chapter 2

# File Index

### 2.1 File List

Here is a list of all files with brief descriptions:

<a href="#">rushHour.cpp</a>	11
<a href="#">rushHour.h</a>	11





## Chapter 3

# Class Documentation

### 3.1 traffic Class Reference

```
#include <rushHour.h>
```

#### Public Member Functions

- [traffic](#) ()
- void [getData](#) (int numCars)
- bool [canMoveForward](#) (int xPos, int yPos) const
- bool [canMoveBack](#) (int xPos, int yPos) const
- void [recSolve](#) (int movesSoFar)
- void [moveBackward](#) (int xPos, int yPos)
- void [moveForward](#) (int xPos, int yPos)
- void [printMoves](#) () const
- void [setDefault](#) ([vehicle](#) &other)

#### 3.1.1 Constructor & Destructor Documentation

##### 3.1.1.1 [traffic::traffic](#) ( )

#### Precondition

Unitialized Traffic Class

#### Postcondition

Grid Initialized numCars and numMoves intialized

#### Algorithm:

- Assign data members values

#### Exceptional/Error Conditions:

- none

### 3.1.2 Member Function Documentation

#### 3.1.2.1 `bool traffic::canMoveBack ( int xPos, int yPos ) const`

##### Precondition

none

##### Postcondition

none

##### Parameters

<i>xPos</i>	The x position of the vehicle to be checked
<i>yPos</i>	The y position of the vehicle to be checked

##### Returns

Returns if the car can move left or up

##### Algorithm:

- Check if moving will move it out of bounds
- check if moving will cause a collision

#### 3.1.2.2 `bool traffic::canMoveForward ( int xPos, int yPos ) const`

##### Precondition

none

##### Postcondition

none

##### Parameters

<i>xPos</i>	The x position of the vehicle to be checked
<i>yPos</i>	The y position of the vehicle to be checked

##### Returns

Returns if the car can move right or down

##### Algorithm:

- Check if moving will move it out of bounds
- check if moving will cause a collision

#### 3.1.2.3 `void traffic::getData ( int numCars )`

##### Precondition

Initialized Grid

##### Postcondition

Grid filled with vehicle data

## Parameters

<i>numCars</i>	This is how many cars to put into the grid
----------------	--

Algorithm:

- Get number of cars
- Insert cars into the Grid based on the input values

#### 3.1.2.4 void traffic::moveBackward ( int *xPos*, int *yPos* )

## Precondition

none

## Postcondition

Vehicle in the grid will be moved Left or Up

## Parameters

<i>xPos</i>	This is the x Position of the vehicle head to be moved
<i>yPos</i>	This is the y Position of the vehicle head to be moved

Algorithm:

- Change the head coordinates
- Assign new head coordinate the vehicle
- Set the tail of the vehicle to default values

#### 3.1.2.5 void traffic::moveForward ( int *xPos*, int *yPos* )

## Precondition

none

## Postcondition

Vehicle in the grid will be moved right or down

## Parameters

<i>xPos</i>	This is the x Position of the vehicle head to be moved
<i>yPos</i>	This is the y Position of the vehicle head to be moved

Algorithm:

- Change the head coordinates
- Assign new head coordinate the vehicle
- Set the head of the vehicle to default values

### 3.1.2.6 void traffic::printMoves ( ) const

#### Precondition

none

#### Postcondition

printed moves

#### Algorithm:

- output numMoves

### 3.1.2.7 void traffic::recSolve ( int movesSoFar )

#### Precondition

none

#### Postcondition

numMoves will now be the smallest moves possible

#### Parameters

<i>movesSoFar</i>	This is how many moves have been taken
-------------------	--

#### Algorithm:

- Check if used too many moves
- Check if finished the puzzle
- If not, find any cars that can move
- Move the cars that can and repeat

### 3.1.2.8 void traffic::setDefault ( vehicle & other )

#### Precondition

none

#### Postcondition

vehicle values changed to default

#### Parameters

<i>other</i>	This is the vehicle to be changed
--------------	-----------------------------------

#### Algorithm:

- assign vehicle data members default values

The documentation for this class was generated from the following file:

- [rushHour.h](#)

## 3.2 vehicle Class Reference

```
#include <rushHour.h>
```

### Public Member Functions

- [vehicle](#) ()
- [vehicle](#) (const [vehicle](#) &other)

### Public Attributes

- int [id](#)
- int [size](#)
- char [orientation](#)
- int [leftX](#)
- int [topY](#)
- bool [justMovedForward](#)
- bool [justMovedBackward](#)

### 3.2.1 Constructor & Destructor Documentation

#### 3.2.1.1 [vehicle::vehicle](#) ( )

##### Precondition

unitialized Vehicle class

##### Postcondition

initialized data members

##### Algorithm:

- initialize data members

#### 3.2.1.2 [vehicle::vehicle](#) ( const [vehicle](#) & *other* )

##### Precondition

unitialized Vehicle class

##### Postcondition

copied vehicle class

##### Algorithm:

- initialize data members using others

### 3.2.2 Member Data Documentation

3.2.2.1 int vehicle::id

3.2.2.2 bool vehicle::justMovedBackward

3.2.2.3 bool vehicle::justMovedForward

3.2.2.4 int vehicle::leftX

3.2.2.5 char vehicle::orientation

3.2.2.6 int vehicle::size

3.2.2.7 int vehicle::topY

The documentation for this class was generated from the following file:

- [rushHour.h](#)

## Chapter 4

# File Documentation

### 4.1 rushHour.cpp File Reference

```
#include <iostream>
#include "rushHour.h"
```

#### Functions

- int `main` ()

#### 4.1.1 Function Documentation

4.1.1.1 int main ( )

### 4.2 rushHour.h File Reference

```
#include <iostream>
```

#### Classes

- class `vehicle`
- class `traffic`

#### Variables

- const int `EMPTY_VAL` = -1

#### 4.2.1 Variable Documentation

4.2.1.1 const int `EMPTY_VAL` = -1

# Index

- canMoveBack
  - traffic, [6](#)
- canMoveForward
  - traffic, [6](#)
- EMPTY\_VAL
  - rushHour.h, [11](#)
- getData
  - traffic, [6](#)
- id
  - vehicle, [10](#)
- justMovedBackward
  - vehicle, [10](#)
- justMovedForward
  - vehicle, [10](#)
- leftX
  - vehicle, [10](#)
- main
  - rushHour.cpp, [11](#)
- moveBackward
  - traffic, [7](#)
- moveForward
  - traffic, [7](#)
- orientation
  - vehicle, [10](#)
- printMoves
  - traffic, [7](#)
- recSolve
  - traffic, [8](#)
- rushHour.cpp, [11](#)
  - main, [11](#)
- rushHour.h, [11](#)
  - EMPTY\_VAL, [11](#)
- setDefault
  - traffic, [8](#)
- size
  - vehicle, [10](#)
- topY
  - vehicle, [10](#)
- traffic, [5](#)
  - canMoveBack, [6](#)
  - canMoveForward, [6](#)

- getData, [6](#)
- moveBackward, [7](#)
- moveForward, [7](#)
- printMoves, [7](#)
- recSolve, [8](#)
- setDefault, [8](#)
- traffic, [5](#)
- vehicle, [9](#)
  - id, [10](#)
  - justMovedBackward, [10](#)
  - justMovedForward, [10](#)
  - leftX, [10](#)
  - orientation, [10](#)
  - size, [10](#)
  - topY, [10](#)
  - vehicle, [9](#)