Analysis Results

bankparserui-main.zip

Report Date
2026-04-22 06:49:01
Report Author
dctuser
Classification Method
By severity
Product Version
10.16
Rules Version
10.127506

Confidentiality Note

This report is intended only for the person(s) or entity to which it is addressed and contains confidential and privileged information. If you are not the intended recipient, you must not view, use, copy, disclose, or otherwise disseminate this report or any part of it. Doing so is strictly prohibited, and may result in legal proceedings. If you received this in error, please notify the sender immediately and destroy any copies of this information.

1 Project Information 4

Dynamics by vulnerabilities 5

Scan History 7

2 Scan Information 60/60 2026-04-22 06:28:49 14

Scan Statistics 14

Language Statistics 15

Vulnerability List 17

Analysis Results 18

WAF Setup Instructions 24

Scan Settings 25

3 Export Settings 27

01 Project Information

Project Name

bankparserui-main.zip

UUID

0e8b2d90-628f-43f7-9c68-c481e1c8be42

Project in DerScanner

Dynamics by vulnerabilities

Vulnerabilities are divided by severity level: critical, medium, low and info.

CRITICAL LEVEL

Likely to lead to compromise confidential data and violation of the integrity of the system.

MEDIUM LEVEL

May be less likely to lead to compromising confidential data and violating the integrity of the system, or are less serious security

LOW LEVEL

Can become a potential security risk.

INFORMATION

Signal a violation of good programming practice.

First of all, pay attention to vulnerabilities of critical and medium levels.



Dynamics by rating

The app score is calculated on a scale from 0 to 5. Score is calculated based on the number of critical and medium level vulnerabilities. The impact of critical vulnerabilities is greater than that of medium level vulnerabilities, and does not take into account the amount of code. Medium level vulnerabilities are taken into account based on their frequency and total number of source code lines.



Scan History

	Date and Time	Status	Languages	Lines of Code	Number of Vulnerabilities					Score
					Critical	Medium	Low	Info	Total	
60/60	2026-04-22 06:28:49	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	48 613	1	3	15	34	53	3.7/5.0
59/60	2026-04-21 11:54:15	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	47 958	0	3	15	34	52	4.7/5.0
58/60	2026-04-20 18:41:12	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	47 711	0	2	15	34	51	4.7/5.0
57/60	2026-04-20 09:45:42	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	46 504	0	2	15	34	51	4.7/5.0
56/60	2026-04-19 14:21:49	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	46 086	0	2	15	32	49	4.7/5.0
55/60	2026-04-17 04:25:58	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 421	0	2	15	31	48	4.7/5.0
54/60	2026-04-15 17:00:12	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 409	0	2	15	31	48	4.7/5.0
53/60	2026-04-15 10:52:22	completed	Config files, Python, JavaScript,	44 412	0	2	15	31	48	4.7/5.0

	Date and Time	Status	Languages	Lines of Code	Number of Vulnerabilities					Score
					Critical	Medium	Low	Info	Total	
			PL/SQL, T-SQL, HTML5							
52/60	2026-04-14 07:04:02	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 298	0	2	15	31	48	4.7/5.0
51/60	2026-04-14 06:30:20	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 412	0	2	15	32	49	4.7/5.0
50/60	2026-04-14 05:48:20	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 220	0	2	15	31	48	4.7/5.0
49/60	2026-04-14 05:28:32	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 220	0	2	15	31	48	4.7/5.0
48/60	2026-04-13 17:50:19	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 072	0	2	13	31	46	4.7/5.0
47/60	2026-04-13 17:41:18	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	44 072	0	2	13	31	46	4.7/5.0
46/60	2026-04-11 11:42:13	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	43 953	0	2	13	31	46	4.7/5.0
45/60	2026-04-08 11:53:09	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	43 924	0	2	13	31	46	4.7/5.0
44/60	2026-04-08 07:09:32	completed	Config files, Python,	43 819	0	2	13	31	46	4.7/5.0

	Date and Time	Status	Languages	Lines of Code	Number of Vulnerabilities					Score
					Critical	Medium	Low	Info	Total	
			JavaScript, PL/SQL, T-SQL, HTML5							
43/60	2026-04-08 06:26:28	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	43 862	0	2	13	31	46	4.7/5.0
42/60	2026-04-03 13:04:41	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	43 268	0	2	13	31	46	4.7/5.0
41/60	2026-04-03 05:58:11	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	42 953	0	2	13	30	45	4.7/5.0
40/60	2026-04-01 11:14:13	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	41 940	0	3	13	29	45	4.7/5.0
39/60	2026-03-31 13:19:09	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	41 655	0	3	13	29	45	4.7/5.0
38/60	2026-03-31 07:10:00	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	41 654	0	3	13	29	45	4.7/5.0
37/60	2026-03-30 11:59:36	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	40 709	0	3	13	25	41	4.7/5.0
36/60	2026-03-28 14:43:50	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	40 080	0	3	13	25	41	4.7/5.0
35/60	2026-03-28	completed	Config files,	39 137	0	3	13	25	41	4.7/5.0

	Date and Time	Status	Languages	Lines of Code	Number of Vulnerabilities					Score
					Critical	Medium	Low	Info	Total	
	13:41:19		Python, JavaScript, PL/SQL, T-SQL, HTML5							
34/60	2026-03-28 12:34:29	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 912	0	3	13	25	41	4.7/5.0
33/60	2026-03-25 05:05:46	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 782	0	3	13	24	40	4.7/5.0
32/60	2026-03-21 14:31:25	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 720	0	3	13	24	40	4.7/5.0
31/60	2026-03-12 11:12:38	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 218	0	0	12	21	33	5.0/5.0
30/60	2026-03-12 10:16:10	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 186	0	0	12	21	33	5.0/5.0
29/60	2026-03-12 10:14:53	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 141	0	0	12	21	33	5.0/5.0
28/60	2026-03-11 12:40:09	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 142	0	0	12	21	33	5.0/5.0
27/60	2026-03-11 10:19:38	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 142	0	0	12	21	33	5.0/5.0

	Date and Time	Status	Languages	Lines of Code	Number of Vulnerabilities					Score
					Critical	Medium	Low	Info	Total	
26/60	2026-03-09 17:47:33	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 142	0	0	12	21	33	5.0/5.0
25/60	2026-03-05 08:09:46	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 143	0	0	12	21	33	5.0/5.0
24/60	2026-03-05 07:02:46	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 142	0	0	12	21	33	5.0/5.0
23/60	2026-03-05 06:37:46	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 142	0	0	12	21	33	5.0/5.0
22/60	2026-03-05 06:35:46	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 142	0	0	12	21	33	5.0/5.0
21/60	2026-03-05 06:21:31	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 144	0	0	12	21	33	5.0/5.0
20/60	2026-03-05 02:51:25	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 144	0	0	12	21	33	5.0/5.0
19/60	2026-03-03 12:14:40	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 143	0	0	11	21	32	5.0/5.0
18/60	2026-03-03 12:13:39	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 140	0	0	11	21	32	5.0/5.0

	Date and Time	Status	Languages	Lines of Code	Number of Vulnerabilities					Score
					Critical	Medium	Low	Info	Total	
17/60	2026-03-03 11:18:09	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 140	0	0	11	21	32	5.0/5.0
16/60	2026-03-03 09:07:39	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 102	0	0	10	21	31	5.0/5.0
15/60	2026-03-03 06:25:48	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 103	0	0	10	21	31	5.0/5.0
14/60	2026-03-03 05:46:48	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 281	2	9	11	28	50	3.2/5.0
13/60	2026-03-02 12:51:06	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 283	2	10	11	28	51	3.2/5.0
12/60	2026-03-02 11:35:36	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 251	2	10	11	28	51	3.2/5.0
11/60	2026-02-25 13:46:21	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 132	2	7	11	28	48	3.3/5.0
10/60	2026-02-25 13:05:52	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 123	2	6	10	28	46	3.3/5.0
9/60	2026-02-25 13:04:50	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	38 124	2	6	10	28	46	3.3/5.0

	Date and Time	Status	Languages	Lines of Code	Number of Vulnerabilities					Score
					Critical	Medium	Low	Info	Total	
8/60	2026-02-25 05:21:23	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 084	2	4	9	21	36	3.3/5.0
7/60	2026-02-24 09:13:59	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 059	1	0	9	21	31	4.0/5.0
6/60	2026-02-24 07:04:28	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 052	1	0	9	21	31	4.0/5.0
5/60	2026-02-20 08:38:02	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 054	1	0	9	21	31	4.0/5.0
4/60	2026-02-20 07:23:41	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 017	2	29	9	21	61	3.1/5.0
3/60	2026-02-19 15:14:00	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	37 025	1	29	9	21	60	3.5/5.0
2/60	2026-02-19 11:50:29	completed	Config files, Python, JavaScript, PL/SQL, T-SQL, HTML5	36 782	0	28	9	21	58	4.4/5.0
1/60	2026-02-19 11:04:46	completed	Config files	4	0	0	0	0	0	5.0/5.0

02

Scan Information

60/60 2026-04-22 06:28:49
10.127506

Scan Statistics

Status
completed

Score
3.7/5.0

Duration
0:07:36

Lines of Code
48 613

Vulnerabilities

1	3	15	34
Critical	Medium	Low	Info

53
Total

Language	Status	Duration	Lines of Code	Number of Vulnerabilities				
				Critical	Medium	Low	Info	Total
Config files	completed	0:00:02	28 655	0	0	4	0	4
Python	completed	0:07:25	18 581	1	3	9	34	47
JavaScript	completed	0:00:05	693	0	0	2	0	2
PL/SQL	completed	0:00:01	300	0	0	0	0	0
T-SQL	completed	0:00:01	299	0	0	0	0	0
HTML5	completed	0:00:00	85	0	0	0	0	0

Language Statistics



Diagram of identified vulnerabilities



Vulnerable Dependencies

Vulnerability List

Vulnerabilities are displayed accordingly to export settings: **4 selected**

Actual: **4 of 53**

Critical vulnerabilities		**1**
Hardcoded password	Python	1
src/api/mssql_source.py:126		Not processed
Medium-level vulnerabilities		**3**
Null encryption key	Python	1
src/core/analysis.py:226		Not processed
Resource injection	Python	2
src/ui/upload_app.py:933		Not processed
src/ui/upload_app.py:938		Not processed
Low-level vulnerabilities		**0**
Info-level vulnerabilities		**0**

* Rejected vulnerabilities are not taken into account

Analysis Results

Hardcoded password (Python)

Description

Password is hardcoded. This may lead to an application data compromise.
Eliminating security risks related to hardcoded passwords is extremely difficult. These passwords are at least accessible to every developer of the application. Moreover, after the application is installed, removing password from its code is possible only via an update. Constant strings are easily extracted from the compiled application by decompilers. Therefore, an attacker does not necessarily need to have an access to the source code to know the parameters of the special account. If these parameters become known to an attacker, system administrators will be forced either to neglect the safety, or to restrict the access to the application.

Example

In the following example, a password is hardcoded:
password = "hardcoded"

Recommendations

- Store not passwords but values of cryptographically secure hash function from the password. Use specialized hash functions designed for this purpose (bcrypt, PBKDF2, scrypt). Use salt obtained from cryptographically secure pseudorandom number generator to resist attacks which use rainbow tables.
- If the hardcoded password is used for the initial authorization, provide the special authentication mode for this purpose in which the user is required to provide his/her own unique password.
- Store authentication information in an encrypted form in a separate configuration file or in a database. Secure the encryption key. If encryption is not possible, limit the access to the repository as much as possible.

Links

1. Use of hard-coded password

2. CWE-259: Use of Hard-coded Password
3. OWASP Top 10 2013-A5-Security Misconfiguration
4. OWASP Top 10 2013-A6-Sensitive Data Exposure
5. Handling passwords used for auth in source code - stackoverflow.com
6. How to securely hash passwords? - security.stackexchange.com
7. OWASP Top 10 2017 A2-Broken Authentication
8. OWASP Top 10 2017-A3-Sensitive Data Exposure
9. CWE-798: Use of Hard-coded Credentials
10. CWE CATEGORY: OWASP Top Ten 2017 Category A2 - Broken Authentication
11. CWE CATEGORY: OWASP Top Ten 2017 Category A6 - Security Misconfiguration

Vulnerability Entries

src/api/mssql_source.py:126

Level Critical

Status Not processed

```
123 _ALIAS_HOST = {"server", "datasource", "addr", "address", "networkaddress"}
124 _ALIAS_DATABASE = {"database", "initialcatalog"}
125 _ALIAS_USER = {"uid", "userid", "user"}
126 _ALIAS_PASSWORD = {"pwd", "password"}
127 _ALIAS_TRUST_CERT = {"trustservercertificate"}
128 _ALIAS_ENCRYPT = {"encrypt"}
129 _ALIAS_TIMEOUT = {"connecttimeout", "connectiontimeout", "timeout"}
```

Null encryption key (Python)

Description

Key with a value of None can result in an application compromise.
You should never use a null encryption key, since it significantly reduces the protection afforded by a good encryption algorithm, but also makes fixing the problem difficult. Information that it uses a null key encryption is accessible to at least every developer of the application. After the application is installed, the null encryption key can not be removed without updating the software. If an account that is protected by a null encryption key is compromised, system administrators will be forced either to neglect the safety, or to restrict the access to the application. Constant strings are easily extracted from the compiled application by decompilers. Therefore, it is not necessary for an attacker to have access to the source code, to determine that a null encryption key is used.
Sensitive Data Exposure vulnerabilities take the third place in the “OWASP Top 10 2017” web-application vulnerabilities ranking.

Example

In the following example, a password is hardcoded and is of value None:
key = None

Recommendations

- Use non-null encryption keys.
- To generate the keys, it is recommended to use a cryptographically secure PRNG (pseudorandom number generators).
- To store keys, you need to use special solutions, such as Hardware Security Modules.
- For security reasons, you need to regularly update your keys.

Links

1. Use of hard-coded password
2. CWE-321: Use of Hard-coded Cryptographic Key
3. OWASP Top 10 2013-A5-Security Misconfiguration
4. OWASP Top 10 2013-A6-Sensitive Data Exposure
5. OWASP Top 10 2017-A3-Sensitive Data Exposure
6. CWE CATEGORY: OWASP Top Ten 2017 Category A6 - Security Misconfiguration
7. OWASP Top 10 2021-A2-Cryptographic Failures

Vulnerability Entries

src/core/analysis.py:226

Level Medium

Status Not processed

```
223                 amount_col="_affil_amount",
224             ) or None
225     except Exception:
226         excluded_counterparty_keys = None
227
228 if excluded_counterparty_keys:
229     ensure_counterparty_columns(df_win)
```

Resource injection (Python)

Description

An attacker can gain access to reading and changing protected system resources of the application has the ability to change the resource identifier.
Resource injection occurs when an atacker can specify identifier that will be used to access the system resource (for example, the port number to connect to the network resource). This allows him, in particular, to transfer valuable data to thied-party server.

Example

In the following example, the program executes a HTTP request in order to find out the price of tickets:

```
host_name = request.GET['host_example']
dbc = db.connect(host = host_name, port = 1235, dbname = ticket_data_base)
c = dbc.cursor()
###
result = c.execute('SELECT * FROM price_list')
###
```

If the request contains special characters, the attacker can receive confidential data.

Recommendations

- Create a whitelist of valid resource IDs and allow a user to select from this list and not to set his/her own value.
- If maintaining a whitelist is too difficult because of the large number of valid IDs, create a whitelist of characters allowed in identifiers. Blacklist in this case is ineffective, as it is likely to initially be incomplete, or sooner or later cease to be relevant.
- If nonetheless blacklist is chosen as a validation mechanism, make sure that it takes into account all the possible encodings and special character values (different for different operating systems). Changing the list should be simple when changing the requirements for validation.

Links

1. OWASP Top 10 2017-A1-Injection
2. OWASP Top 10 2013-A1-Injection
3. OWASP Top 10 2013-A4-Insecure Direct Object References
4. CWE-99: Improper Control of Resource Identifiers (‘Resource Injection’)
5. Dangerous Python Functions, Part 2

6. Create, use, and remove temporary files securely
7. CWE CATEGORY: OWASP Top Ten 2017 Category A1 - Injection
8. CWE-1030

Vulnerability Entries

src/ui/upload_app.py:933

Level Medium

Status Not processed

```
930 for attr in ("enriched_df", "monthly_income_df"):
931     edf = getattr(ps, attr, None)
932     if edf is not None and isinstance(edf, pd.DataFrame) and len(edf) >
SESSION_STATEMENT_MAX_ROWS:
933         setattr(ps, attr, edf.tail(SESSION_STATEMENT_MAX_ROWS).copy())
934
935 for attr in ("header_df", "footer_df", "meta_df"):
936     hdf = getattr(ps, attr, None)
```

src/ui/upload_app.py:938

Level Medium

Status Not processed

```
935     for attr in ("header_df", "footer_df", "meta_df"):
936         hdf = getattr(ps, attr, None)
937         if hdf is not None and isinstance(hdf, pd.DataFrame) and len(hdf) >
SESSION_HEADER_META_MAX_ROWS:
938             setattr(ps, attr, hdf.head(SESSION_HEADER_META_MAX_ROWS).copy())
939
940
941 def _lighten_upload_results_for_session(results: List[Dict[str, Any]], anchor_date: Optional
[date]) -> None:
```

WAF Setup Instructions

Resource injection

Description

An attacker can gain access to reading and changing protected system resources of the application has the ability to change the resource identifier.
Resource injection occurs when an atacker can specify identifier that will be used to access the system resource (for example, the port number to connect to the network resource). This allows him, in particular, to transfer valuable data to thied-party server.

Vulnerability Entries

1. src/ui/upload_app.py:933
2. src/ui/upload_app.py:938

Scan Settings

60/60 2026-04-22 06:28:49

Select files for Analysis

**/*

Branch in Repository

master

Languages

- [ ] ABAP
- [ ] Apex
- [x] C#
- [ ] C/C++
- [ ] COBOL
- [x] Config files
- [x] Dart
- [x] Go
- [ ] Groovy
- [x] HTML5
- [x] Java, Scala, Kotlin
- [x] JavaScript, TypeScript
- [ ] LotusScript
- [ ] Objective-C
- [ ] Delphi, Pascal
- [x] PHP
- [x] PL/SQL, T-SQL
- [x] Python
- [ ] Perl
- [x] Ruby
- [x] Rust
- [x] Solidity
- [x] Swift
- [ ] TSX
- [ ] VB.NET, VBA, VBScript, VB6
- [ ] Vyper
- [ ] 1C

Java/Scala/Kotlin Specific Settings

- (●) Prebuilt project with .class files
- ( ) Source code (will be built by DerScanner)
- ( ) Source code (no build needed, only for Java)
- ( ) Source code (build with own tools)

JavaScript Specific Settings

- [ ] Analyze standard libraries

General Analysis Settings

- [ ] Analyze libraries and nested archives
- [ ] Use extra rules
- [ ] Incremental analysis
- [x] Preprocessing

Source Code Charset	UTF-8
Filename Charset	UTF-8

Rule Sets —

03 Export Settings

Project Information

Project Statistics

- [x] Dynamics by rating
- [x] Dynamics by vulnerabilities

Scan History

- ( ) Do not export scan history
- (•) Export entire scan history
- ( ) Export the latest scans ...

Vulnerability Classification

By severity

Scan Information

- [x] Detected vulnerabilities chart
- [x] Vulnerable Dependencies
- [x] Statistics on languages
- [ ] Analyzed files statistics
- [x] Error information
- [x] Scan settings
- [x] Version Properties

Vulnerability Filter

Severity

- [x] Critical
- [x] Medium
- [ ] Low
- [ ] Info

Vulnerable Dependencies

- [x] In standard libraries

- [x] In .class files that cannot be decompiled
- [x] Vulnerabilities without WAF configuration guide

Languages

- [x] ABAP
- [x] Android
- [x] Apex
- [x] C#
- [x] C/C++
- [x] COBOL
- [x] Config files
- [x] Dart
- [x] Delphi
- [x] Go
- [x] Groovy
- [x] HTML5
- [x] Java
- [x] JavaScript
- [x] Kotlin
- [x] LotusScript
- [x] Objective-C
- [x] Pascal
- [x] PHP
- [x] PL/SQL
- [x] Python
- [x] Perl
- [x] Ruby
- [x] Rust
- [x] Scala
- [x] Solidity
- [x] Swift
- [x] T-SQL
- [x] TSX
- [x] TypeScript
- [x] VB.NET
- [x] VBA
- [x] VBScript
- [x] Visual Basic 6
- [x] Vyper
- [x] 1C

Vulnerability List

Vulnerability Statuses

- [x] Not processed
- [x] Confirmed
- [ ] Rejected

List of Vulnerability Entries

- ( ) Do not export
- (•) Export all entries
- ( ) Export no more than entries ...

Analysis Results

Vulnerability Statuses

- [x] Not processed

- [x] Confirmed
- [ ] Rejected

Vulnerability Entries

- ( ) Do not export
- (•) Export all entries
- ( ) Export no more than entries ...

Source Code

- ( ) Do not export source code
- ( ) Export entire vulnerable source code file
- (•) Export context in the number of lines of code 3

Trace

- ( ) Do not export trace items
- ( ) Export all items
- (•) Export only the first and last items

Additional information

- [x] Vulnerability comment
- [x] Vulnerability actions

WAF Setup Instructions

Guide for Vulnerability Statuses

- [x] Not processed
- [x] Confirmed
- [ ] Rejected

Guide for WAF

- [x] Imperva SecureSphere
- [x] ModSecurity
- [x] F5

General Report Settings

- [x] Table of contents
- [x] Report export settings
- [x] Display vulnerability statuses
- [x] Display results correlation tags