Mathematical Derivations for CARA

We give complete derivations for CARA's query-preservation and one-action admission guarantees. The query results cover family compilation, seed-universal matching, incremental summary views, certified profile acquisition, and deferred physical assignment. The admission results cover finite historical tables and fresh expected gains, including component-conservation supports and numerical enclosures at strict decision boundaries.

1 Placement, workload profiles, and observation roles

Let N workloads occupy H nonempty homogeneous physical hosts with common capacity $C > 0$. A placement assigns every workload exactly once. Hosts have no additional affinity or pinning restrictions. The incumbent is π^{I}, and the selected repair is $\widehat{\pi}$. A scene Z_b supplies finite nonnegative demands x_{bit} for workload $i \in [N]$ and time $t \in [T]$. Its real-arithmetic load is

$$\ell_{bht}(\pi) = \sum_{i:\pi(i)=h} x_{bit}. \tag{1}$$

All candidate feasibility checks use the same supplied forecast $\widehat{x}_{it}$ and the same arithmetic tolerance τ:

$$\sum_{i:\pi(i)=h} \widehat{x}_{it} \le C + \tau \quad (h \in [H],\ t \in [T]). \tag{2}$$

This is a structural forecast predicate. The realized workloads need not satisfy it.

Write $q_{bht} = \mathbf{1}\{\ell_{bht} > C + \tau\}$, $o_{bht} = \mathbf{1}\{\ell_{bht} > C\}$, $e_{bht} = [\ell_{bht}/C - 1]_+$, $a_{bh} = \mathbf{1}\{\max_t \ell_{bht} > 0\}$, and $A_b = \sum_h a_{bh}$. The historical profile contains occurrence $J_b = \max_{h,t} q_{bht}$, affected-host fraction $V_b = H^{-1} \sum_h \max_t q_{bht}$, and the native workload measures

$$\mathrm{VR}_b = \frac{\sum_h T^{-1} \sum_t o_{bht}}{A_b}, \qquad u_b = \frac{\sum_h T^{-1} \sum_t e_{bht}}{A_b}, \tag{3}$$

$$n_{bh} = \sum_t o_{bht}, \qquad \mathrm{VS}_b = \frac{\sum_{h:n_{bh}>0} n_{bh}^{-1} \sum_t e_{bht}}{\sum_h \mathbf{1}\{n_{bh} > 0\}}, \tag{4}$$

$$p_{bh} = \max_t \ell_{bht}, \qquad \mathrm{PAR}_b = \frac{\max_h p_{bh}}{A_b^{-1} \sum_h p_{bh}}. \tag{5}$$

Severity is zero when no host overloads. For an all-idle scene the native replay uses $\mathrm{VR} = \mathrm{PAR} = -1$ and $u = \mathrm{VS} = 0$. Thus the historical profile is $L_b^{\mathrm{hist}} = (J_b, V_b, \mathrm{VR}_b, u_b, \mathrm{VS}_b, \mathrm{PAR}_b)$. The displayed expressions specify real-arithmetic quantities; the canonical replay described below fixes their stored reduction order as well.

Fresh-scene certification uses the fixed-host profile $L^{\mathrm{fr}} = (J, V, R, u_H)$, where

$$R = \frac{1}{HT} \sum_{h,t} q_{ht}, \qquad u_H = \frac{1}{HT} \sum_{h,t} e_{ht}. \tag{6}$$

Fixed H makes these denominators invariant to idle hosts. In particular, R need not equal native VR, and u_H need not equal active-host-normalized u. The gain for any specified loss coordinate is the incumbent loss minus the action loss:

$$G_e(Z) = L_e(\pi^{\mathrm{I}}, Z) - L_e(\widehat{\pi}, Z). \tag{7}$$

For inference, these two losses are the stored binary64 values, interpreted as exact rationals; G_e does not introduce a second rounded subtraction.

Fit supplies the forecast, Build supplies proposal and allocation feedback, and Selection fixes one candidate. Let $\mathcal{F}_0$ include the environment, these observations, the entire proposal transcript, the chosen physical host matching, the final action, all support bounds, and all inferential targets. Conditional on $\mathcal{F}_0$, fresh scenes are iid. No Certification or Evaluation feedback changes the candidate. The released placement equals $\widehat{\pi}$ upon admission and π^{I} otherwise, including empty-pool and evidence-cap outcomes. The historical gate and fresh certificate concern different objects: the former compares its supplied finite table, whereas the latter concerns expectations under the declared fresh-scene law.

2 Complete residual queries and retention

Fix a feasible seed and two nonempty hosts. Let U be the mutable workloads, and let B_1, B_2 be the remaining residents of these hosts. These three sets are pairwise disjoint. Every declared residual assignment has the form

$$(B_1 \cup A,\ B_2 \cup (U \setminus A)), \qquad A \subseteq U. \tag{8}$$

A bit vector in $\{0,1\}^{|U|}$ selects precisely one such subset A. Conversely, every assignment of the mutable workloads to the two labeled hosts selects that bit vector. Enumerating these vectors therefore covers the complete declared labeled family.

Assignments with an empty host, a failed forecast predicate, or a failed incumbent-relative movement constraint are removed. Every other host has its seed membership and remains forecast feasible. Checking the changed groups is therefore sufficient when the seed has already been checked. Canonicalization identifies equal physical partitions, and a previously scored assignment need not be scored again because its fixed Build profile and movement score do not depend on its generating seed. Completion of the family before a new allocation decision accounts for every eligible distinct action through canonical scoring or a valid exclusion certificate.

If $B_1 = B_2 = \varnothing$, swapping the two host labels maps A to $U \setminus A$ and leaves the same unordered partition. Since the seed has two nonempty hosts, U contains at least two workloads. The two complementary subsets are distinct, and exactly one contains $\min U$. Fixing that workload to the first side retains exactly one representative from each host-exchange pair. If either background is nonempty, one of its fixed residents identifies that side: host exchange no longer maps the declared family to itself. Restricting $\min U$ in that case could remove a distinct physical action, so the full $2^{|U|}$ enumeration is required.

The family is exact for its declared seed, pair, and mutable set. The controller may examine several such families before its budget is exhausted.

For retention, let $\succ$ be the fixed total Build order, including deterministic placement tie-breaking. Under balanced retention, maintaining the best P after every insertion preserves the best P of the scored union. Indeed, at the instant an action is discarded, at least P distinct actions precede it; subsequent insertions cannot improve its rank. The score must depend only on its fixed incumbent, workload panel, and placement, as is the case here.

3 Physical matching and incumbent-relative migration

Let $I_1, \ldots, I_H$ be the incumbent resident sets and $C_1, \ldots, C_H$ the candidate's unlabeled groups. Set $n_{hk} = |I_h \cap C_k|$. A permutation σ installs candidate group $C_{\sigma(h)}$ on old physical host h. The unchanged workloads are exactly the disjoint intersections $I_h \cap C_{\sigma(h)}$. Therefore

$$\#\text{unchanged}(\sigma) = \sum_{h=1}^{H} n_{h,\sigma(h)}, \tag{9}$$

$$m(\widehat{\pi}, \pi^{\mathrm{I}}) = \min_{\sigma \in S_H} \left(N - \sum_{h} n_{h,\sigma(h)} \right) = N - \max_{\sigma \in S_H} \sum_{h} n_{h,\sigma(h)}. \tag{10}$$

The maximizing bipartite matching both determines the physical destinations and minimizes the final movement count. All proposals are matched against the fixed incumbent, rather than merely against the preceding search seed. Consequently $m \leq K$ is a constraint on the final action. The matching domain contains every host bijection.

Optional nonuniform movement weights can break ties between maximum-overlap matchings exactly. For finite nonnegative binary64 costs c_i, choose a common power-of-two denominator D_c and integers $z_i = D_c c_i$. Let $z_{hk} = \sum_{i \in I_h \cap C_k} z_i$ and $P_c = 1 + \sum_i z_i$. Optimize the integer objective

$$\max_{\sigma \in S_H} \sum_{h} (P_c n_{h,\sigma(h)} + z_{h,\sigma(h)}). \tag{11}$$

The secondary retained-weight difference between any two matchings has magnitude at most $\sum_i z_i = P_c - 1$. Increasing retained count by one therefore increases the objective by at least $P_c - (P_c - 1) = 1$, regardless of that secondary difference. Among equal-count matchings, maximizing retained weight minimizes moved weight because their sum is the fixed total $\sum_i z_i$. Integer assignment arithmetic preserves both comparisons. The unit-cost family processor uses the integer movement count in Eq. (10); weighted configurations retain this full lexicographic matcher.

Lemma 1 (Shared memberships and the action footprint)**.** *Let $(I_h)_{h=1}^H$ and $(A_h)_{h=1}^H$ be two partitions of the same finite VM set into H nonempty resident sets on homogeneous hosts. All host bijections are permitted. Let σ maximize the total overlap $\sum_{h=1}^H |I_h \cap A_{\sigma(h)}|$, with arbitrary secondary tie breaking, and realize the candidate by assigning resident set $A_{\sigma(h)}$ to incumbent physical host h. Write $\mathcal{K}_I = \{I_h : h \in [H]\}$ and $\mathcal{K}_a = \{A_h : h \in [H]\}$ for the membership sets. Their overlap fraction is $\rho(a) = |\mathcal{K}_I \cap \mathcal{K}_a|/H$. Then every common resident set is paired with itself by every maximizing bijection. Consequently, if $F(a)$ is the set of physical hosts incident to a VM migration, then*

$$|F(a)| = H - |\mathcal{K}_I \cap \mathcal{K}_a| = H\big(1 - \rho(a)\big). \tag{12}$$

Proof. Write $w_{hj} = |I_h \cap A_j|$. Suppose $I_h = A_j = S$. Because the resident sets form partitions and S is nonempty, $w_{hj} = |S| > 0$, $w_{h\ell} = 0$ for every $\ell \neq j$, and $w_{rj} = 0$ for every $r \neq h$. Assume a maximizing bijection does not pair this common resident set with itself. Then $\ell = \sigma(h) \neq j$ and $r = \sigma^{-1}(j) \neq h$. Replace the two pairs (h, ℓ) and (r, j) by (h, j) and (r, ℓ), leaving all other pairs unchanged. This is another permitted bijection, and its overlap increases by

$$w_{hj} + w_{r\ell} - w_{h\ell} - w_{rj} = |S| + w_{r\ell} > 0, \tag{13}$$

contradicting maximality. Hence every common resident set is preserved. Conversely, a physical host is unchanged precisely when its realized resident set equals its incumbent resident set. Such

an equality is a common membership key. Nonempty disjoint resident sets have distinct keys, so the number of unchanged hosts is exactly $|\mathcal{K}_I \cap \mathcal{K}_a|$. Finally, a physical host is incident to a migrated VM if and only if its resident set changes: membership inequality supplies a VM entering or leaving it, whereas an entering or leaving VM supplies membership inequality. Subtracting the unchanged-host count from H proves (12). □

4 Factoring the family matching query

4.1 Count signatures

Let n_r count the free mutable workloads whose incumbent host is r, and let $a_r(A)$ count those assigned to the first changed group by mask A. A symmetry-fixed workload, when present, is included in the fixed background. Write c_{r0}, c_{r1} for background overlaps. In the seed's column order the varying overlap entries are

$$W(A)_{r0} = c_{r0} + a_r(A), \qquad W(A)_{r1} = c_{r1} + n_r - a_r(A). \tag{14}$$

Every other column is fixed. Thus the vector $a(A) = (a_r(A))_r$ determines the complete overlap matrix and its optimum retained count. There are at most

$$S \le \prod_{r:n_r>0} (n_r + 1) \tag{15}$$

such vectors, compared with $2^{|U|}$ unrestricted masks. Masks in one signature class can have different resident sets and workload scores. Only their matching objective is shared. Relabeling candidate columns canonically is a bijection on perfect matchings and therefore preserves its optimum value.

4.2 Support components

Let $\mathcal{B} = (R \cup C, E)$ be a bipartite graph on the H incumbent rows and H seed columns. Its edge set contains every pair (r, c) for which $W(A)_{rc} > 0$ in some family member. Adding extra edges is allowed. To include the seed itself, the construction starts with every positive seed overlap and adds both possible destinations of each mutable workload. Consequently the graph is fixed before any capacity or score filtering. Let its connected components be (R_j, C_j), with $r_j = |R_j|$ and $c_j = |C_j|$, including isolated vertices, and write $E_j = E \cap (R_j \times C_j)$. For a mask A, define

$$\begin{aligned} v_j(A) = \max_{M_j} \sum_{(r,c)\in M_j} W(A)_{rc}, \\ M_j \subseteq R_j \times C_j, \quad |M_j| = \min(r_j, c_j), \end{aligned} \tag{16}$$

where M_j is a matching in the complete rectangular submatrix, including zero entries. Put $v_j(A) = 0$ when either vertex set is empty.

Theorem 1 (Support-component factorization)**.** *For every family member with nonnegative overlaps and unrestricted host bijections,*

$$\max_{\sigma\in S_H} \sum_{r=1}^{H} W(A)_{r,\sigma(r)} = \sum_j v_j(A), \qquad m(A) = N - \sum_j v_j(A). \tag{17}$$

The statement permits unequal row and column counts within a component. A component containing neither changed column has a constant optimum throughout the family.

Proof. Fix a global perfect matching M. Each of its positive edges belongs to one component. In component j, these positive edges form a partial matching. If it has fewer than $\min(r_j, c_j)$ edges, an unused row and an unused column both exist and can be joined inside the complete rectangular matrix. Repeating this step extends the partial matching to the cardinality in Eq. (16). All weights are nonnegative, so the extension cannot decrease its weight. Hence

$$\sum_{(r,c)\in M} W(A)_{rc} = \sum_j \sum_{(r,c)\in M\cap E_j} W(A)_{rc} \le \sum_j v_j(A). \tag{18}$$

Taking the maximum over global perfect matchings proves one inequality.

Conversely, choose an optimal rectangular matching in every component. Their union leaves $\max(r_j - c_j, 0)$ unmatched rows and $\max(c_j - r_j, 0)$ unmatched columns in component j. Its two types of surplus cannot both be positive. Since $\sum_j r_j = \sum_j c_j = H$,

$$\sum_j \max(r_j - c_j, 0) = \sum_j \max(c_j - r_j, 0). \tag{19}$$

Pair these remaining rows and columns arbitrarily. Each pair joins different components, because no component has both kinds of surplus. By the graph's construction every such entry of $W(A)$ is zero. The completed perfect matching therefore has weight exactly $\sum_j v_j(A)$, proving the reverse inequality. Finally, all entries outside the two changed columns are constant by Eq. (14). Any component disjoint from those columns has a fixed submatrix and optimum. □

In this support construction, an unchanged group identical to an incumbent group is an isolated positive edge and contributes its cardinality directly. When the seed equals the incumbent, every unchanged host has this form, and the varying matching is only 2×2. For an intermediate seed, a component can contain more rows or columns; its size is determined by the support graph. Including an unnecessary edge can merge components and increase work, but preserves Theorem 1. Omitting a possible positive edge would invalidate its premise.

Let $\mathcal{A}$ be the components meeting the two changed columns. The fixed components are solved once, and each distinct count signature requires solves only in $\mathcal{A}$. With a rectangular assignment bound $O(rc\min(r, c))$, the matching work is

$$O\left(\sum_{j\notin\mathcal{A}} r_j c_j \min(r_j, c_j) + S\sum_{j\in\mathcal{A}} r_j c_j \min(r_j, c_j)\right), \tag{20}$$

versus $O(SH^3)$ for full matching at each signature. Forming the sparse support reads the workload assignments once; materializing component matrices uses $\sum_j r_j c_j$ cells. The factorization returns the optimum count. The prescribed full matcher supplies the physical destinations of retained candidates by default. Section 5.6 gives a certificate that recovers the same output when the physical optimum is unique.

4.3 Subtree movement bounds

In an aligned mask interval, add each unresolved row count to both varying columns of the forced overlap matrix. A perfect matching uses each incumbent row once and the two changed columns on distinct rows. For the row matched to the first changed column, route all its unresolved workloads to that column; for the row matched to the second, route all its unresolved workloads to the second. These assignments are compatible, and the remaining unresolved workloads can be placed

arbitrarily. Thus the relaxed retained count is attained by an unrestricted completion. Capacity and nonempty-host restrictions can only reduce the eligible optimum. Subtracting this relaxed retained count from N is therefore a lower bound on movement for every eligible descendant. Its positive edges are contained in the same support graph, so component factorization applies to this bound as well.

4.4 Agreement with the prescribed unit-cost matcher

The unit-cost physical matcher assigns an overlap c the stored score $w(c) = \mathrm{RN}(c + \mathrm{RN}(c/(2N)))$. For integer $c \le N \le 2^{50}$, the inputs c and $2N$ are exactly representable. With $u = 2^{-53}$ and $\eta = 2^{-1074}$, the elementary rounding bound gives

$$\left| w(c) - c\left(1 + \frac{1}{2N}\right) \right| \le uc + \frac{(2u + u^2)c}{2N} + (2 + u)\eta. \tag{21}$$

Every assignment selects overlap counts totaling at most N, including the subtree relaxation, since each selected entry is bounded by its incumbent row population. With $H \le N$, its total stored-score error is at most $E = u(N+2) + 3H\eta < 0.126$. Distinct retained integer totals have ideal score gap at least one, while $2E < 0.252$. An optimum stored-score assignment consequently maximizes the same integer retained count, under the assignment solver's optimality contract. Equal-count physical mappings may still differ, so a count value alone cannot replace the final physical tie-breaking routine. Section 5.6 treats the case in which the full optimum is proved unique.

5 A family-wide core for migration matching

Neighborhood removal is an established fixed-edge reduction for a single weighted matching [7]. Its monotonicity permits unchanged target edges to be certified against a common family envelope. We derive the positive certificate graph's star structure and a migration-dependent bound that holds for the actual greedy reduction, then combine the resulting shared core with standard local assignment updates [4, 6]. The original full matcher supplies the final physical action unless the family certificate uniquely determines that same output as shown below.

Weighted matching kernels can instead be bounded by the positive support's feedback-edge number [5]. The dimension bound below uses the seed's migration mass and incumbent occupancies, so it does not require that topological parameter to be small.

5.1 Matrices and family envelopes

Consider a repair family with H original hosts and H candidate groups in a fixed seed-column order. Its nonnegative integer overlap matrix is $W(a) \in \mathbb{Z}_{\ge 0}^{H \times H}$, and the optimum retained count is

$$v(a) = \max_{\sigma \in S_H} \sum_{i=1}^{H} W_{i,\sigma(i)}(a). \tag{22}$$

Zero-weight edges are allowed: a zero overlap does not forbid a physical destination. Every row has the same sum $s_i \ge 1$ throughout the family, since every original workload belongs to exactly one candidate group. Thus $N = \sum_i s_i$ is fixed. Let J be the set of edited columns and $p = |J|$; CARA has $p = 2$. For $j \notin J$, every entry of column j equals its seed value W^0_{ij}. We include the seed when constructing family bounds, even when symmetry removal excludes its particular representative from enumeration.

Let U_{ij} bound $W_{ij}(a)$ from above for every family member and for the seed. For an unedited column use $U_{ij} = W^0_{ij}$. For an edited column the bound is also chosen to obey the row budget

$$U_{ij} \le r_i := s_i - \sum_{k \notin J} W^0_{ik}, \qquad j \in J. \tag{23}$$

This restriction is valid because r_i is the conserved total mass of row i in the edited columns. The ordinary two-host envelope has $U_{i,c} = b_{i,c} + n_i$, where $b_{i,c}$ is the fixed background overlap in edited column c and n_i is the number of mutable workloads originating on host i. It satisfies (23); taking its maximum with the seed entry preserves the same inequality. The two edited upper bounds need not be simultaneously attainable.

For a positive entry of an unedited column define

$$w_{ij} := W^0_{ij} > 0, \qquad R_{ij} := \max_{k \ne j} U_{ik}, \qquad C_{ij} := \max_{\ell \ne i} U_{\ell j}. \tag{24}$$

An empty maximum is zero. Call (i, j) certified when

$$w_{ij} \ge R_{ij} + C_{ij}. \tag{25}$$

For a single matrix, (25) is the $b \equiv 1$, size-two-edge specialization of neighborhood removal [7]. The family form is its monotone consequence: the target weight is fixed, and replacing either competing edge by an upper bound can only make the inequality harder to satisfy. The certificate is therefore shared by every count signature. The proof below also establishes simultaneous fixation and the exact residual value identity needed by the query.

5.2 Exact reduction and its tie semantics

Lemma 2 (A shared persistent edge)**.** *For every family member a, there is an optimum in* (22) *that contains every edge in any matching T of certified edges.*

Proof. First consider one certified edge (i, j) and any optimum M for $W(a)$. If M already contains it, no change is necessary. Otherwise, because M is perfect, it contains (i, k) and (ℓ, j) for distinct $k \ne j$ and $\ell \ne i$. Replace these two edges by (i, j) and (ℓ, k). The new edges have distinct row and column endpoints and match exactly the four previously matched endpoints, so the result M' is again perfect. Its weight change satisfies

$$\begin{aligned} W(a; M') - W(a; M) &= w_{ij} + W_{\ell k}(a) - W_{ik}(a) - W_{\ell j}(a) \\ &\ge w_{ij} - U_{ik} - U_{\ell j} \\ &\ge w_{ij} - R_{ij} - C_{ij} \\ &\ge 0. \end{aligned} \tag{26}$$

The first inequality uses nonnegativity of $W_{\ell k}(a)$ and the two valid upper bounds. Since M was optimal, M' is also optimal.

Now process the edges of T one at a time, starting with any optimum. Suppose all earlier edges are already present. The next edge $(i, j) \in T$ shares no endpoint with them. Neither of the two edges removed in the preceding exchange can be an earlier edge: an earlier edge has neither endpoint i nor endpoint j. Further, its matched endpoints cannot be the replacement endpoint k or ℓ, because those endpoints are already occupied by their earlier edge in the current perfect matching. The exchange therefore preserves every previously fixed edge. Induction proves simultaneous existence for all of T. □

Write I_T and J_T for the row and column endpoints of T, $R = [H] \setminus I_T$, $C = [H] \setminus J_T$, and $c_T = \sum_{(i,j)\in T} w_{ij}$. Then

$$v(a) = c_T + \max_{\sigma: R \to C \text{ bijective}} \sum_{i \in R} W_{i,\sigma(i)}(a). \tag{27}$$

Indeed, Lemma 2 supplies a full optimum containing T; deleting T leaves a feasible residual matching, so the full value is at most the right side. Conversely, adjoining T to any residual optimum produces a feasible full matching, proving the reverse inequality. Thus the residual matrix supplies the exact retained count and $N - v(a)$ supplies the exact movement count.

The lemma states existence, not uniqueness. With equality in (25), a different optimum may omit a certified edge. The non-strict reduction is consequently used for count queries only. Final physical actions retain the original matcher unless the additional strictness and uniqueness conditions in Section 5.6 hold. Both paths preserve its prescribed output.

The same reasoning permits repeated reduction: after removing a certified matching, recompute bounds over the remaining rows and columns and apply the rule again. Each stage preserves the value for every family member. No assertion that repeated reduction finds a smallest possible core is needed.

5.3 Why a simple greedy pass is sufficient

Let G_{cert} be the bipartite graph of all positive certified entries before any removal. Its vertices are the original rows and columns. A greedy pass traverses all certified edges and selects an edge whenever both endpoints remain unused. This is a maximal matching of G_{cert}.

Lemma 3 (Star structure of the certificate graph)**.** *Every nontrivial connected component of G_{cert} is a star. Hence every maximal matching of G_{cert} has maximum cardinality.*

Proof. Suppose two certified edges (i, j) and (i, k) share a row, with $j \neq k$. Put $x = w_{ij} > 0$ and $y = w_{ik} > 0$. The alternative-row maxima in their certificates contain the other positive edge, giving

$$x \geq y + C_{ij}, \qquad y \geq x + C_{ik}. \tag{28}$$

Adding yields $0 \geq C_{ij} + C_{ik}$. Both maxima are nonnegative, so $C_{ij} = C_{ik} = 0$ and $x = y$. Every other entry in columns j and k has upper bound zero. Therefore both columns have degree one in G_{cert}. This argument applies to every neighbor of any row of degree at least two. Interchanging rows and columns gives the symmetric statement for a column of degree at least two. No certificate edge can consequently join a row and a column that both have degree at least two. A connected bipartite graph with that property is a star: a path of length three would have a middle edge whose two endpoints each have degree at least two. Each nontrivial star admits exactly one edge in a maximal matching, and at most one in any matching. A maximal matching thus attains the largest possible cardinality component by component. □

Positivity is essential in this lemma. Zero entries are not inserted into G_{cert}; an all-zero matrix would otherwise yield a complete certificate graph rather than stars. Zero residual entries remain legal in the assignment problem.

5.4 A core bound from the seed's migration count

Choose any optimal perfect matching σ^0 for the seed matrix only as a proof witness. The reduction algorithm does not need to compute this witness. Let

$$\begin{aligned} d_i &= W^0_{i,\sigma^0(i)}, & a_i &= s_i - d_i, & b_i &= t_{\sigma^0(i)} - d_i, \\ t_j &= \sum_i W^0_{ij}, & m_0 &= N - \sum_i d_i. \end{aligned} \tag{29}$$

Here a_i counts original residents not retained in their seed-matched group, b_i counts foreign residents in that group, and m_0 is the seed's minimum unit migration count. Since the row and column sums both total N,

$$\sum_i a_i = m_0, \qquad \sum_i b_i = m_0. \tag{30}$$

Let $E = \{i : \sigma^0(i) \in J\}$. The matching is bijective, so $|E| = p$.

For every $i \notin E$, its witness edge lies in an unedited column. All other entries in its row have envelope at most a_i: fixed entries sum to at most a_i, and an edited entry is at most the edited-row budget $r_i \le a_i$. All other entries in its matched column are fixed and sum to b_i. Hence

$$R_{i,\sigma^0(i)} \le a_i, \qquad C_{i,\sigma^0(i)} \le b_i. \tag{31}$$

It follows that

$$d_i \ge a_i + b_i \quad \Longrightarrow \quad (i, \sigma^0(i)) \in E(G_{\text{cert}}). \tag{32}$$

Such an edge is positive: if $d_i = 0$, the premise would force $a_i = 0$, contradicting $s_i = d_i + a_i \ge 1$.

Theorem 2 (Migration-bounded exact core)**.** *Let T be any maximal matching of the positive family certificate graph and let $k = H - |T|$ be the residual dimension. Define*

$$B = \{i \notin E : d_i < a_i + b_i\}. \tag{33}$$

Then

$$k \le p + |B|, \qquad \sum_{i \in B} (s_i + 1) \le 3m_0. \tag{34}$$

In particular, if every incumbent host contains at least $q \ge 1$ workloads,

$$k \le \min\left\{H,\ p + \left\lfloor \frac{3m_0}{q+1} \right\rfloor \right\}. \tag{35}$$

If the seed respects movement budget K, the same bound holds with K replacing m_0.

Proof. The witness edges with $i \notin E \cup B$ form a matching, since they are a subset of σ^0. By (32), all these $H - p - |B|$ edges belong to G_{cert}. Lemma 3 implies that the maximal matching T is maximum in cardinality, so

$$|T| \ge H - p - |B|, \qquad k = H - |T| \le p + |B|. \tag{36}$$

For any $i \in B$, all counts are integers, so $d_i < a_i + b_i$ gives $d_i + 1 \le a_i + b_i$. Adding a_i and using $s_i = d_i + a_i$ yields

$$s_i + 1 \le 2a_i + b_i. \tag{37}$$

Summing over B and using nonnegativity together with (30),

$$\begin{aligned}\sum_{i\in B}(s_i+1) &\le 2\sum_{i\in B}a_i+\sum_{i\in B}b_i\\ &\le 2\sum_{i=1}^{H}a_i+\sum_{i=1}^{H}b_i\\ &= 3m_0. \end{aligned}\tag{38}$$

If $s_i \ge q$, then $(q+1)|B| \le 3m_0$, hence $|B| \le \lfloor 3m_0/(q+1)\rfloor$. Combining with the first inequality and the trivial bound $k \le H$ proves (35). Finally $m_0 \le K$ and monotonicity of the floor expression justify the budget form. □

The weighted inequality in (34) is useful when incumbent occupancies differ. For example, sort the values s_i+1 increasingly as $z_{(1)},\dots,z_{(H)}$ and put $b^* = \max\{b : \sum_{i=1}^{b} z_{(i)} \le 3m_0\}$. Every set of b rows has mass at least the sum of the b smallest values, so $|B| \le b^*$ and $k \le \min\{H, p+b^*\}$. This does not assume equal host occupancies.

The bound concerns ambiguity in the matching objective, not connectedness of its support. For example, take H hosts with eight residents each and move one resident from every host to the next host on a cycle. The positive overlap support is connected and $m_0 = H = N/8$. With $p=2$ and $q=8$, the theorem gives $k \le \min\{H, 2+\lfloor H/3\rfloor\}$. In this particular cycle the unedited diagonal entries are seven, whereas their other-row and other-column masses are one each, so the certificate actually removes every unedited diagonal and leaves at most two rows and columns. Support-component decomposition alone cannot discover this reduction.

Sharpness for this reduction rule. The coefficient 3 in (35) cannot be replaced by a smaller universal constant for this certificate-based reduction. Fix the number p of edited columns and an integer $t \ge 2$. For $H > \max\{p, 2\}$, let every host have $q = 3t-1$ residents and use cyclic indices to define the seed matrix

$$W^0_{ij} = \begin{cases} 2t-1, & j = i,\\ t, & j = i+1 \pmod H,\\ 0, & \text{otherwise.}\end{cases}\tag{39}$$

Every row and column sums to $3t-1$. Since $2t-1 > t$, selecting the diagonal attains the sum of the individual row maxima and is optimal. Consequently,

$$v_0 = H(2t-1), \qquad N = H(3t-1), \qquad m_0 = N - v_0 = Ht, \qquad \frac{m_0}{q+1} = \frac{H}{3}.\tag{40}$$

Take any p edited columns and any family containing this seed. Its envelope obeys $U \ge W^0$. Every positive fixed entry is either a diagonal entry or a cyclic off-diagonal entry. A diagonal entry has another entry of weight t in both its row and its column, while a cyclic off-diagonal entry has a diagonal of weight $2t-1$ in both. Their certificate margins therefore satisfy, respectively,

$$(2t-1) - (R_{ii} + C_{ii}) \le (2t-1) - 2t = -1 < 0,\tag{41}$$

$$t - (R_{i,i+1} + C_{i,i+1}) \le t - 2(2t-1) = 2 - 3t < 0.\tag{42}$$

No positive fixed edge is certified, so the first reduction pass removes nothing and repeated passes cannot change the matrix. The residual has $k = H$. For any $0 \le c < 3$, choose $H > p/(1-c/3)$; then

$$p + \left\lfloor \frac{cm_0}{q+1} \right\rfloor \le p + \frac{cH}{3} < H = k.\tag{43}$$

Thus replacing 3 by c would violate the bound on this family. This is a tightness statement for the specified certificate and residual-dimension guarantee; it is not a lower bound for other matching reductions or algorithms.

The theorem is stated for the full square overlap problem. The exact value identity (27) may then be combined with the already established support-component decomposition. A rectangular component can be padded on its smaller side by zero-weight dummy vertices before applying the same matching arguments. The global migration bound should not be restated with a component's local row sums or local movement without a separate derivation.

5.5 Two-column primal-dual replay on the core

For the surviving count queries, we apply standard local assignment updates [4, 6]. The family compiler supplies the uniformly valid residual matrix; the updater resolves its changed columns while retaining an exact primal-dual state.

Let $C = -W$ be a $k \times k$ minimum-cost matrix, with a perfect matching M and dual values u_i, v_j satisfying

$$u_i + v_j \le C_{ij} \quad \forall i, j, \qquad u_i + v_j = C_{ij} \quad \forall (i,j) \in M. \tag{44}$$

For every perfect matching P, dual feasibility gives

$$\sum_{(i,j)\in P} C_{ij} \ge \sum_{(i,j)\in P} (u_i + v_j) = \sum_i u_i + \sum_j v_j. \tag{45}$$

Equality holds for M, so M is optimal. This is the only optimality invariant needed for replay.

When a candidate changes columns J', where $|J'| \le 2$, delete the edges of M incident to those columns. They are distinct matching edges, so at most two rows and columns become unmatched. Preserve all u_i and all v_j for $j \notin J'$, and set

$$v'_j = \min_i (C'_{ij} - u_i), \qquad j \in J'. \tag{46}$$

For an unchanged column, the old feasibility inequalities remain valid. For a changed column, $v'_j \le C'_{ij} - u_i$ for every row by definition, so feasibility is restored. Every retained matched edge belongs to an unchanged column and remains tight.

One standard shortest augmenting-path step increases this partial matching by one while maintaining feasible dual values and tight matched edges. To verify its update, let S and T be row and column vertices of an alternating tree rooted at an unmatched row. If no tight edge reaches a column outside T, set

$$\delta = \min_{i\in S, j\notin T} (C'_{ij} - u_i - v_j) \ge 0 \tag{47}$$

and increase u_i by δ on S while decreasing v_j by δ on T. For an edge in $S \times T$ its dual sum is unchanged; for one in $S \times T^c$ the increase is at most its slack; for one in $S^c \times T$ its dual sum decreases; elsewhere it is unchanged. Dual feasibility therefore holds in all four cases. A matched edge has either both endpoints inside the alternating tree or both outside, so its tightness also holds. At least one previously positive boundary slack becomes zero. The tree can grow along this edge, or it reaches an unmatched column and its alternating path is flipped. The flip only uses tight edges and adds one matched edge.

At most $|J'|$ augmentations restore a perfect tight matching. The preceding objective equality then proves optimality for C'. Dense shortest-path implementations keep one minimum slack and predecessor per unvisited column; each newly reached row is scanned once and at most k rows enter the tree. This gives $O(k^2)$ time per augmentation, hence $O(|J'|k^2) = O(k^2)$ per count signature

after the base state is prepared. Integer overlap costs preserve integral slacks and dual updates; the implementation must still respect its machine-integer range.

The base optimum and dual state may be restored before each candidate, or the previous candidate's optimal state may be reused; in either case all changed columns must be identified and their incident matching edges removed. The proof allows arbitrary signature order. When both columns have identical values to the cached state, no reoptimization is required. Rectangular residual matrices require consistent zero padding. A count solver's chosen residual matching is not by itself a physical-output certificate; final mappings use the original full matcher or the unique-output certificate established next.

5.6 Lifting a family certificate to unique physical outputs

The strict case of neighborhood removal follows from the same established exchange argument [7]. We use that case to determine when a family count answer also fixes the prescribed physical output. The contribution here is the safe use of a shared family certificate across the count quotient and the richer result, not a new fixed-edge inequality.

Let $F = (e_1, \dots, e_{H-k})$ be the complete sequence of edges removed by the family compiler, before support-component decomposition; also write F for its set of edges. For edge $e_t = (i_t, j_t)$, let I_t, J_t be the remaining row and column sets when its recorded bounds were computed. Those alternative bounds are

$$R_t = \max_{j \in J_t \setminus \{j_t\}} U_{i_t j}, \qquad C_t = \max_{i \in I_t \setminus \{i_t\}} U_{i j_t}. \tag{48}$$

An empty maximum is zero. The target column is unedited, so its actual value is $W_{i_t j_t}(a) = w_t$ for every family member. The stronger condition needed for physical recovery is

$$w_t > R_t + C_t \qquad \text{for every } e_t \in F. \tag{49}$$

If a batch shares bounds calculated before any edge of that batch is removed, those recorded maxima are still valid: deleting other rows and columns can only decrease the sets of competing entries.

To see the effect of strictness, fix a family member a and an optimum residual matching M that omits e_t. Such a matching contains (i_t, j) and (i, j_t) for distinct $i \neq i_t$ and $j \neq j_t$. The two-edge exchange used in Eq. (26) gives

$$\begin{aligned} W(a; M') - W(a; M) &= w_t + W_{ij}(a) - W_{i_t j}(a) - W_{i j_t}(a) \\ &\geq w_t - U_{i_t j} - U_{i j_t} \\ &\geq w_t - R_t - C_t > 0. \end{aligned} \tag{50}$$

This contradicts optimality. Thus every residual optimum contains e_t. For the first removed edge this applies to every full optimum. Deleting that common edge gives a bijection between full optima and optima of the smaller residual. Induction over t proves that every full optimum for every family member contains all edges of F. Consequently restriction to the final residual gives the stronger set identity

$$\mathrm{Opt}(W(a)) = \{F \cup M : M \in \mathrm{Opt}(W(a)[I_*, J_*])\}, \tag{51}$$

where I_*, J_* are the global remaining vertex sets. The non-strict condition gives equality of optimum values, but it does not justify this equality of optimum sets.

No edited column is removed by the family rule. For the two-host family, $|J_*| = k \geq 2$; hence the condition $k \leq 2$ means exactly $k = 2$ and $J_* = J$. All other $H - 2$ rows and columns are already paired by F. This condition concerns the global square residual, rather than the largest

active support component. Small rectangular components can have several zero-edge completions when combined; their separate sizes do not establish uniqueness of the full matching.

Write $I_* = (i_1, i_2)$ and $J_* = (j_1, j_2)$. Let z_i be the count-signature entry giving the number of free mutable residents from incumbent host i assigned to j_1, and let n_i be their fixed total. With b_{ij} including all fixed background residents and any fixed symmetry representative, the actual residual entries are

$$W_{i,j_1}(a) = b_{i,j_1} + z_i, \qquad W_{i,j_2}(a) = b_{i,j_2} + n_i - z_i, \qquad i \in I_*. \tag{52}$$

These are the candidate's integer overlap entries, not its family upper envelope. Define the two possible retained totals

$$d(z) = W_{i_1 j_1}(a) + W_{i_2 j_2}(a), \qquad x(z) = W_{i_1 j_2}(a) + W_{i_2 j_1}(a). \tag{53}$$

If $d(z) > x(z)$, the unique residual matching is the diagonal; if $x(z) > d(z)$, it is the crossed pairing. When $d(z) = x(z)$, both are optimal and the certificate makes no claim about the prescribed tie choice. By Eq. (51), a strict inequality in Eq. (53) yields a unique full integer-count optimum. Its candidate-column-to-incumbent-row map, denoted ψ_z, combines F with that residual pairing and depends only on the signature in the fixed seed-column order.

The unit-cost physical matcher uses stored scores rather than exact integer overlaps. For completeness, let $1 \le N \le 2^{50}$, $u = 2^{-53}$, and $\eta = 2^{-1074}$. The earlier per-entry rounding bound implies, for every full matching M,

$$\begin{aligned}\left| \sum_{(i,j)\in M} w(W_{ij}) - \left(1 + \frac{1}{2N}\right) \sum_{(i,j)\in M} W_{ij} \right| &\le uN + u + \frac{u^2}{2} + H(2+u)\eta \\ &\le E := u(N+2) + 3H\eta < 0.126. \end{aligned} \tag{54}$$

Here each matching selects total overlap at most N, rather than H times the largest individual entry. If M_* is the unique integer optimum, integrality gives $W(M_*) - W(M) \ge 1$ for every $M \ne M_*$. Therefore

$$\sum_{e\in M_*} w(W_e) - \sum_{e\in M} w(W_e) \ge 1 - 2E > 0.748 > 0. \tag{55}$$

The same matching is the unique optimum of the sum of stored scores. Under the prescribed assignment solver's optimality contract, its deterministic tie rule therefore returns precisely this matching. The statement assumes that the prescribed assignment solver optimizes its supplied stored-score objective.

Finally, a count signature does not specify which individual residents chose each group, nor the resulting canonical group order. For the particular mask a, let $j_a(v)$ be workload v's group in the fixed seed-column order, and let γ_a map those group labels to canonical labels by ascending smallest resident identity. Then its canonical assignment is $a(v) = \gamma_a(j_a(v))$. The physical mapping for canonical columns and the resulting aligned assignment are

$$f_a(c) = \psi_z(\gamma_a^{-1}(c)), \qquad \widetilde{a}(v) = f_a(a(v)) = \psi_z(j_a(v)). \tag{56}$$

The moved set and its count are consequently

$$\mathcal{M}_a = \{v : \widetilde{a}(v) \ne \pi^{\mathrm{I}}(v)\}, \qquad m(a) = |\mathcal{M}_a| = N - v(a). \tag{57}$$

The original output operations applied to this identical aligned assignment give the same moved identities, count, stored movement fraction, and unit movement cost. Only ψ_z may be cached by count signature. The permutation γ_a, aligned assignment, and moved identities must be reconstructed for each actual mask; two masks with equal signatures can differ in all three.

Proposition 1 (A family certificate for the rich physical result)**.** *Consider a unit-cost two-host family with $N \le 2^{50}$. If every removed edge satisfies Eq.* (49)*, its global residual has two rows and two columns, and $d(z) \neq x(z)$, Eqs.* (56)–(57) *recover exactly the physical output of the prescribed full matcher under its optimality contract. Within this supported family domain, a non-strict deletion sequence, larger global core, or residual tie retains the prescribed full matcher.*

The preceding exchange, optimum-set identity, residual comparison, stored-score bound, and canonical relabeling establish each part of the proposition. If the seed equals the incumbent, every unchanged host is an isolated diagonal edge with weight $s_i > 0$ and both alternative maxima zero, so its $H - 2$ fixed edges satisfy the strict premise without a separate reduction pass. The family constructor enforces $N \le 2^{50}$ as a domain condition. Requests with explicit per-workload movement weights remain on the original exact lexicographic matching path; the unique-output certificate applies only to unit movement costs.

This recovery uses the already compiled overlap information and the two-column count signature, avoiding a new whole-placement overlap construction and a dense physical assignment when its premises hold. Constructing the returned assignment and moved identities still requires $O(N)$ output work. The deterministic physical-result map used by the complete-family preservation theorem is unchanged: the certificate and its fallback are two exact ways to evaluate the same map.

6 Canonical shared query execution

6.1 The reference computation

Fix an immutable workload panel $X \in \mathbb{F}_{64}^{B\times N\times T}$, its scene and time order, a numerical backend, finite intermediate values, and the per-row reduction sequences. Canonicalization orders hosts by their smallest resident identity, and every host membership is an ascending workload tuple $I = (i_1, \dots, i_r)$. Define S_r to be the specified binary64 resident reduction, not an arbitrary reassociation of a real sum. A canonical load row is

$$\mathcal{L}(I)_{bt} = \mathsf{S}_r(X_{b,i_1,t}, \dots, X_{b,i_r,t}). \tag{58}$$

For one host, let P_T perform the prescribed time comparisons and reductions. Its seven per-scene projections are activity, tolerance-based overload occurrence, native affected status, native overload fraction, mean uncapped excess, conditional severity, and peak:

$$\mathcal{Z}(I) = \mathsf{P}_T(\mathcal{L}(I)). \tag{59}$$

Let R_H assemble these projections in canonical host order and perform the final host reductions, including zero-denominator conventions. For a placement with canonical groups $I_1, \dots, I_H$, the reference historical query is

$$\mathcal{O}(\pi) = \mathsf{R}_H(\mathcal{Z}(I_1), \dots, \mathcal{Z}(I_H)). \tag{60}$$

This computation is the meaning of full replay in the equivalence claim. Its real-arithmetic formulas alone would not specify the same floating-point computation.

6.2 Membership interning and cardinality batches

A shared session interns a host by its complete membership tuple. A resident entry stores $\mathcal{L}(I)$ and $\mathcal{Z}(I)$ for the same immutable panel, capacity, tolerance, and backend contract. Reuse therefore requires equality of the query inputs, rather than equality of host labels, forecasts, or an approximate workload summary. Changing the panel or numerical parameters starts a distinct session.

For a submitted candidate batch, first collect its groups in a local map. A repeated group in the batch appears once in this map. A registry hit supplies its existing view; each missing group is materialized once for this batch. Missing groups of cardinality r form an index matrix $A \in [N]^{q_r \times r}$ whose rows preserve ascending resident order. Their packed operand tensor satisfies

$$W_{jbit} = X_{b,A_{ji},t}, \qquad (j,b,i,t) \in [q_r] \times [B] \times [r] \times [T]. \tag{61}$$

Only the resident axis is reduced:

$$\widehat{\mathcal{L}}_j(b,t) = \mathsf{S}_r(W_{jb1t}, \ldots, W_{jbrt}). \tag{62}$$

Each logical group therefore has the same operand sequence and resident count as Eq. (58). The execution contract requires that batching preserve that group's reduction tree, including the effective layout seen by the backend. It also requires the same length-T projection tree for each host–scene row. Equal cardinality and unchanged resident order make this contract implementable without padding residents or introducing subtract-and-add sums; they do not license changing the numerical backend's operation tree.

After obtaining the views, a lookup table maps each candidate to its group identifiers in canonical host order. Gathering this table yields projection arrays of shape candidate-by-host-by-scene. Candidate batching changes only an outer index: the final host reduction uses the same H operands, order, and tree as R_H. The Boolean host reductions are exact integer/Boolean operations under nonoverflowing counts; the numerical frequency, excess, severity, and peak reductions retain their specified order.

Theorem 3 (Shared-query equivalence)**.** *Under the fixed replay contract, membership interning, cardinality-batched materialization, and candidate gathering produce exactly the canonical loads and six-coordinate historical profile for every submitted candidate. Registry eviction does not change this equality. The analogous forecast views preserve the canonical capacity predicate.*

Proof. For a missing group I, the packed tensor contains exactly $X_{b,i_1,t}, \ldots, X_{b,i_r,t}$ for each (b,t). The same S_r therefore gives $\widehat{\mathcal{L}}(I) = \mathcal{L}(I)$ bit for bit. Applying the same P_T gives $\widehat{\mathcal{Z}}(I) = \mathcal{Z}(I)$. For a registry hit, its immutable key and session identify these same operands and operators, so its stored values satisfy the same equality. A repeated local key references one of these equal values. Thus every entry obtained for a batch is canonical.

For each candidate, gather these entries in its canonical sequence $(I_1, \ldots, I_H)$. Their values, shapes, and host order equal the reference operands in Eq. (60). Applying the same final reduction gives the same stored output, including threshold indicators and idle-scene sentinels. Eviction can remove only an entry from future registry lookup; the current batch's local map retains it until completion. If an evicted entry is needed later, the preceding missing-group argument reconstructs its canonical value. Hence eviction changes work but not answers.

For a forecast group, replace the workload panel by the fixed forecast panel and use the same ordered resident sum. The resulting load vector and the comparisons against the same stored $C + \tau$ are identical. A conjunction over the same nonempty groups therefore returns the same feasibility predicate. □

The reduction trees are part of the query semantics. The next bounds permit a different arithmetic circuit only when its result is enclosed and an unresolved decision is refined canonically.

6.3 Ranking and search-path consequence

For executions sharing the same candidate order, fix the starting state, random draws, completed operations, and deterministic tie-breaking. Shared-query equivalence gives the same profile for the first scored candidate, hence the same quantized gains, movement score, and retention decision. Inductively, if the retained state agrees before the next recorded operation, equal canonical feasibility and profile values give equal keys and the same next retained state. The same Selection query then selects the same action. Equality of the internal candidate order is not required for completed-family equivalence: Section 10 establishes this stronger result from the fixed total retention order.

A CPU allowance may allow a faster plan to finish additional operations. A feedback allocator using measured family CPU may also choose a different next family. Such executions need not have the same action. A controlled fixed-operation comparison holds the recorded families and attempts fixed, or supplies the same recorded cost feedback; its equality claim concerns numerical answers and decisions on that path.

6.4 Data access, arithmetic work, and storage

Let Q candidates each use H groups. Let $\mathcal{M}$ be the missing groups materialized in one submitted batch, $R_{\mathcal{M}} = \sum_{I\in\mathcal{M}} |I|$, and $r_{\max} = \max_{I\in\mathcal{M}} |I|$. A generic batch constructed from full assignment vectors uses $O(QN)$ membership work. The residual-family representation instead shares its unchanged groups and constructs only the two changing resident tuples for each mask; a full N-label assignment is needed only at a retention tie or a potential insertion. Gathering and summing missing groups reads $BTR_{\mathcal{M}}$ demand values. Their time projections process $BT|\mathcal{M}| \le BTR_{\mathcal{M}}$ cells, because every group is nonempty. Gathering and reducing the final projected candidates processes $O(QHB)$ values. Including initial validation of the panel, the numerical/structural work is

$$O\big(NBT + QN + BTR_{\mathcal{M}} + QHB\big). \tag{63}$$

The NBT startup term is paid once per immutable session. Across batches, the missing-group term sums over materialization events; a group evicted between batches may be materialized again. In contrast, full replay of every candidate reads $QNBT$ demands and performs $O(QHBT)$ profile processing. For forecast predicates the corresponding missing-group demand term is $T\sum_{I\in\mathcal{M}_f} |I|$, with $O(QH)$ final conjunction work.

A resident-view cache stores $O(MBT)$ numerical values for M retained memberships, plus their identities. The immutable input uses $O(NBT)$ values. Candidate gathers require $O(QHB)$ values, and grouped materialization is tiled. These storage terms are separate from the compact partition and component-matching structures.

7 Seed-universal constraint compilation

Let $W^0 \in \mathbb{Z}_{\ge 0}^{H\times H}$ be a seed overlap matrix. Its row sums $s_i = \sum_k W^0_{ik}$ are incumbent occupancies, and its column sums $t_j = \sum_\ell W^0_{\ell j}$ are seed-group sizes. A repair family edits a set J of p columns, retains every other column, and preserves each row sum. The following construction is independent of the family's mutable workload set.

Lemma 4 (A seed-universal edge)**.** *If $w = W^0_{ij} > 0$ and $3w \ge s_i + t_j$, then every repair family with $j \notin J$ has an optimum containing (i, j) in each of its overlap matrices. If $3w > s_i + t_j$, every optimum contains the edge.*

Proof. For every matrix W^a in such a family, the unchanged target column gives $W^a_{ij} = w$. Row conservation and nonnegativity imply

$$\max_{k\neq j} W^a_{ik} \leq \sum_{k\neq j} W^a_{ik} = s_i - w, \tag{64}$$

$$\max_{\ell\neq i} W^a_{\ell j} = \max_{\ell\neq i} W^0_{\ell j} \leq \sum_{\ell\neq i} W^0_{\ell j} = t_j - w. \tag{65}$$

Thus the certificate gives

$$w \geq (s_i - w) + (t_j - w) \geq \max_{k\neq j} W^a_{ik} + \max_{\ell\neq i} W^a_{\ell j}. \tag{66}$$

If an optimum omits (i, j), its two incident edges are (i, k) and (ℓ, j), with $k \neq j$ and $\ell \neq i$. Replacing them by (i, j) and (ℓ, k) changes its weight by

$$\Delta = w + W^a_{\ell k} - W^a_{ik} - W^a_{\ell j} \tag{67}$$

$$\geq w - (s_i - w) - (t_j - w) = 3w - s_i - t_j \geq 0. \tag{68}$$

The replacement is a valid permutation and preserves optimality. Strict positivity contradicts optimality of any permutation omitting the edge. □

Lemma 5 (A linear first-fit seed compilation)**.** *The graph of positive seed-universal edges is a disjoint union of stars and isolated edges. Any maximal matching F of this graph is maximum-cardinality and can be constructed by one first-fit pass.*

Proof. Suppose two certified edges share row i, with positive weights $x = W^0_{ij}$ and $y = W^0_{ik}$. Put $r = \sum_{c\notin\{j,k\}} W^0_{ic}$, $c_j = \sum_{\ell\neq i} W^0_{\ell j}$, and $c_k = \sum_{\ell\neq i} W^0_{\ell k}$. Their certificates become

$$x \geq y + r + c_j, \qquad y \geq x + r + c_k. \tag{69}$$

Adding gives $2r + c_j + c_k \leq 0$. Nonnegativity forces $r = c_j = c_k = 0$, and the two inequalities then force $x = y$. Both column endpoints have degree one even in the full positive overlap support. The column-symmetric argument implies that a vertex of degree at least two can be adjacent only to degree-one vertices. Hence every connected certificate component is a star. A maximal matching contains one edge from each nonempty component, which is maximum-cardinality. First-fit over all certificate edges is maximal. □

For edited columns J, define $F_J = \{(i, j) \in F : j \notin J\}$. Its excluded edges have distinct columns, so

$$|F \setminus F_J| \leq p. \tag{70}$$

Every edge remaining in F_J is valid independently of the restored edges. Fix its edges sequentially. Previously fixed edges have disjoint endpoints; deleting their rows and columns only decreases competitors, so the exchange proof remains valid at every step. If R_J, C_J are the remaining row and column sets, then

$$\mathrm{opt}(W^a) = \sum_{(i,j)\in F_J} W^0_{ij} + \mathrm{opt}(W^a[R_J, C_J]). \tag{71}$$

Restoring a selected edge does not require restoring its whole star: F stored only one edge from that star, and no other stored certificate depends on deleting its endpoints.

7.1 Inheritance of the migration-dependent bound

Theorem 2 already supplies an optimum-alignment witness with retained, outgoing, and incoming counts d_i, a_i, b_i, and the bad-row set $B = \{i : d_i < a_i + b_i\}$. Its established integer-count argument gives

$$\sum_{i \in B} (s_i + 1) \le 3m_0, \qquad |B| \le \lfloor 3m_0/(q+1) \rfloor . \tag{72}$$

The additional step needed for the seed index is that every good witness edge is seed-universal:

$$d_i \ge a_i + b_i \quad \Longrightarrow \quad 3d_i \ge (d_i + a_i) + (d_i + b_i) = s_i + t_{\sigma(i)}. \tag{73}$$

These edges are positive, because $d_i = 0$ and $d_i \ge a_i + b_i$ would contradict $s_i \ge q \ge 1$. They provide $H - |B|$ disjoint edges in the seed-certificate graph. Its maximum-cardinality first-fit matching therefore has $|F| \ge H - |B|$, without computing the witness alignment. Restoring at most p edited-column edges gives

$$k_J = H - |F_J| \le H - (|F| - p) \le p + |B|. \tag{74}$$

Thus the same dimension guarantee in Eq. (35) applies to the actual seed-index compiler. The weighted occupancy refinement following Eq. (34) also carries over unchanged: with sorted occupancies $s_{(i)}$ and $b^* = \max\{b : \sum_{i=1}^{b} (s_{(i)} + 1) \le 3m_0\}$, one has $k_J \le \min\{H, p + b^*\}$. Family-local envelope peeling can only reduce this dimension further. This inherits the existing theorem rather than requiring a separate migration hypothesis.

The index uses $O(N + H + E)$ time and space for N resident identities and E positive seed overlaps. It stores adjacency maps, cardinalities, resident groups, and a first-fit certificate matching. To specialize a family, it restores at most p matched endpoints and inspects either their incident row supports or the k_J^2 residual entries by direct lookup, whichever is smaller. Mutable-origin updates cost $O(wp)$ for width w. Thus preparing the local envelope costs $O(k_J^2 + wp)$, followed by the previous reduction and assignment algorithms on that local envelope. Shared fixed-edge metadata is a sequence view rather than an H-record copy. Rich physical output construction may still traverse those records and all workload identities; this is output work, not a count-query preparation cost.

For strict physical certificates, an unaffected origin row reuses its exact seed alternative maximum. An affected row retains the conservative $s_i - w$ bound, while an unchanged target column reuses its exact other-row maximum. These quantities dominate the corresponding family competitors. Only if every fixed edge is strict and the remaining complete matching is unique may the index recover the rich output. All other cases use the unchanged original matcher and tie policy.

8 Incremental views for score certificates

The view index stores host projections produced by the unchanged canonical resident reader. They comprise integer-valued activity and overload indicators, native overload frequency, stored mean excess and severity, and peak load. The index uses stable resident slots rather than canonical host positions. Its numeric sum summaries enclose real sums of stored projections; they do not replace the canonical stored host reduction used to produce exact profiles.

Lemma 6 (Recovering the native overload count)**.** *Let $0 \le n \le T \le 2^{50}$ be integers and $f = \mathrm{RN}(n/T)$ be a stored native host frequency. Then*

$$\mathrm{rint}\big(\mathrm{RN}(fT)\big) = n. \tag{75}$$

Proof. For $n = 0$ both operations are exact. Otherwise $n/T \geq 2^{-50}$ is normal and T is exactly represented. With unit roundoff $u = 2^{-53}$, write

$$f = \frac{n}{T}(1+\delta_1), \qquad y = \mathrm{RN}(fT) = n(1+\delta_1)(1+\delta_2), \quad |\delta_1|, |\delta_2| \leq u. \tag{76}$$

There is neither overflow nor subnormal underflow in these operations. Their error satisfies

$$|y - n| \leq n\big(|\delta_1| + |\delta_2| + |\delta_1\delta_2|\big) \tag{77}$$

$$\leq 2^{50}(2u + u^2) = \frac{1}{4} + 2^{-56} < \frac{1}{2}. \tag{78}$$

Nearest-integer rounding therefore returns n uniquely. The recovered count fits exactly in binary64 and signed 64-bit integers. Under the index guard $HT \leq 2^{50}$, all partial and complete count sums also fit in signed 64-bit integers. □

Let $z_{he} \geq 0$ denote one stored numeric projection for host h in a fixed scene. A leaf has the exact real interval $[z_{he}, z_{he}]$. Each internal node groups at most $f = 16$ children. For lower endpoints l_c and upper endpoints u_c, its nonnegative reduction enclosures produce

$$l_v \leq \sum_c l_c, \qquad u_v \geq \sum_c u_c. \tag{79}$$

These inequalities include the rounding and subnormal allowances of the nonnegative sum enclosure. If each child's interval contains its real stored-projection sum S_c, then

$$l_v \leq \sum_c l_c \leq \sum_c S_c = S_v \leq \sum_c u_c \leq u_v. \tag{80}$$

Induction over the tree therefore encloses every numeric projection sum at the root independently of slot order. Integer counts are added exactly. Updating a changed leaf and its ancestors reestablishes the same induction; all other nodes keep their valid intervals.

For two edited slots a, b, let L_e, U_e be root enclosures and let z_{ae}, z_{be} be their exact stored leaf values. Directed arithmetic gives the common-group bounds

$$L_e^{\mathrm{com}} = \max\{0, \mathrm{down}(\mathrm{down}(L_e - z_{ae}) - z_{be})\} \tag{81}$$

$$\leq \sum_{h \notin \{a,b\}} z_{he}, \tag{82}$$

$$U_e^{\mathrm{com}} = \max\{0, \mathrm{up}(\mathrm{up}(U_e - z_{ae}) - z_{be})\} \tag{83}$$

$$\geq \sum_{h \notin \{a,b\}} z_{he}. \tag{84}$$

Clamping preserves both claims because the target sum is nonnegative. An unrepresentable finite upper enclosure requests the existing exact-refinement fallback; it does not establish an exclusion.

Lemma 7 (A top-three view for two exclusions)**.** *Store the three largest leaf peaks and their distinct real slot identities at each node, allowing zero-valued dummy records for small subtrees. Merging child records and keeping their three largest values gives the exact maximum peak outside any two excluded real slots.*

Proof. A leaf not in its child's largest three has at least three values no smaller in that child alone and cannot be needed for the parent's largest three. Thus repeated merging retains three largest leaf values at every node. Real slot identities are distinct because disjoint children contain disjoint leaves; dummy zeros may repeat but contribute no positive value. Deleting two real slots can remove at most two of the three retained real records. If a common peak is positive, a retained nonexcluded peak no smaller than it remains; maximality prevents it from exceeding the true common maximum. If every common peak is zero, both the retained eligible maximum and the convention for no remaining hosts are zero. Ties do not affect these conclusions. □

When the seed changes, equality of complete resident tuples identifies unchanged leaves. New resident groups reuse released slots, their canonical projections are recomputed or retrieved, and only their ancestor nodes are refreshed. Slot reuse does not alter the resident tuple's stored projection, the real-sum induction, or the top-three argument. The current canonical-group-to-slot map selects the correct edited leaves even when canonical host labels shift.

The common-view operation returns independent arrays: integer subtraction, directed numeric subtraction, the filtered peak maximum, and stacked edited loads all allocate snapshots. A family bound reads this view once during construction and retains its own common summaries, mutable observations, and background enclosures. Later slot updates cannot change an earlier family's bounds. Exact retained profiles continue to use the original canonical reduction and are unaffected by the summary tree's order.

For B scenes, the stored tree occupies $O(BH)$ values. Refreshing r changed groups requires their missing canonical projections and at most $O(r \log_f H)$ changed ancestors, with $O(Bf)$ work per refreshed node. After the changed resident tuples have been identified and their canonical projections obtained, updating the tree nodes costs $O(Bfr \log_f H)$ and each two-group common summary costs $O(B)$. Projection cache misses require additional resident-load and time-reduction work. A full new assignment can still require $O(N)$ membership identification; this structural input cost must not be described as logarithmic. These valid common summaries feed the unchanged native-loss lower bounds and optimistic gain keys, so the previous strict-exclusion and Top-P preservation proofs apply without changing the query order or physical tie semantics.

9 Native-profile certificates for complete residual subtrees

Scope. Fix a finite nonnegative binary64 source panel with B scenes and T times, a complete H-host seed, two edited host groups, and an ordered mutable set. Every admitted descendant retains exactly H nonempty resident groups. All unchanged groups keep their complete ascending-VM memberships. A numeric mask has its canonical meaning: zero routes a free VM to the first edited group, and one routes it to the second. When both fixed backgrounds are empty, the first mutable VM is fixed in the first group, as in the reference search. An aligned interval $[s, s + 2^k)$ fixes the high mask bits and leaves the low k bits unresolved. We bound every complete descendant of this interval, before constructing an N-label assignment or its complete profile.

The consumer retains the best P repairs under the prescribed balanced relative-gain order. Bounds can order candidates before the pool is full; score exclusion begins only after P distinct exactly evaluated repairs have entered the pool. A family containing a globally idle scene uses canonical evaluation, preserving the native $\mathrm{VR} = \mathrm{PAR} = -1$ sentinels. A nonfinite enclosure uses the same fallback.

9.1 Nonnegative reduction enclosures

Let $u = 2^{-53}$ and $\eta = 2^{-1074}$. We use the conservative elementary model

$$\mathrm{RN}(z) = z(1+\delta) + \epsilon, \qquad |\delta| \le u, \quad |\epsilon| \le \eta,$$

under round-to-nearest binary64 arithmetic with gradual underflow and finite intermediates. For a nonnegative real sum S of n stored operands and any binary summation tree, set

$$m = \max(n-1, 0), \qquad \gamma_n = \frac{mu}{1-mu}, \qquad d_n = \frac{m\eta}{1-mu}.$$

All counts in the implementation are bounded by 2^{50}, so $\gamma_n < 1$. Expanding the computed tree writes its result as a sum of input operands multiplied by products of at most m factors $1+\delta$, plus at most m additive errors multiplied by such products. Therefore its stored result y satisfies

$$(1-\gamma_n)S - d_n \le y \le (1+\gamma_n)S + d_n. \tag{85}$$

Initialization by zero and multiplication by an exactly stored zero or one introduce no extra nonzero error. Consequently the same bound covers the batched zero–one selector products used for mandatory and possible mutable resident sets, including fused multiply-add implementations.

For a known stored reduction y, inversion gives

$$S \in \left[\max\left(0, \frac{y-d_n}{1+\gamma_n}\right), \frac{y+d_n}{1-\gamma_n}\right]. \tag{86}$$

A zero sum of nonnegative stored operands is exactly zero; this special case retains an exact zero upper endpoint. Given a real lower or upper endpoint, Equation (85) transfers it to a bound for another canonical reduction of at most n operands. The constants are formed as exact rationals and converted outwards. Every arithmetic operation on endpoints is rounded in its required direction. In particular, an upper multiplication of two positive values that underflows returns at least η, not zero.

Forecast subset centers and leaf witnesses. The forecast predicate has an analogous enclosure before either changed resident tuple is constructed. Put $r = \max\{|B_0|, |B_1|\} + |U|$ and let D be the largest stored forecast operand among residents of the two edited seed groups. Both quantities are fixed before screening. An outward evaluation of

$$E_r = \gamma_r r D + d_r$$

bounds the error of any finite positive summation tree over at most r such operands. A fixed background sum, a subset-table sum, and their final addition expand into just such a tree: each included resident occurs once. Additions to an exact zero add no error. This remains true when the symmetry-fixed resident is absorbed into the first background.

Let M_{st} be the exact-real demand of residents mandatory on side s at forecast time t, and let $\widetilde{M}_{st}$ be its computed subset center. Then $\widetilde{M}_{st} \le M_{st} + E_r$. Every completion has real load at least M_{st} by nonnegativity, and at most r resident operands, so its canonical stored load is at least $M_{st} - E_r$. Consequently

$$\widehat{\ell}^{\,\mathrm{can}}_{st} \ge \widetilde{M}_{st} - 2E_r.$$

Rounding the radius upward and the final subtraction downward yields a valid lower endpoint. It may be clipped at zero because every canonical load is nonnegative. A strict comparison of this

endpoint with the same stored $\mathrm{RN}(C+\tau)$ therefore certifies infeasibility. Equality does not reject. Nonfinite centers, radii, or unsupported subset-table sizes fall back to the canonical predicate.

For a singleton mask the mandatory set is its complete changed group. Evaluating all such centers in one batch therefore gives the same individual sound rejection statements without requiring an internal-node traversal. If a sorted set $\mathcal{A}$ of nonempty masks has been screened, a bitmap can record these certified rejections. A dyadic witness for interval I may combine them whenever every mask in $\mathcal{A} \cap I$ has a rejection bit. That witness certifies precisely the listed set $\mathcal{A} \cap I$. It makes no assertion about unchecked empty masks or other masks outside that set. Compression changes only the representation of already proved statements; it does not avoid the preceding leaf enumeration. Forecast-ineligible masks remain outside the seen set, as in canonical residual-family execution.

Resident bounds. For each edited seed group, invert its canonical stored load and the stored sum of its mutable residents. Outward subtraction encloses the real fixed background. This is an interval operation; it does not assert that subtracting mutable residents reproduces a canonical background fold. Add the real sums of forced residents to bound the mandatory load, and add all residents still allowed on that side to bound its possible load. Applying Equation (85) with the total number R of residents in the two edited seed groups yields stored-load endpoints $L_{hbt} \le x_{hbt} \le U_{hbt}$ for $h \in \{0,1\}$ in every descendant.

The real total demand of the two groups is conserved. Let S^{-}_{bt} bound this real total from below. Although the two descendant groups have separate canonical reductions, their stored loads obey the coupled lower bound

$$x_{0bt} + x_{1bt} \ge D^{-}_{bt} := \max\{0, (1-\gamma_R)S^{-}_{bt} - 2d_R\}. \tag{87}$$

This statement concerns the real sum of the two stored loads. It remains valid when their resident counts and their canonical column positions change.

9.2 Factorized mutable-sum certificate views

The two changed groups repeatedly request sums of subsets of the same ordered mutable residents. These are certificate operands, rather than replacements for the canonical exact load views in Eq. (58). Let w be the total mutable count and let $b = w - \chi$ be the number of free mask bits, where $\chi \in \{0,1\}$ records the possible symmetry-fixed first resident. Split the free bits into consecutive sets A and D of sizes $a = \lfloor b/2 \rfloor$ and $b - a = \lceil b/2 \rceil$. The source panel, bit order, symmetry-fixed resident, and background intervals remain fixed throughout this family.

For each half and each scene–time cell, initialize its empty-subset entry to zero. Process its bits in the fixed ascending order. At the step for bit i, form one new entry for every subset S of the earlier processed bits:

$$\begin{aligned} F_A[\varnothing] &= 0, & F_A[S \cup \{i\}] &= \mathrm{RN}(F_A[S] + x_i), \\ F_D[\varnothing] &= 0, & F_D[S \cup \{i\}] &= \mathrm{RN}(F_D[S] + x_i). \end{aligned} \tag{88}$$

The recurrence is applied only in this processing order; it does not assign several incompatible floating-point trees to the same subset. Thus each entry is defined exactly once.

For an aligned free-mask interval $[s, s+2^k)$, put $u_k = 2^k - 1$ and $M = 2^b - 1$. Its low k bits are unresolved, and alignment gives $s \,\&\, u_k = 0$. The mandatory and possible free-resident masks are

$$\begin{aligned} M^{-}_0 &= M \oplus s \oplus u_k, & M^{-}_1 &= s, \\ M^{+}_0 &= M \oplus s, & M^{+}_1 &= s \vee u_k. \end{aligned} \tag{89}$$

Indeed, a high bit fixed to zero belongs to the first group, a high bit fixed to one belongs to the second, and each unresolved low bit is allowed in either group. A mandatory mask excludes every unresolved bit, whereas a possible mask includes each bit that can reach that side. Split any requested mask Q into $Q_A = Q \,\&\, (2^a - 1)$ and $Q_D = Q \gg a$. Its stored sum is

$$z(Q) = \mathrm{RN}(F_A[Q_A] + F_D[Q_D])\,. \tag{90}$$

When $\chi = 1$, add the fixed first resident to each left-side answer by one further stored addition; it is absent from both half tables. It is never added to the right-side answer.

Theorem 4 (Valid factorized sum enclosures)**.** *Assume the nonnegative finite source and numerical domain of Eq.* (85)*. For each finite stored answer z of Eqs.* (88)–(90)*, let S_Q be the exact-real sum of its selected mutable residents, including the symmetry-fixed resident when present. Then*

$$\max\left\{0, \frac{z - d_w}{1 + \gamma_w}\right\} \le S_Q \le \frac{z + d_w}{1 - \gamma_w}. \tag{91}$$

Directed evaluation gives valid endpoints for the mandatory and possible real sums used by the profile certificates.

Proof. Expand a requested table entry into the additions that produced it. Each selected free resident appears once in its half; the halves are disjoint. Joining their roots introduces one addition. If present, the fixed resident is a further disjoint leaf attached to the left-side root. Hence the complete expression is a binary addition tree over $n \le w$ stored nonnegative operands. Initial additions to exact zero do not contribute nonzero rounding error. For $n \ge 1$, at most $n - 1 \le w - 1$ additions can be inexact. If $n = 0$, its exact and stored sums are both zero.

Applying Eq. (85) with the conservative count w gives

$$(1 - \gamma_w)S_Q - d_w \le z \le (1 + \gamma_w)S_Q + d_w. \tag{92}$$

Since $1 - \gamma_w > 0$, rearrange its left inequality as $S_Q \le (z + d_w)/(1 - \gamma_w)$. Rearranging the right inequality gives $S_Q \ge (z - d_w)/(1 + \gamma_w)$; nonnegativity permits clipping this lower endpoint at zero. These are exactly Eq. (91). An exact zero answer can use the sharper zero upper endpoint already justified for nonnegative sums. The mandatory set is contained in every completion and the possible set contains every completion. Substitution into the existing resident-bound derivation therefore lower-bounds mandatory load and upper-bounds possible load. The final transfer to canonical resident reductions still uses Eq. (85); the table result is never asserted to have the canonical load's bits. □

For a leaf, $k = 0$ in Eq. (89), so $M_0^- = M_0^+$ and $M_1^- = M_1^+$. Mandatory and possible answers may then share one computed array. The strict lookup/add kernel evaluates the same one joining addition, and the optional subsequent fixed-resident addition, directly into each output cell. Vectorizing independent scene–time cells does not reassociate either cell's expression. The enclosure proof is consequently unchanged while intermediate gathered arrays and duplicate leaf products are avoided.

Proposition 2 (Sum-view work and storage)**.** *For a family with b free bits, B scenes and T times, the enabled two-half index has $2^{\lfloor b/2 \rfloor} + 2^{\lceil b/2 \rceil}$ rows. Constructing it and answering q range requests uses*

$$O\Big((2^{\lceil b/2 \rceil} + q)BT\Big) \tag{93}$$

work and $O(2^{\lceil b/2 \rceil}BT)$ stored table values, in addition to output workspace.

Proof. The two recurrences form respectively $2^a - 1$ and $2^{b-a} - 1$ new rows, each by BT additions. Each range supplies at most four side/mode masks. A mask uses two constant-time half indices and one BT-cell joining addition, with at most one further BT-cell addition for a fixed resident. Thus requests use $O(qBT)$ work. Summing construction and request work yields Eq. (93); storing exactly the two half relations gives the stated space. In particular, the construction has no 2^b-row demand table. □

Construction is lazy. A fixed request-count rule, depending only on bit width and work already requested within this family, delays it on small queries; a byte budget prevents an oversized table. Before construction, a selector product obtains the same real subset sums through another floating-point tree. Equation (85) covers that tree too. The switch can change the tightness of a computed enclosure but not its validity. Consequently the work bound in Proposition 2 describes the indexed sum-view path, not a guarantee that every family chooses that path or that the entire repair query avoids identity processing.

9.3 All six native loss lower bounds

The following definitions apply separately in every scene. Unchanged groups provide exact Boolean projections and canonical stored time projections. We enclose only reductions of those stored numeric projections when combining them with the changing groups. This avoids assuming that canonical host summation is invariant under column permutation.

Tolerant occurrence and host fraction. Let $c_\tau = \mathrm{RN}(C + 10^{-12})$, the exact stored comparison threshold used by the reference. A changing group certainly violates when some $L_{ht} > c_\tau$. Equation (87) also forces at least one changing group to violate whenever $D_t^- > 2c_\tau$. Thus a lower bound on the number of violating changing hosts is the maximum of the number individually forced to violate and the indicator that the coupled test holds at some time. Add the exact common-host count. The indicator that this total is positive is a lower bound for J, and its canonical stored division by H is a lower bound for V. When a common host violates, the lower bound for J is exactly one; when both reference and lower candidate occurrence are zero, their stored occurrence gain is exactly zero.

Active and affected denominators. An edited host is possibly active if some $U_{ht} > 0$, and certainly active if some $L_{ht} > 0$. If the conserved pair contains positive demand in this scene, at least one of its hosts is active. With exact common-host counts, these facts give $A^- \le A \le A^+$ for the descendant's active-host count. Similarly, an edited host is possibly affected if some $U_{ht} > C$. Adding the exact common affected-host count gives an upper bound M^+ on the native affected-host denominator. Using a profile computed directly from lower loads would be unsound: its active and affected denominators could be smaller than the descendant's. We bound these denominators separately.

Native violation rate. At each time a lower bound on the number of overloaded changing hosts is

$$q_t^- = \max\{\mathbf{1}[L_{0t} > C] + \mathbf{1}[L_{1t} > C], \mathbf{1}[D_t^- > 2C]\}.$$

Add $\sum_t q_t^-$ to the exact common count of native overloaded cells. If T is a power of two, every stored host frequency n_h/T and their sum are exact dyadic values in the stated $HT \le 2^{50}$ range.

The original division of this frequency lower bound by A^+ is a valid lower bound for native VR. For other T, the real sum of stored frequencies is bounded by

$$\sum_h \mathrm{RN}(n_h/T) \geq (1-u)\frac{\sum_h n_h}{T} - H\eta.$$

Downward evaluation and Equation (85) cover the subsequent canonical host sum, before division by A^+.

Stored excess and the coupled lower bound. For one finite nonnegative stored load x, write

$$r = x/C, \qquad y = \mathrm{RN}(r), \qquad e(x) = \max\{\mathrm{RN}(y-1), 0\}.$$

If $y < 1$, monotonicity of round-to-nearest implies $r < 1$, so $\max\{(1-2u)r - 1, 0\} = 0$. If $y \geq 1$, the elementary arithmetic model gives

$$\begin{aligned} e(x) &\geq (1-u)(y-1) - \eta \\ &\geq (1-u)^2 r - (1-u) - (2-u)\eta \\ &\geq (1-2u)r - 1. \end{aligned}$$

The last inequality follows because the difference is $u^2 r + u - (2-u)\eta \geq 0$; it does not rely on incidental outward ulps hiding underflow error. Since excess is also nonnegative,

$$e(x_0) + e(x_1) \geq \max\left\{(1-2u)\frac{x_0 + x_1}{C} - 2, 0\right\}. \tag{94}$$

Evaluate the right side downward using D_t^-. The maximum of this result and a downward sum of the individual monotone bounds $e(L_{0t}), e(L_{1t})$ gives a lower bound E_t^- on the sum of stored excesses at time t.

Raw excess. For individual hosts, first bound the canonical time sum of $e(L_{ht})$ using the real-sum inversion and the stored-sum transfer, then use the original stored division by T. This bounds each stored time mean from below. For the coupled bound, let $E^- \leq \sum_t E_t^-$. The sum of the two stored time sums is at least $(1-\gamma_T)E^- - 2d_T$. If this lower bound is Z^-, then the real sum of their two stored time means is at least

$$(1-u)Z^-/T - 2\eta.$$

Take the maximum of the individual and coupled bounds. Add the real lower bound for the common stored time means, transfer through the canonical H-host fold, and perform the canonical division by A^+. The result bounds the native, uncapped, active-host-normalized raw loss from below.

Native severity. For an edited host let n_h^+ count times with $U_{ht} > C$. Its stored excess-sum lower bound divided by n_h^+ bounds its severity whenever $n_h^+ > 0$; otherwise the lower bound is zero. A zero actual overload count implies zero actual excess numerator. Moreover the original stored severity is at least the canonical stored mean excess, since they share a numerator and the positive overload count is at most T. Consequently the coupled pair mean-excess lower bound also lower-bounds the real sum of the pair's stored severities. Combine this with the individual severity bounds, the common severity lower sum, the canonical H-host reduction allowance, and finally division by M^+. If $M^+ = 0$, the original severity and its lower bound are both zero.

Native peak-to-average ratio. The largest stored host peak has lower bound

$$P^- = \max\left\{P_{\text{common}}, \max_{h,t} L_{ht},\ \tfrac{1}{2}\max_t D_t^-\right\}.$$

The upper endpoints give individual edited-peak upper bounds. A coupled upper bound avoids counting every unresolved resident twice. Let F_{ht} denote the real mandatory load and I the unresolved residents. Then

$$\max_t x_{0t}^{\text{real}} + \max_t x_{1t}^{\text{real}} \le \max_t F_{0t} + \max_t F_{1t} + \sum_{i\in I} \max_t X_{it}.$$

Each unresolved VM belongs to exactly one completed group. This explains the single occurrence of its peak in the upper bound. Apply the resident growth factor $1+\gamma_R$ and add $2d_R$ to cover the two stored peak values. Take the smaller of this coupled upper bound and the sum of the individual peak upper bounds. Add the common real peak-sum upper bound, transfer through the canonical host fold, and divide by A^- using the prescribed rounding. This yields an upper bound $\overline{p}^+$ on the canonical stored mean peak. Thus $\mathrm{RN}(P^-/\overline{p}^+)$ is a PAR lower bound whenever the canonical stored mean peak is positive.

A positive lower bound for the stored denominator is required: a nonnegative host sum is at least its largest operand, so $\mathrm{RN}(P^-/A^+)$ lower-bounds the stored mean peak. Failure to prove strict positivity requests exact refinement. The native nonpositive-mean sentinel is therefore never replaced by a positive lower loss.

Finite-range guard. All endpoint operations must remain finite. In addition the largest possible stored capacity ratio must not exceed $\mathrm{maxfloat}/(4HT)$, including unchanged groups. In the stated bounded-count scope, the factor four dominates every positive reduction-growth allowance. This ensures that native excess sums cannot overflow. Nonfinite gain or quantization intermediates request exact refinement. These restrictions are conservative sufficient conditions, not claims of maximal supported range.

9.4 Stored gain keys and controller preservation

Let $\underline{P}$ be the resulting $B \times 6$ stored lower-profile array and P any descendant's canonical stored profile. Coordinatewise, $\underline{P} \le P$. Both profiles are evaluated by the same canonical gain circuit, with the same reference operands, selected coordinates, row order, and prescribed reduction tree:

$$g(P) = \mathrm{RN}\left(\frac{\mathrm{mean}_{\text{can}}(\mathrm{RN}(P^{\text{ref}} - P))}{\max\{|\,\mathrm{mean}_{\text{can}}\, P^{\text{ref}}|, 10^{-8}\}}\right).$$

This is the mean of stored row differences, not a difference of means. Round-to-nearest subtraction with fixed first operand is antitone in its second operand. Addition, division by a fixed positive value, and each prescribed averaging step are monotone. Fixed arithmetic trees therefore give $g(\underline{P}) \ge g(P)$ coordinatewise, even under cancellation.

Lemma 8 (Batching the canonical gain circuit)**.** *Let E be the number of selected coordinates. Suppose the fixed numerical backend uses the same prescribed tree for a length-B contiguous reduction, independently of the number of adjacent, separately reduced rows. The scalar gain circuit can then be batched without changing any stored gain by packing its operands in $Q \times E \times B$ contiguous order and reducing only the last axis. The reference scale must be computed on the reference layout before any packing.*

Proof. The scalar advanced-index selection produces a $B \times E$ column-major array. For coordinate e, its unit-stride row operands are $P_{1e}^{\mathrm{ref}}, \ldots, P_{Be}^{\mathrm{ref}}$ and $P_{1e}, \ldots, P_{Be}$. Elementwise subtraction therefore produces the ordered stored sequence

$$d_{qe1}, \ldots, d_{qeB}, \qquad d_{qeb} = \mathrm{RN}(P_{be}^{\mathrm{ref}} - P_{qbe}).$$

Packing these same operands in row-major $Q \times E \times B$ order changes only their addresses. Every (q, e) row has the same sequence of rounded differences, length, unit stride, and reduction tree as the scalar column. Induction over that tree gives the same stored sum; the subsequent division by B is the same operation. Computing the reference means before packing also preserves their potentially different original strides and reduction tree. Their saved positive scales therefore give the same final divisions. Thus all finite gains are bitwise identical, including cancellation cases. Nonfinite arithmetic is not converted into a finite certificate. □

The scalar and packed computations use the same reduction trees. This permits the packed circuit to serve both exact candidate scoring and optimistic-key scoring. Reference scales can be shared throughout an immutable query session; family-specific load bounds, idle cases, and finite-range checks are still evaluated for each family.

Multiplication by 2^{40}, floor, and the conversion of finite results to integer preserve this ordering. Sorting coordinate values ascending also preserves coordinatewise order: if $a_i \geq b_i$ for every i, the jth smallest a cannot be less than the jth smallest b, because that would require at least j entries of b below its own jth order statistic. Equivalently, the number of coordinates below any threshold can only decrease when coordinates are increased. Appending $-m^-$ and $-c^-$ for valid movement-count and cost lower bounds produces a complete lexicographic upper key K^+ for every descendant on which those movement bounds are valid. In particular, after exact nonempty-host, forecast and seen filtering, one may take the minimum movement value over the remaining active signature classes. The profile enclosure still covers every complete descendant, but this tighter complete-key bound is asserted only for that active subset. Every excluded identity and every exclusion witness refers to the same subset.

Let K_0 be the worst key of a full balanced retained pool at any point in the family. If $K^+ < K_0$ strictly, no active descendant covered by the bound can enter the final pool. The worst retained key cannot decrease as additional candidates are processed, so the same exclusion remains valid later in the family. A static plan fixes K_0 at family entry; a progressive plan updates it after exact scoring batches. Equality does not exclude: the canonical-assignment tie order must remain available.

Every forecast-feasible identity is inserted into the seen set, including a candidate excluded by movement or score. Forecast-ineligible identities are not inserted. Numeric masks retain their prescribed membership meaning, but surviving candidates may be scored in any order. Equal score keys retain the canonical-assignment tie order, independently of arrival. The following results combine these state rules with progressive evaluation and deferred physical matching.

9.5 Compiled load-radius certificates

The preceding resident enclosures combine stored subset sums with background intervals and transfer the results to canonical resident reductions. The same positive-tree and elementary-rounding bounds yield a family-wide absolute load-error budget. Compiling this budget once permits the supported leaf queries to form conservative stored-load endpoints with ordinary binary64 additions and subtractions.

Operands and supported domain. Consider one scene–time cell and one edited side. The scalar argument below applies independently to every such cell. Let B be the exact-real sum of its fixed background residents. The existing outward background calculation supplies finite nonnegative binary64 endpoints

$$0 \le B_{\mathrm{lo}} \le B \le B_{\mathrm{hi}}. \tag{95}$$

Let w be the total mutable count, including a symmetry-fixed resident when present, and let R be the total resident count of the two edited seed groups. A requested subset uses at most w mutable operands, and each completed group uses at most R residents. These are conservative counts. Let S denote the exact-real sum of the mutable operands assigned to this side, and let s be the stored subset answer. The existing selector and two-half backends both satisfy the positive-tree contract: selected operands are nonnegative, each selected resident occurs once, and zero–one products introduce no additional nonzero multiplication error. This includes the symmetry-fixed resident; see Eq. (85) and Theorem 4.

A finite binary64 upper endpoint for the real sum of all mutable residents in this cell is compiled once:

$$0 \le S \le \sum_{i \in U} X_i \le S_{\max}. \tag{96}$$

It is obtained with the existing real-sum upper enclosure. A side that cannot receive some mutable residents may still use this conservative total. Let C_{can} be the binary64 value produced by the prescribed canonical reduction of the completed group's residents; its real operand sum is $B + S$. All counts obey the existing 2^{50} bound. Source, reference, capacity, memberships, subset order and background endpoints remain immutable during the family.

Outward coefficients. Write Up for the implementation's upward evaluation. Every intermediate addition, multiplication or subtraction needed for an upper bound is evaluated upwards; it is insufficient to round only the final total upwards. Let g_n, Δ_n be the stored growth and additive coefficients of the existing reduction enclosure:

$$g_n \ge 1 + \gamma_n, \qquad \Delta_n \ge d_n, \qquad \gamma_n = \frac{\max(n-1,0)u}{1 - \max(n-1,0)u}, \qquad u = 2^{-53}. \tag{97}$$

For $n < 2$, $g_n = 1$ and $\Delta_n = 0$. Define

$$\kappa_n = g_n - 1. \tag{98}$$

This subtraction is exact. The supported count gives $\gamma_n < 1/7$, and its upward stored growth lies in $[1, 2)$; hence g_n and 1 satisfy Sterbenz's subtraction condition. In particular $\kappa_n \ge \gamma_n$. The upper growth deviation alone bounds both absolute error directions: for a finite positive-tree result y with exact-real nonnegative operand sum Q,

$$|y - Q| \le \gamma_n Q + d_n \le \kappa_n Q + \Delta_n. \tag{99}$$

Both deviations are therefore covered by the existing positive-tree enclosure.

Compile the following quantities:

$$\begin{aligned} E_s &= \mathrm{Up}(\kappa_w S_{\max} + \Delta_w), \\ Q_{\max} &= \mathrm{Up}(B_{\mathrm{hi}} + S_{\max}), \\ E_c &= \mathrm{Up}(\kappa_R Q_{\max} + \Delta_R), \\ M &= \mathrm{Up}(B_{\mathrm{lo}} + \mathrm{Up}(S_{\max} + E_s)), \\ E_a &= \mathrm{Up}(uM + \eta), \qquad \eta = 2^{-1074}, \\ E_b &= \mathrm{Up}(B_{\mathrm{hi}} - B_{\mathrm{lo}}), \\ \rho_{\mathrm{lo}} &= \mathrm{Up}(\mathrm{Up}(E_s + E_c) + E_a), \\ \rho_{\mathrm{hi}} &= \mathrm{Up}(\rho_{\mathrm{lo}} + E_b), \\ Z_{\max} &= \mathrm{Up}(M + \rho_{\mathrm{hi}}). \end{aligned} \tag{100}$$

All accepted fields are finite and nonnegative. In computing E_b, the exact difference is nonnegative by Eq. (95); an ordinary subtraction followed by its next representable upper value is a valid upper endpoint even when represented as addition of $-B_{\mathrm{lo}}$. This may give a positive subnormal upper endpoint for a zero width, which is conservative. Upper multiplication retains the existing positive-underflow treatment. Both u and η are exactly representable.

The center-addition budget E_a uses the elementary rounding bound. We first rule out overflow and then justify its $uM + \eta$ allowance.

Acceptance and first overflow. Let F be the largest finite binary64 value. The fast radius is accepted only when every compiled field is finite and

$$Z_{\max} \le F/8. \tag{101}$$

The factor supplies ample representable margin. Importantly, the check controls the center upper endpoint *plus* the upper radius; a check of the radius alone would not suffice. Any unsupported count, nonfinite compilation or failed guard selects the original outward-enclosure path.

First consider subset acquisition. The compiled inequalities imply

$$S_{\max} + E_s \le M \le Z_{\max} \le F/8. \tag{102}$$

Suppose a supported nonnegative subset reduction had a first overflowing addition. Its child results and all preceding operations are finite. Expanding those finite subtrees and leaving the root unrounded gives no more potentially inexact operations than the existing w-operand positive-tree bound. If the root's true operand sum is $S_{\mathrm{root}} \le S_{\max}$, its exact pre-rounding value is therefore at most

$$(1 + \gamma_w) S_{\mathrm{root}} + d_w \le S_{\max} + \kappa_w S_{\max} + \Delta_w \le S_{\max} + E_s \le F/8. \tag{103}$$

Such a value cannot overflow when rounded, a contradiction. Multiplication by a stored zero or one cannot be the first overflow either. The same reasoning covers all two-half table entries, since each uses a subset of the same source. Thus s is finite, and the positive-tree bound is now applicable without an unproved finiteness premise:

$$|s - S| \le E_s, \qquad 0 \le s \le S_{\max} + E_s. \tag{104}$$

Next, the upward compilation and the background-width inequality give

$$\begin{aligned} Z_{\max} &\ge M + \rho_{\mathrm{hi}} \\ &\ge B_{\mathrm{lo}} + S_{\max} + 2E_s + E_c + E_a + E_b \\ &\ge B_{\mathrm{hi}} + S_{\max} + E_c. \end{aligned} \tag{105}$$

If the canonical resident reduction had a first overflowing addition, the exact value formed from its finite predecessors would be at most

$$(1+\gamma_R)(B_{\mathrm{hi}}+S_{\max})+d_R \le B_{\mathrm{hi}}+S_{\max}+E_c \le Z_{\max} \le F/8. \tag{106}$$

This again contradicts overflow. The argument uses the nonnegative operand structure, not a property of arbitrary signed reductions. Consequently the canonical load is finite and

$$|C_{\mathrm{can}} - (B+S)| \le E_c. \tag{107}$$

For the center, Eq. (104) gives

$$0 \le B_{\mathrm{lo}} + s \le B_{\mathrm{lo}} + S_{\max} + E_s \le M \le F/8. \tag{108}$$

Thus the ordinary operation

$$p = \mathrm{RN}(B_{\mathrm{lo}} + s) \tag{109}$$

is finite. We may now apply the existing elementary error model:

$$|p - (B_{\mathrm{lo}} + s)| \le u(B_{\mathrm{lo}} + s) + \eta \le uM + \eta \le E_a. \tag{110}$$

In addition, M is itself binary64. Monotonicity yields

$$0 \le p = \mathrm{RN}(B_{\mathrm{lo}} + s) \le \mathrm{RN}(M) = M. \tag{111}$$

The upper endpoint's exact pre-rounding value is at most $M + \rho_{\mathrm{hi}} \le Z_{\max} \le F/8$. Both p and ρ_{lo} are at most $Z_{\max}$, so their exact difference lies in $[-Z_{\max}, Z_{\max}]$. Both endpoint operations are finite. Nonfinite arithmetic encountered while attempting an unsuccessful compilation causes fallback and is never used as a valid radius.

Asymmetric enclosure. Using exact-real arithmetic on the displayed stored operands, write

$$p - C_{\mathrm{can}} = \big(p - (B_{\mathrm{lo}} + s)\big) + (s - S) + (B_{\mathrm{lo}} - B) + \big(B + S - C_{\mathrm{can}}\big). \tag{112}$$

The background contribution satisfies $B_{\mathrm{lo}} - B \le 0$, so Eqs. (104), (107) and (110) imply

$$p - C_{\mathrm{can}} \le E_a + E_s + E_c \le \rho_{\mathrm{lo}}, \tag{113}$$

$$C_{\mathrm{can}} - p \le E_c + (B - B_{\mathrm{lo}}) + E_s + E_a \le E_c + E_b + E_s + E_a \le \rho_{\mathrm{hi}}. \tag{114}$$

Hence, as real inequalities,

$$p - \rho_{\mathrm{lo}} \le C_{\mathrm{can}} \le p + \rho_{\mathrm{hi}}. \tag{115}$$

Omitting E_b from the lower radius is valid specifically because the center uses the lower background endpoint.

The runtime endpoints are

$$L = \max\{0, \mathrm{RN}(p - \rho_{\mathrm{lo}})\}, \qquad U = \mathrm{RN}(p + \rho_{\mathrm{hi}}). \tag{116}$$

They use ordinary round-to-nearest operations. Soundness does not require round-to-nearest to act as directed rounding. The target C_{can} is a representable binary64 value, so monotonicity and idempotence give

$$\mathrm{RN}(p - \rho_{\mathrm{lo}}) \le \mathrm{RN}(C_{\mathrm{can}}) = C_{\mathrm{can}}, \tag{117}$$

$$\mathrm{RN}(p + \rho_{\mathrm{hi}}) \ge \mathrm{RN}(C_{\mathrm{can}}) = C_{\mathrm{can}}. \tag{118}$$

Clipping the lower result at zero preserves its inequality because $C_{\mathrm{can}} \geq 0$. Therefore $L \leq C_{\mathrm{can}} \leq U$. This proof includes subnormal endpoints and underflow to zero; the additive η allowances were compiled already. It would not justify the same ordinary endpoints for a general unrepresentable real target.

Once p is formed, Eq. (116) requires two ordinary arithmetic endpoint operations and a lower clamp, without per-cell nextafter. Forming p itself is one ordinary addition to the stored subset answer. Subset acquisition and subsequent profile-envelope work remain.

Proposition 3 (Compiled stored-load enclosure)**.** *For a supported leaf whose compiled fields satisfy Eq.* (101)*, the ordinary endpoints in Eq.* (116) *contain its canonical stored resident load in every scene–time cell. Unsupported families and nonleaf batches retain the original outward-enclosure path.*

Proof. The first-overflow argument proves finite subset, canonical, center and endpoint operations. Equations (104), (107) and (110) imply the asymmetric real interval in Eq. (115). Representability and monotonicity in Eq. (118), followed by the nonnegative lower clamp, prove the stated stored-load enclosure. The fallback path is the existing valid resident enclosure. □

Range inclusion and the leaf-only implementation. For completeness, the same radii have a range argument based on *real* subset inclusion. It must not assert that canonical stored loads for different memberships are monotone, since their summation trees and shapes can differ. Let S_{m} and S_{p} be the real mandatory and possible mutable sums for a range. Every descendant obeys

$$S_{\mathrm{m}} \leq S \leq S_{\mathrm{p}} \leq S_{\max}. \tag{119}$$

Let $s_{\mathrm{m}}, s_{\mathrm{p}}$ be their stored subset answers and let $p_{\mathrm{m}}, p_{\mathrm{p}}$ be the ordinary centers formed with B_{lo}. The same budgets prove

$$p_{\mathrm{m}} \leq B_{\mathrm{lo}} + S_{\mathrm{m}} + E_s + E_a, \tag{120}$$

$$C_{\mathrm{can}} \geq B + S - E_c \geq B_{\mathrm{lo}} + S_{\mathrm{m}} - E_c, \tag{121}$$

so $p_{\mathrm{m}} - \rho_{\mathrm{lo}} \leq C_{\mathrm{can}}$. Likewise

$$C_{\mathrm{can}} \leq B + S + E_c \leq B_{\mathrm{hi}} + S_{\mathrm{p}} + E_c, \tag{122}$$

$$p_{\mathrm{p}} \geq B_{\mathrm{lo}} + S_{\mathrm{p}} - E_s - E_a, \tag{123}$$

so $C_{\mathrm{can}} \leq p_{\mathrm{p}} + \rho_{\mathrm{hi}}$. Applying Eq. (118) gives stored-target endpoints for every completed descendant. No comparison between stored mandatory and stored complete canonical reductions was used.

The supported compiled path applies to batches consisting entirely of leaf requests. Mandatory and possible sets then coincide, so one subset answer and one center per side suffice. A batch containing a nonleaf request, or a family whose radius compilation fails, uses the original outward resident enclosures and their existing profile bounds. Thus the range argument establishes validity of the numerical construction, while the implemented nonleaf path retains the original enclosures.

A sufficient stored-peak upper sum. The fast leaf path does not construct a real mandatory-load upper endpoint. In particular, its U is not substituted for an upper endpoint on an unreduced real resident sum. The PAR bound can instead use upper endpoints on stored peaks directly.

Let $\pi_h = \max_t C_{\mathrm{can},ht}$ be the edited groups' stored peaks. Taking maxima of valid stored-load endpoints gives

$$p_h^- := \max_t L_{ht} \leq \pi_h \leq p_h^+ := \max_t U_{ht}. \tag{124}$$

The plain upper pair sum

$$P^{+}_{\mathrm{pair}} = p^{+}_{0} \oplus_{\uparrow} p^{+}_{1} \geq \pi_0 + \pi_1 \tag{125}$$

is therefore sufficient. Let P^{+}_{c} be the existing upper endpoint on the real sum of common groups' stored peaks. Adding it outward to P^{+}_{pair} and applying the existing canonical H-operand upper transfer yields

$$P^{+}_{\Sigma} \geq \mathrm{sum}^{\mathrm{can}}_{h=1,\ldots,H} \pi_h. \tag{126}$$

The common and pair operands bound real sums of already stored peaks; the final host-reduction allowance is still retained.

Let P^{-} be the original lower endpoint for the largest stored peak, obtained from common peaks, edited lower peaks and half the conserved pair load. With the existing active-host endpoints $A^{-} \leq A \leq A^{+}$ and positive A^{-},

$$\overline{P}^{+} = \mathrm{RN}(P^{+}_{\Sigma}/A^{-}) \geq \mathrm{RN}(\mathrm{sum}^{\mathrm{can}}_{h} \pi_h/A) = \overline{P}. \tag{127}$$

The original check $\mathrm{RN}(P^{-}/A^{+}) > 0$ guarantees $\overline{P} > 0$: a canonical nonnegative peak fold is at least its largest operand and hence at least P^{-}. Under the retained finite and positive denominator checks, monotonicity then gives

$$\mathrm{RN}(P^{-}/\overline{P}^{+}) \leq \mathrm{RN}\left(\max_{h} \pi_h/\overline{P}\right) = \mathrm{PAR}. \tag{128}$$

A failed finite or positivity check leaves PAR's universal lower value -1. In particular, this preserves the native sentinel when a nonzero scene has a stored mean peak rounded to zero.

The compiled leaf path uses this plain peak-sum upper endpoint. The original outward path retains its optional minimum with the conservation-refined upper endpoint. Both are valid; their relative tightness is not needed for preservation.

Profile, key and family preservation. Accepted compiled leaves supply finite stored-load enclosures, so the preceding six-native-loss derivation applies to their tolerant/native counts, active and affected denominators, individual time projections, common summaries and conserved-pair excess. Equation (128) supplies the guarded PAR lower coordinate. Availability of the full family enclosure, the saved-reference finite-scale check, the family-wide finite-profile guard of Lemma 9, the global-idle fallback and the local finite and stored-mean-peak positivity checks are retained. The load-domain guard alone does not bound all profile intermediates: division by a tiny capacity or a subsequent host reduction can overflow even when every resident load is finite.

Each returned profile is consequently still a lower endpoint for the canonical stored loss profile. The unchanged native gain circuit, positive quantization, floor and ascending order statistics therefore yield a valid optimistic key. A failed refinement uses its existing universal lower value; an unavailable complete certificate has formal upper key $+\infty$ and excludes nothing. Proposition 4 applies to every strict score exclusion. No compiled endpoint replaces an exact retained summary, and Theorem 8 preserves the completed-family retained pool, seen set and physical record.

Cost and storage. Compilation scans the wBT mutable values and $O(BT)$ background endpoints once per family, using $O(wBT)$ time and retaining an $O(BT)$ radius payload. After resident-subset acquisition, each accepted leaf uses one center addition and two ordinary endpoint operations per changed load cell, without candidate-wise nextafter operations on those endpoints. Enclosing q inspected leaves still costs $O(qBT)$; the reuse reduces repeated arithmetic rather than removing the dependence on q or making the procedure output-sensitive. Bounded candidate-axis tiling limits

endpoint workspace as in Lemma 10, separately from scalar mask and key metadata. Resident subset-table construction and storage, selector fallback, the subsequent native-profile calculations, eligibility, identity and complete seen bookkeeping, exact retained profiles and final physical materialization keep their separate costs.

9.6 Endpoint-selective certificate acquisition

A two-coordinate indicator filter is one valid certificate-acquisition plan. Occurrence and tolerant host fraction require only mandatory load endpoints and conserved pair load; this filter leaves the remaining losses at universal lower values. When used on its own, it starts after P distinct exact records establish an input cutoff. Sections 9.7–9.8 then derive the supported aggregate-and-peak plan, including exact pilot acquisition before the first full cutoff.

Fix one scene b and let $C_\tau = \mathrm{RN}(C + \tau)$. Let c_b be the exact number of unchanged family groups whose stored load exceeds C_τ at some time. For changed groups $h \in \{0, 1\}$ let L_{hbt} be their stored-load lower endpoints and let D^-_{bt} be the conserved-pair lower bound from Eq. (87). Set

$$\begin{aligned} d^-_b &= \sum_{h=0}^{1} \mathbf{1}\{\exists t : L_{hbt} > C_\tau\}, \\ r^-_b &= \mathbf{1}\{\exists t : D^-_{bt} > 2C_\tau\}, \\ k^-_b &= c_b + \max\{d^-_b, r^-_b\}. \end{aligned} \tag{129}$$

An individually counted group certainly violates by monotonicity. If the coupled test holds and neither changed group violated, their two stored loads would sum to at most $2C_\tau$, contradicting the definition of D^-_{bt}. Thus k^-_b is a lower bound on the actual affected-host count k_b.

Define the coarse stored profile

$$C^-_b = \big(\mathbf{1}\{k^-_b > 0\},\ \mathrm{RN}(k^-_b/H),\ -1,\ 0,\ 0,\ -1\big)\,. \tag{130}$$

Counts and H are exactly represented in the stated domain. Monotonicity of fixed positive division gives $\mathrm{RN}(k^-_b/H) \le \mathrm{RN}(k_b/H)$. The native definitions give $\mathrm{VR}_b \ge -1$, $\mathrm{PAR}_b \ge -1$, $u_b \ge 0$ and $\mathrm{VS}_b \ge 0$, including idle sentinels. Therefore $C^-_b \le L_b(a)$ coordinatewise for every covered candidate. The values -1 for VR and PAR are essential: replacing an unknown sentinel-bearing loss by zero would not be a valid universal lower bound. This stage evaluates no candidate peak, severity denominator, or excess projection.

A family-uniform finite-profile guard. A finite seed and a finite reference profile alone do not prove that every alternative group's canonical reduction is finite. Let n_0, n_1 be the two seed resident counts, $R = n_0 + n_1$, and let s_{hbt} be their stored seed loads. Outward inversion of Eq. (86) supplies real upper endpoints s^+_{hbt}. Conservation gives

$$\sum_{i \text{ in the two seed groups}} x_{bit} \le S^+_{bt} := \mathrm{up}(s^+_{0bt} + s^+_{1bt}). \tag{131}$$

Every edited descendant group is a subset of this resident union. Its real load is at most S^+_{bt}, and it has at most R residents, so its canonical stored load is at most

$$U^*_{bt} = \mathrm{StoredUpper}_R(S^+_{bt}) := \mathrm{up}\big((1 + \gamma_R)S^+_{bt} + d_R\big)\,. \tag{132}$$

This is a bound on each changed group's load, rather than an assertion that the two stored descendant reductions sum to their seed reductions.

Put $K_b^+ = \max_t U_{bt}^*$. Let $P_{\mathrm{com,b}}^+$ be a real upper bound on the sum of stored unchanged-host peaks, and $P_{\mathrm{com,b}}^{\max}$ their stored maximum. Before using Eq. (130), the coarse stage requires finite U^* and, for every scene,

$$\mathrm{StoredUpper}_H\Big(\mathrm{up}(P_{\mathrm{com,b}}^+ + \mathrm{up}(2K_b^+))\Big) < \infty,$$
$$\mathrm{up}\left(\frac{\max\{K_b^+, P_{\mathrm{com,b}}^{\max}\}}{C}\right) \le \bar{r} := \mathrm{RN}\left(\frac{F_{\max}}{4HT}\right), \tag{133}$$

where $F_{\max}$ is the largest finite binary64 value. The guard costs $O(BT)$ family work and is shared by its candidate leaves. All upper operations retain $+\infty$ on overflow. In particular, no downward clipping helper is allowed to turn an overflowing intermediate into a finite exclusion witness.

Lemma 9 (Finite coarse-certificate domain)**.** *Under the nonnegative source, count and rounding assumptions already stated, Eqs.* (132)–(133) *suffice to keep every covered candidate's canonical loads and native profile finite. If the guard cannot be proved, omitting only the coarse stage preserves the ordinary refined path.*

Proof. The positive-tree majorants also provide a sufficient no-overflow test without assuming the conclusion. Suppose an addition in a covered nonnegative tree were the first to overflow. Every child computation before it is finite, so its expanded exact input is bounded by the same positive majorant, using at most the global count's number of error factors. A partial tree has no more leaves and no larger exact input sum than the complete tree. The checked finite upward majorant is at least that input and at most $F_{\max}$. Monotonicity then gives a finite rounded result, contradicting a first overflow. The argument applies to the resident, peak and excess folds below.

Equation (132) bounds each changed load by a finite value; unchanged loads already belong to the finite canonical source views. Each changed stored peak is at most K_b^+, so the first guard bounds the canonical positive fold of all stored peaks, regardless of their canonical column order. To spell out the excess guard, the stored positive excess of a cell is at most its stored capacity ratio: monotonicity gives $\mathrm{RN}(r-1) \le \mathrm{RN}(r) = r$ for stored $r \ge 1$, while clipping gives zero when $r < 1$. Hence every excess operand is at most $\bar{r}$. Since $HT \le 2^{50}$ and $u = 2^{-53}$, the growth factors satisfy

$$1 + \gamma_H \le 8/7, \qquad 1 + \gamma_T \le 8/7, \qquad \bar{r} \le \frac{(1+u)F_{\max}}{4HT} + \eta. \tag{134}$$

A worst-case time fold followed by a host fold is consequently at most

$$(1+\gamma_H)\big[H((1+\gamma_T)T\bar{r} + d_T)\big] + d_H$$
$$\le \frac{16(1+u)}{49}F_{\max} + 5HT\eta < F_{\max}. \tag{135}$$

Here $d_n \le (8/7)n\eta$; substituting these bounds makes the coefficient of $HT\eta$ less than four, so five is conservative. Division by positive integer time or count normalizers cannot increase a stored positive sum, because $\mathrm{RN}(x/d) \le \mathrm{RN}(x) = x$ for $d \ge 1$. Thus Eq. (135) also covers the affected-host severity fold and the implemented normalized excess folds. Boolean and frequency counts are finite under the exactly represented count normalizers.

For completeness, let $P > 0$ be the largest stored peak, $A \in [H]$ the active-host count and S the finite canonical stored sum of peaks. Nonnegative rounded addition is monotone, so $S \ge P$. Every active peak is at least η. Since $A \le 2^{50}$, all integer multiples $j\eta$ for $j \le A$ are exactly represented. Induction through the positive fold consequently gives $S \ge A\eta$, and its stored mean $\mu = \mathrm{RN}(S/A)$

is at least η. If $P \le 2H\eta$, then $\mu \ge \eta \ge P/(2H)$. Otherwise $P/H > 2\eta$, and rounding a positive value at least η cannot decrease it by a factor greater than two. Hence

$$\mu \ge \mathrm{RN}(P/H) \ge P/(2H). \tag{136}$$

Thus $\mathrm{RN}(P/\mu) \le \mathrm{RN}(2H) = 2H$, which is finite and exactly represented. A zero-active-host scene uses the finite native sentinel instead. These arguments cover PAR as well as the other coordinates. When any guard is unavailable, the implementation acquires the original full bound or exact profile rather than issuing a coarse exclusion. Its previous numerical and query-preservation arguments therefore remain applicable. □

Theorem 5 (Endpoint cascade preserves the retained answer)**.** *For each active candidate, derive an upper key $U_{\mathrm{ind}}(a)$ from the coarse profiles in Eq.* (130) *by the fixed native gain circuit and exact movement count. Exclude a candidate only when its finite upper key is strictly below the worst key c of the exact full pool. Refine every remaining candidate using the original six-coordinate bounds and progressive acquisition. This cascade preserves the complete retained result, physical outputs and continuing seen state.*

Proof. The profile inequality proved above and the stored-gain monotonicity argument imply

$$C^- \le L(a) \quad \Longrightarrow \quad g(C^-) \ge g(L(a)) \quad \Longrightarrow \quad U_{\mathrm{ind}}(a) \ge K(a). \tag{137}$$

The second implication uses monotonicity of positive quantization, floor and ascending order statistics, and appends the same exact movement objective. A coarse exclusion therefore satisfies

$$K(a) \le U_{\mathrm{ind}}(a) < c. \tag{138}$$

Already P distinct exactly evaluated identities precede a. Subsequent exact retention can only improve the cutoff, so a cannot belong to the final top-P. For a group D of excluded leaves, $\max_{a \in D} U_{\mathrm{ind}}(a) < c$ is a valid joint witness by the same inequalities. The remaining full-bound exclusions satisfy the original proof. No coarse field replaces an exact stored profile in a retained record. Every forecast-feasible identity is still inserted into the seen set, including movement- and score-excluded candidates, and physical output construction still uses its unique-matching certificate or the reference matcher. Lemma 11, Proposition 4 and Theorem 8 then establish the stated retained-record and continuation equivalence. □

Both stages require valid bounds, but their separately computed upper keys need not be numerically identical or nested. The theorem also makes no universal CPU or profile-count reduction claim. Its advantage is that an excluded candidate need not acquire its more expensive six-coordinate bound profile at all.

9.7 Aggregate and peak profile certificates

Fix the immutable source, capacity, reference profile, incumbent, two edited resident groups, and complete-family retention contract of Section 9. The following bounds apply separately to each scene and to every complete descendant of an aligned mask interval. They concern the canonical stored profile, rather than a real-arithmetic surrogate. Write RN for the prescribed binary64 round-to-nearest operation, $u = 2^{-53}$, and $\eta = 2^{-1074}$. All counts, including HT, obey the existing 2^{50} bound. The capacity C is finite and strictly positive. The family source and its saved reference operands are finite, nonnegative where required, and immutable.

We reuse resident-load endpoints $L_{ht} \le x_{ht} \le U_{ht}$ for the two edited groups $h \in \{0,1\}$, and the conserved-pair endpoint $D_t^- \le x_{0t} + x_{1t}$ from Eq. (87). The original outward path supplies these endpoints for its supported ranges. On supported uniform-radius leaves, Proposition 3 supplies endpoints for the same canonical stored targets; a nonleaf batch or unavailable radius uses the original outward path. Here x_{ht} is the canonical stored load in a particular descendant, and the addition in the conserved-pair inequality is an exact-real addition of those two stored values. Existing common-group summaries provide exact active, tolerant-violating, affected and native overloaded-cell counts, denoted A_{c}, Q_{c}, M_{c} and N_{c}. They also provide lower endpoints E_{c}^- and S_{c}^- for the real sums of the common groups' canonical stored mean-excess and severity projections. Peak summaries and all enclosure operations retain their existing definitions.

Let $a \oplus_{\downarrow} b$ and $a \oplus_{\uparrow} b$ denote the implementation's nonnegative outward lower and upper additions. Let $\mathrm{Down}(z) = \max\{\mathrm{nextafter}(z, -\infty), 0\}$ for a stored nonnegative value or stored arithmetic result. For any nonnegative real-sum lower endpoint z, write $\mathcal{S}_n^-(z)$ for its transfer through a canonical reduction of at most n nonnegative stored operands. Equation (85), evaluated outwards, gives

$$\mathcal{S}_n^-(z) \le \max\{0, (1-\gamma_n)z - d_n\} \le \mathrm{sum}_{i=1,\dots,n}^{\mathrm{can}}\, v_i \quad \text{whenever} \quad z \le \sum_{i=1}^{n} v_i. \tag{139}$$

The first inequality allows the outward implementation to be more conservative than the exact displayed expression. The construction of γ_n, d_n and the validity under arbitrary supported nonnegative reduction trees are unchanged.

Denominators and extrema. Define $c_\tau = \mathrm{RN}(C + 10^{-12})$, $p_h^- = \max_t L_{ht}$ and $p_h^+ = \max_t U_{ht}$. Since C is representable and the added tolerance is nonnegative, $c_\tau \ge C$. The existing active-host endpoints are

$$A^+ = A_{\mathrm{c}} + \sum_{h=0}^{1} \mathbf{1}[p_h^+ > 0], \tag{140}$$

$$A^- = A_{\mathrm{c}} + \max\left\{ \sum_{h=0}^{1} \mathbf{1}[p_h^- > 0],\ \kappa \right\}, \tag{141}$$

where κ is the indicator that the conserved edited pair contains positive demand in this scene. A positive source operand remains positive under every nonnegative canonical resident reduction, so $\kappa = 1$ forces at least one active edited group. Thus $A^- \le A \le A^+$. The affected-host upper endpoint is

$$M^+ = M_{\mathrm{c}} + \sum_{h=0}^{1} \mathbf{1}[p_h^+ > C] \ge M. \tag{142}$$

For each side, $\mathbf{1}[p_h^+ > C] = \mathbf{1}[\exists t : U_{ht} > C]$. Hence this affected-host endpoint requires no additional time-by-host Boolean tensor once the upper peaks are available. These are upper denominator bounds for raw excess, VR and severity; replacing them by the counts observed in the lower-load array would not be sound.

Occurrence and tolerant host fraction. Put $b_{ht} = \mathbf{1}[L_{ht} > c_\tau]$ and

$$Q^- = Q_{\mathrm{c}} + \max\left\{ \sum_{h=0}^{1} \mathbf{1}[\exists t : b_{ht} = 1],\ \mathbf{1}[\exists t : D_t^- > 2c_\tau] \right\}. \tag{143}$$

Each individual test implies a tolerant violation by that edited group. The coupled test implies a violation by at least one edited group, because two loads at most c_τ have real sum at most $2c_\tau$. Taking the maximum avoids counting the same compulsory violation twice. Consequently

$$J^- = \mathbf{1}[Q^- > 0] \le J, \qquad V^- = \mathrm{RN}(Q^-/H) \le V. \tag{144}$$

The last inequality follows from monotonicity of the same stored division used by the native tolerant host fraction.

Native violation rate from tolerant Boolean counts. Although b_{ht} uses the tolerant threshold, it can safely lower-bound the strict native count: $b_{ht} = 1$ implies $x_{ht} > c_\tau \ge C$. At each time set

$$q_t^- = \max\left\{b_{0t} + b_{1t},\ \mathbf{1}[D_t^- > 2C]\right\}, \qquad N^- = N_{\mathrm{c}} + \sum_{t=1}^{T} q_t^-. \tag{145}$$

The first argument is bounded by the number of actually overloaded edited hosts at that time. The second is also bounded by that count, by pair conservation. Thus $q_t^- \le \sum_{h=0}^{1} \mathbf{1}[x_{ht} > C]$, and $N^- \le N := \sum_{h=1}^{H} n_h$, where $n_h = \sum_t \mathbf{1}[x_{ht} > C]$ is the descendant's strict native overload count. In particular, no tolerant count is asserted to equal a native count. The comparison with C in the coupled test remains strict.

If $T = 2^k$, each n_h/T is exactly representable. Every nonnegative partial sum of these frequencies is an integer multiple of 2^{-k} with numerator at most $HT \le 2^{50}$, and is therefore exactly representable too. Hence the canonical host sum of the stored frequencies equals N/T exactly, and

$$\mathrm{VR}^- = \mathrm{RN}\big((N^-/T)/A^+\big) \le \mathrm{RN}((N/T)/A) = \mathrm{VR}. \tag{146}$$

The division N^-/T on the left is exact. The final stored division is monotone in its nonnegative numerator and antitone in its positive denominator.

For other positive T, the elementary rounding model gives, for every host,

$$f_h := \mathrm{RN}(n_h/T) \ge (1-u)n_h/T - \eta. \tag{147}$$

Summing these inequalities as real inequalities and using $N^- \le N$ yields

$$\sum_{h=1}^{H} f_h \ge (1-u)N/T - H\eta \ge (1-u)N^-/T - H\eta. \tag{148}$$

Let F^- be a nonnegative outward lower evaluation of $\max\{0, (1-u)N^-/T - H\eta\}$. Clipping is valid because the real sum of the nonnegative stored frequencies is itself nonnegative. In the implementation this is obtained by downwardly enclosing N^-/T, multiplying downward by the exactly represented $1-u$, subtracting an upward representation of $H\eta$, and clipping the result downward at zero. Therefore $F^- \le \sum_h f_h$. Transferring to the canonical stored host reduction before dividing gives

$$\mathrm{VR}^- = \mathrm{RN}\big(\mathcal{S}_H^-(F^-)/A^+\big) \le \mathrm{RN}(\mathrm{sum}_h^{\mathrm{can}}\, f_h/A) = \mathrm{VR}. \tag{149}$$

All integer counts and positive integer denominators used here are exactly represented in the supported range. The proof permits downward rounding to zero and does not presume that non-dyadic host frequencies are exact.

A family-constant excess bound. For a canonical stored load x define its native stored excess by

$$e(x) = \max\{\mathrm{RN}(\mathrm{RN}(x/C) - 1), 0\}. \tag{150}$$

Let $Z_h = \mathrm{sum}_t^{\mathrm{can}}\, e(x_{ht})$ and $\mu_h = \mathrm{RN}(Z_h/T)$ be the canonical time sum and stored mean excess of an edited host. The existing coupled-excess derivation, Eq. (94), supplies a lower endpoint for each time,

$$a_t^- \le \max\left\{(1-2u)D_t^-/C - 2, 0\right\} \le e(x_{0t}) + e(x_{1t}). \tag{151}$$

The endpoint a_t^- is evaluated entirely downwards. In particular, it does not require either edited host's per-time individual excess array. Lower-bound the real sum $\sum_t a_t^-$, transfer through the two time reductions with allowance $2d_T$, and then cover the two stored divisions by T exactly as in the existing coupled raw-excess derivation. The resulting scene-wise value c satisfies

$$0 \le c \le \mu_0 + \mu_1. \tag{152}$$

For completeness, if $a^- \le \sum_t a_t^-$, a valid sequence of nonnegative downward evaluations is

$$z^- \le \max\{0, (1-\gamma_T)a^- - 2d_T\} \le Z_0 + Z_1, \tag{153}$$

$$c \le \max\{0, (1-u)z^-/T - 2\eta\} \le \mathrm{RN}(Z_0/T) + \mathrm{RN}(Z_1/T). \tag{154}$$

These are the already established conservative coupled-mean operations, specialized by dropping the optional maximum with the per-time individual excess bounds. Dropping that maximum can weaken the result but cannot invalidate either inequality. Every operand depends only on the conserved edited pair and the source; thus c is computed once per family and scene, rather than once per candidate. If a finite lower endpoint cannot be formed, $c = 0$ is a valid conservative fallback.

Peak-implied mean and severity bounds. Define a stored peak-excess endpoint by the following downward operations,

$$e_h^- = \mathrm{Down}\big(\max\{\mathrm{RN}(\mathrm{Down}(\mathrm{RN}(p_h^-/C)) - 1), 0\}\big)\,. \tag{155}$$

All arguments in this expression are nonnegative where required. If the preliminary ratio is nonfinite, this particular refinement uses zero instead. Since $p_h^- \le \max_t x_{ht}$, monotonicity of correctly rounded division, subtraction and maximum proves

$$0 \le e_h^- \le \max_t e(x_{ht}). \tag{156}$$

The outward steps only decrease the endpoint. In every supported nonnegative addition tree, the stored sum is at least each stored operand: if $a, b \ge 0$ are representable, then $\mathrm{RN}(a+b) \ge a, b$, because the exact sum is at least each representable endpoint and round-to-nearest is monotone. Induction along the path from any leaf to the root gives

$$Z_h \ge \max_t e(x_{ht}) \ge e_h^-. \tag{157}$$

This argument also covers subnormal operands and additions to exact zero. Therefore

$$\mu_h^- := \mathrm{RN}(e_h^-/T) \le \mathrm{RN}(Z_h/T) = \mu_h. \tag{158}$$

Use the strict native threshold to define $n_h^+ = \sum_t \mathbf{1}[U_{ht} > C]$. Then $n_h \le n_h^+$. The native stored severity is $s_h = \mathrm{RN}(Z_h/n_h)$ if $n_h > 0$, and zero otherwise. If $n_h > 0$, monotonicity in the numerator and denominator gives

$$s_h^- := \mathrm{RN}\big(e_h^- / \max\{1, n_h^+\}\big) \le \mathrm{RN}(Z_h/n_h) = s_h. \tag{159}$$

If $n_h = 0$, then every $x_{ht} \le C$. Monotonicity gives $\mathrm{RN}(x_{ht}/C) \le 1$, so every $e(x_{ht}) = 0$. Equation (156) implies $e_h^- = 0$, and the displayed lower bound is zero as required, even when uncertain upper loads give $n_h^+ > 0$. Thus the use of $\max\{1, n_h^+\}$ introduces no false positive bound in the zero-overload case. Counts are exact integers, and both stored divisions in Eqs. (158)–(159) may safely underflow to zero. No positive lower bound is inferred from a vanished subnormal result.

The native severity is also at least the native mean excess. When $n_h > 0$, $n_h \le T$ and both quantities use the same stored numerator Z_h, so $s_h = \mathrm{RN}(Z_h/n_h) \ge \mathrm{RN}(Z_h/T) = \mu_h$. When $n_h = 0$, both quantities are zero. Consequently Eq. (152) lower-bounds the real sum of either the two stored means or the two stored severities. Combine the independent valid endpoints as

$$B_\mu^- = \max\{c, \mu_0^- \oplus_\downarrow \mu_1^-\} \le \mu_0 + \mu_1, \tag{160}$$

$$B_s^- = \max\{c, s_0^- \oplus_\downarrow s_1^-\} \le s_0 + s_1. \tag{161}$$

The maximum is taken separately for the mean and severity bounds. It does not assert that the two per-host peak witnesses occur at the same time; each canonical host time sum separately dominates that host's own largest excess.

Raw excess and severity. The common summaries bound real sums of already stored host projections. Hence

$$R^- = \mathcal{S}_H^-\big(E_{\mathrm{c}}^- \oplus_\downarrow B_\mu^-\big) \le \mathrm{sum}_h^{\mathrm{can}}\, \mu_h, \tag{162}$$

$$S^- = \mathcal{S}_H^-\big(S_{\mathrm{c}}^- \oplus_\downarrow B_s^-\big) \le \mathrm{sum}_h^{\mathrm{can}}\, s_h. \tag{163}$$

Applying the native final divisions with upper denominators proves

$$\mathrm{raw}^- = \mathrm{RN}(R^-/A^+) \le \mathrm{raw}, \qquad \mathrm{VS}^- = \begin{cases} \mathrm{RN}(S^-/M^+), & M^+ > 0, \\ 0, & M^+ = 0 \end{cases} \le \mathrm{VS}. \tag{164}$$

If $M^+ = 0$, then $M = 0$, every stored severity is zero and the zero branch agrees with the native definition. The active denominator is positive on the supported nonidle scene. This derivation avoids constructing a per-candidate time-by-host excess array or reducing such an array. It requires upper-load Boolean counts for the peak-severity denominator, as well as the already available peaks and common summaries.

Peak-to-average ratio and numerical guards. Both numerical paths use the maximum of the common peak, the edited lower peaks and half the conserved pair total as a lower endpoint for the largest stored peak. Their upper endpoints for the mean peak are formed according to the load-enclosure path. The original outward path uses the established minimum of the individual and conservation-based edited peak-sum upper endpoints, then combines the common peak-sum upper endpoint, the canonical host reduction allowance and A^-. Its PAR proof in Section 9 is unchanged.

The uniform-radius leaf path instead uses the plain stored-peak upper sum

$$P_{\mathrm{pair}}^+ = p_0^+ \oplus_\uparrow p_1^+ \ge \max_t x_{0t} + \max_t x_{1t}. \tag{165}$$

Combine this with the common real sum of stored peaks, transfer through the canonical H-host upper reduction, and divide by A^- to upper-bound the native stored mean peak. Equations (125)–(128) prove the resulting PAR lower coordinate. This path requires no real mandatory-load upper endpoint. The plain sum is a sufficient valid upper endpoint even though it may be less tight than the conservation-refined minimum. The choice belongs to the numerical load-enclosure path: a uniform-radius leaf in either the partial or full-bound stage may use the plain stored-peak construction, whereas an original outward branch retains its conservation-refined minimum.

Both paths retain the positive lower test for the stored mean peak. A nonzero scene may have a subnormal stored mean peak rounded to zero, in which case native PAR is -1; a positive PAR lower bound is unavailable and must not replace that sentinel.

Availability of the full family enclosure is a prerequisite, not a replacement for the coarse family-wide finite-profile guard of Lemma 9. That guard, the saved-reference finite-scale checks, the finite resident and common-summary endpoints, and the original finite/overflow checks remain in force. A globally idle scene disables this family certificate and uses canonical evaluation. A failed local PAR positivity or finite check retains the universal lower value -1 for PAR. A failed VR refinement retains its universal lower value -1; a failed raw or severity refinement retains zero. If the family-wide guard or the required resident enclosure is unavailable, the complete partial certificate is unavailable. An unavailable key is formal $+\infty$ and cannot exclude any candidate. In particular, finite lower values from one coordinate do not justify ignoring a potentially nonfinite native profile in another coordinate.

Theorem 6 (Aggregate and peak lower profile)**.** *Under the numerical and family guards above, the assembled scene-wise profile*

$$L_{\mathrm{ap}}^- = (J^-, V^-, \mathrm{VR}^-, \mathrm{raw}^-, \mathrm{VS}^-, \mathrm{PAR}^-) \tag{166}$$

is componentwise at most the canonical stored profile of every complete descendant covered by its range. Replacing any unavailable refinement by its stated universal lower value preserves this conclusion.

Proof. Equations (144), (146)–(149) and (164) establish the first five coordinates with their native comparison thresholds, time projections, host reductions and denominators. The guarded PAR construction for the selected numerical load path establishes the last: the original outward proof applies to its ranges, and Eqs. (165) and (128) apply to supported uniform-radius leaves. The universal values -1 for VR and PAR and zero for nonnegative raw excess and severity are lower bounds including their prescribed idle cases. The family guard excludes unsupported finite-arithmetic cases rather than interpreting their nonfinite results as ordinary losses. Every inequality holds for all completed descendants because the only descendant-dependent assumptions used were the common resident endpoints and conservation statements that already hold for the entire range. □

From partial profiles to optimistic keys. Let $K(a)$ be the original balanced key of candidate a, including its unit-cost movement coordinates, and let $U_{\mathrm{ap}}(a)$ be the key obtained by applying the unchanged saved-reference gain circuit, quantization by 2^{40}, floor and ascending coordinate sort to L_{ap}^-. Append the same exact unit-cost movement count and cost for a leaf, or valid lower movement and cost bounds for a range. The stored gain-circuit monotonicity argument in Section 9 yields

$$L_{\mathrm{ap}}^- \le L(a) \quad\Longrightarrow\quad g(L_{\mathrm{ap}}^-) \ge g(L(a)) \quad\Longrightarrow\quad K(a) \le U_{\mathrm{ap}}(a). \tag{167}$$

All reference operands and scales are those of the original circuit; neither a difference of means nor a differently ordered scene reduction replaces it. The final implication uses monotonicity of

multiplication by a positive constant, floor and every ascending order statistic. It does not require the partial and full-bound optimistic keys to be nested, equal or computed in the same mask order.

9.8 Exact pilot acquisition and sampled execution-plan selection

Let $\mathcal{R}_0$ be the input retained pool, with size at most P, and let $\mathcal{A}$ be the distinct eligible canonical family identities absent from the input seen set. Forecast and movement eligibility retain their original exact predicates or sound existing certificates. Restrict this execution path to the original balanced gain order with unit movement cost, for which the same summary suffices for retention; coverage archives and other score modes retain their original path. The staged plan is considered after forecast, movement and seen filtering, for $q = |\mathcal{A}| > 1024$; smaller families use the original execution plan. When the input pool is not full, the implemented pilot orders available identities by increasing exact movement count and then numeric mask, and acquires up to P of them. Their canonical profiles, original exact keys and retained summaries are produced by the ordinary exact consumer. Each pilot identity is removed from pending acquisition after being scored once.

After each completed pilot batch, read a score cutoff only from the actual retained pool. If fewer than P distinct identities are retained, there is no score cutoff: continue exact acquisition or use the ordinary no-cutoff plan. If the family is exhausted, return the current pool. Otherwise, for a full pool $\mathcal{R}$, define $c = \min_{b\in\mathcal{R}} K(b)$. The argument does not assume that P mask numbers imply P distinct identities, and does not use a fictitious cutoff inferred from partial keys.

Before acquiring an empty-pool pilot, the implementation checks the structural cost condition

$$qT \geq P(H + TR), \tag{168}$$

where R is the resident count of the two edited seed groups. A failed condition selects the original full-bound-first plan. If an exact input cutoff already exists, no pilot or pilot-shape check is needed: the staged plan may proceed directly to partial screening. The condition selects an execution plan and makes no score exclusion.

After an exact cutoff exists, at most 64 pending identities are sampled at deterministic evenly spaced positions of their current order. If fewer than 1/8 of the inspected identities have a valid key strictly below the cutoff, the remaining identities proceed directly to full-bound acquisition. Otherwise their partial keys are acquired before full-bound refinement. Every sampled identity with $U_{\mathrm{ap}}(a) < c$ may still be excluded under either choice. An unsampled identity, a sampled equality, and a sampled unavailable key remain pending unless another sound predicate resolves them. A flat sample with no rejection consequently takes the full-bound path as well. Every additional partial exclusion passes its own valid strict comparison, and inspected keys can be reused. The surviving identities then acquire full-bound keys and enter the original progressive exact-profile consumer. These cost choices change acquisition only; they are not inferences about the keys of unchecked identities.

Theorem 7 (Pilot, sample and refined-stage composition)**.** *Fix the original query inputs, balanced total order, input pool and input seen set. Suppose that pilot profiles are canonical, every partial or full-bound key is a valid optimistic key or unavailable, and score exclusion uses only strict comparison with the cutoff of a full actual exact pool. Then any composition of exact pilot acquisition, sample-based plan selection, partial-key exclusions, original full-bound exclusions and progressive exact evaluation returns the same completed-family retained summaries, seen set and physical records as complete canonical enumeration. The internal candidate order and positive batch sizes may differ.*

Proof. First ignore every score exclusion. If $\mathcal{E}_t$ denotes all distinct identities exactly scored through any completed batch, ordinary retention and Lemma 11 give

$$\mathcal{R}_t = T_P(\mathcal{R}_0 \cup \mathcal{E}_t). \tag{169}$$

Thus pilot order, sample inspection order and later exact batch partition cannot change the top-P of the scored union. They also cannot create an exact summary without a canonical profile. If fewer than P identities are ever available, all eligible identities are scored and the theorem follows already.

Now consider any score-excluded identity a. At its exclusion time a full pool $\mathcal{R}_t$ of P distinct exactly scored identities exists. By the relevant partial or full optimistic-key proof and the strict comparison,

$$K(a) \le U(a) < c_t := \min_{b \in \mathcal{R}_t} K(b) \le K(b) \qquad (b \in \mathcal{R}_t). \tag{170}$$

These P identities all precede a in the prescribed total order. They belong to the union used by complete enumeration even if a later candidate evicts some of them. Hence a cannot enter the top-P of that complete union. An unavailable key supplies no such inequality and never excludes. Equality is retained for exact evaluation because the canonical-assignment tie-break may still favor a.

The same argument applies independently to an exclusion found in the sample, an exclusion from scanning the unsampled remainder, an original full-bound exclusion, and a progressive stopping witness bounding all pending keys. A sampled cost decision itself excludes nothing. In particular, a mistaken prediction of selectivity can change only which valid stage is executed, not the retained result. Cutoffs cannot decrease under exact top-P retention, so a previously proved strict exclusion remains valid after later pilot or refinement batches. For a listed set D of independently excluded identities, $\max_{a \in D} U(a) < c_t$ is a valid compressed witness for precisely that set; it asserts nothing about unsampled identities between their mask numbers.

Removing all such strict losers leaves the complete union's top-P unchanged. Apply Lemma 11 to the remaining exact acquisitions and Eq. (169) to obtain the same completed summary pool as complete enumeration. Selecting pilot identities before the full-key ordering does not alter this conclusion. Removing them from pending acquisition avoids duplicate profiles while preserving the scored union.

Seen bookkeeping remains independent of the acquisition plan. At the family boundary it is the input seen set union the original forecast-feasible canonical family identities, including movement-ineligible identities and every partial-, full- or progressive-score rejection; forecast-ineligible identities retain the original treatment. All identities are formed and marked through the original canonical membership contract. Hence the completed seen set equals complete enumeration, including when sample-based selection skipped most partial keys.

Finally, retained exact summaries use the same canonical assignments, stored means, gain keys and exact movement counts. No partial profile is inserted into a retained record. Deferred physical materialization applies Proposition 6: each final retained identity receives the same deterministic physical matching record from its unique-matching certificate or the reference matcher. Its validity and tie handling are unaffected by the pilot or sampling order. No next seed or other consumer observes an unfinished family. Thus the completed rich pool is identical. The next operation therefore reads the same state; induction over completed families, with common external random draws and feedback, gives the same subsequent completed-family decisions. □

Work and the role of the sample. After construction of the resident-sum views, forming mandatory/possible loads, tolerant counts, upper strict counts and peaks for q_{ap} inspected candi-

dates costs $O(q_{\mathrm{ap}}BT)$ numeric work. The conserved mean-excess lower endpoint in Eq. (152) costs $O(BT)$ once per family. The additional common-summary, peak-mean and peak-severity arithmetic is $O(q_{\mathrm{ap}}B)$; the VR and upper-native-count Boolean time reductions are still $O(q_{\mathrm{ap}}BT)$, not $O(q_{\mathrm{ap}}B)$. If q' survivors acquire full-bound keys, the bound-acquisition work is

$$O(BT) + O(q_{\mathrm{ap}}BT) + q'\,C_{\mathrm{full}}(B,T), \qquad 0 \le q_{\mathrm{ap}}, q' \le q, \tag{171}$$

where $C_{\mathrm{full}}(B,T) = O(BT)$ denotes the original full-bound work with its larger collection of per-time numeric projections. Include separately the actual pilot and survivor canonical-profile costs, resident-sum index construction, scalar gain/key metadata, eligibility, matching, identity formation, complete seen bookkeeping and final physical outputs. Without indexed resident sums, the selected subset-sum backend contributes its original additional cost; Eq. (171) does not replace that cost by a constant lookup.

If the sample skips the partial scan, q_{ap} may be only the sample size and q' may be almost q. If it selects the scan, it may still reject no candidate. A small deterministic sample is a cost heuristic, not a statistical guarantee of unsampled selectivity, an optimal plan, lower total runtime, fewer exact profiles, or dominance over another execution plan. The bound is not output-sensitive: up to q partial keys may be inspected regardless of how small the retained pool is, and source, identity and eligibility work need not shrink with P. Reported efficiency must therefore come from measured end-to-end execution and stage counts; it is not implied by the preservation theorem.

9.9 Tiling and bounded certificate caches

Each coarse or refined range query requests a fixed scene-by-coordinate lower profile. An unavailable field denotes the formal optimistic value $+\infty$ and never excludes a candidate. Tile these requests only along the outer candidate/range axis. Within a tile, each resident, time and scene reduction retains its prescribed logical operands or its valid outward enclosure. The native gain circuit still reduces the same contiguous length-B row and uses its original saved reference scale; it is not recomputed from a differently packed reference.

Lemma 10 (Certificate tiling and eviction preserve semantics)**.** *Under the existing fixed-backend reduction contract, processing bound requests in finite outer tiles and using a bounded cache of independently owned lower profiles preserve validity of all upper keys. Recomputing evicted fields and sharing identical leaf mandatory/possible answers preserve the exact family result.*

Proof. For an index table, every tile looks up the same requested subsets of the immutable source. For the selector fallback, every resulting sum remains a tree over exactly its requested nonnegative operands; Eq. (85) and Theorem 4 cover its possible reassociation. Thus tiling does not turn a lower endpoint into an overestimate or an upper endpoint into an underestimate. The native gain-circuit lemma preserves its row reduction after packing, since tiling changes only the number of adjacent rows. Equation (137) and the original full-bound argument therefore remain valid in every tile.

A cache hit returns a previously proved field for the same immutable source, seed/family identities and numerical parameters. Eviction removes only the lookup reference. Local references for the current request keep their independently owned arrays until the request completes. If an evicted field is requested again, either valid sum-view path reconstructs another valid lower profile; bitwise equality of a recomputed bound is unnecessary because every exclusion is justified anew. For a leaf, Eq. (89) proves equality of mandatory and possible sets. Reusing the same read-only computed answer for both cannot change either inequality. Finally, every omitted exact profile still has an upper key strictly below an exact full-pool cutoff. Theorem 8 applies regardless of the

order of bound requests or their cache history, proving equality of retained physical records and seen state. □

For a target tile budget M of changed-load values, the tile length is at most $\max\{1, \lfloor M/(2BT)\rfloor\}$. Its numeric intermediate arrays therefore require $O(M + BT)$ workspace: one complete request is unavoidable even when $2BT > M$, and the profile dimension is fixed. With a lower-profile cache target of C_{cache} values, the refined cache stores at most $\max\{1, \lfloor C_{\text{cache}}/(6B)\rfloor\}$ profiles and hence at most $\max\{C_{\text{cache}}, 6B\}$ values; the coarse cache may instead decline to retain an oversized profile. Owning each cached profile separately prevents one small cache entry from pinning an entire discarded tile. The two-half tables have the storage in Proposition 2. Scalar optimistic keys and active-mask descriptors require $O(q)$ additional fixed-dimensional metadata. These bounds concern numerical certificate arrays and key metadata. Explicit family identities, complete forecast-feasible seen bookkeeping, matching state and final physical outputs retain their separate space and work costs.

10 Complete-family preservation and deferred physical matching

A candidate's retention summary contains its canonical assignment a, stored Build means and gains, balanced key, and optimum movement count. In the unit-cost setting its movement cost is $m(a)$ as well. Let $s(a)$ denote this summary and let $D(a)$ be the prescribed full physical-matching record, including aligned host destinations and moved workload identities. The rich record is $r(a) = (s(a), D(a))$. The map D depends only on the fixed incumbent, canonical assignment, and deterministic matching rule.

10.1 Order-independent retention

Fix the total order that compares exact balanced keys in descending order and then canonical assignments in ascending order. Keys are fixed by the immutable query inputs. For $P \geq 1$, let $T_P(A)$ retain the first $\min(P, |A|)$ distinct canonical identities in a finite set A, with their summaries. Repeated identities have the same summary and contribute one element.

Lemma 11 (Top-P composition)**.** *For finite candidate sets A and B under this fixed total order,*

$$T_P(T_P(A) \cup B) = T_P(A \cup B). \tag{172}$$

Consequently, exact scoring in any order or batch partition returns the same final retained pool.

Proof. If $a \in A \setminus T_P(A)$, then at least P distinct identities in A precede a. Those predecessors remain present in $A \cup B$, so $a \notin T_P(A \cup B)$. Thus removing $A \setminus T_P(A)$ cannot remove any element of the right-hand side. Both sides retain the first P available identities in the same total order, or all identities when fewer than P exist, proving Eq. (172). Repeated application gives the result for any sequence of batches with the same union. The final assignment tie-break makes this order independent of candidate arrival. □

10.2 Progressive certified evaluation

Let $\mathcal{R}$ be the exact retained pool after the candidates scored so far, and let $\mathcal{U}$ contain the remaining eligible family identities absent from the input seen set. For each $a \in \mathcal{U}$, a valid optimistic key $K^+(a)$ satisfies $K(a) \leq K^+(a)$ in lexicographic key order. The same bound may cover a residual subtree. An unavailable or invalid enclosure, represented by `None`, is assigned the formal upper

value $+\infty$; it cannot justify score exclusion. Process candidates in descending optimistic-key order and score each selected batch canonically. After updating the exact pool, a full pool permits stopping when

$$\max_{a \in \mathcal{U}} K^{+}(a) < K(\text{worst}(\mathcal{R}))\,. \tag{173}$$

If $\mathcal{U}$ is empty, the family is already complete. With fewer than P retained identities, the score cutoff does not permit early stopping.

Proposition 4 (Progressive evaluation preservation)**.** *Suppose every omitted candidate has a valid upper key strictly below the worst key of a full current pool, either individually or by Eq.* (173)*. Progressive evaluation returns the same final summary pool as scoring every eligible family identity in numeric mask order. The conclusion holds for any positive batch size and any internal scoring order.*

Proof. Without exclusions, Lemma 11 gives the exact top-P of the input pool and all scored identities, independently of order and batching. For a candidate a omitted at some point, the valid bound gives

$$K(a) \le K^{+}(a) < K(\text{worst}(\mathcal{R})) \le K(b) \qquad (b \in \mathcal{R}). \tag{174}$$

The P distinct identities in $\mathcal{R}$ therefore all precede a in the total order. They belong to the full candidate union even if later evicted, so adding any remaining identities cannot place a in its top-P. This argument applies to every omitted candidate and, under Eq. (173), to the entire remaining set. Removing these identities leaves the full union's top-P unchanged. Lemma 11 then proves equality with complete numeric-mask enumeration. □

Strict inequality is essential when only score keys are bounded: a candidate whose upper key equals the cutoff may win through its canonical assignment and must be scored. A missing bound remains $+\infty$ until exact scoring or another valid eligibility test resolves that candidate; it prevents the global stopping test. Descending-bound order tends to raise the cutoff sooner but is not required for preservation. Any positive batch size is an execution parameter, not a premise of the proof; the reported query experiments use batches of at most 16 profiles. The static entry-cutoff plan is the special case that never tightens its cutoff. Where the native-profile score gate is disabled, exact scoring supplies the same result without this progressive filter.

Score exclusion never suppresses identity bookkeeping. Independently of which profiles are evaluated, form the same set of forecast-feasible canonical family identities and insert all of them into the seen set, including movement-ineligible and score-excluded identities. No next seed, selection query, or other consumer may inspect a provisional pool before family completion. Cache materialization and eviction may follow the scoring order, provided shared-query equivalence continues to hold.

10.3 Bootstrapping selective evaluation from an empty pool

The original full-bound-first bootstrap is also a valid plan when the input pool has fewer than P entries. Let $\mathcal{U}_0$ be the finite eligible family identities not already seen, and let $U(a) \ge K(a)$ be a valid optimistic key, with an unavailable bound represented by $+\infty$. Order $\mathcal{U}_0$ by decreasing $U(a)$, using a deterministic assignment or mask order to resolve scheduling ties. This order concerns acquisition only; final retention still uses the prescribed exact score and canonical-assignment order. Theorem 7 permits the movement-first exact pilot as an alternative without preacquiring every full-bound key.

Proposition 5 (Empty-pool bootstrap)**.** *Starting with any pool of size at most P, evaluate candidates exactly in optimistic order until the pool contains P distinct identities or the family is exhausted. Once the pool is full, prune only candidates whose optimistic key is strictly below its current worst exact key. This procedure returns the same final retained pool and seen set as canonical complete enumeration, including when the input pool is empty.*

Proof. Let $\mathcal{E}_t$ be the set of identities exactly evaluated through batch t and $\mathcal{R}_0$ the input pool. Before the first score exclusion, every eligible identity is either in $\mathcal{E}_t$ or remains pending. Top-P composition gives

$$\mathcal{R}_t = T_P(\mathcal{R}_0 \cup \mathcal{E}_t). \tag{175}$$

If the family is exhausted while $|\mathcal{R}_t| < P$, this already equals complete enumeration. Otherwise let t_0 be the first completed batch with $|\mathcal{R}_{t_0}| = P$. For every later batch define the exact cutoff $c_t = K(\text{worst}(\mathcal{R}_t))$. Since candidate union only grows, the cutoff cannot decrease:

$$c_{t+1} \geq c_t \qquad (t \geq t_0). \tag{176}$$

For any identity a excluded at time t, the test and the valid bound imply

$$K(a) \leq U(a) < c_t \leq K(b) \qquad \text{for every } b \in \mathcal{R}_t. \tag{177}$$

Thus P distinct identities in the complete candidate union precede a. No later evaluation can put a in that union's top-P. Removing every such identity therefore preserves the final pool by Proposition 4. An upper key equal to c_t is not excluded, so canonical-assignment ties are preserved. Identities with upper key $+\infty$ must be evaluated before the global stopping condition can hold. Finally, independently of profile acquisition, the seen set receives every forecast-feasible identity, including all movement and score rejections. Its final value is therefore the same as canonical enumeration. □

The proof permits any positive batch size. A batch can fill the pool past the first P evaluations without affecting correctness. Optimistic ordering can discover a useful cutoff earlier; it introduces no new statistical observation and makes no assumption about its correlation with the exact keys.

10.4 Deferred physical materialization

Proposition 6 (Deferred physical materialization)**.** *Suppose a complete family is processed before any next seed, selection, or release decision. Within that family, feasibility, score comparison, duplicate handling, and retention depend only on $s(a)$. Replacing rich intermediate records by their summaries and constructing $D(a)$ only for candidates in the final pool produces exactly the same complete-family output as constructing $D(a)$ at every intermediate insertion. At most P new physical matchings are needed for a pool of size P.*

Proof. Let π_s project a pool of rich records onto its summaries. Canonical assignment remains in the summary, so both score and final assignment ties have the same total order. If T_P denotes retaining the first P distinct records in that order, then

$$\pi_s(T_P(\mathcal{R} \cup \{r(a)\})) = T_P(\pi_s(\mathcal{R}) \cup \{s(a)\})\,. \tag{178}$$

To verify this identity, each record on either side has the same identity and comparison key, and T_P consults no component of D. Thus both select exactly the same candidate identities and stored summary fields. Eligibility and seen-set decisions also consult only the summary and canonical identity, so they agree before this insertion.

Induct over any chosen processing order, beginning from the common input pool and seen set. Equation (178) preserves the summary pool at every step relative to eager evaluation in that order; the preceding eligibility observation preserves the seen set. Lemma 11 and Proposition 4 show that the completed summary pool also equals that of full numeric-mask enumeration. A provisional entrant later evicted has no effect on the final pool and never needs $D(a)$. At the family boundary, apply the same deterministic map D to each retained summary missing its physical record. The completed rich records then equal those of eager enumeration, including matching ties and moved workload identities. Existing rich input records need no reconstruction. There are at most P retained candidates, proving the final bound. □

The implementation still forms a canonical assignment when an exact key can enter the pool or must resolve an assignment tie. Deferral removes the physical matching of transient entrants; it does not replace canonical assignment tie-breaking. For weighted movement, the secondary optimum can depend on workload identities beyond count signatures, so that path computes the complete matching before retention.

Theorem 8 (Complete-family semantics)**.** *Fix the source, numerical reduction program, balanced retention order, incumbent, family, input pool, and seen set. Count signatures, family-wide fixed-edge reduction, support-component factorization, exact two-column assignment replay, certified capacity and profile filters, compiled load-radius enclosures, aggregate/peak bounds, shared canonical views, exact pilot and progressive acquisition, and deferred physical materialization return the same final pool, seen set, and physical records as full canonical enumeration. Candidate scoring order and batch partition may differ. Under common completed-family operations, random draws, and cost feedback, successive completed-family states and the selected action also agree.*

Proof. Count signatures identify identical overlap objectives. Equation (27) preserves each objective after family-wide edge reduction, and Theorem 1 preserves it under component decomposition. The tight primal-dual invariant (44) proves that two-column replay returns the same residual optimum. Together these steps preserve each exact movement count; none substitutes its own tie matching for the final physical consumer. Capacity filtering rejects only masks whose canonical forecast violates the constraint. Shared views and the gain-circuit lemma preserve the exact stored profiles and keys of each scored candidate. Proposition 3 gives valid compiled load endpoints, and Theorem 6 gives valid aggregate/peak loss lower bounds. Every resulting score exclusion satisfies the strict domination condition in Proposition 4, using either the full pool's entry cutoff or its current cutoff. Theorem 7 preserves that condition under pilot acquisition and sampled execution-plan choices. These results and Lemma 11 preserve the final summary pool despite different scoring orders, batch partitions, or omitted profiles. Every forecast-feasible identity enters the seen set, regardless of movement or score rejection, so the final seen set is also identical. Proposition 6 restores precisely the same rich physical records at family completion. The next deterministic operation sees the same state; induction over completed-family operations gives the final assertion. □

CPU-limited executions may complete different families. The theorem concerns equivalence of the specified family query; measurements under a common time budget separately evaluate the additional search enabled by faster execution.

11 Historical admission and source-keyed replay

For one selected action and $n > 0$ audit rows, the exact mean gain of coordinate e is

$$\bar{g}_e = \frac{1}{n}\sum_{b=1}^{n}\big(\mathrm{dyad}(L_{be}(\pi^{\mathrm{I}})) - \mathrm{dyad}(L_{be}(\widehat{\pi}))\big), \tag{179}$$

where dyad interprets a finite stored binary64 value as its exact rational value. Admission requires all $\bar{g}_e \geq 0$ and at least one $\bar{g}_e > 0$. Every row retains its original multiplicity, including overlapping or repeated windows.

Lemma 12 (Integer dyadic census)**.** *Let an integer state (a, e) represent the accumulated value $a2^{-e}$. Initialize it at $(0, 0)$. For a signed operand $\sigma m 2^{-q}$, with $\sigma \in \{-1, 1\}$, update*

$$e' = \max(e, q), \qquad a' = a2^{e'-e} + \sigma m 2^{e'-q}. \tag{180}$$

Applying this update separately to each incumbent loss and its negative action loss yields the exact numerator total in Eq. (179)*. Its sign gives the same admission decision as exact rational averaging.*

Proof. Both exponents in Eq. (180) are nonnegative integers. Its represented value is

$$a'2^{-e'} = a2^{e'-e}2^{-e'} + \sigma m 2^{e'-q}2^{-e'} = a2^{-e} + \sigma m 2^{-q}. \tag{181}$$

Thus each update adds exactly the next signed operand. Induction over the $2n$ operands gives the exact coordinate total. Arbitrary-precision integer shifts and additions introduce no rounding. Division by the positive integer n preserves every sign, proving the gate equivalence. Processing the two stored losses separately also avoids rounding their difference before summation. □

11.1 Canonical source cells

Let the hourly source be $X \in \mathbb{F}_{64}^{N\times L}$, and let an audit window with start s_b contain $x_{bit} = X_{i,s_b+t}$. On the supported canonical resident fold, a host's stored load at absolute hour τ is determined solely by its ascending resident tuple and the operands $(X_{i\tau})_i$. Computing this fold once for every host-hour and retrieving it at all window occurrences therefore preserves every stored load. Direct window replay uses the same operands and fold at each occurrence. Unsupported numerical shapes use the prescribed reference reduction.

For the eight-hour excess projection, let $e_h(s)$ be a canonical stored cell excess, and define

$$\begin{aligned} R_2(s) &= \mathrm{RN}(e_h(s) + e_h(s+1)),\\ R_4(s) &= \mathrm{RN}(R_2(s) + R_2(s+2)),\\ R_8(s) &= \mathrm{RN}(R_4(s) + R_4(s+4)). \end{aligned} \tag{182}$$

Expanding $R_8(s)$ gives the prescribed balanced eight-leaf tree. A keyed plan evaluates each identical node once and reuses its stored result; a direct plan evaluates that same tree for each window. Both use the same strict overload predicates, exact integer occurrence counts, maxima, and canonical host assembly.

Lemma 13 (Historical query preservation)**.** *The keyed and direct plans described above return the same canonical historical profiles and dyadic census result, including unsorted or repeated window starts.*

Proof. Each requested window load has the same resident operands and reduction tree in both plans. Each stored excess cell and Boolean predicate therefore agrees. Equation (182) supplies identical time sums, while exact occurrence counts and maxima agree on the same cells. Final host projections receive these equal operands in canonical host order, preserving all ratios and idle sentinels. Unsorted starts change output positions only; repeated starts repeat the same values with their stated multiplicity. Substitution of identical stored profiles into Lemma 12 preserves the complete gate result. □

This is a census of a fixed finite table. Independence among its rows is unnecessary; claims about a fresh population use the separate sampling model below.

12 Action-footprint bounds for fixed-host indicators

The physical host matching is fixed before Certification. Let $M = \{i : \pi^{\mathrm{I}}(i) \neq \widehat{\pi}(i)\}$, let $A = \{\pi^{\mathrm{I}}(i), \widehat{\pi}(i) : i \in M\}$, and write $k = |A|$. Every host outside A has the same membership in both placements. Under paired canonical replay on the same scene and reduction shape, its stored loads and threshold bits are therefore identical. Let $q^I_{ht}, q^a_{ht} \in \{0, 1\}$ denote those bits.

Lemma 14 (Boolean footprint)**.** *The exact fixed-host ratios of canonical threshold bits satisfy $|G_V| \leq k/H$ and $|G_R| \leq k/H$. Occurrence satisfies $|G_J| \leq 1$. If $k = 0$, all four fresh paired gains vanish exactly.*

Proof. For duration, the unchanged hosts cancel and every remaining Boolean difference has magnitude at most one:

$$|G_R| = \frac{1}{HT}\left|\sum_{h\in A,t}(q^I_{ht} - q^a_{ht})\right| \tag{183}$$

$$\leq \frac{1}{HT}\sum_{h\in A,t}|q^I_{ht} - q^a_{ht}| \leq \frac{kT}{HT} = \frac{k}{H}. \tag{184}$$

Let $v^I_h = \max_t q^I_{ht}$ and $v^a_h = \max_t q^a_{ht}$. These bits also agree outside A, giving

$$|G_V| = \frac{1}{H}\left|\sum_{h\in A}(v^I_h - v^a_h)\right| \leq \frac{1}{H}\sum_{h\in A}|v^I_h - v^a_h| \leq \frac{k}{H}. \tag{185}$$

Occurrence is one Boolean value. When $k = 0$, every host membership and replay projection agrees, so every loss and paired gain agrees as well. □

The indicator ratios are stored after exact integer counting. Assume count accumulation does not overflow and $HT \leq 2^{53}$, so both normalization integers are represented exactly. Correct rounding of a ratio in $[0, 1]$ has absolute error at most $\epsilon = 2^{-53}$: adjacent binary64 numbers in this interval are at most 2^{-53} apart, and rounding chooses a nearest representable value. For stored $\widehat{V}^I, \widehat{V}^a$ and exact ratios V^I, V^a,

$$|\widehat{V}^I - \widehat{V}^a| \leq |V^I - V^a| + |\widehat{V}^I - V^I| + |\widehat{V}^a - V^a| \tag{186}$$

$$\leq k/H + 2\epsilon. \tag{187}$$

The same argument applies to R. Stored ratios remain in $[0,1]$, hence valid stored paired bounds are

$$B_J = 1, \qquad B_V = B_R = \mathrm{up}\big(\min\{1, k/H + 2^{-52}\}\big), \tag{188}$$

with all bounds zero for an unchanged action. Here up rounds outward to binary64. This argument uses equality of unchanged threshold bits, not real-arithmetic load conservation across potentially different summation trees. It therefore remains valid at floating-point capacity boundaries. It does not apply unchanged to native VR with placement-dependent active-host normalization.

13 Migration-graph bounds for uncapped excess

13.1 Count and topology

Assume $0 \le x_{it} \le b_i$ on every possible fresh scene, with all b_i declared before certification. At a fixed time, a moved workload forms an edge $i : s_i \to t_i$ from its old host to its matched destination. Its contribution to the real load change is $-x_i$ at s_i and $+x_i$ at t_i. Thus

$$d_h = \ell_h(\widehat{\pi}) - \ell_h(\pi^{\mathrm{I}}) = \sum_{i:t_i=h} x_i - \sum_{i:s_i=h} x_i, \qquad \sum_h d_h = 0. \tag{189}$$

Writing $W_x = \sum_{i\in M} x_i$, each positive change is at most the incoming moved demand at that host. Therefore

$$\sum_h [d_h]_+ \le W_x, \qquad \sum_h [-d_h]_+ = \sum_h [d_h]_+. \tag{190}$$

For $f(z) = [z/C - 1]_+$, monotonicity and $1/C$-Lipschitz continuity give

$$f(\ell_h + d_h) - f(\ell_h) \le [d_h]_+ / C. \tag{191}$$

Apply this inequality in both directions, sum hosts, and average times. If every $b_i \le d_{\max}$, then

$$|G_{u_H}| \le \frac{\sum_{i\in M} b_i}{HC} \le \frac{m d_{\max}}{HC}. \tag{192}$$

No factor two is needed: conservation equates total positive and total negative change, rather than adding both totals.

The count bound ignores edge destinations. Define the maximum incoming directed cut

$$D_* = \max_{S\subseteq[H]} \sum_{i:s_i\notin S,\ t_i\in S} b_i. \tag{193}$$

For any real vector d, a maximizing subset contains its positive entries and excludes its negative entries, so $\sum_h [d_h]_+ = \max_S \sum_{h\in S} d_h$. Edges internal to S cancel, yielding

$$\sum_h [d_h]_+ = \max_S \left(\sum_{i\in\partial^- S} x_i - \sum_{i\in\partial^+ S} x_i \right) \tag{194}$$

$$\le \max_S \sum_{i\in\partial^- S} b_i = D_*. \tag{195}$$

The support box is compact and the cut family is finite. Interchanging the two maxima and maximizing the fixed cut's linear expression gives

$$\max_{0\le x_i\le b_i} \sum_h [d_h(x)]_+ = \max_S \max_{0\le x_i\le b_i} \left(\sum_{i\in\partial^- S} x_i - \sum_{i\in\partial^+ S} x_i \right) \tag{196}$$

$$= \max_S \sum_{i\in\partial^- S} b_i = D_*. \tag{197}$$

The inner maximum sets entering demands to b_i and exiting demands to zero; internal demands have coefficient zero. Thus D_* is exactly the largest total positive load change over the support box. A correlated population whose support is a strict subset of that box still satisfies the bound but need not attain it.

Combining Eqs. (191) and (195), using $\sum_h [-d_h]_+ = \sum_h [d_h]_+$ for the reverse direction, and averaging times proves

$$|G_{u_H}| \le D_*/(HC) \le \sum_{i\in M} b_i/(HC) \le m d_{\max}/(HC). \tag{198}$$

Reversing every edge preserves D_*, because the entering cut of S in the reversed graph is the entering cut of S^c in the original graph. Consequently this two-sided envelope is symmetric in the placements, despite its directed definition.

13.2 Components and a scalable upper envelope

Ignore edge directions and zero-weight edges to obtain support components $\mathcal{C}_1, \dots, \mathcal{C}_q$. Every edge lies within one component. The sets $S \cap \mathcal{C}_j$ can be selected independently, so

$$D_* = \sum_{j=1}^{q} \max_{S_j \subseteq \mathcal{C}_j} \sum_{i: s_i \in \mathcal{C}_j \setminus S_j,\ t_i \in S_j} b_i. \tag{199}$$

A component with v vertices and e nonzero aggregate edges can be enumerated in $O(e2^v)$ arithmetic operations by checking its subsets. This exponential dependence is confined to small components; no polynomial-time exact directed-cut algorithm is claimed.

For a larger component aggregate parallel edges as $W_{hk} = \sum_{i: s_i = h, t_i = k} b_i$. A cut contains at most one direction of an unordered host pair, hence

$$D_* \le U_{\text{pair}} := \sum_{h<k} \max(W_{hk}, W_{kh}). \tag{200}$$

A second linear-time upper bound uses total weight $W = \sum_{h,k} W_{hk}$ and imbalance $\beta_h = \sum_k W_{kh} - \sum_k W_{hk}$. For a cut, let $a(S)$ be its entering weight and $b(S)$ its exiting weight. Then

$$a(S) + b(S) \le W, \qquad a(S) - b(S) = \sum_{h\in S} \beta_h. \tag{201}$$

Since $\sum_h \beta_h = 0$, positive and negative imbalance totals have equal magnitude, and

$$\sum_{h\in S} \beta_h \le \sum_h [\beta_h]_+ = \frac{1}{2} \sum_h |\beta_h|. \tag{202}$$

Adding the preceding two inequalities yields

$$D_* \le U_{\mathrm{bal}} := W/2 + \|\beta\|_1/4. \tag{203}$$

Let L be a common denominator of the rational aggregate weights. Every cut weight is an integer multiple of $1/L$, so $\lfloor LU_{\mathrm{bal}} \rfloor / L$ remains a valid upper bound. Use its minimum with U_{pair}. Summing exact small-component maxima and these large-component upper bounds gives a global $U(G) \ge D_*$. Both fallback quantities require $O(e+v)$ arithmetic operations per component. For a unit-weight directed cycle of length $2r+1$, Eq. (203) with lattice rounding gives r, while $U_{\mathrm{pair}} = 2r+1$.

13.3 Conserved capacity and tight examples

At one time let $y_h = \ell_h/C$, let $Q_0 = \sum_h y_h$ be the common normalized total demand, and define $s(y) = \sum_h \min(y_h, 1)$. Each summand is at most y_h and at most one, giving $s(y) \le \min(Q_0, H)$. If $Q_0 \le 1$, every $y_h \le 1$ and $s(y) = Q_0$. If $Q_0 > 1$, either some $y_h \ge 1$ or all are below one; these two cases give $s(y) \ge 1$ and $s(y) = Q_0 > 1$, respectively. Thus

$$\min(Q_0, 1) \le s(y) \le \min(Q_0, H). \tag{204}$$

The identity $[y_h - 1]_+ = y_h - \min(y_h, 1)$ gives $\sum_h [y_h - 1]_+ = Q_0 - s(y)$. Equal totals in the two placements therefore imply

$$\left| \frac{1}{H} \sum_h [y_h^a - 1]_+ - \frac{1}{H} \sum_h [y_h^I - 1]_+ \right| = |s(y^a) - s(y^I)|/H \tag{205}$$

$$\le \{\min(Q_0, H) - \min(Q_0, 1)\}/H \le (H-1)/H. \tag{206}$$

After averaging time, both physical envelopes hold simultaneously:

$$|G_{u_H}| \le B_{u_H}^{\mathrm{global}} := \min\{U(G)/(HC), (H-1)/H\}. \tag{207}$$

The fixed denominator H and conservation of every workload's demand are essential. This derivation does not replace H by a placement-dependent active-host count.

The graph envelope can be attained. Take $H = 2, C = 1$, incumbent groups $\{0,1,2\}, \{3,4,5\}$, candidate groups $\{0,1,3\}, \{2,4,5\}$, and one-time demands $(1/2, 0, 1/2, 0, 1/2, 1/2)$. Identity matching retains four workloads, while the exchanged matching retains two, so $m = 2$. With common support $b_i = 1/2$, the two edge directions each have weight $1/2$, hence $D_* = 1/2$. Loads change from $(1,1)$ to $(1/2, 3/2)$, attaining $|G_{u_H}| = 1/4 = D_*/(HC)$, half the count envelope.

The combined envelope with exact D_* is sharp as a function of D_*, H, C over the allowed support class. Fix $H \ge 2$ and any $D \ge 0$. Put one stationary workload of demand C at a hub and one stationary zero-demand anchor plus one moved workload at each of $H-1$ source hosts. Move every latter workload to the hub and give it support $D/(H-1)$. Each incumbent–candidate overlap is at most one; identity matching retains one workload at every host and therefore maximizes overlap, moving $H-1$ workloads. The graph is an inward star with $D_* = D$. For $D \le (H-1)C$, set each moved demand to $D/(H-1)$. Incumbent hosts do not overload, while candidate excess is D at the hub, giving $|G_{u_H}| = D/(HC)$. For $D \ge (H-1)C$, set each moved demand to C, which its support permits. Loads change from $(C, \ldots, C)$ to $(HC, 0, \ldots, 0)$, attaining $(H-1)/H$. Source groups remain nonempty because their anchors stay. These constructions prove sharpness over this class, rather than attainment for every fixed action or correlated workload law.

13.4 Component conservation and selective evidence

Let $\mathcal{C}$ be the connected components of the undirected support of the physical migration graph after zero-demand-bound edges have been removed. Every component $C \in \mathcal{C}$ contains at least two hosts. Write $v_C = |C|$, let D_C^* be its maximum incoming directed-cut weight, and let $\overline{D}_C \geq D_C^*$ be the corresponding computed upper bound. The fixed total number of physical hosts is H, and the common capacity is $c > 0$ in this subsection. The positive support convention permits a migration with bound $b_i = 0$ to be absent: its demand is zero almost surely and contributes no real load change.

Theorem 9 (Component-conservation support)**.** *For every scene whose workload demands satisfy the predeclared bounds, the real fixed-host excess gain satisfies*

$$|G_{u_H}| \leq B_{\text{comp}} := \frac{1}{H} \sum_{C \in \mathcal{C}} \min \left\{ \frac{\overline{D}_C}{c}, v_C - 1 \right\}. \tag{208}$$

In particular,

$$B_{\text{comp}} \leq \min \left\{ \frac{\sum_C \overline{D}_C}{Hc}, \frac{H-1}{H} \right\}. \tag{209}$$

If the canonical stored loss of each placement differs from its real loss by at most e_u, then $\text{up}(B_{\text{comp}} + 2e_u)$ *is a valid bound for the exact difference of the two stored losses.*

Proof. Fix one time index and one component C. Write ℓ_h^I and ℓ_h^a for incumbent and repaired real loads. A positive-demand migration cannot enter or leave C, since its two endpoints would then be in the same support component. Zero-bound migrations carry zero demand. Hence the total normalized demand

$$Q_C := \sum_{h \in C} \ell_h^I / c = \sum_{h \in C} \ell_h^a / c \tag{210}$$

is conserved within the component. No host-load feasibility or upper bound by capacity is assumed.

For nonnegative component loads $y = (y_h)_{h \in C}$ summing to Q_C, define $S(y) = \sum_{h \in C} \min(y_h, 1)$. Each term is at most both y_h and one, so $S(y) \leq \min(Q_C, v_C)$. If $Q_C \leq 1$, every $y_h \leq 1$ and $S(y) = Q_C$. If $Q_C > 1$, either some $y_h \geq 1$, which gives $S(y) \geq 1$, or all $y_h < 1$, which gives $S(y) = Q_C > 1$. Therefore

$$\min(Q_C, 1) \leq S(y) \leq \min(Q_C, v_C). \tag{211}$$

Since $[y_h - 1]_+ = y_h - \min(y_h, 1)$, the total component excess is $Q_C - S(y)$. Its change between the two placements obeys

$$\left| \sum_{h \in C} [\ell_h^a / c - 1]_+ - \sum_{h \in C} [\ell_h^I / c - 1]_+ \right| = |S(\ell^I / c) - S(\ell^a / c)| \tag{212}$$

$$\leq \min(Q_C, v_C) - \min(Q_C, 1) \tag{213}$$

$$\leq v_C - 1. \tag{214}$$

Independently, let $d_h = \ell_h^a - \ell_h^I$. Conservation gives $\sum_{h \in C} d_h = 0$, and the directed-cut identity

gives

$$\sum_{h\in C}[d_h]_+ = \max_{S\subseteq C}\sum_{h\in S} d_h \tag{215}$$

$$= \max_{S\subseteq C}\left(\sum_{i\in\partial^- S} x_i - \sum_{i\in\partial^+ S} x_i\right) \tag{216}$$

$$\le \max_{S\subseteq C}\sum_{i\in\partial^- S} b_i = D_C^* \le \overline{D}_C. \tag{217}$$

For the increasing $1/c$-Lipschitz function $f(z) = [z/c - 1]_+$,

$$f(\ell_h^I + d_h) - f(\ell_h^I) \le [d_h]_+/c. \tag{218}$$

Summing over C proves an upper change bound $\overline{D}_C/c$. Reversing the placements and using $\sum_h[-d_h]_+ = \sum_h[d_h]_+$ proves the same bound for the negative change. Combining this with (214) gives

$$\left|\sum_{h\in C} f(\ell_h^a) - \sum_{h\in C} f(\ell_h^I)\right| \le \min\{\overline{D}_C/c, v_C - 1\}. \tag{219}$$

Hosts outside the positive migration support have zero real load change. Summing the component absolute bounds and averaging over the H hosts and all time indices proves (208).

Every summand is at most $\overline{D}_C/c$, proving the first bound in (209). If there are $r \ge 1$ components touching $k \le H$ hosts, every summand is also at most $v_C - 1$, and

$$\sum_C (v_C - 1) = k - r \le H - 1. \tag{220}$$

If $r = 0$, the component sum is zero and the same conclusion holds. Finally, with stored losses $\widehat{u}^I, \widehat{u}^a$,

$$|\widehat{u}^I - \widehat{u}^a| \le |u^I - u^a| + |\widehat{u}^I - u^I| + |\widehat{u}^a - u^a| \tag{221}$$

$$\le B_{\text{comp}} + 2e_u. \tag{222}$$

Outward rounding preserves this inequality and proves the stored bound. □

The componentwise minimum matters. At capacity one, consider six hosts, two support components with $(v_C, \overline{D}_C) = (2, 10)$ and $(3, 1/2)$, and one unchanged host. The global bound is $\min(10.5/6, 5/6) = 5/6$, whereas (208) is $(1 + 1/2)/6 = 1/4$. Both component contributions can be attained simultaneously: keep a unit-demand workload at each component's hub, give each other host a stationary zero-demand anchor, move demand one from the first component's source to its hub, and move demand $1/4$ from each of the second component's two sources to its hub. All groups remain nonempty. The first component uses its conservation cap and the second uses its directed-cut cap; their excess changes have the same sign. Maximum-overlap matching retains the stationary anchors and both hubs, so the specified physical migrations are feasible under the unrestricted host matching model.

The new support is fixed after physical matching and before fresh evidence. It changes only the normalization of the same bounded-gain mixture and therefore retains the one-action false-admission guarantee. Through the normalized gap $\Delta_e/(B_e + |q_e|)$ it can improve the finite-sample evidence bound. It does not imply that every observed stopping time decreases: another coordinate can determine the joint crossing, and the wealth paths of two differently normalized bets need not be ordered.

14 A uniform allowance for stored excess replay

The preceding load conservation and graph arguments concern real arithmetic. The certificate consumes stored raw losses. Assume correctly rounded binary64 elementary operations, no intermediate overflow, a fixed positive binary64 capacity, and exactly represented normalization $Q = HT \le 2^{53}$. Let $\epsilon = 2^{-53}$ and $\zeta = 2^{-1075}$. A finite elementary result obeys

$$|\operatorname{fl}(z) - z| \le \epsilon|z| + \zeta. \tag{223}$$

The additive term covers subnormal results. Stored input demands are interpreted as exact dyadic operands satisfying the declared support.

For m nonnegative operands bounded by A, define

$$S(m, A) = \big((1+\epsilon)^{m-1} - 1\big)mA + \zeta(m-1)(1+\epsilon)^{m-1}. \tag{224}$$

To see why this covers any binary summation tree, write every rounded addition as its exact operand sum times $1+\delta$, $|\delta| \le \epsilon$, plus an additive error of magnitude at most ζ. On expanding the tree, each input is multiplied by at most $m-1$ factors. Its coefficient differs from one by at most $(1+\epsilon)^{m-1} - 1$. There are m inputs of magnitude at most A. Each of the $m-1$ additive errors is amplified by at most $(1+\epsilon)^{m-1}$. Summing their absolute contributions gives Eq. (224). In particular, $S(1, A) = 0$.

Let $D = d_{\max}$ bound every demand, let N bound a host's resident count, and put $A_0 = ND/C$. The following quantities bound the error after each stage:

$$e_\ell = S(N, D), \tag{225}$$
$$e_q = (1+\epsilon)e_\ell/C + \epsilon A_0 + \zeta, \tag{226}$$
$$e_f = (1+\epsilon)e_q + \epsilon(A_0 + 1) + \zeta, \tag{227}$$
$$e_\Sigma = Qe_f + S(Q, A_0 + e_f), \tag{228}$$
$$e_u = (1+\epsilon)e_\Sigma/Q + \epsilon A_0 + \zeta. \tag{229}$$

Equation (225) follows directly from the tree bound; using N rather than the actual resident count is conservative because all terms are nonnegative and the bound is nondecreasing in that count. For division, $|\widehat{\ell} - \ell| \le e_\ell$, $\ell/C \le A_0$, and

$$|\operatorname{fl}(\widehat{\ell}/C) - \ell/C| \le e_\ell/C + \epsilon|\widehat{\ell}/C| + \zeta \tag{230}$$
$$\le e_\ell/C + \epsilon(A_0 + e_\ell/C) + \zeta = e_q. \tag{231}$$

For subtraction of one, the exact intermediate ratio differs from its stored counterpart by at most e_q, while the magnitude of the latter minus one is at most $A_0 + e_q + 1$. Thus its rounded error is at most

$$e_q + \epsilon(A_0 + e_q + 1) + \zeta = e_f. \tag{232}$$

Clipping at zero is a 1-Lipschitz map and adds no error beyond selecting its already stored operand or exact zero, so the same e_f covers each stored excess.

There are Q nonnegative excess operands. Replacing exact excesses by stored ones contributes at most Qe_f. Each stored excess is at most $A_0 + e_f$, so summing them adds at most $S(Q, A_0 + e_f)$, proving Eq. (228). Finally the exact mean is at most A_0, and the same division argument gives

$$|\operatorname{fl}(\widehat{\Sigma}/Q) - \Sigma/Q| \le e_\Sigma/Q + \epsilon(A_0 + e_\Sigma/Q) + \zeta = e_u. \tag{233}$$

The uniform bounds on loads, ratios, and sums also provide a conservative check that these intermediate results remain finite. The derivation presupposes this nonoverflowing contract.

For the paired stored losses, the triangle inequality now yields

$$|\widehat{u}_H^I - \widehat{u}_H^a| \le |u_H^I - u_H^a| + |\widehat{u}_H^I - u_H^I| + |\widehat{u}_H^a - u_H^a| \tag{234}$$
$$\le B_{\mathrm{comp}} + 2e_u. \tag{235}$$

Consequently a valid predeclared stored bound is

$$B_{u_H} = \mathrm{up}(B_{\mathrm{comp}} + 2e_u)\,. \tag{236}$$

The replay allowance is added after summing the component physical bounds. The global-cap control instead substitutes $B_{u_H}^{\mathrm{global}}$ for B_{comp} and uses the same allowance. Both bounds concern exact differences of the canonical stored losses. All support-weight and cut comparisons may use exact rationals; only the final declared binary64 bound needs outward rounding.

15 Fresh expected-gain admission

15.1 Targets and bounded transformations

Let $B_e \ge 0$ be a predeclared almost-sure bound on the stored paired gain, and fix $0 < \alpha < 1$. The action-footprint bounds in Eqs. (188) and (236) supply such bounds for (J, V, R, u_H). Let r be the fixed strict-improvement anchor, let $\eta \ge 0$ be its required gain, and let $\delta_e \ge 0$ be the other coordinates' noninferiority margins. Set

$$q_e = \begin{cases} \eta, & e = r, \\ -\delta_e, & e \ne r, \end{cases} \qquad A_e = B_e + |q_e|, \qquad Y_{en} = \begin{cases} (G_e(Z_n) - q_e)/A_e, & A_e > 0, \\ 0, & A_e = 0. \end{cases} \tag{237}$$

The specified targets are $r = R$, $\eta = .005$, and $(\delta_J, \delta_V, \delta_R, \delta_{u_H}) = (.01, .01, 0, .001)$. These decimals denote exact rationals. Native VS and PAR remain evaluated outcome measures rather than coordinates of this four-loss certificate.

Because $|G_e| \le B_e$, we have $|G_e - q_e| \le B_e + |q_e|$ and hence $Y_{en} \in [-1, 1]$. If $A_e = 0$, both B_e and q_e are zero, so the gain is zero almost surely and the strict target cannot hold. Otherwise, under the conditional null $\mathbb{E}[G_e(Z_n) \mid \mathcal{F}_{n-1}] \le q_e$,

$$\mathbb{E}[Y_{en} \mid \mathcal{F}_{n-1}] = \frac{\mathbb{E}[G_e(Z_n) \mid \mathcal{F}_{n-1}] - q_e}{A_e} \le 0. \tag{238}$$

Conditional iid sampling is sufficient to obtain this null whenever the action's conditional mean gain is at most q_e. Mere temporal stationarity or a sample maximum is not a replacement for the conditional sampling and support assumptions.

15.2 A fixed mixture and a computable lower bound

For each fixed $0 < \lambda < 1$, define $W_{e,\lambda}(n) = \prod_{i=1}^{n}(1 + \lambda Y_{ei})$, with $W_{e,\lambda}(0) = 1$. Every factor lies in $[1 - \lambda, 1 + \lambda]$ and is positive. Under the conditional null,

$$\mathbb{E}[W_{e,\lambda}(n) \mid \mathcal{F}_{n-1}] = W_{e,\lambda}(n-1)\big(1 + \lambda \mathbb{E}[Y_{en} \mid \mathcal{F}_{n-1}]\big) \tag{239}$$
$$\le W_{e,\lambda}(n-1). \tag{240}$$

Thus each product is a nonnegative supermartingale. Use the fixed countable bets and weights

$$(w_0, \lambda_0) = (1/2, 255/256), \qquad (w_j, \lambda_j) = (2^{-j-1}, 2^{-j}) \quad (j \geq 1). \tag{241}$$

Their weights sum to one. At every finite n, each product is at most 2^n, so the mixture $E_e(n) = \sum_{j\geq 0} w_j W_{e,\lambda_j}(n)$ is integrable. Conditional monotone convergence gives

$$\mathbb{E}[E_e(n) \mid \mathcal{F}_{n-1}] = \sum_{j\geq 0} w_j \mathbb{E}[W_{e,\lambda_j}(n) \mid \mathcal{F}_{n-1}] \tag{242}$$

$$\leq \sum_{j\geq 0} w_j W_{e,\lambda_j}(n-1) = E_e(n-1). \tag{243}$$

Also $E_e(0) = 1$. Ville's inequality therefore gives the time-uniform bound

$$\mathbb{P}\left(\sup_n E_e(n) \geq 1/\alpha \mid \mathcal{F}_0\right) \leq \alpha. \tag{244}$$

These are standard bounded-mean betting and confidence-sequence tools [2, 3]; the action-specific supports enter through Eq. (237).

At prefix $n \geq 1$, materialize only components through $J(n) = \max\{8, \lfloor \log_2 n \rfloor + 1\}$ and compute

$$\underline{E}_e(n) = \sum_{j=0}^{J(n)} w_j W_{e,\lambda_j}(n) \leq E_e(n). \tag{245}$$

Every newly introduced component is evaluated on the entire observed prefix, as if present from time zero. The changing partial sum need not itself be a supermartingale; its pathwise domination by the fixed complete mixture is sufficient. A coordinate locks at its first inspected crossing of $1/\alpha$. Its computations may stop after locking because only its previously established crossing is used.

Theorem 10 (One-action false-admission control)**.** *Conditional on $\mathcal{F}_0$, suppose the action, targets, and valid gain supports are fixed, and fresh scenes are iid. If any required expected-gain target $\mathbb{E}[G_e \mid \mathcal{F}_0] > q_e$ is false, joint admission has probability at most α. Dependence across coordinates is unrestricted.*

Proof. For a false joint statement select one failing coordinate e_0 with $\mathbb{E}[G_{e_0} \mid \mathcal{F}_0] \leq q_{e_0}$. Conditional iid sampling makes its conditional mean at every step the same failing mean, so Eq. (244) applies. If $A_{e_0} = 0$, its transformed observations are zero and no partial mixture can exceed one; it cannot cause admission. Otherwise, joint admission implies that this coordinate crossed at some inspection, regardless of when other coordinates locked. Therefore

$$\mathbb{P}(\text{admit} \mid \mathcal{F}_0) \leq \mathbb{P}\left(\sup_n \underline{E}_{e_0}(n) \geq 1/\alpha \mid \mathcal{F}_0\right) \tag{246}$$

$$\leq \mathbb{P}\left(\sup_n E_{e_0}(n) \geq 1/\alpha \mid \mathcal{F}_0\right) \leq \alpha. \tag{247}$$

This is an intersection–union argument: one false coordinate suffices to bound the false joint statement. No independence across coordinates or Bonferroni allocation is required. Different crossing times and persistent locks do not change the implication. □

More generally, the same proof applies without iid scenes if a fixed failing coordinate satisfies $\mathbb{E}[G_e(Z_n) \mid \mathcal{F}_{n-1}] \leq q_e$ at every step. That statement concerns a conditional-mean null, not an arbitrary marginal-mean claim under dependence. Choosing the strict anchor or another action after observing Certification would require a different simultaneous-testing argument.

15.3 Consistency under strict alternatives

For $|x| \le \lambda < 1$, use the identity

$$\log(1+x) = x - \int_0^x \frac{s}{1+s}\, ds. \tag{248}$$

For $x \ge 0$, the integral is at most $x^2/[2(1-\lambda)]$ because $1+s \ge 1-\lambda$. For $x < 0$, substitute $s = -v$ to obtain $\int_0^x s/(1+s)\, ds = \int_0^{-x} v/(1-v)\, dv$, which has the same bound. Consequently, for $|y| \le 1$ and $0 < \lambda \le 1/2$,

$$\log(1+\lambda y) \ge \lambda y - \frac{\lambda^2 y^2}{2(1-\lambda)} \ge \lambda y - \lambda^2. \tag{249}$$

Suppose $\theta_e = \mathbb{E}[Y_{en} \mid \mathcal{F}_0] > 0$. Choose a fixed dyadic $0 < \lambda_j < \min\{\theta_e, 1/2\}$. Then

$$\mathbb{E}[\log(1+\lambda_j Y_{en}) \mid \mathcal{F}_0] \ge \lambda_j \theta_e - \lambda_j^2 > 0. \tag{250}$$

These iid log factors are bounded between $\log(1-\lambda_j)$ and $\log(1+\lambda_j)$. The strong law gives $n^{-1}\log W_{e,\lambda_j}(n) \to c_e > 0$ almost surely. Since $J(n) \to \infty$, that component is eventually materialized and

$$\underline{E}_e(n) \ge w_j W_{e,\lambda_j}(n) \longrightarrow \infty \tag{251}$$

almost surely. With finitely many coordinates, the intersection of these probability-one events still has probability one. Their finite crossing times have a finite maximum, so unbounded inspections eventually admit whenever all targets hold strictly.

A tied non-anchor with $\delta_e > 0$ has transformed mean $\delta_e/(B_e + \delta_e) > 0$ and is an interior alternative. A zero-margin true tie has no such consistency guarantee. A fixed finite bet grid bounded away from zero would not establish consistency for arbitrarily small positive transformed means.

15.4 Finite-sample evidence bound

Let d be the number of required coordinates, let $\mu_e = \mathbb{E}[G_e \mid \mathcal{F}_0]$, and suppose every gap $\Delta_e = \mu_e - q_e$ is positive. Define

$$\theta_e = \frac{\Delta_e}{B_e + |q_e|}, \qquad \rho = \min_e \theta_e \in (0,1]. \tag{252}$$

All denominators are positive under this strict alternative. The unknown ρ is used only to analyze power, not to choose a bet or a target. For $0 < \beta < 1$, let

$$n_\beta(\rho) = \left\lceil \max\left\{ \frac{2}{\rho}, \frac{32}{\rho^2}\log\frac{d}{\beta}, \frac{8}{\rho^2}\log\frac{8}{\alpha\rho} \right\} \right\rceil. \tag{253}$$

At every deterministic inspected prefix $n \ge n_\beta(\rho)$, admission has occurred by that inspection with probability at least $1-\beta$.

To prove this statement, choose a dyadic $\lambda_j \in [\rho/4, \rho/2]$. Such a component exists because adjacent dyadic bets differ by a factor of two. It has $j \ge 1$ and $w_j = \lambda_j/2 \ge \rho/8$. Since $2^{j-1} \le 2/\rho \le n$, it is included among components through $J(n)$.

Let $S_e(n) = \sum_{i=1}^n Y_{ei}$. Hoeffding's inequality for independent bounded variables with range length two [1] gives

$$\mathbb{P}\{S_e(n) < n\theta_e - a \mid \mathcal{F}_0\} \le \exp\left(-\frac{2a^2}{\sum_{i=1}^n (1-(-1))^2}\right) \tag{254}$$

$$= \exp(-a^2/(2n)). \tag{255}$$

Set $L_0 = \log(d/\beta)$ and $a = \sqrt{2nL_0}$. A union bound over the d coordinates gives, with probability at least $1 - \beta$,

$$S_e(n) \geq n\theta_e - \sqrt{2nL_0} \geq n\rho - \sqrt{2nL_0} \quad \text{for every } e. \tag{256}$$

The condition $n \geq 32L_0/\rho^2$ implies $\sqrt{2nL_0} \leq n\rho/4$. On this event, Eq. (249) yields

$$\begin{aligned} \log W_{e,\lambda_j}(n) &\geq \lambda_j S_e(n) - n\lambda_j^2 && (257)\\ &\geq n\lambda_j(3\rho/4 - \lambda_j) && (258)\\ &= n\left(\rho^2/8 + (\lambda_j - \rho/4)(\rho/2 - \lambda_j)\right) && (259)\\ &\geq n\rho^2/8. && (260) \end{aligned}$$

Both factors in the product are nonnegative. Hence every still-unlocked coordinate satisfies

$$\underline{E}_e(n) \geq w_j W_{e,\lambda_j}(n) \geq (\rho/8)\exp(n\rho^2/8) \geq 1/\alpha, \tag{261}$$

where the last step uses $n \geq 8\rho^{-2}\log(8/(\alpha\rho))$. Coordinates locked earlier already satisfy admission. This proves the stated power bound.

For fixed inspection batch size b and deterministic cap $c \geq n_\beta(\rho)$, the next inspection is $n_b = \min\{b\lceil n_\beta(\rho)/b\rceil, c\}$, so $n_\beta(\rho) \leq n_b < n_\beta(\rho) + b$. Thus admission by n_b has probability at least $1-\beta$. This fixed-time concentration argument does not assert the same power bound for a data-dependent next inspection. False-admission validity still holds for adaptive inspection by the time-uniform mixture argument.

The support dependence is explicit:

$$\rho^{-2} = \max_e \frac{(B_e + |q_e|)^2}{\Delta_e^2}, \qquad n_\beta(\rho) = O\left(\rho^{-2}\log\frac{d}{\alpha\beta\rho}\right). \tag{262}$$

The footprint and graph envelopes reduce these sufficient normalized-gap requirements without changing the action or target. Another coordinate can still determine the maximum. The bound does not imply monotonic stopping on every realized sample path, or that fewer migrations necessarily produce a larger gain.

16 Streaming paired workload queries

A paired reader exposes one predeclared consecutive scene stream. Every scene is generated independently under the declared conditional law. A fixed role-specific random stream makes the scene prefix invariant to the partition of requests. Fit, Build, Selection, Certification, and Evaluation use distinct streams. Any declared demand clipping is part of this population law and therefore precedes replay.

For a fixed replay batch shape, the reader constructs both placements from the same scenes, optionally sharing membership views within that panel. A short tail is padded to the same numerical shape and only its requested rows are returned. Consequently the stored paired loss for each scene uses the same per-scene computation under stopped and fixed-cap acquisition. The registry cannot be shared across different scene panels because its input data have changed.

The stopped certificate requests a batch only when earlier evidence has not completed the joint decision. Every such request and the decision to stop are measurable with respect to the already observed filtration. They therefore retain the supermartingale validity above. A fixed-cap rule can acquire the identical replay-batch sequence but inspect its mixture only at the cap. The two rules differ in inspection schedule, not in action, targets, scene law, or numerical definition of a row.

If stopping occurs after n_s scenes in replay batches of size b, exactly $\lceil n_s/b \rceil$ batches are generated and paired-replayed. No later scenes are acquired. Scene generation produces $n_s NT$ demand values, while a fixed cap c produces cNT. Peak scene-panel storage is $O(bNT)$ rather than $O(cNT)$, separately from stored evidence rows, mixture arithmetic, and query views. The statistical procedure is also valid on precomputed loss arrays, but only on-demand acquisition realizes these generation and replay savings. End-to-end timing consequently includes reader work and exact statistical arithmetic; action-bound construction is accounted for separately.

17 Exact numerical evaluation of the certificate

17.1 Exact crossing arithmetic

Write the transformed observations as exact rationals $Y_i = z_i/d_i$, $d_i > 0$, and let $D_n = \prod_{i=1}^{n} d_i$. Then

$$W_0(n) = N_0(n)/(D_n 2^{8n}), \qquad N_0(n) = \prod_{i=1}^{n} (256 d_i + 255 z_i), \tag{263}$$

$$W_j(n) = N_j(n)/(D_n 2^{jn}), \qquad N_j(n) = \prod_{i=1}^{n} (2^j d_i + z_i). \tag{264}$$

Set $\kappa_n = \max\{8n+1, J(n)n + J(n) + 1\}$. Including the mixture weights gives the common integer numerator

$$\mathcal{N}_n = N_0(n) 2^{\kappa_n - 8n - 1} + \sum_{j=1}^{J(n)} N_j(n) 2^{\kappa_n - jn - j - 1}, \qquad \underline{E}(n) = \mathcal{N}_n/(D_n 2^{\kappa_n}). \tag{265}$$

All exponents are nonnegative. For exact $\alpha = p/q$, the crossing test is the integer comparison $p\mathcal{N}_n \geq q D_n 2^{\kappa_n}$. Arbitrary-precision products and shifts decide it without approximate log wealth. Balanced product trees change evaluation cost but not this exact integer value.

17.2 Gain and normalized-observation intervals

A paired query returns intervals $[g_i^-, g_i^+]$ containing the exact dyadic differences of the canonical stored losses. Complete canonical replay obtains such an interval by outward subtraction; a shared or enclosed query may provide it directly. The predeclared population bound gives the additional valid interval $[-B, B]$. Their intersection still contains the gain.

For target q and scale $A = B + |q| > 0$, let $q^- \leq q \leq q^+$ and $0 < A^- \leq A \leq A^+$ be outward endpoints. If

$$n^- = \mathrm{RD}(g_i^- - q^+), \qquad n^+ = \mathrm{RU}(g_i^+ - q^-), \tag{266}$$

then $n^- \leq G_i - q \leq n^+$. The normalized endpoints are

$$y_i^- = \mathrm{RD}\left(\frac{n^-}{A^+ \mathbf{1}\{n^- \geq 0\} + A^- \mathbf{1}\{n^- < 0\}} \right),$$
$$y_i^+ = \mathrm{RU}\left(\frac{n^+}{A^- \mathbf{1}\{n^+ > 0\} + A^+ \mathbf{1}\{n^+ \leq 0\}} \right). \tag{267}$$

For a negative numerator, division by a smaller positive denominator is more negative; the other signs follow similarly. Hence $y_i^- \leq Y_i \leq y_i^+$. Intersecting with $[-1, 1]$ is valid. If no positive finite lower scale endpoint exists, exact rational normalization precedes outward conversion. If $A = 0$, the canonical observation is zero.

17.3 Positive-product filtering

For a fixed represented rate $0 < \lambda < 1$, monotonicity gives

$$0 < 1 + \lambda y_i^- \le 1 + \lambda Y_i \le 1 + \lambda y_i^+. \tag{268}$$

Outward addition and multiplication produce factor endpoints. Inductively multiplying their positive intervals from $[1, 1]$ encloses every partial product. Underflow uses zero as a lower endpoint and an outward positive upper endpoint; unresolved overflow requests exact refinement. Positive weighted addition gives

$$L_n \le \underline{E}(n) \le U_n. \tag{269}$$

Every newly introduced mixture component replays its complete observed prefix. A weight too small for the endpoint format is omitted only from the lower sum; its unresolved upper contribution forces refinement unless the lower sum already proves crossing.

Write $\alpha = p/q$ exactly. If $pL_n \ge q$, the canonical partial mixture crosses; if $pU_n < q$, it does not. These endpoint comparisons use exact rational values. Otherwise the integer computation above resolves the same comparison, including equality. Thus the filter adds no statistical error term.

Theorem 11 (Inspected-decision preservation)**.** *Suppose each query interval contains its canonical stored paired gain and every ambiguous comparison uses the same immutable scene prefix for exact refinement. The filtered and exact certificates have identical coordinate crossings, locks, stopping row, and released action.*

Proof. Equation (267) contains each exact normalized observation. Positive interval multiplication and addition give Eq. (269); separated comparisons therefore equal the exact threshold bit, and ambiguous comparisons explicitly compute that bit. Initially the two executions have identical action, stream position, and locks. If these states agree before an inspection, they acquire the same next scene indices and produce the same crossing bit for every unlocked coordinate. Their locks and stopping decisions then agree. Induction over inspections proves the entire trajectory. A replayed prefix is a numerical reconstruction of previously acquired scenes and contributes no additional inferential observations. □

17.4 Preserving the action-support calculation

The raw support calculation contains the exact nonnegative expression $2e_u$ and the rational component support $p = B_{\text{comp}}$. Its stored output is defined by

$$b_{\text{err}} = \text{nextUp}(\text{RN}(2e_u)), \qquad B_u = \text{nextUp}(\text{RN}(p + \text{dyad}(b_{\text{err}}))). \tag{270}$$

Directed interval evaluation of the additions, products, divisions, and integer powers in e_u yields $L \le 2e_u \le U$. For integer powers, repeated squaring of positive intervals encloses the exact power by induction. If $\text{RN}(L) = \text{RN}(U) = v$, monotonicity of rounding proves $\text{RN}(2e_u) = v$. Apply the two rounding stages in Eq. (270) unchanged. If endpoint roundings disagree, increase precision or evaluate the exact rational expression. This construction preserves the normalized evidence itself, as well as its validity; finite-range guards are resolved by the same interval separation or exact comparison.

18 Enclosed paired views

The primary paired reader performs canonical replay with shared complete resident groups. A compared plan also shares nonempty incumbent–candidate intersections. This section gives the latter's numerical enclosure without changing the canonical target.

18.1 Intersection fragments

For incumbent groups $I_1, \dots, I_H$ and physically aligned action groups $A_1, \dots, A_H$, let $F_{hk} = I_h \cap A_k$ and let $\mathcal{G}$ contain the nonempty fragments. Each resident belongs to exactly one fragment. With $E = |\mathcal{G}|$ and m migrants, $H \le E \le N$ and $E - H \le m$: every host has an incident fragment, at most H fragments are diagonal, and each off-diagonal fragment contains a migrant.

Reduce each fragment's resident demands to a stored sum, then combine its incident fragments to obtain each old or new host center z_h. Let r_h be that host's resident count and let D bound every input demand. With the tree allowance S in Eq. (224),

$$|z_h - \ell_h| \le S(r_h, D), \qquad |z_h - \widehat{\ell}_h^{\mathrm{can}}| \le 2S(r_h, D) =: \rho_h. \tag{271}$$

To prove the first inequality, expand a fixed host root into its fragment trees. Its fragments are disjoint and partition exactly that host's residents, so the expanded expression is a binary positive summation tree with r_h leaves, each appearing once. Sharing a fragment with the other placement creates no duplicate path to this fixed root. Equation (224) applies. The canonical load is a second tree over the same leaves; the triangle inequality proves the second inequality.

For efficient outward evaluation, one may replace $(1+u)^{r-1}$ in S by the larger rational $(1-(r-1)u)^{-1}$ whenever $(r-1)u < 1$. Indeed the binomial coefficient of u^k is at most $(r-1)^k$, so the finite binomial sum is bounded by the positive geometric series. This yields a conservative geometric tree allowance. Any finite outward enlargement of a numerical radius preserves its enclosure.

Each primitive demand contributes once to a fragment. The old and new host roots require $2(E - H)$ further additions, because their respective positive fragment degrees each sum to E. These root operations and projection work are additional to the N primitive demand contributions; a smaller contribution count alone does not establish a lower total running time.

18.2 Canonical loss enclosures

Clip each center to nonnegative values, which cannot increase its distance from the nonnegative canonical load. Equation (271) gives load endpoints. Strict threshold predicates evaluated at their lower and upper endpoints bound the canonical bits, and monotone integer sums and positive fixed normalization bound the occurrence, host-fraction, and duration losses.

For raw excess, let K denote canonical loads and Z the centers. Let U bound both arrays, computed from $r_h D + S(r_h, D) + \rho_h$, and put $Q = HT$, $A = U/C$, $u = 2^{-53}$, and $\zeta = 2^{-1075}$. Define

$$\begin{aligned} e_q &= uA + \zeta, \\ e_f &= (1+u)e_q + u(A+1) + \zeta, \\ e_\Sigma &= Qe_f + S(Q, A + e_f), \\ e_P(U) &= (1+u)e_\Sigma/Q + uA + \zeta. \end{aligned} \tag{272}$$

These are the capacity-division, subtraction-and-clipping, positive-sum, and final-mean bounds already derived for stored excess, now applied to a supplied load array. Thus every supported projection tree F differs from its exact-real counterpart P by at most $e_P(U)$. Since the excess map is $1/C$-Lipschitz,

$$|P(K) - P(Z)| \le \frac{1}{HTC} \sum_{h,t} |K_{ht} - Z_{ht}| \le \frac{1}{HC} \sum_h \rho_h. \tag{273}$$

Consequently, even when the two projection trees differ,

$$|F_{\mathrm{can}}(K) - F_{\mathrm{ctr}}(Z)| \le \frac{1}{HC} \sum_h \rho_h + 2e_P(U). \tag{274}$$

Outward conversion and paired subtraction of the two placement intervals enclose the exact canonical gain.

18.3 Late normalization

A center projection may sum load-unit excess before dividing by capacity. Put $V = [U - C]_+$ and

$$\begin{aligned} \eta_f &= uV + \zeta, \qquad E_\Sigma = Q\eta_f + S(Q, V + \eta_f), \\ E_a &= (1+u)E_\Sigma/Q + uV + \zeta, \\ E_{\text{late}} &= (1+u)E_a/C + uV/C + \zeta. \end{aligned} \tag{275}$$

For $z \geq 0$, clipping commutes with rounding of $z - C$: both $\max\{\mathrm{RN}(z-C), 0\}$ and $\mathrm{RN}([z-C]_+)$ are zero if $z \leq C$, and coincide otherwise. Each stored clipped term therefore differs from $[z-C]_+$ by at most η_f. The same positive-tree argument bounds the sum error by E_Σ. Dividing first by Q gives error E_a, and subsequently dividing by C gives error E_{late}. The exact-real target is

$$P(Z) = \frac{1}{Q}\sum_{h,t}[Z_{ht}/C - 1]_+ = \frac{1}{QC}\sum_{h,t}[Z_{ht} - C]_+. \tag{276}$$

Combining this with the canonical projection error gives

$$|F_{\text{can}}(K) - F_{\text{late}}(Z)| \leq \frac{1}{HC}\sum_h \rho_h + e_P(U) + E_{\text{late}}. \tag{277}$$

All intermediate values and outward bounds must be finite. A failed range guard invokes canonical replay. Theorem 11 then preserves every inspected decision for either center consumer.

18.4 Exact ordered prefixes

When a canonical resident reduction is an ordered linear fold, identical ordered resident prefixes can share their stored partial sum exactly. Assign a symbolic state to each full ordered prefix. Two next additions are shared only when they have the same prefix state and current resident identity. Induction over resident order gives equal stored parent accumulators, equal operands, and equal next additions. Different histories are never merged merely because their numerical values coincide. After the loads, retaining the prescribed Boolean and excess projection trees yields identical canonical losses. A shape outside this fold contract uses the reference computation. In particular, sharing a complete group or a prefix does not justify reassociating the canonical sum.

19 A local-migration counterexample to subtract-and-add replay

The difference between canonical replay and a delta update can occur for one physical migration on the same nonnegative demand vector. It does not require comparing unrelated summation examples. Take a power-of-two capacity C in the normal binary64 range, with no overflow or underflow in the following operations, and let $a = C2^{-53}$. The incumbent memberships are $I_0 = (0, 1, 2, 3)$ and $I_1 = (4)$, with demands

$$(x_0, x_1, x_2, x_3, x_4) = (C, a, a, C, 0). \tag{278}$$

Move VM 0 from host 0 to host 1. The new nonempty memberships are $A_0 = (1, 2, 3)$ and $A_1 = (0, 4)$; maximum-overlap matching preserves these physical labels, retaining four VMs and moving one. Under ascending-resident replay, round-to-nearest with ties to even gives

$$\widehat{\ell}_0^{\,I} = \mathrm{fl}(\mathrm{fl}(\mathrm{fl}(C + a) + a) + C) = 2C, \tag{279}$$

$$\widehat{\ell}_0^{\,a} = \mathrm{fl}(\mathrm{fl}(a + a) + C) = C + C2^{-52}, \tag{280}$$

$$\widetilde{\ell}_0^{\,a} = \mathrm{fl}(\widehat{\ell}_0^{\,I} - C) = C. \tag{281}$$

Here $C + a$ is halfway between C and its successor, so it rounds to C. The sum $a + a = C2^{-52}$ is exact, and $C + C2^{-52}$ is exactly the successor of C. Both plans give load C on host 1, but the strict overload bit on host 0 is one under canonical replay and zero under the delta update. Thus a physically valid single-VM departure can change native VR from $1/2$ to zero solely by changing the numerical execution; the canonical fixed-host excess is 2^{-53} while its delta-replayed value is zero. The example demonstrates why a signed load update requires an enclosure or an exact canonical reconstruction at strict capacity boundaries.

References

[1] W. Hoeffding, "Probability inequalities for sums of bounded random variables," *Journal of the American Statistical Association*, vol. 58, no. 301, pp. 13–30, 1963. doi: 10.1080/01621459.1963.10500830.

[2] S. R. Howard, A. Ramdas, J. McAuliffe, and J. Sekhon, "Time-uniform, nonparametric, nonasymptotic confidence sequences," *The Annals of Statistics*, vol. 49, no. 2, pp. 1055–1080, 2021. doi: 10.1214/20-AOS1991.

[3] I. Waudby-Smith and A. Ramdas, "Estimating means of bounded random variables by betting," *Journal of the Royal Statistical Society Series B: Statistical Methodology*, vol. 86, no. 1, pp. 1–27, 2024. doi: 10.1093/jrsssb/qkad009.

[4] G. A. Mills-Tettey, A. Stentz, and M. B. Dias, "The dynamic Hungarian algorithm for the assignment problem with changing costs," Robotics Institute, Carnegie Mellon University, Tech. Rep. CMU-RI-TR-07-27, July 2007.

[5] V. Korenwein, A. Nichterlein, R. Niedermeier, and P. Zschoche, "Data reduction for maximum matching on real-world graphs: Theory and experiments," in *26th Annual European Symposium on Algorithms*, LIPIcs, vol. 112, pp. 53:1–53:13, 2018. doi: 10.4230/LIPIcs.ESA.2018.53.

[6] K. Morita, S. Shiroshita, Y. Yamaguchi, and Y. Yokoi, "Fast primal-dual update against local weight update in linear assignment problem and its application," *Information Processing Letters*, vol. 183, article 106432, 2024. doi: 10.1016/j.ipl.2023.106432.

[7] E. Großmann, F. Joos, H. Reinstädtler, and C. Schulz, "Engineering hypergraph b-matching algorithms," *Journal of Graph Algorithms and Applications*, vol. 30, no. 1, pp. 1–24, 2026. doi: 10.7155/jgaa.v30i1.3166.