Initial Parameter Constraints

10/27/2026

Basic Generation Settings (note strict and not strict inequalities):

- prompt: string. minLength = 1, maxLength=2000
- max_new_tokens: Integer. $1 \leq max_new_tokens \leq 100$. Default value =50.
- do_sample: Boolean. Default = False.
- temperature: float. $0 < temp \leq 10$. Default=0.8.
- top_k: integer. $0 \leq top_k \leq 100$. Default=50.
- top_p: float. $0 \leq top_p \leq 1$. Default=0.95.
- repetition_penalty: float. $0 < repetition_penalty \leq 50$. Default: 1.1.
- enable_thinking: boolean. Default = False.

The following are only relevant if the user chooses an intervention, which is optional. Currently we have 2 types of interventions: mlp or attention. For now, the backend allows selection of either one or the other.

MLPInterventionSettings:

- layers: list. The list must at least have one element, and each element must be an integer between 0 and 27. So [] is not valid. $[0]$ is valid. $[0, 1, 7, 27]$ is also valid. But $[0, 1, 28]$ is not valid.
- proportion: float. $0 \leq proportion \leq 1$. Default=0.25.

- seed: integer. Default = 42. No constraints other than the fact it needs to be an integer.

AttentionInterventionSettings:

- layers: Same constraints as for MLPInterventionSettings.
- head_idxs: List. The list must at least have one element, and each element must be an integer between 0 and 15. So [] is not valid. $[0]$ is valid. $[0, 1, 7, 15]$ is also valid. But $[0, 1, 16]$ is not valid.