

Data Structures and Algorithms

Live Class 5

Heikki Peura

h.peura@imperial.ac.uk



Announcements

Homework 1 deadline tomorrow:

- ▶ Your functions should almost always return rather than print.
- ▶ Make sure not to print anything unless explicitly requested.

I will post a **mock exam** next week

Today

1. Recap
2. Sorting algorithms:
 - ▶ Selection sort
 - ▶ Merge sort

Go to [menti.com](https://www.menti.com)

What is the output?

```
1 a = 'hiphop'
2 b = a[2]
3 c = a[:len(a) - 1]
4 print(b, c)
```

- A. i hipho
- B. p hipho
- C. i hiph
- D. p hiph
- E. I don't know

What is the output?

```
1 a = 'hip'
2 for i in range(1, len(a)):
3     print(a[i] + a[i - 1])
```

- A. An error
- B. hp, ih, pi
- C. ih, pi
- D. hi, ip
- E. I don't know

This algorithm is...?

```
1 def fun_function(s):  
2     # s is a list of length n  
3     new_list = []  
4     for v1 in s:  
5         for v2 in s:  
6             new_list.append(v1 + v2)  
7     return new_list
```

- A. Constant time - $O(1)$
- B. Linear time - $O(n)$
- C. Quadratic time - $O(n^2)$
- D. None of the above
- E. I don't know

Which of these reverses the string?

A:

```
1 s = 'hiphop'
2 new_s = s[0:len(s):1]
```

B:

```
s = 'hiphop'
new_s = s[::-1]
```

C:

```
1 s = 'hiphop'
2 new_s = ''
3 for char in s:
4     new_s = new_s + char
```

D:

```
s = 'hiphop'
new_s = ''
for i in range(len(s)):
    new_s += s[len(s) - i - 1]
```


E: More than one of the above

Asymptotic analysis

- 1: measure number of basic operations as function of input size
- 2: focus on worst-case analysis
- 3: ignore constant factors and lower-order terms
- 4: only care about large inputs

Formal way to describe this approach:

- ▶ Big-O notation: upper bound on worst-case running time



Big O: for **large enough inputs**, an $O(n)$ algorithm will be slower than $O(\log(n))$

Basic operations

Operations that a **computer can perform “quickly”** (constant time $O(1)$ for any input)

- ▶ Arithmetic operations
- ▶ Comparisons
- ▶ Variable assignment
- ▶ Memory access

Basic operations

Operations that a **computer can perform “quickly”** (constant time $O(1)$ for any input)

- ▶ Arithmetic operations
- ▶ Comparisons
- ▶ Variable assignment
- ▶ Memory access

What if the data structure is more complicated?

- ▶ For example, if `L` is a list: `L.append()`, `L[5]` ?
- ▶ Are these basic constant-time operations?
- ▶ Wait for it... assume for now that list operations are constant time

Complexity classes

Fast algorithm: worst-case running time grows slowly with input size

- ▶ $O(1)$: constant running time — basic operations
- ▶ $O(\log n)$: logarithmic running time — binary search
- ▶ $O(n)$: linear running time — linear search
- ▶ $O(n \log n)$: log-linear running time — ??
- ▶ $O(n^c)$: polynomial running time — ??
- ▶ $O(c^n)$: exponential running time — ??

Sorting algorithms

So if we have an unsorted list, should we sort it first?

- ▶ Suppose complexity $O(\text{sort}(n))$
- ▶ Is it less work to sort and then do binary search than to do linear search?
- ▶ Is $\text{sort}(n) + \log(n) < n$?
- ▶ No...

But what if we need to search repeatedly, say k times?

- ▶ Is $\text{sort}(n) + k \log(n) < kn$?
- ▶ Depends on k ...

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
9	24	99	32	56	61	57	79

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

9	24	99	32	56	61	57	79
---	----	----	----	----	----	----	----

9	24	99	32	56	61	57	79
---	----	----	----	----	----	----	----

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
9	24	99	32	56	61	57	79
9	24	99	32	56	61	57	79
9	24	32	99	56	61	57	79

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
9	24	99	32	56	61	57	79
9	24	99	32	56	61	57	79
9	24	32	99	56	61	57	79
9	24	32	56	99	61	57	79

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
9	24	99	32	56	61	57	79
9	24	99	32	56	61	57	79
9	24	32	99	56	61	57	79
9	24	32	56	99	61	57	79
9	24	32	56	57	61	99	79

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
9	24	99	32	56	61	57	79
9	24	99	32	56	61	57	79
9	24	32	99	56	61	57	79
9	24	32	56	99	61	57	79
9	24	32	56	57	99	61	79
9	24	32	56	57	61	99	79

How would you intuitively sort a list?

56	24	99	32	9	61	57	79
9	24	99	32	56	61	57	79
9	24	99	32	56	61	57	79
9	24	32	99	56	61	57	79
9	24	32	56	99	61	57	79
9	24	32	56	57	99	61	79
9	24	32	56	57	61	99	79
9	24	32	56	57	61	79	99

How would you intuitively sort a list?

56	24	99	32	9	61	57	79	n-1
9	24	99	32	56	61	57	79	n-2
9	24	99	32	56	61	57	79	n-3
9	24	32	99	56	61	57	79	...
9	24	32	56	99	61	57	79	
9	24	32	56	57	61	99	79	2
9	24	32	56	57	61	99	79	1
9	24	32	56	57	61	79	99	

In words: Find smallest item and move to front (swap with first unsorted item). Repeat with remaining unsorted items.

$$n-1+n-2+\dots+2+1 = n(n-1)/2 \text{ comparisons} \rightarrow O(n^2)$$

Selection sort algorithm

Selection sort list L of length n :

Selection sort algorithm

Selection sort list L of length n :

- ▶ Repeat n times:
 - ▶ Find smallest unsorted element
 - ▶ Swap its position with the first unsorted element

Selection sort algorithm

Selection sort list L of length n :

- ▶ Repeat n times:
 - ▶ Find smallest unsorted element
 - ▶ Swap its position with the first unsorted element

Python:

```
1 def selection_sort(L):
2     M = L[:] # make a copy to preserve original list
3     n = len(M)
4     for index in range(n):
5         min_index = find_min_index(M, index) # index with smallest element
6         M[index], M[min_index] = M[min_index], M[index] # swap positions
7     return M
```

Selection sort complexity

Correctness (for those into math): can be proved by induction

Selection sort complexity

Correctness (for those into math): can be proved by induction

Complexity:

- ▶ $O(n)$ passes of main loop
- ▶ Each pass: search for the smallest element in $O(n)$
- ▶ Total $O(n^2)$

Selection sort complexity

Correctness (for those into math): can be proved by induction

Complexity:

- ▶ $O(n)$ passes of main loop
- ▶ Each pass: search for the smallest element in $O(n)$
- ▶ Total $O(n^2)$

Can we do better?

Selection sort complexity

Correctness (for those into math): can be proved by induction

Complexity:

- ▶ $O(n)$ passes of main loop
- ▶ Each pass: search for the smallest element in $O(n)$
- ▶ Total $O(n^2)$

Can we do better?

- ▶ Yes! **Merge sort** is $O(n \log n)$
- ▶ But you can't do any better than that...

Sidebar: recursion

The factorial of n is the product of integers $1, \dots, n$.

- ▶ As a function: $\text{fact}(n) = n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1$
- ▶ By convention, $\text{fact}(0) = 1$

Sidebar: recursion

The factorial of n is the product of integers $1, \dots, n$.

- ▶ As a function: $\text{fact}(n) = n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1$
- ▶ By convention, $\text{fact}(0) = 1$

```
1 def fact(n):
2     result = 1
3     for i in range(1, n+1):
4         result = result * i
5     return result
6 print(fact(4))
```

Sidebar: recursion

The factorial of n is the product of integers $1, \dots, n$.

- ▶ As a function: $\text{fact}(n) = n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1$
- ▶ By convention, $\text{fact}(0) = 1$

```
1 def fact(n):
2     result = 1
3     for i in range(1, n+1):
4         result = result * i
5     return result
6 print(fact(4))
```

But we can also write the factorial as follows:

$$\text{fact}(n) = 1, \text{ for } n = 0$$

$$\text{fact}(n) = n \times \text{fact}(n - 1), \text{ for } n > 0$$

Sidebar: recursion

We can also write the factorial as follows:

$$\text{fact}(n) = 1, \text{ for } n = 0$$

$$\text{fact}(n) = n \times \text{fact}(n - 1), \text{ for } n > 0$$

Factorial can be expressed as a smaller version of itself:

Sidebar: recursion

We can also write the factorial as follows:

$$\text{fact}(n) = 1, \text{ for } n = 0$$

$$\text{fact}(n) = n \times \text{fact}(n - 1), \text{ for } n > 0$$

Factorial can be expressed as a smaller version of itself:

```
1 def fact_rec(n):
2     if n == 0:
3         return 1
4     else:
5         return n*fact_rec(n-1)
6 print(fact_rec(4))
```

This is called **recursion**

- ▶ Function calls itself
- ▶ Can make some problems easier to define → merge sort!

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

- ▶ Base case: if list length $n < 2$, the list is sorted

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

- ▶ Base case: if list length $n < 2$, the list is sorted
- ▶ Divide: if list length $n \geq 2$, split into two lists and merge sort each

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

- ▶ Base case: if list length $n < 2$, the list is sorted
- ▶ Divide: if list length $n \geq 2$, split into two lists and merge sort each
- ▶ Combine (merge) the results of the two smaller merge sorts

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i_1 = i_2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

y =

19	57	61
----	----	----

z =

--

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i1 = i2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

 $i1 = 0$

y =

19	57	61
----	----	----

 $i2 = 0$

z =

--

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i1 = i2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

 $i1 = 0$

y =

19	57	61
----	----	----

 $i2 = 1$

z =

19

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i1 = i2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

 $i1 = 1$

y =

19	57	61
----	----	----

 $i2 = 1$

z =

19	24
----	----

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i1 = i2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

 $i1 = 2$

y =

19	57	61
----	----	----

 $i2 = 1$

z =

19	24	32
----	----	----

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i1 = i2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

 $i1 = 3$

y =

19	57	61
----	----	----

 $i2 = 1$

z =

19	24	32	56
----	----	----	----

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i1 = i2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

 $i1 = 3$

y =

19	57	61
----	----	----

 $i2 = 2$

z =

19	24	32	56	57
----	----	----	----	----

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i1 = i2 = 0$, update with every copy operation

x =

24	32	56
----	----	----

 $i1 = 3$

y =

19	57	61
----	----	----

 $i2 = 3$

z =

19	24	32	56	57	61
----	----	----	----	----	----

How to merge two sorted lists into one?

Loop through both lists simultaneously, copy smaller item to new list z

- ▶ Compare items at indices $i_1 = i_2 = 0$, update with every copy operation

$x =$

24	32	56
----	----	----

 $i_1 = 3$

$y =$

19	57	61
----	----	----

 $i_2 = 3$

$z =$

19	24	32	56	57	61
----	----	----	----	----	----

What is the complexity of this operation?

- ▶ Lengths of lists are n_1 and n_2
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations

Merge sort

Dividing

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

Merging

Merge sort

Dividing

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----


m

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

Merging

Merge sort


Dividing



Merging

Merge sort


Dividing




Merging

Merge sort

Dividing




Merging




Merge sort

Dividing




Merging



Merge sort

Dividing




Merging




Merge sort

Dividing




Merging




Merge sort

Dividing




Merging




Merge sort

Dividing




Merging




Merge sort

Dividing




Merging




Merge sort

Dividing




Merging




Merge sort

Dividing




Merging




Merge sort

Dividing



Merging



Merge sort

Dividing

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

56	24	99	32	9	61	57	79
----	----	----	----	---	----	----	----

Merging

24	56	32	99	9	61	57	79
----	----	----	----	---	----	----	----

24	32	56	99	9	57	61	79
----	----	----	----	---	----	----	----

9	24	32	56	57	61	79	99
---	----	----	----	----	----	----	----

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging \times # number of divisions

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging \times # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging \times # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)
- ▶ Log-linear: $O(n \log n)$

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging \times # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)
- ▶ Log-linear: $O(n \log n)$
- ▶ Big improvement over selection sort!

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ No more comparisons than copy operations
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging \times # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)
- ▶ Log-linear: $O(n \log n)$
- ▶ Big improvement over selection sort!
- ▶ Does need some more space due to copying lists

Complexity classes

Fast algorithm: worst-case running time grows slowly with input size

- ▶ $O(1)$: constant running time — primitive operations
- ▶ $O(\log n)$: logarithmic running time — binary search
- ▶ $O(n)$: linear running time — linear search
- ▶ $O(n \log n)$: log-linear time — merge sort
- ▶ $O(n^c)$: polynomial running time — selection sort
- ▶ $O(c^n)$: exponential running time — ??

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Theoretical bound for worst-case performance is $O(n \log n)$ – **we can't do better than merge sort**

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Theoretical bound for worst-case performance is $O(n \log n)$ – **we can't do better than merge sort**

But other algorithms are **better on average**

- ▶ Python uses **timsort** (In 2002, a Dutch guy called Tim got frustrated with existing algorithms)
- ▶ Exploit the fact that lists tend to be partly sorted already

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Theoretical bound for worst-case performance is $O(n \log n)$ – **we can't do better than merge sort**

But other algorithms are **better on average**

- ▶ Python uses **timsort** (In 2002, a Dutch guy called Tim got frustrated with existing algorithms)
- ▶ Exploit the fact that lists tend to be partly sorted already

Review

Sorting is a canonical computer science problem

- ▶ We've looked at two (of many) algorithms
- ▶ Selection sort involves repeatedly finding minimum element – intuitive but slow
- ▶ Merge sort is blazingly fast and has a neat recursive structure

Review exercises

- ▶ Implement sorting
- ▶ More looping and function practice