

Business Intelligence: OLAP, Data Warehouse, and Column Store

Thomas Heinis

Why we still study OLAP/Data Warehouse in Big Data?

- Understand the Big Data history
 - How does the requirement of (big) data analytics/business intelligence evolve over the time?
 - What are the architecture and implementation techniques being developed? Will they still be useful in Big Data?
 - Understand their limitation and what factors have changed from 90's to now?
- NoSQL is not only SQL
- Hive/Impala aims to provide OLAP/BI for Big Data using Hadoop

Outline

- OLAP
 - Multi-relational Data model
 - Operators
 - SQL
- Data warehouse (architecture, issues, optimizations)
- Join Processing
- Column Stores (Optimized for OLAP workload)

Back to the 70's: Relational Databases

Basic Structure

- Formally, given sets D_1, D_2, \dots, D_n a **relation** r is a subset of $D_1 \times D_2 \times \dots \times D_n$

Thus, a relation is a set of n -tuples (a_1, a_2, \dots, a_n) where each $a_i \in D_i$

- Example:

customer_name = {Jones, Smith, Curry, Lindsay}

customer_street = {Main, North, Park}

customer_city = {Harrison, Rye, Pittsfield}

Then $r = \{$ (Jones, Main, Harrison),
 (Smith, North, Rye),
 (Curry, North, Rye),
 (Lindsay, Park, Pittsfield) $\}$

is a relation over

customer_name, *customer_street*,
customer_city

Relation Schema

- A_1, A_2, \dots, A_n are *attributes*
- $R = (A_1, A_2, \dots, A_n)$ is a *relation schema*

Example:

*Customer_schema = (customer_name,
customer_street, customer_city)*

- $r(R)$ is a *relation* on the *relation schema* R

Example:

customer (Customer_schema)

Relation Instance

- The current values (*relation instance*) of a relation are specified by a table
- An element t of r is a *tuple*, represented by a *row* in a table

The diagram shows a table representing a relation instance. The table has three columns and four rows. Arrows point from the text 'attributes (or columns)' to the column headers. Arrows point from the text 'tuples (or rows)' to the data rows. The table is labeled 'customer' at the bottom.

<i>customer_name</i>	<i>customer_street</i>	<i>customer_city</i>
<i>Jones</i>	Main	Harrison
<i>Smith</i>	North	Rye
<i>Curry</i>	North	Rye
<i>Lindsay</i>	Park	Pittsfield

customer

Database

- A database consists of multiple relations
- Information about an enterprise is broken up into parts, with each relation storing one part of the information
 - account* : stores information about accounts
 - depositor* : stores information about which customer owns which account
 - customer* : stores information about customers
- Storing all information as a single relation such as *bank(account_number, balance, customer_name, ..)* results in repetition of information (e.g., two customers own an account) and the need for null values (e.g., represent a customer without an account)

Banking Example

branch (branch-name, branch-city, assets)

customer (customer-name, customer-street, customer-city)

account (account-number, branch-name, balance)

loan (loan-number, branch-name, amount)

*depositor (customer-name,
account-number)*

*borrower (customer-name,
loan-number)*

Relational Algebra

- Primitives
 - Projection (π)
 - Selection (σ)
 - Cartesian product (\times)
 - Set union (\cup)
 - Set difference ($-$)
 - Rename (ρ)
- Other operations
 - Join (\bowtie)
 - Group by... aggregation
 - ...

What happened next?

- SQL
- System R (DB2), INGRES, ORACLE, SQL-Server, Teradata
 - B+-Tree (select)
 - Transaction Management
 - Join algorithm

Early 90's: OLAP & Data Warehouse

Database Workloads

- OLTP (online transaction processing)
 - Typical applications: e-commerce, banking, airline reservations
 - User facing: real-time, low latency, highly-concurrent
 - Tasks: relatively small set of “standard” transactional queries
 - Data access pattern: random reads, updates, writes (involving relatively small amounts of data)
- OLAP (online analytical processing)
 - Typical applications: business intelligence, data mining
 - Back-end processing: batch workloads, less concurrency
 - Tasks: complex analytical queries, often ad hoc
 - Data access pattern: table scans, large amounts of data involved per query

OLTP

- Most database operations involve *On-Line Transaction Processing* (OLTP).
 - Short, simple, frequent queries and/or modifications, each involving a small number of tuples.
 - Examples: Answering queries from a Web interface, sales at cash registers, selling airline tickets.

OLAP

- Of increasing importance are *On-Line Application Processing* (OLAP) queries.
 - Few, but complex queries --- may run for hours.
 - Queries do not depend on having an absolutely up-to-date database.


OLAP Examples

1. Amazon analyzes purchases by its customers to come up with an individual screen with products of likely interest to the customer.
2. Analysts at Wal-Mart look for items with increasing sales in some region.

One Database or Two?

- Downsides of co-existing OLTP and OLAP workloads
 - Poor memory management
 - Conflicting data access patterns
 - Variable latency
- Solution: separate databases
 - User-facing OLTP database for high-volume transactions
 - Data warehouse for OLAP workloads
 - How do we connect the two?

OLTP/OLAP Architecture




OLTP/OLAP Integration

- OLTP database for user-facing transactions
 - Retain records of all activity
 - Periodic ETL (e.g., nightly)
- Extract-Transform-Load (ETL)
 - Extract records from source
 - Transform: clean data, check integrity, aggregate, etc.
 - Load into OLAP database
- OLAP database for data warehousing
 - Business intelligence: reporting, ad hoc queries, data mining, etc.
 - Feedback to improve OLTP services

The Data Warehouse

- The most common form of data integration.
 - Copy sources into a single DB (*warehouse*) and try to keep it up-to-date.
 - Usual method: periodic reconstruction of the warehouse, perhaps overnight.
 - Frequently essential for analytic queries.

Warehouse Architecture



Star Schemas

- A *star schema* is a common organization for data at a warehouse. It consists of:
 1. *Fact table* : a very large accumulation of facts such as sales.
 - Often “insert-only.”
 2. *Dimension tables* : smaller, generally static information about the entities involved in the facts.

Example: Star Schema

- Suppose we want to record in a warehouse information about every beer sale: the bar, the brand of beer, the drinker who bought the beer, the day, the time, and the price charged.
- The fact table is a relation:
`Sales(bar, beer, drinker, day, time, price)`

Example, Continued

- The dimension tables include information about the bar, beer, and drinker “dimensions”:

Bars(bar, addr, license)

Beers(beer, manf)

Drinkers(drinker, addr, phone)

Visualization – Star Schema

Dimension Table (**Bars**)

--	--	--	--

Dimension Table (**Drinkers**)

--	--	--	--

Dimension Attrs.

Dependent Attrs.

--	--	--	--	--	--

Fact Table - **Sales**

--	--	--	--

Dimension Table (**Beers**)

--	--	--	--


Dimension Table (etc.)

Dimensions and Dependent Attributes

- Two classes of fact-table attributes:
 1. *Dimension attributes* : the key of a dimension table.
 2. *Dependent attributes* : a value determined by the dimension attributes of the tuple

Warehouse Models & Operators

- Data Models
 - relations
 - stars & snowflakes
 - cubes
- Operators
 - slice & dice
 - roll-up, drill down
 - pivoting
 - other



Star


product	<u>prodId</u>	name	price
	p1	bolt	10
	p2	nut	5

store	<u>storeId</u>	city
	c1	nyc
	c2	sfo
	c3	la

sale	<u>oderId</u>	date	custId	prodId	storeId	qty	amt
	o100	1/7/97	53	p1	c1	1	12
	o102	2/7/97	53	p2	c1	2	11
	105	3/8/97	111	p1	c3	5	50


customer	<u>custId</u>	name	address	city
	53	joe	10 main	sfo
	81	fred	12 main	sfo
	111	sally	80 willow	la

Star Schema




Terms

- Fact table
- Dimension tables
- Measures



Dimension Hierarchies



store	<u>storeld</u>	cityld	tld	mgr
	s5	sfo	t1	joe
	s7	sfo	t2	fred
	s9	la	t1	nancy

sType	<u>tld</u>	size	location
	t1	small	downtown
	t2	large	suburbs

city	<u>cityld</u>	pop	regld
	sfo	1M	north
	la	5M	south


➔ snowflake schema

region	<u>regld</u>	name
	north	cold region
	south	warm region

Aggregates

- Add up amounts for day 1
- In SQL: `SELECT sum(amt) FROM SALE
WHERE date = 1`

sale	prodlid	storeid	date	amt
	p1	c1	1	12
	p2	c1	1	11
	p1	c3	1	50
	p2	c2	1	8
	p1	c1	2	44
	p1	c2	2	4




81

Aggregates

- Add up amounts by day
- In SQL: `SELECT date, sum(amt) FROM SALE GROUP BY date`

sale	prodId	storeId	date	amt
	p1	c1	1	12
	p2	c1	1	11
	p1	c3	1	50
	p2	c2	1	8
	p1	c1	2	44
	p1	c2	2	4




ans	date	sum
	1	81
	2	48

Another Example

- Add up amounts by day, product
- In SQL: `SELECT date, sum(amt) FROM SALE GROUP BY date, prodId`

sale	prodId	storeId	date	amt
	p1	c1	1	12
	p2	c1	1	11
	p1	c3	1	50
	p2	c2	1	8
	p1	c1	2	44
	p1	c2	2	4



sale	prodId	date	amt
	p1	1	62
	p2	1	19
	p1	2	48

—— rollup —→

← drill-down ——

Cube

Fact table view:

sale	prodId	storeId	amt
	p1	c1	12
	p2	c1	11
	p1	c3	50
	p2	c2	8



Multi-dimensional cube:

	c1	c2	c3
p1	12		50
p2	11	8	


dimensions = 2

3D Cube

Fact table view:

sale	prodl	storeld	date	amt
	p1	c1	1	12
	p2	c1	1	11
	p1	c3	1	50
	p2	c2	1	8
	p1	c1	2	44
	p1	c2	2	4

Multi-dimensional cube:





dimensions = 3


Multidimensional Data

Sales volume as a function of product, month, and region


Dimensions: Product, Location, Time
Hierarchical summarization paths




A Sample Data Cube




Cuboids Corresponding to the Cube



Cube Aggregation




Cube Operators




Pivoting

Fact table view:


sale	prodl	storeld	date	amt
	p1	c1	1	12
	p2	c1	1	11
	p1	c3	1	50
	p2	c2	1	8
	p1	c1	2	44
	p1	c2	2	4



Multi-dimensional cube:



	c1	c2	c3
day 2	44	4	
day 1	12		50



CUBE Operator (SQL-99)

Chevy Sales Cross Tab				
Chevy	1990	1991	1992	Total (ALL)
<i>black</i>	50	85	154	289
<i>white</i>	40	115	199	354
<i>Total (ALL)</i>	90	200	353	1286

```

SELECT      model, year, color, sum(sales) as sales
FROM        sales
WHERE       model in ( 'Chevy' )
AND         year BETWEEN 1990 AND 1992
GROUP BY    CUBE (model, year, color);
  
```

CUBE Contd.


```
SELECT      model, year, color, sum(sales) as sales
FROM        sales
WHERE       model in ('Chevy')
AND         year BETWEEN 1990 AND 1992
GROUP BY    CUBE (model, year, color);
```

Computes union of 8 different groupings:

{(model, year, color), (model, year), (model, color),
(year, color), (model), (year), (color), ()}

Example Contd.

SALES			
Model	Year	Color	Sales
Chevy	1990	red	5
Chevy	1990	white	87
Chevy	1990	blue	62
Chevy	1991	red	54
Chevy	1991	white	95
Chevy	1991	blue	49
Chevy	1992	red	31
Chevy	1992	white	54
Chevy	1992	blue	71
Ford	1990	red	64
Ford	1990	white	62
Ford	1990	blue	63
Ford	1991	red	52
Ford	1991	white	9
Ford	1991	blue	55
Ford	1992	red	27
Ford	1992	white	62
Ford	1992	blue	39



DATA CUBE			
Model	Year	Color	Sales
ALL	ALL	ALL	942
chevy	ALL	ALL	510
ford	ALL	ALL	432
ALL	1990	ALL	343
ALL	1991	ALL	314
ALL	1992	ALL	285
ALL	ALL	red	165
ALL	ALL	white	273
ALL	ALL	blue	339
chevy	1990	ALL	154
chevy	1991	ALL	199
chevy	1992	ALL	157
ford	1990	ALL	189
ford	1991	ALL	116
ford	1992	ALL	128
chevy	ALL	red	91
chevy	ALL	white	236
chevy	ALL	blue	183
ford	ALL	red	144
ford	ALL	white	133
ford	ALL	blue	156
ALL	1990	red	69
ALL	1990	white	149
ALL	1990	blue	125
ALL	1991	red	107
ALL	1991	white	104
ALL	1991	blue	104
ALL	1992	red	59
ALL	1992	white	116
ALL	1992	blue	110

Aggregates

- Operators: sum, count, max, min, median, avg
- “Having” clause
- Cube (& Rollup) operator
- Using dimension hierarchy
 - average by region (within store)
 - maximum by month (within date)

Query & Analysis Tools

- Query Building
- Report Writers (comparisons, growth, graphs,...)
- Spreadsheet Systems
- Web Interfaces
- Data Mining

Other Operations

- Time functions
 - e.g., time average
- Computed Attributes
 - e.g., $\text{commission} = \text{sales} * \text{rate}$
- Text Queries
 - e.g., find documents with words X AND B
 - e.g., rank documents by frequency of words X, Y, Z