

# AI-Enabled Multi-Objective Inverse Design of Chiral Metasurfaces for Biosensing via Moth-Eye Template Nanofabrication

Xiaoyang Zheng

## Research Motivation and Background

Detecting biomolecular chirality is essential for drug discovery and diagnostics, yet traditional circular dichroism (CD) spectroscopy requires expensive instrumentation and large sample volumes [1]. Professor Mana Toma's group has pioneered plasmonic metasurface biosensors leveraging collective plasmon modes for label-free colorimetric detection using silver nanodome arrays [2, 3, 4], enabling practical spectrometer-free biosensing through industrially scalable moth-eye nanoimprint lithography [5].

I aim to extend this platform to chiral sensing, where superchiral electromagnetic fields achieve ultrasensitive detection of molecular handedness [6]. Current AI-driven metasurface design methods cannot efficiently generate manufacturable chiral structures optimized for both signal enhancement and biosensing performance [7], creating urgent need for an AI framework generating moth-eye-compatible designs with multi-objective optimization.

## Research Objectives

I propose developing a conditional Generative Adversarial Network (cGAN) framework tailored to Professor Toma's moth-eye fabrication platform for rapid generation of optimized chiral plasmonic metasurface biosensor designs [8, 9]:

1. **Define parametric design space:** Mathematical model describing achievable 3D chiral nanostructures within moth-eye constraints, inspired by Professor Toma's silver nanodome architectures.
2. **Generate training dataset:** High-quality dataset ( $>10,000$  designs) via automated FDTD simulations evaluating CD enhancement and LSPR wavelength shifts.
3. **Develop cGAN architecture:** PyTorch-based cGAN with dual performance targets (chiroptical response + colorimetric sensitivity) as inputs and manufacturable parameters as outputs.
4. **Experimental validation:** Fabricate top designs using moth-eye templates and characterize via Professor Toma's protocols (CD spectroscopy, colorimetric immunoassays).

## Methodology

**Phase 1 (Months 1–8):** Develop automated Python-FDTD pipeline sampling moth-eye parameter space (silver thickness, template depth, asymmetry), generating paired geometric and performance data (CD enhancement, refractive index sensitivity).

**Phase 2 (Months 9–16):** Train forward-predicting surrogate network for rapid evaluation, then train cGAN with multi-objective loss (adversarial learning, dual-target reconstruction, physics constraints), validated via FDTD and comparison with Professor Toma's published designs.

**Phase 3 (Months 17–24):** Fabricate selected designs using Professor Toma's moth-eye process with silver deposition. Characterize via SEM, CD spectroscopy, and label-free binding assays with model biomolecules (chiral amino acids, IgG) [4, 10].

## Expected Outcomes and Impact

Deliverables: (1) validated cGAN tool for rapid chiral biosensor customization without re-training, (2) design library demonstrating chiroptical-colorimetric trade-offs, and (3) proof-of-concept devices with  $<10\%$  prediction-experiment deviation. This directly advances Professor Toma's mission of democratizing biosensing [11] by combining her scalable moth-eye platform with AI-driven multi-objective design for pharmaceutical quality control and point-of-care diagnostics.

## References

- [1] Benjamin L. Miller and Nathan C. Lindquist. “Unlocking the Translational Potential of Nanophotonic Biosensors: Perspectives on Application-Guided Design”. In: *ACS Photonics* (2025). DOI: 10 . 1021 / acsphotronics.5c00838.
- [2] Toma Research Group. *Research Topics*. Tokyo Institute of Technology. 2025.
- [3] Mana Toma et al. “Collective Plasmon Modes Excited on a Silver Nanoparticle 2D Crystalline Sheet”. In: *Physical Chemistry Chemical Physics* 13 (2011), pp. 7459–7466. DOI: 10 . 1039/c0cp02953j.
- [4] Kosuke Toma et al. “Label-Free Detection of DNA Using Plasmonic Nanodome Arrays”. In: *Biosensors and Bioelectronics* 180 (2021), p. 113119. DOI: 10 . 1016/j . bios . 2021 . 113119.
- [5] S. J. Barcelo and Z. Li. “Nanoimprint lithography for nanodevice fabrication”. In: *Nano Convergence* 3.1 (2016), p. 21. DOI: 10 . 1186/s40580-016-0081-y.
- [6] E. Hendry et al. “Ultrasensitive Detection and Characterization of Biomolecules Using Superchiral Fields”. In: *Nature Nanotechnology* 5 (2010), pp. 783–787. DOI: 10 . 1038/nnano . 2010 . 209.
- [7] Wei Ma et al. “Deep learning for the design of photonic structures”. In: *Nature Photonics* 15.2 (2021), pp. 77–90. DOI: 10 . 1038/s41566-020-0685-y.
- [8] Sunae So et al. “Designing nanophotonic structures using conditional deep convolutional generative adversarial networks”. In: *Nanophotonics* 8.7 (2019), pp. 1255–1261. DOI: 10 . 1515/nanoph-2019-0117.
- [9] Zhaocheng Liu et al. “Generative Model for the Inverse Design of Metasurfaces”. In: *Nano Letters* 18.10 (2018), pp. 6570–6576. DOI: 10 . 1021/acs . nanolett . 8b03171.
- [10] Mana Toma et al. “Surface Plasmon-Coupled Emission on Plasmonic Bragg Gratings”. In: *Optics Express* 20.13 (2012), pp. 14042–14053. DOI: 10 . 1364/OE . 20 . 014042.
- [11] Toma Research Group. *Achievements*. Tokyo Institute of Technology. 2025.