

siteco



NEW

Types,
data sheets,
configuration -
everything at
a glance:

Lunis R



Lunis R

From past to future.

From past to future.

Flexible

Versatile mounting options for flexible room design – ideal for refurbishment and new builds.

Modular

With suitable accessories, various light characteristics can be implemented flexibly and precisely – ideal for office applications with glare-free, standard-compliant lighting (UGR < 19).



Made in

Traunreut

Efficient

Up to 164 lm/W – for reduced operating costs and an optimized amortization time.


Versatile

Available in various light colors and color renderings, with DALI and ON/OFF multi-lumen drivers – for optimal lighting results and customized solutions.


Up to
164
lm/W

Light as desired.

Suitable for:




Recessed




Surface-mounted


Light colors.



Tunable White
2,700 – 6,500 K



3,000 K




4,000 K

Color rendering.

- CRI 80
- CRI 90

Drivers.



- ON / OFF Multilumen
- DALI DT 6
- DALI DT 8

Housing colors.



black




white




silver

- Surface-mounted
- Surface-mounted
- Surface-mounted
- Recessed


Lighting accessories.



C-grid
To achieve
UGR 19



Collector lens



Diffuse cover

Lunis R at a glance.



Lunis R Surface-mounted / Recessed

Technical data

Diameter: 380 mm

Weight: 2 kg

Luminous flux: 2,020 ... 4,800 lm

Luminous efficacy: bis zu 164 lm/W

Beam angle: direct symmetrical wide distribution

Service life: 50,000 h (L85)

Color temperature: 3,000 K | 4,000 K | TW

Color rendering index: CRI $\geq$ 80 | CRI $\geq$ 90

Control: DALI 2, ON / OFF Multilumen

Electrical connection: with terminal 3+2 pole, max. 2.5 mm²

Housing: aluminum white, black or silver (recessed only silver)

Contact.

Siteco GmbH

Georg-Simon-Ohm-Str. 50
83301 Traunreut, Deutschland
Tel. +49 8669 330
sales-int@siteco.com

[siteco.com](https://www.siteco.com)