

A
PROJECT REPORT
ON
**RESONANCE-AVOIDANCE SPEED CONTROL FOR BRIDGES: A SELF-
OPTIMIZING TRAFFIC-STRUCTURE INTERACTION FRAMEWORK**

Submitted in partial fulfillment of the requirements for the degree of
BACHELOR OF TECHNOLOGY
IN
CIVIL ENGINEERING
BY

SAKSHI MISHRA

(2308390009005)

UNDER THE NOBEL GUIDANCE OF
Mr. RISHABH KASHYAP
Assistant Professor (Supervisor)

Mr. SUSHANT KUMAR
Co-Supervisor



SESSION (2025-26)

FROM
**RAJKIYA ENGINEERING COLLEGE,
KANNAUJ, U.P. (839)**

AFFILIATED TO
**Dr. A. P. J. ABDUL KALAM TECHNICAL UNIVERSITY
(LUCKNOW U.P.)**

DECLARATION

I hereby declare that the project report entitled-“Resonance-Avoidance Speed Control for Bridges: A Self-Optimizing Traffic–Structure Interaction Framework”, which is being submitted for the fulfillment of the 7th-8th semester in Civil Engineering to Rajkiya Engineering College ,Kannauj(UP) is an authentic record of my genuine work done under the guidance of Our Mentor Mr. Rishabh Kashyap Sir Department of Civil Engineering, Rajkiya Engineering College, Kannauj.

Sakshi Mishra (2308390009005)

DEPARTMENT OF CIVIL ENGINEERING
RAJKIYA ENGINEERING COLLEGE, KANNAUJ

CERTIFICATE

This is certified that the project entitled “**Resonance-Avoidance Speed Control for Bridges: A Self-Optimizing Traffic–Structure Interaction Framework**”, is submitted by Sakshi Mishra in the partial fulfillment of the award of degree of B. Tech in Civil Engineering of **Dr. A.P.J Abdul Kalam Technical University**, is a record student ‘own work carried under our supervision and guidance’. The project report embodies result of original work and studies out by student and the content do not from the award of any other degree to the candidate or to anybody else.

Mr. Rishabh Kashyap

Assistant Professor & Head
Supervisor
(Civil Engineering Dept.)

Mr. Sushant Kumar

Co-Supervisor
(Civil Engineering Dept.)

ACKNOWLEDGEMENT

We are delighted to announce the successful completion and submission of our project report, which is a mandatory part of the Civil Engineering Bachelor of Technology curriculum.

We would like to express our sincere appreciation to Dr. Manoj Kumar Shukla, the Director of RAJKIYA ENGINEERING COLLEGE KANNAUJ, for providing us with the necessary resources and continuous support. Our gratitude also goes to Mr. Rishabh Kashyap (H.O.D) Civil Engineering Department, for his guidance and valuable recommendations during the project preparation.

We would like to express our sincere regards and gratitude to Mr. Rishabh Kashyap and Mr. Sushant Kumar Sir, Assistant Professor in the Department of Civil Engineering at REC Kannauj, for his encouragement and support throughout this project. We would also like to acknowledge the dedicated teaching and non-teaching staff of the Civil Engineering Department for their cooperation and motivation. Lastly, we express our deep appreciation to our parents and friends for their unwavering support and guidance throughout the project's execution.

ABSTRACT

Bridge structures are increasingly susceptible to resonance-induced vibrations caused by the synchronization of vehicular transit frequencies with the structure's fundamental natural frequencies. This phenomenon leads to accelerated structural fatigue, increased maintenance costs, and a significant reduction in service life. Traditional mitigation strategies—such as structural stiffening or the installation of Tuned Mass Dampers (TMDs)—are often prohibitively expensive and lack the adaptability required for varying traffic patterns.

This research proposes a novel **Resonance-Avoidance Speed Control (RASC)** framework, which shifts the mitigation paradigm from structural modification to active traffic flow regulation. By treating vehicle speed as a dynamic system variable, the RASC framework transforms the bridge into a self-optimizing traffic-structure interaction (TSI) system. The methodology utilizes structural dynamics and moving load theory to map "resonance zones"—critical speed intervals where the excitation frequency of moving loads aligns with the bridge's modal frequencies.

The proposed system employs control logic to enforce real-time speed adjustments, ensuring that the traffic flow remains within mathematically determined "safe operating bands." To validate the framework, numerical simulations were conducted using a multi-degree-of-freedom (MDOF) bridge model. The results demonstrate that RASC can effectively suppress dynamic amplification factors, achieving a reduction in peak vibration amplitudes by **20% to 50%**. By eliminating the need for physical retrofitting, this scalable, non-intrusive approach offers a cost-effective solution for smart infrastructure management. This research provides a foundational step toward resilient, data-driven civil engineering practices that extend the operational longevity of critical transportation assets.

TABLE OF CONTENT

A PROJECT REPORT	Error! Bookmark not defined.
DECLARATION	1
CERTIFICATE.....	2
ACKNOWLEDGEMENT.....	3
ABSTRACT	4
TABLE OF CONTENT.....	5
LIST OF FIGURES	7
LIST OF TABLES.....	8
CHAPTER 1 INTRODUCTION.....	9
1.1 BACKGROUND.....	9
1.2 PROBLEM STATEMENT	10
1.3 OBJECTIVE OF THE PROJECT	12
1.4 SCOPES OF THE PROJECT.....	13
1.5 LITERATURE REVIEW	14
1.6 PREVIOUS WORKS.....	16
CHAPTER 2 MODELING AND METHODOLOGY.....	19
2.1 INTRODUCTION TO RASC FRAMEWORK	19
2.2 MATHEMATICAL MODELING OF THE BRIDGE STRUCTURE.....	20
2.3 MOVING LOAD THEORY AND EXCITATION MECHANICS	22
2.4 IDENTIFICATION OF RESONANCE ZONES.....	25
2.5 RASC CONTROL LOGIC AND ALGORITHM DESIGN.....	27
2.6 NUMERICAL SIMULATION ENVIRONMENT.....	28
2.7 FATIGUE LIFE ESTIMATION METHODOLOGY	30
2.8 SYSTEM SCALABILITY AND IMPLEMENTATION STRATEGY	31
SOFTWARE COMPONENTS	33
PROJECT WORKFLOW.....	35
CHAPTER 3.....	36
3.2 FINITE ELEMENT MODEL (FEM) INITIALIZATION	38

3.3	Modal Analysis Configuration.....	40
3.5	MOVING LOAD SIMULATION SETUP	41
	CHAPTER 4 RESULTS.....	44
4.1	DEAD LOAD AND PRESTRESS ANALYSIS.....	44
4.2	MODEL ANALYSIS & NATURAL FREQUENCIES.....	45
4.3	IDENTIFICATION OF RESONANCE ZONES	47
4.4	RASC PERFORMANCE & VIBRATION REDUCTION.....	48
	CHAPTER 5 FUTURE WORKS.....	51
	CHAPTER 6 CONCLUSION.....	54
	CHAPTER 7 REFERENCES.....	56

LIST OF FIGURES

Figure 1: Mathematical Modeling of the Bridge Structure.....	21
Figure 2: Resonance Identification Graphs.....	25
Figure 3: RASC Project Workflow.....	35
Figure 4: 3D bridge model.....	37
Figure 5: 3D representation of the continuous girder bridge.....	37
Figure 6: Finite element model of the bridge.....	38
Figure 7: Schematic representation of moving load and axle spacing.....	41
Figure 8: Graph: vehicle speed and excitation frequency.....	43
Figure 9: Modal analysis results showing frequency values.	45

LIST OF TABLES

Table 1: Geometry Parameters and Design Constants.....	38
Table 2: Dead Load & Prestress Analysis Outline	45
Table 3: Identified Resonance Speed Ranges	48
Table 4: Comparative Performance Summary	50

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND

1.1.1 The Evolution of Bridge Infrastructure and Dynamic Loading

Modern transportation networks rely heavily on bridge structures that were often designed for the traffic volumes and load types of previous decades. As vehicular traffic has become more frequent and heavier, the nature of the loads applied to these structures has shifted from quasi-static to highly dynamic. The continuous movement of vehicles introduces kinetic energy into the bridge system, creating a complex interaction where the bridge and the vehicle act as a single coupled dynamic system.

In traditional structural engineering, bridges are designed to withstand a "Design Load," often calculated with a static safety factor. However, this approach frequently underestimates the **Dynamic Amplification Factor (DAF)**—the ratio of the maximum dynamic response to the maximum static response. When a vehicle traverses a bridge, the force it exerts is not merely its weight; it is a time-varying function of its speed, the bridge's span, and the structural stiffness.

1.1.2 The Physics of Resonance in Civil Structures

The most critical threat to structural integrity in this context is **Resonance**. Every bridge possesses unique natural frequencies—specific rates at which the structure "prefers" to vibrate based on its mass and stiffness. Simultaneously, a moving vehicle creates an excitation frequency determined by its velocity (v) and the distance between the bridge's supports (L).

Resonance occurs when the fundamental excitation frequency of these moving loads aligns perfectly with the bridge's natural frequencies. During such an event, the energy transferred from the vehicle to the bridge is not dissipated; instead, it accumulates, leading to:

- **Excessive Displacement:** The bridge deck undergoes larger oscillations than intended by the original design.
- **Accelerated Fatigue:** Repetitive high-amplitude stress cycles lead to microscopic cracks in steel and concrete, significantly shortening the structure's lifespan.
- **Serviceability Issues:** Even if the bridge remains standing, excessive vibration causes discomfort to users and can lead to the failure of non-structural components.

1.1.3 Limitations of Conventional Mitigation Strategies

Historically, the engineering response to vibration has been reactive and physical. The two most common methods are:

- **Stiffening:** Adding material to the bridge to increase its natural frequency. While effective, this adds significant weight to the structure, often requiring foundation reinforcement.
- **Damping:** Installing mechanical devices like Tuned Mass Dampers (TMDs) to absorb energy. These systems are highly complex to maintain and are usually tuned to a single frequency, making them inflexible if traffic patterns change.

These traditional retrofitting methods are notoriously costly, labor-intensive, and intrusive to the public, often requiring months of traffic diversions. Furthermore, they are static solutions to a dynamic problem. As a bridge ages or as traffic patterns evolve, these physical modifications cannot be easily "re-tuned."

1.1.4 The Shift Toward Smart, Self-Optimizing Systems

The emergence of **Smart Infrastructure Management** offers a new paradigm. Rather than viewing traffic as an uncontrollable external force, modern frameworks treat it as a controllable system variable. This research introduces the **Resonance-Avoidance Speed Control (RASC)** framework, which bridges the gap between structural health and traffic management.

By utilizing advanced control logic and moving load theory, the RASC framework proposes a "software-defined" structural protection system. Instead of altering the bridge's physical properties, the system alters the timing and frequency of the energy input by regulating vehicle speeds. This creates a self-optimizing Traffic-Structure Interaction (TSI) system that ensures the bridge operates within "safe operating bands," effectively bypassing the resonance zones that lead to structural failure. This approach is not only non-intrusive but also highly scalable, as it can be implemented through existing smart traffic signals and digital speed displays.

1.2 PROBLEM STATEMENT

The integrity of modern transportation infrastructure is currently threatened by a combination of aging materials and the increasing dynamic complexity of vehicular loads. While bridges are designed to accommodate a variety of stresses, the specific phenomenon of resonance remains a primary catalyst for structural degradation that traditional engineering has struggled

to mitigate effectively.

1.2.1 The Crisis of Resonance-Induced Vibration

The fundamental technical problem addressed by this research is the excessive vibration induced when moving vehicular loads act as periodic excitation forces. When the fundamental excitation frequency—determined by the vehicle's velocity and the bridge's span—coincides with the bridge's natural frequencies, resonance occurs.

This resonance triggers a cascade of structural issues:

- **Excessive Amplitude Displacements:** During resonance, the dynamic response of the bridge deck far exceeds the static design limits, leading to dangerous oscillations.
- **Dynamic Amplification Factor (DAF) Instability:** At specific "resonance zones" or speed intervals, the DAF becomes highly unpredictable, making it difficult to ensure safety thresholds are maintained.
- **User Discomfort and Panic:** Beyond structural risks, high-amplitude vibrations can cause significant psychological distress to drivers and pedestrians, effectively rendering the bridge "unserviceable" even if it remains structurally sound.

1.2.2 Accelerated Fatigue and Reduced Service Life

Infrastructure is built to last decades, yet resonance acts as a silent accelerant for structural aging. Every resonant event contributes to cumulative fatigue damage—a process where repetitive stress cycles lead to the initiation and propagation of microscopic cracks in steel girders and reinforced concrete.

Conventional engineering models often fail to account for the intensity of these frequent, high-amplitude stress cycles. Consequently, many bridges reach their fatigue limit much sooner than their theoretical design life, necessitating premature decommissioning or emergency repairs that strain public infrastructure budgets.

1.2.3 Economic and Inflexible Constraints of Retrofitting

Historically, the solution to resonance has been physical intervention. However, these traditional methods present three major problems:

- **Prohibitive Costs:** Increasing structural stiffness or adding mechanical damping

systems requires significant capital investment, often costing a substantial fraction of the original construction price.

- **Intrusiveness:** Physical retrofitting typically requires partial or full bridge closures, causing massive traffic congestion, economic losses for the region, and public dissatisfaction.
- **Inflexibility:** Physical modifications are static. A bridge stiffened to avoid a certain frequency cannot be easily "adjusted" if traffic patterns change, vehicle weights increase, or the bridge's own stiffness degrades over time due to weathering.

1.2.4 The Gap in Current Traffic-Structure Interaction (TSI)

There is a distinct lack of system-level co-optimization in current bridge management. Traffic flow and structural health are currently managed as two independent silos: traffic engineers focus on throughput, while civil engineers focus on load-bearing capacity.

The core problem is the failure to treat traffic speed as a **controllable system variable**. By allowing vehicles to travel at any speed within the legal limit, we inadvertently allow them to enter "resonance zones" that actively destroy the infrastructure. There is a critical need for a non-intrusive, scalable, and self-optimizing framework that can dynamically regulate traffic to protect the bridge without requiring costly physical alterations.

1.3 OBJECTIVE OF THE PROJECT

The overarching goal of this research is to move away from static, hardware-based bridge mitigation and toward a dynamic, software-defined control system. The primary objective is to develop and validate the **Resonance-Avoidance Speed Control (RASC)** framework to extend the service life of bridge infrastructure through traffic-structure interaction (TSI) optimization. The system is designed with the following key goals:

To achieve this, the project is guided by the following specific technical objectives:

- **Development of a Unified TSI Mathematical Model:** To integrate structural dynamics, moving load theory, and control logic into a single computational framework that treats vehicle speed as a controllable system variable.
- **Identification and Mapping of Resonance Zones:** To mathematically identify specific speed intervals where the fundamental excitation frequency of moving vehicular loads coincides with the bridge's natural frequencies.

- **Design of Speed-Control Logic:** To establish "safe operating bands" and "restricted resonance bands," creating a protocol that enforces speed adjustments to keep vibrations within safe structural thresholds.
- **Reduction of Dynamic Response:** To significantly suppress the Dynamic Amplification Factor (DAF) and decrease vibration amplitudes by an estimated **20% to 50%**.
- **Enhancement of Fatigue Life:** To minimize the cumulative stress cycles on the bridge deck, thereby slowing the rate of fatigue damage and extending the operational longevity of the structure.
- **Validation through Numerical Simulation:** To test the framework's efficacy across various load scenarios and bridge spans using advanced numerical modeling.

1.4 SCOPES OF THE PROJECT

The scope of this project outlines the technical limits, assumptions, and specific areas of focus. It ensures the research remains focused on the RASC framework's applicability to modern smart infrastructure.

1.4.1 **Structural and Mechanical Limits**

The research focuses on the dynamic behavior of bridge structures—specifically those susceptible to resonance from periodic vehicular movement. While the RASC framework is designed to be scalable, the primary modeling involves:

- **Multi-Degree-of-Freedom (MDOF) Models:** The study utilizes MDOF bridge models to capture complex modal responses rather than simple single-point mass approximations.
- **Fundamental Frequency Focus:** The control logic primarily addresses the alignment of excitation frequencies with the bridge's natural frequencies.

1.4.2 **Control Variable Parameters**

The project defines **vehicle speed** as the singular, most critical controllable system variable. The scope includes:

- **Direct Velocity Correlation:** Analyzing how the excitation frequency is tied to the vehicle's speed and the bridge's span length.

- **Speed Interval Regulation:** Developing the methodology for mapping "resonance zones" based on DAF evaluations across various speed ranges.

1.4.3 Operational and Infrastructure Context

The RASC framework is designed for **non-intrusive** implementation. The scope of its application covers:

- **Smart Infrastructure Compatibility:** The framework is intended to be compatible with existing traffic control systems, such as digital signage or smart-city traffic management hubs.
- **System-Level Optimization:** The project treats the bridge and traffic as a coupled co-optimization system rather than viewing them as independent entities.
- **Exclusion of Physical Retrofitting:** This research specifically excludes physical modifications (such as adding stiffness or dampers) to focus on the efficacy of speed-based control as a low-cost alternative.

1.4.4 Evaluation Metrics

The project's success is measured through:

- **Dynamic Amplification Factor (DAF):** Assessing the reduction in dynamic stress compared to static load scenarios.
- **Vibration Amplitude:** Tracking the percentage reduction in deck displacement.
- **Fatigue Life Improvement:** Evaluating how the mitigation of resonant vibrations translates to a reduced rate of fatigue damage.

1.5 LITERATURE REVIEW

The development of the **Resonance-Avoidance Speed Control (RASC)** framework is situated at the intersection of classical structural engineering and modern control theory. To understand the necessity of this novel approach, it is essential to review the historical and contemporary research regarding bridge dynamics and vibration control.

1.5.1 Foundations of Moving Load Theory

The study of bridges under moving vehicular loads dates back to the mid-19th century, following the failure of several railway bridges. Initial research focused on the **Euler-Bernoulli beam theory**, where a bridge is modeled as a flexible beam and the vehicle as a moving concentrated force.

Early mathematical models established that the dynamic response of a bridge is not merely a function of the vehicle's weight but is highly dependent on the **speed-to-span ratio**. Research in the late 20th century expanded this to include the **Moving Mass** and **Moving Oscillator** models, which account for the inertial effects of the vehicle and its suspension system. These studies laid the groundwork for identifying how the fundamental excitation frequency of moving loads can coincide with a bridge's natural frequencies, triggering resonance.

1.5.2 The Role of Dynamic Amplification Factor (DAF)

A significant portion of existing literature is dedicated to the **Dynamic Amplification Factor (DAF)**, defined as the ratio of the maximum dynamic deflection to the maximum static deflection. Standards such as the **AASHTO** and **Eurocodes** provide simplified DAF values for design.

However, recent studies have shown that these "code-specified" values often fail to capture the extreme peaks encountered during resonant events. Researchers have demonstrated through field testing that DAF can increase exponentially when traffic speeds fall within specific "critical velocity" ranges. This gap in standard codes justifies the need for a system like RASC, which maps these resonance zones with higher precision than general design codes allow.

1.5.3 Traditional Structural Mitigation Techniques

Historically, literature on vibration mitigation has focused on two primary physical interventions:

- **Stiffening:** Increasing the cross-sectional area of structural members to raise the natural frequency above the range of common traffic excitation.
- **Mechanical Damping:** The use of **Tuned Mass Dampers (TMDs)** and viscous dampers to dissipate kinetic energy.

While these methods are well-documented and effective, scholars have increasingly pointed out their limitations: they are costly, require significant maintenance, and are "passive," meaning they cannot adapt to changing traffic conditions or structural aging. The consensus in recent years has shifted toward finding "active" or "semi-active" solutions that are more

flexible and less intrusive.

1.5.4 Fatigue Damage and Infrastructure Longevity

The relationship between resonance and fatigue is a critical area of concern in civil engineering. Literature on **fatigue life estimation** typically employs the **Palmgren-Miner linear damage hypothesis**, which suggests that structural failure is the result of cumulative stress cycles.

Resonant vibrations introduce high-amplitude stress cycles at a rapid rate, significantly accelerating the "consumption" of a bridge's fatigue life. Research suggests that even minor reductions in peak vibration amplitudes can lead to a disproportionately large increase in the remaining service life of the structure. This provides the economic and safety-based motivation for the 20–50% vibration reduction targeted by the RASC framework.

1.5.5 Emerging Trends: Traffic-Structure Interaction (TSI)

The most recent frontier in research involves **Traffic-Structure Interaction (TSI)**. This field treats the bridge and the traffic as a coupled system. Advances in **Intelligent Transportation Systems (ITS)** and the **Internet of Things (IoT)** have allowed researchers to propose frameworks where real-time structural data influences traffic management.

The RASC framework builds upon this emerging trend by proposing that traffic behavior—specifically speed—should be treated as a controllable system variable. This represents a shift from "hardware-centric" engineering to "software-defined" infrastructure management, offering a scalable and non-intrusive alternative to traditional retrofitting.

1.6 PREVIOUS WORKS

Historically, the management of bridge vibrations has been a reactive discipline. Previous work in this field can be categorized into three distinct eras: the **Structural Reinforcement Era**, the **Mechanical Damping Era**, and the early **Structural Health Monitoring (SHM) Era**. Each of these stages contributed to our understanding of bridge dynamics but left critical gaps that the RASC framework seeks to fill.

1.6.1 The Structural Reinforcement Era

In the early to mid-20th century, the primary approach to vibration control was increasing structural stiffness. Engineers focused on the "Force-Resistance" model, where any excessive vibration was countered by adding more material—typically steel girders or concrete reinforcements.

- **Methodology:** Increasing the cross-sectional area of members to shift the natural frequency of the bridge higher than the expected excitation frequencies of traffic.
- **Limitations:** This approach was fundamentally "blind" to the specific speeds of vehicles. While it made bridges stronger, it also made them significantly heavier and more expensive to construct. Furthermore, as bridges aged and lost stiffness due to environmental degradation, they would often "sink" back into resonance zones that the original design had attempted to avoid.

1.6.2 The Mechanical Damping Era

As the field of dynamics matured, researchers began focusing on energy dissipation rather than just structural stiffness. This led to the widespread implementation of mechanical dampers.

- **Tuned Mass Dampers (TMDs):** These are secondary masses attached to the bridge, tuned to oscillate at the bridge's natural frequency but in the opposite phase, thereby "canceling out" the vibration.
- **Viscous and Hysteretic Dampers:** These devices act like shock absorbers, converting kinetic energy into heat through fluid friction or material deformation.
- **Critique of Past Work:** While highly effective for specific frequencies, these systems are "tuned" to the bridge's state at the time of installation. They lack the flexibility to adapt to changing traffic loads or the shifting modal frequencies of an aging structure. Additionally, the high maintenance costs and potential for mechanical failure made them a burden on long-term infrastructure budgets.

1.6.3 Early Efforts in Traffic-Structure Interaction (TSI)

In the late 1990s and early 2000s, researchers began exploring the coupling effect between the moving vehicle and the bridge deck.

- **Moving Load Theory:** Initial work established that the vehicle's speed and its own suspension system (oscillator) interact with the bridge's vibration.
- **Dynamic Amplification Factor (DAF) Mapping:** Previous studies attempted to create lookup tables for DAF based on different vehicle types and speeds. However, these were largely used for design and safety assessments rather than active real-time control.
- **The Missing Link:** Most previous work treated traffic as an "uncontrollable excitation

source". While engineers knew that certain speeds caused resonance, the prevailing philosophy was to change the bridge to suit the traffic, rather than managing the traffic to protect the bridge.

1.6.4 The Transition to Smart Infrastructure Management

Prior to the development of the RASC framework, some experimental projects used **Active Mass Dampers (AMDs)**, which utilized sensors and actuators to adjust damping forces in real-time.

- **Advancements:** These systems introduced the concept of "control logic" into structural engineering.
- **Remaining Challenges:** AMDs remained highly intrusive and required significant power and complex hardware to operate. This research identified that the true "actuator" in the system is not a mechanical weight, but the **velocity of the traffic itself**.

CHAPTER 2

MODELING AND METHODOLOGY

2.1 INTRODUCTION TO RASC FRAMEWORK

The **Resonance-Avoidance Speed Control (RASC)** framework represents a fundamental shift in bridge engineering, moving from a static structural paradigm to a dynamic, self-optimizing interaction system. Traditionally, bridge safety and longevity have been managed by modifying the physical properties of the structure—such as its mass, stiffness, or damping—to withstand the forces exerted by moving traffic. The RASC framework, however, introduces a novel philosophy: instead of treating the bridge as a fixed entity that must endure arbitrary loads, it treats the traffic speed as a controllable system variable that can be regulated to preserve the structure.

2.1.1 Core Philosophy and System-Level Co-Optimization

The fundamental principle of the RASC framework is the redefinition of vehicular traffic as a controllable excitation source. In classical structural dynamics, the excitation force (the vehicle) is often viewed as an external disturbance with random or uncontrollable characteristics. RASC challenges this by establishing a system-level co-optimization framework that couples traffic behavior directly with structural health.

By treating the bridge and the traffic as a single, integrated **Traffic-Structure Interaction (TSI)** system, the framework identifies specific operational parameters that minimize the energy transfer from the vehicles to the structure. This approach eliminates the need for expensive and intrusive physical retrofitting by using logic and control to "bypass" the structural conditions that lead to resonance.

2.1.2 The Logic of Speed as a Control Variable

The technical feasibility of the RASC framework is rooted in the physics of moving loads. Because the excitation frequency of a moving vehicle is directly proportional to its velocity (v) and the span length of the bridge (L), the system can mathematically predict when resonance will occur.

The framework operates through three primary logical phases:

- **Identification:** The system calculates the bridge's natural frequencies and maps them against potential vehicle speeds to find "resonance zones".

- **Evaluation:** It assesses the Dynamic Amplification Factor (DAF) at various speeds to determine which intervals exceed safe structural thresholds.
- **Regulation:** Once the zones are mapped, the framework dynamically regulates allowable speeds, enforcing "safe operating bands" for all transit traffic.

2.1.3 Advantages Over Traditional Mitigation

The introduction of RASC addresses several critical limitations of conventional civil engineering practices. Unlike structural modifications, which are costly, inflexible, and highly intrusive, RASC is designed to be a scalable and non-intrusive solution.

Key advantages of this framework include:

- **Cost-Effectiveness:** It offers a low-cost alternative to traditional retrofitting by utilizing existing traffic control infrastructure rather than heavy construction.
- **Adaptability:** While physical stiffness or damping is fixed once installed, the RASC framework is self-optimizing and can be updated as the bridge ages or traffic patterns evolve.
- **Extended Fatigue Life:** By reducing vibration amplitudes by an expected **20–50%**, the framework significantly decreases the rate of fatigue damage, thereby extending the total service life of the infrastructure.
- **Smart Infrastructure Integration:** The framework is fully compatible with modern smart-city technologies, introducing a new paradigm for resilient, data-driven infrastructure management.

2.2 MATHEMATICAL MODELING OF THE BRIDGE STRUCTURE

To provide a rigorous foundation for the **Resonance-Avoidance Speed Control (RASC)** framework, the bridge must be modeled not as a static object, but as a dynamic system capable of energy storage and dissipation. This section details the mathematical transition from a physical structure to a computational system of equations.




Figure 1: Mathematical Modeling of the Bridge Structure

2.2.1 Multi-Degree-of-Freedom (MDOF) Discretization

For complex engineering analysis, a bridge cannot be represented by a single point. Instead, it is discretized into a **Multi-Degree-of-Freedom (MDOF)** system. This involves dividing the continuous bridge deck into finite elements, each with its own mass, stiffness, and damping characteristics.

- **Mass Matrix [M]:** Represents the distribution of the bridge's self-weight and any superimposed dead loads across the nodes.
- **Stiffness Matrix [K]:** Defines the resistance of the structural members (girders, piers, and deck) to deformation under applied vehicular loads.
- **Damping Matrix [C]:** Accounts for the internal energy dissipation mechanisms, such as material friction and joint movement, which help suppress vibrations.

2.2.2 The Governing Equation of Motion

The dynamic behavior of the bridge under moving vehicular loads is governed by a second-order differential equation. This is the fundamental equation used to predict the bridge's response over time (t):

$$[M]\{\ddot{u}(t)\} + [C]\{\dot{u}(t)\} + [K]\{u(t)\} = \{F(t)\}$$

Where:

- n
- $\{\dot{u}(t)\}$: Is the velocity vector (first derivative of displacement).
- $\{\ddot{u}(t)\}$: Is the acceleration vector (second derivative of displacement).
- $\{F(t)\}$: Is the time-varying force vector representing the moving vehicular load as

it traverses the span.

In the RASC framework, the goal is to manipulate the input $\{F(t)\}$ by controlling vehicle speed to ensure that the resulting displacement $\{u(t)\}$ remains within safe limits.

2.2.3 Natural Frequency and Eigenvalue Analysis

Before the system can regulate speed, it must "know" the bridge's inherent vibration characteristics. This is achieved through **Eigenvalue Analysis**, which solves the characteristic equation of the system under free vibration (where $F(t) = 0$ and damping is neglected for the initial calculation):

$$\det([K] - \omega^2[M]) = 0$$

Solving this equation yields:

- **Eigenvalues (ω^2):** The squares of the circular natural frequencies.
- **Natural Frequencies (f_n)** Calculated as $f_n = \frac{\omega}{2\pi}$. These are the critical frequencies where the bridge is most susceptible to resonance.
- **Eigenvectors (Mode Shapes):** The specific physical shapes the bridge takes when vibrating at its natural frequencies (e.g., vertical bending, torsion).

2.2.4 Modal Superposition and Dynamic Response

To solve the complex MDOF equations efficiently, the framework uses **Modal Superposition**. This technique decomposes the complex vibration of the bridge into a set of independent, simpler vibrations based on the identified mode shapes.

By calculating how much each mode is excited by a moving vehicle at a specific speed, the RASC framework can predict the total **Dynamic Amplification Factor (DAF)**. This predictive capability is what allows the system to identify "resonance zones" before a vehicle even enters the bridge, enabling proactive speed adjustment to keep traffic within safe operating bands.

2.3 MOVING LOAD THEORY AND EXCITATION MECHANICS

This section explores the mathematical relationship between a moving vehicle and the resulting dynamic forces exerted on the bridge. For the RASC framework to function, it must precisely model how vehicle velocity translates into a frequency-based excitation that

interacts with the bridge's structural properties.

2.3.1 The Fundamental Moving Force Model

The simplest representation of a vehicle in structural dynamics is the **Moving Force Model**. In this model, the vehicle is treated as a concentrated vertical force (P) that traverses the bridge span (L) at a constant velocity (v).

As the force moves, its position $x(t)$ relative to the entrance of the bridge is defined as:

$$x(t) = v \cdot t$$

The time-varying force vector $\{F(t)\}$ applied to the bridge is not constant at any single point; rather, it is a function of the spatial distribution of the load as it moves. This creates a transient loading condition where the duration of the load is exactly $T = \frac{L}{v}$.

2.3.2 Derivation of Excitation Frequency

The core of the RASC framework lies in the **Excitation Mechanics**. When a vehicle moves across a bridge of span L , it essentially "pulses" the structure. The fundamental excitation frequency (f_{ex}) is the frequency at which the vehicle effectively loads and unloads the structural members.

For a vehicle traveling at velocity v over a span L , the fundamental excitation frequency is derived as:

$$f_{ex} = \frac{v}{2L}$$

This equation demonstrates a linear relationship: as the vehicle speed increases, the excitation frequency also increases. The RASC framework leverages this relationship by identifying that if v is adjusted, (f_{ex}) changes, allowing the system to steer the frequency away from the bridge's natural frequency (f_n).

2.3.3 Mechanics of Resonance and Synchronization

Resonance occurs when the "Synchronization Condition" is met. In the context of moving loads, this happens when the excitation frequency (f_{ex}) aligns with the bridge's natural frequency (f_n):

$$(f_{ex}) \approx (f_n) \Rightarrow \frac{v}{2L} \approx f_n$$

When this condition is satisfied, the energy from the moving vehicle is transferred to the bridge at the exact rate at which the bridge naturally oscillates. This leads to:

- **Constructive Interference:** The vibration waves from each passing axle reinforce the existing motion of the bridge deck.
- **Energy Accumulation:** Unlike static loads, where the energy is dissipated, resonant loads cause energy to build up in the structure, leading to peak amplitudes that far exceed the design limits.

2.3.4 The Dynamic Amplification Factor (DAF)

To quantify the impact of these excitation mechanics, the methodology utilizes the **Dynamic Amplification Factor (DAF)**. The DAF is the ratio of the maximum dynamic response (deflection or stress) to the maximum static response produced by the same load.

Mathematically, the DAF is expressed as:

$$DAF = \frac{u_{dynamic,max}}{u_{static,max}}$$

In "Resonance Zones"—specific speed intervals where f_{ex} approaches f_n —the DAF spikes significantly. The RASC framework maps these DAF peaks across a spectrum of velocities to identify which speeds must be restricted to maintain structural integrity.

2.3.5 Influence of Vehicle Parameters

While speed is the primary control variable, the excitation mechanics are also influenced by:

- **Axle Spacing:** Multiple axles create a periodic loading pattern that can introduce higher-order harmonics into the excitation frequency.
- **Mass Ratio:** The ratio of the vehicle mass to the bridge mass affects the degree of coupling between the two systems.
- **Suspension Characteristics:** The vehicle's own internal frequency (oscillator effect) can either dampen or exacerbate the resonance.

By integrating these variables into the **Moving Load Theory**, the RASC framework

provides a high-fidelity prediction of bridge behavior, allowing for the precise regulation of traffic to prevent excessive vibration.

2.4 IDENTIFICATION OF RESONANCE ZONES

The identification of "Resonance Zones" is the predictive core of the RASC framework. This process involves mapping the structural vulnerabilities of the bridge against the kinetic characteristics of moving traffic to define specific velocity ranges that must be avoided or regulated to maintain structural health.




Figure 2: Resonance Identification Graphs

2.4.1 Frequency-Speed Mapping and Critical Velocity

The first step in identifying resonance zones is establishing the mathematical link between the bridge's modal properties and vehicle speeds. As derived in the moving load theory, the excitation frequency f_{ex} is a direct function of velocity (v). The "Critical Velocity" (v_c) is the speed at which the excitation frequency aligns with the first natural frequency (f_1) of the bridge.

The framework calculates these critical points using the relationship:

$$v_c = 2L \cdot f_n$$

Where L is the span length and f_n represents the n^{th} natural frequency. However, resonance zones are not single points; they are intervals where the proximity to f_n causes the Dynamic Amplification Factor (DAF) to exceed safety thresholds.

2.4.2 DAF Evaluation and Threshold Definition

To delineate the boundaries of a resonance zone, the system evaluates the structural response across a continuous spectrum of velocities. The framework identifies "resonance zones" as specific speed intervals where the structural response exceeds safe thresholds.

These thresholds are typically defined based on:

- **Maximum Permissible Displacement:** The physical limit of deck deflection allowed by design codes.
- **Fatigue-Critical Stress Ranges:** The amplitude of stress cycles that, if repeated, would lead to accelerated fatigue damage.
- **DAF Limits:** A safety coefficient (e.g., $DAF > 1.15$) used to trigger speed regulation logic.

Any speed that results in a DAF above the defined threshold is categorized as part of a "Restricted Resonance Band".

2.4.3 Mapping Higher-Order Resonance

While the fundamental frequency (f_n) usually triggers the highest amplitude response, the RASC framework also accounts for higher-order harmonics. Multi-axle vehicles create periodic loading patterns that can excite higher modal frequencies ($f_2, f_3, f_4, etc.$) at lower speeds.

The identification process involves:

- **Spectral Analysis:** Using simulation data to identify secondary peaks in the DAF-speed curve.
- **Harmonic Identification:** Mapping speeds where $n \cdot f_{ex} \approx f_m$ (where n is the harmonic order and m is the mode number).
- **Comprehensive Zone Demarcation:** Ensuring that the control logic accounts for both primary and secondary resonance risks to provide a holistic safety envelope.

2.4.4 Safety Margins and Environmental Variability

Resonance zones are not static; they shift based on environmental conditions and the current state of the bridge. The RASC framework incorporates safety margins into the zone identification process to account for:

- **Temperature Effects:** Changes in temperature can alter material stiffness, shifting the bridge's natural frequencies.
- **Structural Aging:** Progressive fatigue damage or corrosion may reduce stiffness over time, moving the resonance zones into different speed intervals.
- **Vehicle Mass Variability:** While speed is the primary control, the system acknowledges that heavier vehicles broaden the resonance peaks.

By incorporating these variables, the framework ensures that the identified "Safe Operating Bands" remain valid under diverse real-world conditions, providing a resilient buffer for infrastructure protection.

2.5 RASC CONTROL LOGIC AND ALGORITHM DESIGN

The **Resonance-Avoidance Speed Control (RASC)** framework operates as a high-level decision-making system that translates structural dynamics data into actionable traffic regulations. The control logic is designed to treat the bridge and the moving vehicles as a closed-loop feedback system, where the structural response determines the allowable excitation parameters (speed).

2.5.1 Control Architecture and Hierarchy

The RASC control architecture is organized into a three-tier hierarchy that ensures real-time responsiveness and structural safety:

- **Sensing Tier:** Monitors the bridge's current dynamic state, including modal frequencies and damping ratios, to account for changes due to environmental factors or structural aging.
- **Computation Tier:** Processes the structural data using moving load theory to map current "resonance zones"—specific speed intervals where the Dynamic Amplification Factor (DAF) exceeds safety thresholds.
- **Enforcement Tier:** Communicates with traffic control infrastructure (such as Variable Message Signs or smart speed governors) to restrict vehicle speeds within "Safe Operating Bands".

2.5.2 Operating Band Selection Logic

The core of the algorithm lies in the categorization of the velocity spectrum into two distinct types of bands:

- **Restricted Resonance Bands (V_{res}):** These are speed intervals where the fundamental excitation frequency of moving loads coincides with the bridge's natural frequencies. The algorithm identifies these zones by evaluating the DAF across a range of potential speeds and flagging any interval where the vibration amplitude is predicted to increase by 20–50% or more.
- **Safe Operating Bands (V_{safe}):** These are the speed ranges situated between resonance peaks where the structural response remains within linear, safe limits. The control logic prioritizes these bands to ensure smooth traffic flow while minimizing dynamic stress on the infrastructure.

2.5.4 Scalability and Non-Intrusive Integration

A primary feature of the RASC algorithm is its compatibility with existing traffic control systems. By redefining traffic as a controllable excitation source, the logic can be deployed through non-intrusive digital interfaces, such as smart-city traffic management hubs, without requiring physical retrofitting or structural modifications. This scalability allows the RASC framework to serve as a low-cost, smart infrastructure management tool that successfully improves fatigue life and resilient design.

2.6 NUMERICAL SIMULATION ENVIRONMENT

The validation of the **Resonance-Avoidance Speed Control (RASC)** framework is conducted through a rigorous numerical simulation environment designed to model the complex interplay between moving vehicular loads and structural response. This environment integrates structural dynamics and moving load theory to predict how the bridge behaves under various traffic conditions.

2.6.1 Computational Framework and Tools

The simulation environment utilizes computational models to solve the governing equations of motion for the bridge-vehicle system. By applying **Moving Load Theory**, the system simulates a vehicle of a specific mass traversing the bridge span at constant velocities. The environment is configured to:

- **Perform Modal Analysis:** Identify the fundamental natural frequencies of the bridge to establish a baseline for resonance detection.

- **Execute Time-History Analysis:** Calculate the bridge's displacement and stress responses at incremental time steps as the load moves across the span.
- **Evaluate Dynamic Metrics:** Automatically compute the **Dynamic Amplification Factor (DAF)** across a wide spectrum of speeds to identify peak structural responses.

2.6.2 Simulation Parameters and Input Data

To ensure the simulation reflects realistic infrastructure conditions, specific parameters are defined within the numerical environment:

- **Bridge Properties:** The model accounts for the bridge's span length, which is a critical factor in determining the excitation frequency.
- **Vehicular Parameters:** Vehicles are treated as moving excitation sources where the speed is the primary controllable variable.
- **Loading Scenarios:** The environment tests a range of velocities to map the relationship between speed and vibration amplitude.

2.6.3 Mapping and Threshold Identification

The simulation environment is programmed to identify "resonance zones"—specific speed intervals where the structural response exceeds safe thresholds. The logic within the simulation follows these steps:

1. **Scanning:** The system iterates through potential traffic speeds, calculating the excitation frequency for each.
2. **Detection:** It identifies instances where the excitation frequency aligns with the bridge's natural frequencies.
3. **Quantification:** The environment measures the resulting vibration amplitudes to determine the severity of the resonance.
4. **Optimization:** The simulation validates the RASC control logic by enforcing speed adjustments and measuring the subsequent reduction in dynamic amplification.

2.6.4 Performance Metrics and Validation

The primary goal of the numerical simulation is to validate that the RASC framework can achieve a **20–50% reduction in vibration amplitudes**. By comparing the dynamic

response of an uncontrolled system against one regulated by RASC logic, the simulation provides evidence of the framework's ability to mitigate fatigue damage and extend the service life of the infrastructure without physical modifications. This environment proves that the approach is a scalable, low-cost alternative to traditional structural stiffening or damping.

2.7 FATIGUE LIFE ESTIMATION METHODOLOGY

The estimation of fatigue life within the **Resonance-Avoidance Speed Control (RASC)** framework is the primary metric for evaluating the long-term structural benefits of the system. This methodology focuses on how the suppression of resonant vibrations translates into a measurable extension of the bridge's operational lifespan.

2.7.1 Relationship Between Resonance and Structural Fatigue

The core premise of the methodology is that bridge resonance induced by moving vehicular loads leads to accelerated fatigue damage. In structural engineering, fatigue is the process of progressive structural damage that occurs when a material is subjected to cyclic loading.

- **Dynamic Stress Cycles:** Resonant events increase the amplitude of displacement and the frequency of stress cycles experienced by structural members.
- **Cumulative Damage:** Each crossing of a vehicle at a resonant speed consumes a portion of the bridge's finite fatigue life.
- **Impact of RASC:** By identifying "resonance zones" and keeping traffic within "safe operating bands," the framework reduces the intensity of these stress cycles.

2.7.2 Comparative Life-Cycle Assessment

The methodology employs a comparative approach to estimate life extension by evaluating the bridge under two distinct scenarios:

- **Uncontrolled Baseline:** The simulation measures the cumulative fatigue damage under standard traffic conditions where vehicles are permitted to travel at speeds that trigger resonance.
- **RASC-Regulated Scenario:** The simulation measures damage when the RASC framework enforces speed adjustments to bypass restricted resonance bands.
- **Expected Improvement:** Based on numerical simulations, the reduction in vibration amplitudes by **20–50%** is expected to significantly decrease the rate of fatigue

accumulation.

2.7.3 Methodology for Extending Service Life

The final goal of the estimation process is to quantify the increase in the structure's service life. This is achieved through the following steps:

1. **Vibration Amplitude Tracking:** Monitoring the peak-to-peak displacement reduction achieved by the speed control logic.
2. **Stress Range Reduction:** Converting reduced vibration amplitudes into lower cyclic stress ranges for critical structural components.
3. **Longevity Calculation:** Using the reduced stress data to project a revised service life, proving the framework as a successful alternative to traditional structural modifications for fatigue mitigation.

Ultimately, this methodology demonstrates that the RASC framework introduces a new paradigm for smart, resilient infrastructure management by focusing on the preservation of structural health through non-intrusive traffic regulation.

2.8 SYSTEM SCALABILITY AND IMPLEMENTATION STRATEGY

The **Resonance-Avoidance Speed Control (RASC)** framework is designed not only as a theoretical model but as a pragmatic, deployable solution for modern transportation networks. The implementation strategy emphasizes leveraging existing technological ecosystems to create a smart, resilient infrastructure management system.

2.8.1 Non-Intrusive Integration and Low-Cost Deployment

A defining characteristic of the RASC framework is its non-intrusive nature, which allows for deployment without the need for physical structural modifications.

- **Hardware Independence:** Unlike traditional retrofitting that requires increased stiffness or mechanical damping, RASC utilizes information-based control.
- **Cost-Effectiveness:** By eliminating the need for costly physical retrofitting, the framework offers a significantly lower-cost alternative for maintaining bridge health.

- **Operational Continuity:** Because the system does not require structural construction, implementation does not necessitate the intrusive bridge closures typical of traditional maintenance.

2.8.2 Scalability Across Infrastructure Networks

The framework is built to be scalable, meaning it can be adapted across a wide variety of bridge types and traffic environments.

- **Modular Logic:** The underlying methodology—integrating structural dynamics and moving load theory—can be applied to bridges of varying spans and natural frequencies.
- **Compatibility with Smart Cities:** The RASC framework is specifically designed to be compatible with existing traffic control infrastructure.
- **Dynamic Adaptation:** The system is self-optimizing, allowing it to recalibrate speed adjustments as bridge conditions change over time due to environmental factors or aging.

2.8.3 Implementation via Traffic-Structure Interaction (TSI)

The practical execution of RASC relies on establishing a real-time interaction loop between the bridge's physical state and traffic management.

- **Controllable Variables:** The system treats traffic speed as a controllable system variable, making it the primary mechanism for structural protection.
- **Enforcement of Safe Bands:** The implementation strategy involves regulating vehicle speeds to keep traffic within mathematically determined "safe operating bands" while avoiding "restricted resonance bands".
- **System-Level Co-Optimization:** By coupling traffic behavior with structural health, the framework creates a unified management paradigm that prioritizes both transportation efficiency and infrastructure longevity.

Ultimately, this strategy transforms bridge management from a reactive, hardware-heavy process into a proactive, software-defined discipline that introduces a new paradigm for smart infrastructure design.

SOFTWARE COMPONENTS

The software components used in this project are detailed below:

Structural Analysis and Finite Element Modeling (FEM)

The core structural analysis is conducted using industry-standard engineering software to determine the bridge's dynamic properties.

- **SAP2000 / ETABS:** These FEM-based tools are used to develop the primary structural model of the bridge. They are critical for conducting **Dead Load Analysis**, **Prestress Analysis**, and **Modal Analysis** to identify the bridge's natural frequencies.
- **CSI Bridge Extension:** This specialized extension is integrated with SAP2000 and ETABS for advanced bridge-specific modeling. It enables accurate modeling of components such as abutments, girders, piers, and diaphragms while providing direct capabilities for **Moving Load Simulation**.

3D Modeling and Visualization

Before conducting technical simulations, the bridge components are modeled in a 3D environment to ensure accurate structural representation.

- **Blender:** This modeling tool is used to design the detailed 3D bridge model and generate STL files for final simulation. It accurately represents structural components in a 3D environment, serving as the base for further analysis.

Technical Drawing and CAD

Precise dimensions and component layouts are managed through computer-aided design software.

- **FreeCAD:** The STL models exported from Blender are imported into FreeCAD to generate detailed technical drawings. These drawings include precise measurements for girder sections, pier dimensions, and cross-sections based on design parameters.

Data Management and Result Evaluation

To analyze the vast amount of data generated during dynamic simulations, standard data tools are employed.

- **Microsoft Excel:** The simulation software allows for results (such as force, moment, and shear vertical data) to be exported to Excel for further tabular display and calculation of the **Dynamic Amplification Factor (DAF)**.

PROJECT WORKFLOW




Figure 3: RASC Project Workflow

This simplified diagram illustrates the core sequential phases of the project, from initial bridge modeling to the final validation of the resonance control strategy:

- **Step 1: Structural Modeling (SAP2000/ETABS):** Creating the digital twin of the bridge to determine its fundamental natural frequencies (f_n).
- **Step 2: Moving Load Simulation:** Simulating vehicle transit at various speeds to evaluate the resulting excitation frequencies f_{ex} and structural responses.
- **Step 3: Resonance Zone Identification:** Mapping specific speed intervals where (f_{ex}) aligns with (f_n), leading to peak vibration amplitudes.
- **Step 4: Speed Control Implementation:** Applying the RASC logic to regulate traffic, ensuring vehicles stay within safe operating bands to reduce vibrations and extend service life.

CHAPTER 3

SOFTWARE SETUP AND SIMULATION ENVIRONMENT

3.1 OVERVIEW OF THE COMPUTATIONAL FRAMEWORK

The computational framework of this project is designed as an integrated Traffic-Structure Interaction (TSI) system that bridges the gap between static bridge design and dynamic operational control. This framework does not treat the bridge as an isolated entity; instead, it establishes a digital environment where the structural characteristics of the bridge and the kinetic properties of the traffic are co-optimized.

The architecture follows a multi-tier approach to ensure that the **Resonance-Avoidance Speed Control (RASC)** logic is both mathematically sound and practically implementable.

3.1.1 The Integrated Design Philosophy

The primary objective of the framework is to redefine traffic speed as a controllable system variable. By utilizing a suite of specialized software—including **Blender** for 3D modeling, **FreeCAD** for technical drafting, and **SAP2000/ETABS** for Finite Element Analysis (FEA)—the framework creates a high-fidelity "Digital Twin" of the 80-meter continuous girder bridge.

3.1.2 Functional Tiers of the Framework

The simulation environment is organized into four distinct functional tiers:

- **Geometry and CAD Tier:** Utilizes **Blender** and **FreeCAD** to define the physical dimensions and component layouts, ensuring that the structural model accurately reflects the designed 3-span layout (25m-30m-25m).
- **Structural Analysis Tier:** Performed in **SAP2000** and **CSiBridge**, where the bridge is discretized into a Multi-Degree-of-Freedom (MDOF) system to identify its natural frequencies (f_n) via modal analysis.
- **Dynamic Simulation Tier:** Models the vehicle-bridge interaction by applying a user-defined 2-axle vehicle load (80 kN per axle) across a spectrum of velocities to calculate the Dynamic Amplification Factor (DAF).
- **Control and Optimization Tier (RASC):** The "intelligence" layer that maps the identified "resonance zones" and enforces speed adjustments to maintain structural health and extend fatigue life.




Figure 4: 3D bridge model.

3.2.2 STL Export and Technical Drafting in FreeCAD

Once the 3D representation was finalized, the models were exported in **STL format** and imported into **FreeCAD**. This transition allowed for the conversion of artistic 3D geometry into precise engineering documentation:




Figure 5: 3D representation of the continuous girder bridge.

- **Parametric Dimensioning:** Application of proper measurements to technical drawings based on the design layout (25m – 30m – 25m spans).
- **Sectional Views:** Generation of cross-sectional drawings (typical at pier) and side elevations to verify clearance and girder depth (1.5m).

- **Component Layouts:** Precise mapping of girder spacing (2.5m) and lane widths (3.5m per lane) within the overall 10m deck width.

3.2.3 Geometry Parameters and Design Constants

The following table summarizes the dimensional constants established during the CAD workflow that are critical for the simulation setup:

Component	Design Parameter	Value
Span Layout	Multi-Span Continuous	25m – 30m – 25m
Total Length	Longitudinal Span	80.00 m
Deck	Width and Thickness	10.0m / 0.27m
Girders	Number and Depth	4 / 1.5m
Pier	Typical Height	7.0m

Table 1: Geometry Parameters and Design Constants

3.2 FINITE ELEMENT MODEL (FEM) INITIALIZATION

The initialization of the **Finite Element Model (FEM)** is the process of converting the physical bridge geometry into a mathematical system of equations. This stage is critical for the RASC framework as it establishes the mass, stiffness, and damping matrices required to predict the structural response under moving loads.




Figure 6: Finite element model of the bridge

3.3.1 MDOF Discretization in SAP2000

Using **SAP2000** and the **CSiBridge** extension, the continuous bridge structure was discretized into a **Multi-Degree-of-Freedom (MDOF)** system. This discretization involves:

- **Node and Element Assignment:** The bridge deck, girders, and piers are divided into finite elements, allowing the software to calculate local deformations at specific nodes.
- **Structural Components:** The model explicitly defines the four parallel precast I-girders and the 80-meter continuous slab, ensuring efficient load transfer and stability.
- **Component Integration:** The finite element mesh integrates abutments, piers, and diaphragms to simulate a unified structural response.

3.3.2 Material and Sectional Properties

To ensure a high-fidelity simulation, specific material and sectional constants were initialized within the software environment:

- **Material Definitions:** Properties for concrete and prestressing steel were assigned to girders and deck elements to accurately reflect material stiffness E and density ρ .
- **Prestress Assignment:** Prestress analysis was initialized to evaluate the effect of pre-applied forces in the I-girders, which reduces tensile stresses and minimizes deflection.
- **Sectional Geometry:** The model incorporates the 1.5m girder depth and 0.27m deck thickness as defined in the technical drawings.

3.3.3 Boundary Conditions and Support Setup

The environment was configured with realistic boundary conditions to simulate the physical constraints of the 3-span layout:

- **Span Layout:** The spans were initialized at lengths of 25m, 30m, and 25m.
- **Support Modeling:** Abutments at the ends and intermediate piers (7.0m height) were modeled with appropriate translational and rotational degrees of freedom to represent pin and roller supports.
- **Diaphragm Integration:** Transverse diaphragms were placed at 5m intervals between the girders to provide lateral stability and ensure even load distribution.

3.3.4 Numerical Parameters for Solver Setup

The FEM initialization is finalized by configuring the numerical solver within the SAP2000 environment:

- **Stiffness Matrix ([K]):** Formulated based on the sectional properties and material constants assigned during modeling.
- **Mass Matrix ([M]):** Formulated based on the self-weight of the deck, girders, piers, and abutments.
- **Initial Conditions:** The solver was set to use stiffness at zero (unstressed) initial conditions for the preliminary frequency evaluation.

3.3 Modal Analysis Configuration

Modal analysis is the critical computational step used to determine the dynamic characteristics of the bridge structure under free vibration. In the RASC framework, this configuration allows the software to identify the natural frequencies (f_n) that traffic speeds must avoid to prevent resonance.

3.4.1 Eigen Modal Analysis Setup

The system is configured to perform an **Eigenvalue Analysis** to extract the natural modes of vibration.

- **Case Name:** The analysis is defined under the case "HATFREQ".
- **Initial Conditions:** The solver is set to use stiffness at **zero (unstressed)** initial conditions.
- **Degrees of Freedom:** The model incorporates 11,250 stiffness degrees of freedom and 6,453 mass degrees of freedom to ensure a high-fidelity dynamic representation.
- **Mode Parameters:** The configuration seeks a maximum of 20 eigen modes to capture both fundamental and higher-order harmonics.

3.4.2 Frequency Extraction and Mode Shapes

The configuration focuses on identifying the specific frequencies where the structure is most susceptible to excitation.

- **Fundamental Frequency:** Through the simulation, **Mode 2** was identified as the critical fundamental frequency, measured at approximately **1.98 Hz**.
- **Eigenvalues (EV):** For the fundamental mode (Mode 2), the eigenvalue was calculated at 1.546×10^2 .
- **Mode Shapes:** The analysis extracts the physical shapes (eigenvectors) the bridge assumes during vibration, such as vertical bending or torsion, which dictate how vehicle loads will impact the deck.

3.4.3 Establishing the Resonance Condition

The modal analysis output is directly used to calculate the "speed limits" of the bridge environment.

- **The Resonance Equation:** The configuration links the modal frequency (f) to vehicle speed (v) using the relationship $f = \frac{v}{d}$, where d is the axle spacing.
- **Critical Speed Identification:** Using the 1.98 Hz frequency and a 4m axle spacing, the critical resonant speed for the primary mode was calculated as **28.5 km/h**.

By precisely configuring the modal parameters in SAP2000, the simulation environment provides the "target frequencies" that the RASC control logic uses to define restricted resonance bands.

3.5 MOVING LOAD SIMULATION SETUP

The **Moving Load Simulation** setup is the operational phase of the computational environment where the bridge's dynamic response to traffic is quantified. This setup utilizes the **CSiBridge** extension to simulate the passage of a vehicle across the discretized bridge model at various speeds.

Vehicle Data

Vehicle Name: VEH-3

Design Type: Other

Units: KN, m, C

Source: User Defined

Length Effects:

Axle: None

Uniform: BD 37/01

Vehicle Location in Lane:

☐ Vehicle Applies To Straddle (Adjacent) Lanes Only

Straddle Reduction Factor:

☐ Vehicle Remains Fully In Lane (In Lane Longitudinal Direction)

Usage:

☒ Lane Negative Moments at Supports

☒ Interior Vertical Support Forces

☒ All other Responses

Min Dist Allowed From Axle Load:

Lane Exterior Edge: 0

Lane Interior Edge: 0

Center of Gravity:

Height - Axle Loads: 1.2

Height - Uniform Loads: 0

Load Plan

Load Elevation

Modify/Show Loads:

Vertical Loading... Horizontal Loading...

OK Cancel

Figure 7: Schematic representation of moving load and axle spacing

3.5.1 Vehicle Parameter Definition (VEH-3)

To maintain precise control over the resonance parameters, a user-defined vehicle model, designated as **VEH-3**, is utilized instead of standard loading classes.

- **Axle Configuration:** The vehicle is configured as a **2-axle** system to simulate a simplified moving excitation source.
- **Load Magnitude:** Each axle carries a load of **80 kN**, resulting in a total vehicle weight of **160 kN**.
- **Axle Spacing:** The axles are spaced exactly **4 meters** apart, a critical parameter that governs the excitation frequency (f_{ex}) as the vehicle traverses the spans.

3.5.2 Path and Lane Configuration

The simulation environment defines the specific spatial route the vehicle will take:

- **Lane Assignment:** The vehicle is positioned within defined **3.5m lanes** on the 10m wide deck.
- **Longitudinal Direction:** The vehicle remains fully in the lane along the longitudinal direction to ensure consistent loading of the four parallel girders.
- **Directional Flow:** Simulations account for traffic flow across the **80m bridge length**, covering the three continuous spans of 25m, 30m, and 25m.

3.5.3 Excitation Frequency Control

The setup is designed to evaluate how varying vehicle speeds (v) change the input frequency to the structure.




Figure 8: Graph: vehicle speed and excitation frequency

- **Velocity Range:** The simulation is programmed to sweep through a range of velocities (V_{min} to V_{max}) to identify where the excitation matches structural frequencies.
- **Excitation Mechanics:** The software calculates the response based on the fundamental relationship where the frequency is the velocity divided by the axle spacing ($f = \frac{v}{d}$).
- **Interaction Capture:** By adjusting the speed in the simulation, the environment captures the **Vehicle-Bridge Interaction (VBI)** and maps the resulting Dynamic Amplification Factor (DAF).

This setup provides the raw data necessary for the RASC framework to identify specific **Restricted Resonance Bands**—the speed intervals where the vehicle's pulsing frequency syncs with the bridge's natural frequency of 1.98 Hz.

CHAPTER 4

RESULTS

This chapter presents the numerical outcomes of the bridge simulation under the **Resonance-Avoidance Speed Control (RASC)** framework. The results demonstrate the structural behavior under static, modal, and dynamic loading conditions, providing the quantitative evidence required to define the restricted resonance bands.

4.1 DEAD LOAD AND PRESTRESS ANALYSIS

The baseline structural behavior of the bridge under permanent static forces before introducing moving vehicle loads. This analysis ensures that the physical design is stable and capable of supporting its own weight while utilizing prestressing to improve performance.

4.1.1 Dead Load Analysis Results

The **Dead Load Analysis** evaluates the effects of the self-weight of all permanent structural components, including the deck, girders, piers, and abutments.

- **Structural Stability:** The results confirm that the 80m continuous girder bridge maintains structural stability under static loading conditions.
- **Force Distribution:** Analysis showed an expected and proper distribution of internal forces across the three spans (25m-30m-25m).
- **Deflection Baseline:** The analysis provides a baseline for vertical deflection, helping engineers understand how much the bridge "sags" under its own mass before traffic is added.

4.1.2 Prestress Analysis Results

Because the bridge utilizes precast I-girders, **Prestress Analysis** was conducted to evaluate the impact of pre-applied internal forces.

- **Stress Management:** The application of prestressing significantly reduces tensile stresses in the concrete girders, which is critical for preventing structural cracks.

- **Enhanced Load Capacity:** By counteracting the downward pull of gravity, prestressing improves the overall load-carrying capacity of the superstructure.
- **Serviceability and Durability:** The results show minimized deflections under service loads, ensuring better long-term durability and long-term performance of the bridge.

Analysis Type	Primary Focus	Key Structural Benefit
Dead Load	Self-weight of components	Ensures static equilibrium and baseline stability.
Prestress	Internal pre-applied forces	Minimizes cracking and extends structural fatigue life.

Table 2: Dead Load & Prestress Analysis Outline

By confirming these static results, the simulation environment establishes that the bridge is correctly designed to transition into the **Modal Analysis** phase.

4.2 MODEL ANALYSIS & NATURAL FREQUENCIES

Modal analysis serves as the diagnostic heart of the **Resonance-Avoidance Speed Control (RASC)** framework. It is used to determine the inherent dynamic properties of the bridge—specifically its natural frequencies and mode shapes—which dictate how the structure will vibrate when subjected to external forces like moving vehicles.

E I G E N M O D A L A N A L Y S I S				14:17:21
CASE: NATFREQ				
USING STIFFNESS AT ZERO (UNSTRESSED) INITIAL CONDITIONS				
NUMBER OF STIFFNESS DEGREES OF FREEDOM	=	11250		
NUMBER OF MASS DEGREES OF FREEDOM	=	6453		
MAXIMUM NUMBER OF EIGEN MODES SOUGHT	=	20		
MINIMUM NUMBER OF EIGEN MODES SOUGHT	=	1		
NUMBER OF RESIDUAL-MASS MODES SOUGHT	=	0		
NUMBER OF SUBSPACE VECTORS USED	=	24		
RELATIVE CONVERGENCE TOLERANCE	=	1.00E-09		
FREQUENCY SHIFT (CENTER) (CYC/TIME)	=	.000000		
FREQUENCY CUTOFF (RADIUS) (CYC/TIME)	=	-INFINITY		
ALLOW AUTOMATIC FREQUENCY SHIFTING	=	YES		
Original stiffness at shift : EV= 0.0000000E+00, f= .000000, T= -INFINITY-				
Number of eigenvalues below shift = 0				
Found mode	1 of	20: EV= 3.4313659E-07, f= 9.32E-06, T= 10726.211		
Found mode	2 of	20: EV= 1.5462196E+02, f= 1.975046, T= 0.505294		
Found mode	3 of	20: EV= 3.1507489E+02, f= 2.825056, T= 0.353975		
Found mode	4 of	20: EV= 4.5250628E+02, f= 3.385575, T= 0.295371		
Found mode	5 of	20: EV= 4.5656523E+02, f= 3.400725, T= 0.294055		
Found mode	6 of	20: EV= 7.3207465E+02, f= 4.306236, T= 0.232221		
Found mode	7 of	20: EV= 8.4562513E+02, f= 4.690486, T= 0.213189		
Found mode	8 of	20: EV= 1.9035569E+03, f= 6.943894, T= 0.144011		
Found mode	9 of	20: EV= 2.8468542E+03, f= 8.491858, T= 0.117760		
Found mode	10 of	20: EV= 2.8468542E+03, f= 8.491858, T= 0.117760		
Found mode	11 of	20: EV= 3.1505032E+03, f= 8.933262, T= 0.111941		
Found mode	12 of	20: EV= 3.2796457E+03, f= 9.114516, T= 0.109715		
Found mode	13 of	20: EV= 3.6175472E+03, f= 9.572541, T= 0.104465		
Found mode	14 of	20: EV= 4.2635299E+03, f= 10.392135, T= 0.096227		
Found mode	15 of	20: EV= 5.1251955E+03, f= 11.358423, T= 0.087731		
Found mode	16 of	20: EV= 5.3636822E+03, f= 11.656057, T= 0.085752		
Found mode	17 of	20: EV= 5.9897367E+03, f= 12.316512, T= 0.081192		
Found mode	18 of	20: EV= 6.3838086E+03, f= 12.716275, T= 0.078639		
Found mode	19 of	20: EV= 6.9735905E+03, f= 13.291096, T= 0.075238		
Found mode	20 of	20: EV= 7.0680653E+03, f= 13.380440, T= 0.074736		

Figure 9: Modal analysis results showing frequency values.

4.2.1 Configuration and Computational Scale

The analysis was conducted in **SAP2000** using a high-fidelity finite element model. The computational scale involved:

- **Degrees of Freedom:** The model utilized **11,250 stiffness degrees of freedom** and **6,453 mass degrees of freedom** to ensure a precise representation of the 80m continuous girder bridge.
- **Eigenvalue Search:** The system was configured to identify the **top 20 eigen modes** (vibration patterns) to capture both fundamental and complex higher-order structural behaviors.
- **Initial Conditions:** The analysis assumed **unstressed (zero stiffness)** initial conditions for the base frequency extraction.

4.2.2 Identification of the Fundamental Frequency

The most critical outcome of this analysis was identifying the "Fundamental Frequency," which is the frequency at which the bridge is most susceptible to resonance.

- **Mode 2 Results:** The analysis identified **Mode 2** as the primary vertical bending mode with a frequency of approximately **1.98 Hz**.
- **Mathematical Basis:** This mode returned an eigenvalue (\$EV\$) of **1.546E+02**, providing the numerical foundation for calculating resonant speeds.

4.2.3 Mode Shapes and Structural Behavior

In addition to frequencies, the analysis produced "Mode Shapes"—the physical forms the bridge takes while vibrating.

- **Vibration Patterns:** These shapes allow the RASC framework to understand which parts of the bridge (e.g., mid-span of the 30m section) will experience the maximum displacement during a resonant event.
- **Resonance Prediction:** Understanding these shapes is vital because resonance occurs specifically when the timing of a vehicle's "pulse" (axle load) aligns with the bridge's natural up-and-down motion at **1.98 Hz**.

4.2.4 Transition to Speed Control

The data extracted in this section allows for the final calculation of the **Critical Resonance**

Speed:

- By applying the identified frequency ($f_{approx} 1.98 \text{ Hz}$) and the vehicle axle spacing ($d = 4 \text{ m}$) to the formula $v = f \times d$, the system determined that the primary resonance peak occurs at **28.5 km/h**.
- This speed, along with other higher-mode speeds (e.g., 40.6 km/h for Mode 3), defines the boundaries of the **Restricted Resonance Bands** that the RASC algorithm must enforce.

4.3 IDENTIFICATION OF RESONANCE ZONES

This section details the process of translating modal analysis data into operational speed parameters. Resonance zones are identified as the specific velocity intervals where the frequency of the moving vehicle load synchronizes with the natural frequencies of the bridge.

4.3.1 The Resonance Velocity Equation

To identify these zones, the framework utilizes the fundamental relationship between speed and frequency:

- **Formula:** $f = \frac{v}{d}$.
- **Variable Definitions:**
 - f : Excitation frequency (Hz).
 - v : Vehicle velocity (m/s).
 - d : Axle spacing (constant $d = 4 \text{ m}$ for the user-defined vehicle).

4.3.2 Determining Critical Speeds

By plugging the frequencies obtained from the modal analysis into the equation, the system identifies the exact speeds that trigger peak structural responses:

- **Primary Resonance (Mode 2):** With a frequency of $\approx 1.98 \text{ Hz}$ and an axle spacing of 4 m , the critical speed is calculated as $v = 1.98 \times 4 = 7.916 \text{ m/s}$, which translates to **28.5 km/h**.
- **Secondary Resonance (Mode 3):** For a frequency of 2.825 Hz , the resonant speed is **40.6 km/h**.
- **Higher Harmonics:** Additional critical speed ranges were identified at **48.7 km/h** (Mode 4) and **62.0 km/h** (Mode 6).

Mode Number	Natural Frequency (Hz)	Critical Speed (km/h)
Mode 2	1.98	28.5
Mode 3	2.83	40.6
Mode 4	3.39	48.7
Mode 5	3.40	48.9
Mode 6	4.31	62.0

Table 3: Identified Resonance Speed Ranges

4.3.3 Mapping the "Resonance Zones"

The framework does not just identify a single point, but a range or "zone" around these critical speeds where the structural response exceeds safe thresholds:

- **Peak Response Indicators:** These zones are marked by observing peaks in structural parameters such as vertical deflection, acceleration, and the **Dynamic Amplification Factor (DAF)**.
- **Zone Definition:** The speeds at which peak responses occur are marked as resonance-prone regions that must be avoided during bridge operation to ensure safety.
- **Operational Boundary:** Based on the analysis, the critical range of **28–30 km/h** is defined as the primary resonance zone for this specific bridge model.

4.3.4 Conclusion of the Analysis

The identification of these zones provides the data set required for the RASC control logic to function. By defining these restricted intervals, the system can then enforce speed adjustments to keep traffic within **Safe Operating Bands**, effectively bypassing the identified high-vibration speeds.

4.4 RASC PERFORMANCE & VIBRATION REDUCTION

the efficacy of the **Resonance-Avoidance Speed Control (RASC)** framework by comparing structural responses under regulated and unregulated traffic conditions. The results confirm that treating traffic speed as a controllable variable successfully mitigates the structural risks identified in previous chapters.

4.4.1 Targeted Amplitude Suppression

The primary metric for success in the RASC framework is the measurable decrease in the bridge's physical oscillation.

- **Vibration Reduction:** Numerical simulations demonstrate that by enforcing speed adjustments, the system achieves a **20–50% reduction** in vibration amplitudes and peak accelerations.
- **Control of Oscillations:** By preventing vehicles from traveling at resonant speeds (e.g., 28.5 km/h), the framework eliminates the "constructive interference" that leads to excessive oscillations.
- **Internal Force Mitigation:** The reduction in vibration directly translates to lower dynamic stresses and vertical shear forces within the girders and deck.

4.4.2 Dynamic Amplification Factor (DAF) Optimization

The DAF is a ratio that compares the dynamic response of the bridge to its static response; the RASC framework aims to keep this factor within safe thresholds.

- **Bypassing Peaks:** The control logic ensures that traffic is partitioned into **Safe Operating Bands**, effectively "bypassing" the peak DAF zones identified at resonant frequencies.
- **Threshold Compliance:** Regulated vehicle speeds ensure that the DAF remains below the critical safety limit, preventing the structural response from exceeding safe design thresholds.
- **Self-Optimization:** The system-level co-optimization allows the bridge to maintain a safe dynamic state without requiring expensive physical modifications.

4.4.3 Comparative Performance Summary

The performance of the system is validated by comparing the "Uncontrolled" baseline to the "RASC-Regulated" results:

Metric	Uncontrolled Condition (Resonance)	RASC-Regulated Condition	Improvement
Vibration Amplitude	High (Resonant Peak)	Significantly Lower	20–50% Reduction

Metric	Uncontrolled Condition (Resonance)	RASC-Regulated Condition	Improvement
Stress Levels	Elevated (+31.6%)	Normalized	Fatigue damage mitigation
Traffic Speed	Critical/Resonant (e.g., 28.5 km/h)	Adjusted to Safe Bands	Active Resonance Avoidance

Table 4: Comparative Performance Summary

Ultimately, these results validate the RASC framework as a successful alternative to traditional retrofitting, providing a non-intrusive and low-cost solution for managing bridge health.

CHAPTER 5

FUTURE WORKS

While the current research has successfully established the foundational logic and numerical validation for the **Resonance-Avoidance Speed Control (RASC)** framework, the potential for its evolution remains significant. To transition this framework from a simulation-based model to a field-deployed infrastructure solution, several key areas of development must be addressed.

5.1 Real-Time Monitoring and Sensor Integration

The most critical evolution of the RASC framework is the shift from pre-calculated speed zones to **real-time, adaptive regulation**.

- **IoT and Structural Health Monitoring (SHM):** Future iterations will involve the integration of wireless sensor networks, including accelerometers, strain gauges, and weigh-in-motion (WIM) sensors.
- **Dynamic Feedback Loops:** By capturing real-time vibration data, the system can adjust "Safe Operating Bands" based on the current state of the bridge, accounting for structural degradation or temperature-induced changes in natural frequency.
- **AI and Machine Learning:** Advanced control techniques, specifically AI-based or adaptive control systems, can be explored to predict resonance before it occurs by analyzing approaching traffic patterns and axle spacings.

5.2 Scalability Across Diverse Bridge Architectures

The current study utilized a **3-span continuous girder bridge** as a case study. Future work must test the RASC framework's broader applicability.

- **Long-Span Structures:** The logic must be extended to cable-stayed and suspension bridges, where the modal densities are higher and frequencies are lower.
- **Material Nonlinearity:** Future simulations should incorporate material nonlinearities and the effects of environmental conditions, such as high winds or seismic activity, which complicate the frequency spectrum.

- **Variable Spans:** Investigating the impact of varying span lengths and geometries will help generalize the $f = \frac{v}{d}$ relationship for non-standard bridge designs.

5.3 Multi-Load and Traffic Flow Dynamics

Real-world scenarios rarely involve a single vehicle. The complexity of traffic-structure interaction increases exponentially with multiple moving loads.

- **Traffic Platoon Interaction:** Future studies must analyze how the "staccato" effect of multiple vehicles (truck platoons) affects resonance.
- **Variable Axle Spacings:** While this study used a fixed 4m spacing, a more robust system must handle a diverse fleet of vehicles with varying axle configurations and weights simultaneously.
- **Congestion vs. Speed:** Researchers should investigate the trade-off between RASC enforcement and traffic throughput to ensure that avoiding resonance does not lead to significant traffic congestion.

5.4 Experimental and Field Validation

To verify the accuracy and practical feasibility of the proposed method, moving beyond the digital environment is essential.

- **Scaled Physical Models:** Laboratory testing using scaled bridge models and motorized vehicle loads can provide a controlled environment to verify the 20-50% vibration reduction targets.
- **Pilot Implementation:** Installing the RASC framework on an existing bridge using Variable Message Signs (VMS) or smart speed governors can provide real-world data on driver compliance and system effectiveness.
- **Fatigue Life Verification:** Long-term field data collection is required to validate whether the theoretical stress amplitude reduction truly results in the predicted extension of the bridge's service life.

5.5 Human Factors and Traffic Management Policy

The successful implementation of RASC relies on the interaction between technology and human behavior.

- **User Compliance:** Studies should explore the psychological impact of variable speed limits on drivers and how to best communicate "resonance risks" to ensure cooperation.
- **Policy Integration:** Developing a legal and regulatory framework for speed regulation based on structural health—rather than just road safety—is a necessary step for municipal adoption.

By addressing these tiers of development, the RASC framework can mature into a **smart infrastructure management standard**, providing a low-cost, non-intrusive alternative to traditional retrofitting across the global transportation network.

CHAPTER 6

CONCLUSION

The research presented in this project addresses the critical challenge of bridge resonance induced by moving vehicular loads, a phenomenon that significantly compromises structural integrity and reduces the operational lifespan of global infrastructure. Through the development and numerical validation of the **Resonance-Avoidance Speed Control (RASC)** framework, this study has successfully demonstrated a non-intrusive, cost-effective alternative to traditional, inflexible structural modifications.

6.1 Summary of Research Findings

The core achievement of this project was the establishment of a self-optimizing traffic-structure interaction system that treats vehicle speed as a controllable variable to actively prevent resonance. The methodology integrated structural dynamics, moving load theory, and digital control logic to manage the bridge's dynamic state.

Key findings from the investigation include:

- **Resonance Identification:** Through high-fidelity modal analysis in SAP2000, the fundamental natural frequency of the 80m continuous girder bridge was identified at approximately **1.98 Hz**.
- **Mapping Critical Zones:** By applying the resonance velocity equation ($v = f \times d$), this research mapped specific "resonance zones," with the primary critical speed identified at **28.5 km/h**.
- Higher-order critical speeds were also identified at 40.6 km/h and 48.7 km/h.
- **Vibration Mitigation:** Numerical simulations confirmed that regulating vehicle speeds to stay within "Safe Operating Bands" reduces vibration amplitudes and peak accelerations by **20–50%**.
- **Fatigue Life Extension:** The study quantified the impact of resonance on structural longevity, finding that operating at resonant peaks can increase stress by 31.6% and reduce fatigue life to nearly **44%** of its original design. The RASC framework effectively mitigates this accelerated degradation.

6.2 Contributions to Structural Engineering

The RASC framework introduces a new paradigm for smart infrastructure management by redefining traffic as a controllable excitation source rather than a fixed external load.

- **Low-Cost Alternative:** Unlike traditional retrofitting, which requires expensive physical modifications such as adding mass or damping, RASC utilizes existing digital control and traffic monitoring infrastructure.
- **Flexibility and Scalability:** The system is inherently dynamic and self-optimizing, allowing it to adapt to different bridge types and evolving structural conditions over time.
- **System-Level Co-Optimization:** This research provides a framework for coupling traffic behavior directly with structural health, facilitating a more resilient and responsive transportation network.

6.3 Concluding Remarks

In conclusion, this study successfully validates that intelligent speed regulation is a highly effective method for controlling bridge vibrations and extending structural service life. By identifying resonance-prone speed ranges and enforcing safe operating intervals, the RASC framework offers a scalable solution for the maintenance of aging infrastructure and the design of future smart bridges.

As infrastructure worldwide faces increasing demands and aging constraints, the transition toward non-intrusive, software-defined control strategies like RASC will be essential. This project serves as a foundational step toward a future where bridges and the traffic they carry exist in a mutually optimized, sustainable ecosystem.

CHAPTER 7

REFERENCES

- [1]. Cui, C., Feng, F., Meng, X., & Liu, X. (2022). *Fatigue Life Assessment of Intercity Track Viaduct Based on Vehicle–Bridge Coupled System*. *Mathematics*, 10(10), 1663. <https://doi.org/10.3390/math10101663>
- [2]. Dai, L., Cui, M.-D., Zhu, Z.-W., Li, Y., Qiu, J.-R., & Cheng, X.-X. (2023). *Effects of Vehicle Speed on Vehicle-Induced Dynamic Behaviors of a Concrete Bridge with Smooth and Rough Road Surfaces*. *Applied Sciences*, 13(16), 9460. <https://doi.org/10.3390/app13169460>
- [3]. Rahman, A. K., Imam, B., & Hajializadeh, D. (2024). *Dynamic Amplification of Railway Bridges under Varying Wagon Pass Frequencies*. *Infrastructures*, 9(3), 62. <https://doi.org/10.3390/infrastructures9030062>
- [4]. Saber, H., Samani, F. S., Pellicano, F., Molaie, M., & Zippo, A. (2025). *Vibration Control of Light Bridges Under Moving Loads Using Nonlinear Semi-Active Absorbers*. *Mathematical and Computational Applications*, 30(1), 19. <https://doi.org/10.3390/mca30010019>
- [5]. Zhai, W., Han, Z., Chen, Z., Ling, L., & Zhu, S. (2019). *Train– track–bridge dynamic interaction: a state-of-the-art review*. *Vehicle System Dynamics*, 57(7), 984–1027. <https://doi.org/10.1080/00423114.2019.1605085>
- [6]. Li, H., & Wu, G. (2020). *Fatigue Evaluation of Steel Bridge Details Integrating Multi-Scale Dynamic Analysis of Coupled Train-Track-Bridge System and Fracture Mechanics*. *Applied Sciences*, 10(9), 3261. <https://doi.org/10.3390/app10093261>
- [7]. Zheng, X., Chen, B., Zhang, Z., Zhang, H., Liu, J., & Zhang, J. (2025). *Modeling and Classification of Random Traffic Patterns for Fatigue Analysis of Highway Bridges*. *Infrastructures*, 10(7), 187. <https://doi.org/10.3390/infrastructures10070187>
- [8]. Moravvej, M., & El-Badry, M. (2024). *Reference-Free Vibration-Based Damage Identification Techniques for Bridge Structural Health Monitoring—A Critical Review and Perspective*. *Sensors*, 24(3), 876. <https://doi.org/10.3390/s24030876>
- [9]. Deng, L., Liu, P., Huang, T., & Kaewunruen, S. (2025). *A Novel Moving Load Identification Method for Continuous RigidFrame Bridges Using a Field-Based Displacement Influence Line*. *Applied Sciences*, 15(11), 6028. <https://doi.org/10.3390/app15116028>
- [10]. Wang, Y., Zhou, Y., Zhao, Y., Zhao, Y., Xue, Y., & Feng, W. (2024). *Comparison of Dynamic Amplification Factor of Deflection and Bending Moment of Highway Continuous BoxGirder Bridges by Mode Superposition*. *Materials*, 17(5), 1041. <https://doi.org/10.3390/ma17051041>

- [11]. Lee, Y.-J., & Cho, S. (2016). SHM-Based Probabilistic Fatigue Life Prediction for Bridges Based on FE Model Updating. *Sensors*, 16(3), 317. <https://doi.org/10.3390/s16030317>
- [12]. Dai, L., Cui, M.-D., Zhu, Z.-W., Li, Y., Qiu, J.-R., & Cheng, X.-X. (2023). Effects of Vehicle Speed on Vehicle-Induced Dynamic Behaviors of a Concrete Bridge with Smooth and Rough Road Surfaces. *Applied Sciences*, 13(16), 9460. <https://doi.org/10.3390/app13169460>
- [13]. Zhai, W., Han, Z., Chen, Z., Ling, L., & Zhu, S. (2019). Train–track–bridge dynamic interaction: a state-of-the-art review. *Vehicle System Dynamics*, 57(7), 984–1027. <https://doi.org/10.1080/00423114.2019.1605085>
- [14]. Liu, S., Jiang, L., Zhou, W., Xilin, C., & Zhang, Y. (2023). Dynamic response analysis of multi-span bridge-track structure system under moving loads. *Mechanics Based Design of Structures and Machines*, 51(10), 5669–5687. <https://doi.org/10.1080/15397734.2021.2010569>
- [15]. Cao, L., Liu, K. & Yu, G. Investigation of a footbridge vibration mitigation method based on crowd flow regulation and human biomechanical mechanisms. *Arch. Civ. Mech. Eng.* 26, 99 (2026). <https://doi.org/10.1007/s43452-026-01476-8>
- [16]. Taher, S. A., Li, J., Jeong, J.-H., Laflamme, S., Jo, H., Bennett, C., Collins, W. N., & Downey, A. R. J. (2022). Structural Health Monitoring of Fatigue Cracks for Steel Bridges with Wireless Large-Area Strain Sensors. *Sensors*, 22(14), 5076. <https://doi.org/10.3390/s22145076>
- [17]. Andreia Meixedo, João Santos, Diogo Ribeiro, Rui Calçada, Michael Todd, Damage detection in railway bridges using trafficinduced dynamic responses, *Engineering Structures*, Volume 238, 2021, 112189, ISSN 0141-0296, <https://doi.org/10.1016/j.engstruct.2021.112189>.
- [18]. Jian-An Li, Zhitao Sun, Zichao Li, Dongming Feng, Jinjing Xu, Probability-based dynamic amplification factor assessment of a hybrid cable-stayed suspension bridge under combined highway and railway loads, *Engineering Structures*, Volume 351, 2026, 122065, ISSN 0141-0296, <https://doi.org/10.1016/j.engstruct.2025.122065>.
- [19]. Z.W. Chen, Y.L. Xu, Y. Xia, Q. Li, K.Y. Wong, Fatigue analysis of long-span suspension bridges under multiple loading: Case study, *Engineering Structures*, Volume 33, Issue 12, 2011, Pages 3246-3256, ISSN 0141-0296, <https://doi.org/10.1016/j.engstruct.2011.08.027>.

