

Homework 1
Computer Science
Spring 2017
B351

Steven Myers

January 29, 2017

All the work herein is mine.

Answers

1. Here are the definitions for the terms listed in Problem 3.10:
 - (a) **State** - A particular assignment of value to all variables for a given situation.
 - (b) **State space** - All of the possible assignments of values to variable in a scenario.
 - (c) **Search tree** - An arrangement of states such that no state is repeated twice when traversing all states.
 - (d) **Search node** - A particular node in a search tree that has a cost and ingoing or outgoing paths. Each node contains the cost of the current node, its data (state values), and the cost of visiting other accessible states.
 - (e) **Goal** - A final search node with an ideal or target state that we want to obtain to resolve a problem.
 - (f) **Action** - An operation that results in a change of state.
 - (g) **Transition model** - The process of moving from one state to another when an action is applied.
 - (h) **Branching factor** - The maximum number of "branches" or pathways that some search node can have. This is used to limit the search space and prevent a machine from running out of memory before resolving a problem when the search space is too large.
2. A state space where iterative deepning search would perform worse than DFS is one in which the following are true:
 - (a) The branching factor is large.
 - (b) The depth of each branch is shallow, and the goal node exists in a branch which is deeper than the others.

A state space such as Figure 1 could produce a circumstance where DFS would perform significantly better than iterative deepening search.




Figure 1: Attach a goal node **S** as a node **O**'s right child. (Image taken from textbook figure 3.16 on page 86, Russel & Norvig)

3. Yes, the graph is consistent. Here are the statements for each node and its successors:
 - (a) AB: $1 \leq 6$
 - (b) AC: $1 \leq 8$
 - (c) BC: $4 \leq 4$