

Assignment 6
Computer Science
Fall 2017
B461

Steven Myers

October 29, 2017

Answers

1. (a)

$$\pi_{sid,bookno}(\sigma_{Buys.bookno \neq Buys2.bookno \wedge Student.name = 'Eric' \wedge Buys.bookno \neq '2010'}(Student \times Buys \times Buys2))$$

(b) i. Original Query

```
SELECT DISTINCT b.bookno, b.title
FROM book b, student s
WHERE b.price = SOME(select b1.price
                      from buys t, book b1
                      where b1.price > 50 and
                      s.sid = t.sid and
                      t.bookno = b1.bookno);
```

ii. Convert from using SOME to an exists statement

```
SELECT DISTINCT b.bookno, b.title
FROM book b, student s
WHERE EXISTS(select 1
             from buys t, book b1
             where b1.price > 50 and
             s.sid = t.sid and
             t.bookno = b1.bookno);
```

iii. Push down student s relation into subquery as $s1$.

```
SELECT DISTINCT b.bookno, b.title
FROM book b, student s
WHERE EXISTS(select 1
             from buys t, book b1, student s1
             where b1.price > 50 and
             s1.sid = t.sid and
             t.bookno = b1.bookno);
```

iv. The inner query can be translated as:

$$\pi_{b1.price}(\sigma_{b1.price > 50 \wedge s1.sid = t.sid \wedge t.bookno = b1.bookno}(T \times B1 \times S1))$$

v. Finally, we perform the semi-join with the inner query and the student and book relation:

$$\pi_{b.bookno, b.title}(S \times B) \ltimes \pi_{b1.price}(\sigma_{b1.price > 50 \wedge s1.sid = t.sid \wedge t.bookno = b1.bookno}(T \times B1 \times S1))$$

(c) i. Original Query

```
SELECT b.bookno
FROM book b
WHERE b.bookno IN
(SELECT b1.bookno FROM book b1 WHERE b1.price > 50)
UNION
(SELECT c.bookno FROM cites c);
```

ii. RA representation of inner query (simple translation)

$$\pi_{bookno}(\sigma_{price>50}(book)) \cup \pi_{bookno}(cites)$$

iii. Since the IN predicate is equivalent to saying that there exists one bookno for which a bookno in the inner query matches, we can use the semi join

$$\pi_{bookno}(book) \ltimes \pi_{bookno}(\sigma_{price>50}(book)) \cup \pi_{bookno}(cites)$$

(d) i. Original Query

```
SELECT b.bookno FROM book b
WHERE b.price >= 80 and
NOT EXISTS(SELECT b1.bookno
            FROM book b1
            WHERE b1.Price > b.Price);
```

ii. First, push down book b relation into subquery as book b2.

```
SELECT b.bookno FROM book b
WHERE b.price >= 80 and
NOT EXISTS(SELECT b1.bookno
            FROM book b1, book b2
            WHERE b1.Price > b2.Price);
```

iii. Now, we can properly translate the inner query as:

$$\pi_{b1.bookno}(\sigma_{b1.price>b2.price}(B1 \times B2))$$

iv. To preserve the semantics of the original outer query, we need to perform an anti-semi join:

$$\pi_{b.bookno}(\sigma_{b.price \geq 80}(B \bar{\ltimes} \pi_{b1.bookno}(\sigma_{b1.price>b2.price}(B1 \times B2))))$$

- (e) i. Original query:

```
SELECT s.sid
FROM Student s
WHERE EXISTS(SELECT 1
              FROM Book b
              WHERE b.price > 50 AND
                    b.bookno IN (SELECT t.bookno
                                FROM Buys t
                                WHERE s.sid = t.sid AND
                                      s.sname = 'Eric'))
```

- ii. First, push down parameterized values in the inner-most query. We will push down the student s relation as $s1$.

```
SELECT s.sid
FROM Student s
WHERE EXISTS(SELECT 1
              FROM Book b
              WHERE b.price > 50 AND
                    b.bookno IN (SELECT t.bookno
                                FROM Buys t, Student s1
                                WHERE s1.sid = t.sid AND
                                      s1.sname = 'Eric'))
```

- iii. Next, convert the first inner subquery IN expression into an EXISTS statement. We can do this by pushing the book relation completely into the inner most subquery and adding its conditions

```
SELECT s.sid
FROM Student s
WHERE EXISTS(SELECT t.bookno
              FROM Buys t, Student s1, Book b
              WHERE s1.sid = t.sid AND
                    b.price > 50 AND
                    b.bookno = t.bookno
                    s1.sname = 'Eric')
```

- iv. We can translate the inner query as:

$$\pi_{t.bookno}(\sigma_{s1.sid=t.sid \wedge b.price>50 \wedge b.bookno=t.bookno \wedge s1.sname='Eric'}(S1 \times B \times T))$$

- v. Finally, we can translate our outer exists expression with a semijoin and project the student sid.

$$\pi_{s.sid}(S \ltimes \pi_{t.bookno}(\sigma_{s1.sid=t.sid \wedge b.price>50 \wedge b.bookno=t.bookno \wedge s1.sname='Eric'}(S1 \times B \times T)))$$

- (f) i. Original query:

```
SELECT s1.sid, s2.sid
FROM student s1, student s2
WHERE s1.sid <> s2.sid AND
      NOT EXISTS(SELECT 1
                  FROM Buys t1
                  WHERE t1.sid = s1.sid AND
                        t1.bookno NOT IN (SELECT t2.bookno
                                          FROM Buys t2
                                          WHERE t2.sid = s2.sid));
```

- ii. ...