

Introduction to Machine Learning for Social Science

Class 5: Logistic Regression

Rochelle Terman

Postdoctoral Fellow
Center for International Security Cooperation
Stanford University

January 18th, 2018

Updates:

HW 2: Assigned 1/23, Due 1/30





Goal: predict Iraq vote (probability of yes, classify senators as for and against)

Method: Linear Probability Model & Logistic regression

Evaluation:

- 1) Accuracy
- 2) Precision
- 3) Recall

Two Estimation Goals

Estimate:

Two Estimation Goals

Estimate:

- Probability of voting yes: $\Pr(\widehat{\text{Vote}_i} = 1 | \mathbf{x}_i)$

Two Estimation Goals

Estimate:

- Probability of voting yes: $\widehat{\Pr(\text{Vote}_i = 1 | \mathbf{x}_i)}$
- Classification of vote: $\widehat{\text{Vote}_i} = I(\widehat{\Pr(\text{Vote}_i = 1 | \mathbf{x}_i)} > t)$, where t is a threshold

Linear Probability Model

Linear Probability Model

$$\text{Vote}_i = \beta \cdot \mathbf{x}_i + \epsilon_i$$

Linear Probability Model

$$\begin{aligned}\text{Vote}_i &= \beta \cdot \mathbf{x}_i + \epsilon_i \\ \Pr(\widehat{\text{Vote}_i} = 1 | \mathbf{X}_i) &= \hat{\beta} \cdot \mathbf{x}_i\end{aligned}$$

Linear Probability Model

$$\begin{aligned}\text{Vote}_i &= \beta \cdot \mathbf{x}_i + \epsilon_i \\ \Pr(\widehat{\text{Vote}_i} = 1 | \mathbf{X}_i) &= \hat{\beta} \cdot \mathbf{x}_i \\ \widehat{\text{Vote}_i} &= 1 \text{ if } \hat{\beta} \cdot \mathbf{x}_i > t\end{aligned}$$

Linear Probability Model

$$\begin{aligned}\text{Vote}_i &= \beta \cdot \mathbf{x}_i + \epsilon_i \\ \Pr(\widehat{\text{Vote}_i} = 1 | \mathbf{X}_i) &= \hat{\beta} \cdot \mathbf{x}_i \\ \widehat{\text{Vote}_i} &= 1 \text{ if } \hat{\beta} \cdot \mathbf{x}_i > t \\ \widehat{\text{Vote}_i} &= 0 \text{ if } \hat{\beta} \cdot \mathbf{x}_i \leq t\end{aligned}$$

Linear Probability Model

$$\begin{aligned}\text{Vote}_i &= \beta \cdot \mathbf{x}_i + \epsilon_i \\ \Pr(\widehat{\text{Vote}_i} = 1 | \mathbf{X}_i) &= \hat{\beta} \cdot \mathbf{x}_i \\ \widehat{\text{Vote}_i} &= 1 \text{ if } \hat{\beta} \cdot \mathbf{x}_i > t \\ \widehat{\text{Vote}_i} &= 0 \text{ if } \hat{\beta} \cdot \mathbf{x}_i \leq t\end{aligned}$$

(Potential) Problems with Linear Probability Model

- Probabilities greater than 1, less than 0
- Potentially implausible relationship between covariates and response

(Potential) Problems with Linear Probability Model

- Probabilities greater than 1, less than 0
- Potentially implausible relationship between covariates and response

Solution: **Logistic Regression**: $0 \leq f(X) \leq 1$

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

Some rules of logarithms

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

Some rules of logarithms

- $\exp(\log(a)) = e^{\log(a)} = a$

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

Some rules of logarithms

- $\exp(\log(a)) = e^{\log(a)} = a$
- $\log(a \times b) = \log(a) + \log(b)$

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

Some rules of logarithms

- $\exp(\log(a)) = e^{\log(a)} = a$
- $\log(a \times b) = \log(a) + \log(b)$
- $\log(\frac{a}{b}) = \log(a) - \log(b)$

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

Some rules of logarithms

- $\exp(\log(a)) = e^{\log(a)} = a$
- $\log(a \times b) = \log(a) + \log(b)$
- $\log(\frac{a}{b}) = \log(a) - \log(b)$
- $\log(a^b) = b \log(a)$

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

Some rules of logarithms

- $\exp(\log(a)) = e^{\log(a)} = a$
- $\log(a \times b) = \log(a) + \log(b)$
- $\log(\frac{a}{b}) = \log(a) - \log(b)$
- $\log(a^b) = b \log(a)$
- $\log(1) = 0$

A Brief Reminder About (Natural) Logarithms

Logarithm \log is a **class** of functions.

- $\log_e z = x$ if $e^x = z$.
- We'll call \log_e **natural logarithm**. And we'll assume $\log = \log_e$
- $\log e = 1$ (because $e^1 = e$)
- $\log_{10} 1000 = 3$ (because $10^3 = 1000$)

Some rules of logarithms

- $\exp(\log(a)) = e^{\log(a)} = a$
- $\log(a \times b) = \log(a) + \log(b)$
- $\log(\frac{a}{b}) = \log(a) - \log(b)$
- $\log(a^b) = b \log(a)$
- $\log(1) = 0$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$\text{Vote}_i \sim \text{Bernoulli}(p_i)$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$\text{Vote}_i \sim \text{Bernoulli}(p_i)$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$$\text{Vote}_i \sim \text{Bernoulli}(p_i)$$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

$$\log \left(\frac{\hat{p}_i}{1 - \hat{p}_i} \right) = \beta \cdot \mathbf{x}_i$$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$$\text{Vote}_i \sim \text{Bernoulli}(p_i)$$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

$$\log \left(\frac{\hat{p}_i}{1 - \hat{p}_i} \right) = \beta \cdot \mathbf{x}_i$$

$$\hat{p}_i = \frac{\exp(\beta \cdot \mathbf{x}_i)}{1 + \exp(\beta \cdot \mathbf{x}_i)}$$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$$\text{Vote}_i \sim \text{Bernoulli}(p_i)$$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

$$\log \left(\frac{\hat{p}_i}{1 - \hat{p}_i} \right) = \beta \cdot \mathbf{x}_i$$

$$\begin{aligned} \hat{p}_i &= \frac{\exp(\beta \cdot \mathbf{x}_i)}{1 + \exp(\beta \cdot \mathbf{x}_i)} \\ &= \frac{1}{1 + \exp(-\beta \cdot \mathbf{x}_i)} \end{aligned}$$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$$\text{Vote}_i \sim \text{Bernoulli}(p_i)$$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

$$\log \left(\frac{\hat{p}_i}{1 - \hat{p}_i} \right) = \beta \cdot \mathbf{x}_i$$

$$\begin{aligned} \hat{p}_i &= \frac{\exp(\beta \cdot \mathbf{x}_i)}{1 + \exp(\beta \cdot \mathbf{x}_i)} \\ &= \frac{1}{1 + \exp(-\beta \cdot \mathbf{x}_i)} \end{aligned}$$

Important functions:

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$$\text{Vote}_i \sim \text{Bernoulli}(p_i)$$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

$$\log \left(\frac{\hat{p}_i}{1 - \hat{p}_i} \right) = \beta \cdot \mathbf{x}_i$$

$$\begin{aligned} \hat{p}_i &= \frac{\exp(\beta \cdot \mathbf{x}_i)}{1 + \exp(\beta \cdot \mathbf{x}_i)} \\ &= \frac{1}{1 + \exp(-\beta \cdot \mathbf{x}_i)} \end{aligned}$$

Important functions:

$$\text{odds}(p) = \frac{p}{1 - p}$$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$$\text{Vote}_i \sim \text{Bernoulli}(p_i)$$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

$$\log \left(\frac{\hat{p}_i}{1 - \hat{p}_i} \right) = \beta \cdot \mathbf{x}_i$$

$$\begin{aligned} \hat{p}_i &= \frac{\exp(\beta \cdot \mathbf{x}_i)}{1 + \exp(\beta \cdot \mathbf{x}_i)} \\ &= \frac{1}{1 + \exp(-\beta \cdot \mathbf{x}_i)} \end{aligned}$$

Important functions:

$$\text{odds}(p) = \frac{p}{1 - p}$$

$$\log \text{ odds or logit}(p) = \log \left(\frac{p}{1 - p} \right)$$

Call $p_i = \Pr(\text{Vote}_i = 1 | \mathbf{x}_i)$

$$\text{Vote}_i \sim \text{Bernoulli}(p_i)$$

$$\hat{p}_i = \beta \cdot \mathbf{x}_i$$

$$\log \left(\frac{\hat{p}_i}{1 - \hat{p}_i} \right) = \beta \cdot \mathbf{x}_i$$

$$\begin{aligned} \hat{p}_i &= \frac{\exp(\beta \cdot \mathbf{x}_i)}{1 + \exp(\beta \cdot \mathbf{x}_i)} \\ &= \frac{1}{1 + \exp(-\beta \cdot \mathbf{x}_i)} \end{aligned}$$

Important functions:

$$\text{odds}(p) = \frac{p}{1 - p}$$

$$\log \text{ odds or logit}(p) = \log \left(\frac{p}{1 - p} \right)$$

$$\text{logistic function or logit}^{-1}(a) = \frac{1}{1 + \exp(-a)}$$

R Code (Section 3)

How do we interpret β ?

Linear Regression: $\beta_1 \rightsquigarrow$ average change in Y with one-unit increase in X_1 .

How do we interpret β ?

Linear Regression: $\beta_1 \rightsquigarrow$ average change in Y with one-unit increase in X_1 .

Logistic Regression: $\beta_1 \rightsquigarrow$ average change in *log odds* with one-unit increase in X_1

How do we interpret β ?

Linear Regression: $\beta_1 \rightsquigarrow$ average change in Y with one-unit increase in X_1 .

Logistic Regression: $\beta_1 \rightsquigarrow$ average change in *log odds* with one-unit increase in X_1

- Non-linear relationship between X and $p(X)$.

How do we interpret β ?

Linear Regression: $\beta_1 \rightsquigarrow$ average change in Y with one-unit increase in X_1 .

Logistic Regression: $\beta_1 \rightsquigarrow$ average change in *log odds* with one-unit increase in X_1

- Non-linear relationship between X and $p(X)$.
- Amount that $p(X)$ changes due to one-unit change in X will depend on current value of X .

How do we interpret β ?

Linear Regression: $\beta_1 \rightsquigarrow$ average change in Y with one-unit increase in X_1 .

Logistic Regression: $\beta_1 \rightsquigarrow$ average change in *log odds* with one-unit increase in X_1

- Non-linear relationship between X and $p(X)$.
- Amount that $p(X)$ changes due to one-unit change in X will depend on current value of X .
- Regardless of value of X , if $\beta_1 > 0$, then increasing $X \rightsquigarrow$ increasing $p(X)$.

How do we interpret β ?

Linear Regression: $\beta_1 \rightsquigarrow$ average change in Y with one-unit increase in X_1 .

Logistic Regression: $\beta_1 \rightsquigarrow$ average change in *log odds* with one-unit increase in X_1

- Non-linear relationship between X and $p(X)$.
- Amount that $p(X)$ changes due to one-unit change in X will depend on current value of X .
- Regardless of value of X , if $\beta_1 > 0$, then increasing $X \rightsquigarrow$ increasing $p(X)$.
- **odds ratio:** e^{β_1} , represents how the *odds* change with a 1 unit increase in β_1 holding all other variables constant. Remains constant for any value of X .

Fitting a Logistic Regression Model

Maximum Likelihood Estimation:

- O : Observed outcomes

Fitting a Logistic Regression Model

Maximum Likelihood Estimation:

- O : Observed outcomes
- θ : Parameters describing the data generating process.

Fitting a Logistic Regression Model

Maximum Likelihood Estimation:

- O : Observed outcomes
- θ : Parameters describing the data generating process.
- Probability: $P(O|\theta)$.

Fitting a Logistic Regression Model

Maximum Likelihood Estimation:

- O : Observed outcomes
- θ : Parameters describing the data generating process.
- Probability: $P(O|\theta)$. But we don't know θ !

Fitting a Logistic Regression Model

Maximum Likelihood Estimation:

- O : Observed outcomes
- θ : Parameters describing the data generating process.
- Probability: $P(O|\theta)$. But we don't know θ !
- Likelihood: $L(\theta|O) = P(O|\theta)$

Fitting a Logistic Regression Model

Maximum Likelihood Estimation:

- O : Observed outcomes
- θ : Parameters describing the data generating process.
- Probability: $P(O|\theta)$. But we don't know θ !
- Likelihood: $L(\theta|O) = P(O|\theta)$
- Find value of coefficients, β^{\max} that maximize likelihood \rightsquigarrow numerical optimization

Fitting a Logistic Regression Model

Maximum Likelihood Estimation:

- O : Observed outcomes
- θ : Parameters describing the data generating process.
- Probability: $P(O|\theta)$. But we don't know θ !
- Likelihood: $L(\theta|O) = P(O|\theta)$
- Find value of coefficients, β^{\max} that maximize likelihood \rightsquigarrow numerical optimization

We will use the package `glm` to fit the model

Predicting with a Logistic Regression

$$\begin{aligned}\hat{p}_i &= \frac{1}{1 + \exp(-\hat{\beta}\mathbf{x}_i)} \\ \widehat{\text{Vote}}_i &= 1 \text{ if } \hat{p}_i > t \\ \widehat{\text{Vote}}_i &= 0 \text{ if } \hat{p}_i \leq t\end{aligned}$$

R Code

Evaluating In Sample Model Fit

- Evaluate fit with **gold standard** data
- In sample: dependent variable of model
- Out of sample: **held out** data, “test” data

Assessing Classification Performance

Measures of classification performance

Guess	Actual Label	
	Yea	Nay
Yea	True Yea	False Yea
Nay	False Nay	True Nay

Assessing Classification Performance

Measures of classification performance

Guess	Actual Label	
	Yea	Nay
Yea	True Yea	False Yea
Nay	False Nay	True Nay

$$\text{Accuracy} = \frac{\text{TrueYea} + \text{TrueNay}}{\text{TrueYea} + \text{TrueNay} + \text{FalseYea} + \text{FalseNay}}$$

Assessing Classification Performance

Measures of classification performance

Guess	Actual Label	
	Yea	Nay
Yea	True Yea	False Yea
Nay	False Nay	True Nay

$$\text{Accuracy} = \frac{\text{TrueYea} + \text{TrueNay}}{\text{TrueYea} + \text{TrueNay} + \text{FalseYea} + \text{FalseNay}}$$

$$\text{Precision} = \frac{\text{True Yea}}{\text{True Yea} + \text{False Yea}}$$

Assessing Classification Performance

Measures of classification performance

Guess	Actual Label	
	Yea	Nay
Yea	True Yea	False Yea
Nay	False Nay	True Nay

$$\text{Accuracy} = \frac{\text{TrueYea} + \text{TrueNay}}{\text{TrueYea} + \text{TrueNay} + \text{FalseYea} + \text{FalseNay}}$$

$$\text{Precision} = \frac{\text{True Yea}}{\text{True Yea} + \text{False Yea}}$$

$$\text{Recall} = \frac{\text{True Yea}}{\text{True Yea} + \text{False Nay}}$$

Assessing Classification Performance

Measures of classification performance

Guess	Actual Label	
	Yea	Nay
Yea	True Yea	False Yea
Nay	False Nay	True Nay

$$\text{Accuracy} = \frac{\text{TrueYea} + \text{TrueNay}}{\text{TrueYea} + \text{TrueNay} + \text{FalseYea} + \text{FalseNay}}$$

$$\text{Precision} = \frac{\text{True Yea}}{\text{True Yea} + \text{False Yea}}$$

$$\text{Recall} = \frac{\text{True Yea}}{\text{True Yea} + \text{False Nay}}$$

$$F = \frac{2 \times \text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

R Code

Key Terms:

- Classification
- Linear Probability Model
- Logit function and logit inverse function, Logistic regression
- Accuracy and the Precision/Recall Tradeoff

Key Techniques and R Functions

- `glm`
- Natural logarithm `log`
- `subset` , `cbind`
- `table`