

# Design and Analysis of Algorithms

## Part I: Divide and Conquer

### Lecture 4: Maximum Contiguous Subarray Problem



**Ke Xu and Yongxin Tong**

**(许可 与 童咏昕)**

**School of CSE, Beihang University**

# Outline

---

- Introduction to Part I
- Maximum Contiguous Subarray Problem
  - Problem definition
  - A brute force algorithm
  - A data-reuse algorithm
  - A divide-and-conquer algorithm
  - Analysis of the divide-and-conquer algorithm

# Introduction to Part I

---

- **Divide-and-conquer** (D&C) is an important algorithm design paradigm.
  - **Divide**  
Dividing a given problem into two or more subproblems (ideally of approximately equal size)
  - **Conquer**  
Solving each subproblem (directly if small enough or **recursively**)
  - **Combine**  
Combining the solutions of the subproblems into a global solution

# Introduction to Part I

---

- In Part I, we will illustrate Divide-and-Conquer using several examples:
  - Maximum Contiguous Subarray (最大子数组)
  - Counting Inversions (逆序计数)
  - Polynomial Multiplication (多项式乘法)
  - QuickSort and Partition (快速排序与划分)
  - Randomized Selection (随机化选择)
  - Lower Bound for Sorting (基于比较的排序下界)

# Outline

---

- Introduction to Part I
- **Maximum Contiguous Subarray Problem**
  - Problem definition
  - A brute force algorithm
  - A data-reuse algorithm
  - A divide-and-conquer algorithm
  - Analysis of the divide-and-conquer algorithm

# Maximum Contiguous Subarray (MCS) Problem

## ACME Corp<sup>1</sup> – PROFIT HISTORY

Year	1	2	3	4	5	6	7	8	9
Profit M\$	-3	2	1	-4	5	2	-1	3	-1

Between years 1 and 9:

- ACME earned  $-3 + 2 + 1 - 4 + 5 + 2 - 1 + 3 - 1 = 4$  M\$

Between years 2 and 6:

- ACME earned  $2 + 1 - 4 + 5 + 2 = 6$  M\$

Between years 5 and 8:

- ACME earned  $5 + 2 - 1 + 3 = 9$  M\$

如果所有数组元素都是非负数，整个数组和肯定是最大

Problem: Find the span of years in which ACME earned the **most**

Answer: Year 5-8, 9 M\$

<sup>1</sup>A Company that Makes Everything

# Formal Definition

---

- **Input**: An array of reals  $A[1...n]$
- The **value** of **subarray**  $A[i...j]$  is

$$V(i, j) = \sum_{x=i}^j A(x)$$

Definition (Maximum Contiguous Subarray Problem)

Find  $i \leq j$  such that  $V(i, j)$  is maximized.

# Outline

---

- Introduction to Part I
- **Maximum Contiguous Subarray Problem**
  - Problem definition
  - **A brute force algorithm**
  - A data-reuse algorithm
  - A divide-and-conquer algorithm
  - Analysis of the divide-and-conquer algorithm



# A Brute Force Algorithm

Calculate the value of  $V(i,j)$  for each pair  $i \leq j$  and return the maximum value

```
VMAX  $\leftarrow$  A[1];
for  $i \leftarrow 1$  to  $n$  do
  for  $j \leftarrow i$  to  $n$  do
    // calculate  $V(i,j)$ 
     $V \leftarrow 0$ ;
    for  $x \leftarrow i$  to  $j$  do
       $V \leftarrow V + A[x]$ ;
    end
    if  $V > VMAX$  then
       $VMAX \leftarrow V$ ;
    end
  end
end
return VMAX
```

$O(n^3)$  arithmetic additions

# Outline

---

- Introduction to Part I
- **Maximum Contiguous Subarray Problem**
  - Problem definition
  - A brute force algorithm
  - **A data-reuse algorithm**
  - A divide-and-conquer algorithm
  - Analysis of the divide-and-conquer algorithm

# A Data-Reuse Algorithm

## Idea:

- don't need to calculate each  $V(i, j)$  from scratch
- exploit the fact:  $V(i, j) = \sum_{x=i}^j A[x] = V(i, j-1) + A[j]$

```
VMAX ← A[1];  
for i ← 1 to n do  
  V ← 0;  
  for j ← i to n do  
    // calculate V(i,j)  
    V ← V + A[j];  
    if V > VMAX then  
      VMAX ← V;  
    end  
  end  
end  
return VMAX
```

$O(n^2)$  arithmetic additions


# Outline

---

- Introduction to Part I
- **Maximum Contiguous Subarray Problem**
  - Problem definition
  - A brute force algorithm
  - A data-reuse algorithm
  - **A divide-and-conquer algorithm**
  - Analysis of the divide-and-conquer algorithm

# A Divide-and-Conquer Algorithm

Set  $m = \lfloor (n + 1)/2 \rfloor$



$A_1 = \text{MCS on left containing } A[m]$      $A_2 = \text{MCS on right containing } A[m+1]$

$A = A_1 \cup A_2$

The MCS  $S$  must be **one** of

- ①  $S_1$ : the MCS in  $A[1 \dots m]$
- ②  $S_2$ : the MCS in  $A[m + 1 \dots n]$
- ③  $A$ : the MCS across the cut.

So,

最终，在  $S_1$ ,  $S_2$  和  $A$  (跨越中点的最大子数组) 这三种情况中选取和最大者

$S = \text{the best among } \{S_1, S_2, A\}$

# An Example of Divide-and-Conquer Algorithm

1	-5	4	2	-7	3	6	-1		2	-4	7	-10	2	6	1	-3
---	----	---	---	----	---	---	----	--	---	----	---	-----	---	---	---	----


- $S_1 = [3, 6]$  and  $S_2 = [2, 6, 1]$

1	-5	4	2	-7	3	6	-1		2	-4	7	-10	2	6	1	-3
---	----	---	---	----	---	---	----	--	---	----	---	-----	---	---	---	----

- $A_1 = [3, 6, -1]$  and  $A_2 = [2, -4, 7]$
- $A = A_1 \cup A_2 = [3, 6, -1, 2, -4, 7]$
- $Value(S_1) = 9$ ;  $Value(S_2) = 9$ ;  $Value(A) = 13$
- solution: **A**

# Divide: MCS across The Cut

Set  $m = \lfloor (n + 1)/2 \rfloor$




$A_1$  = MCS on left containing  $A[M]$      $A_2$  = MCS on right containing  $A[M+1]$

$A = A_1 \cup A_2$

$$A = A_1 \cup A_2$$

- $A_1$ : MCS among contiguous subarrays ending at  $A[m]$
- $A_2$ : MCS among contiguous subarrays starting at  $A[m+1]$

# Conquer: Finding the " $A_1$ " Subarrays



$A_1$  is in the form  $A[i \dots m]$ ,  $V(i, m) = V(i + 1, m) + A[i]$

```

MAX  $\leftarrow$  A[m];
SUM  $\leftarrow$  A[m];
for  $i \leftarrow m - 1$  downto 1 do
    SUM  $\leftarrow$  SUM + A[i];
    if SUM > MAX then
        MAX  $\leftarrow$  SUM;
    end
end
A1 = MAX;
  
```



# Conquer: Finding "A" with A Linear Time

---

- There are only  $m$  sequences of the form
  - $A_1$  can be found in  $O(m)$  time
- Similarly,  $A_2$  is in the form  $A[m+1...j]$ 
  - there are only  $n-m$  such sequences
  - $A_2$  can be found in  $O(n-m)$  time
- $A = A_1 \cup A_2$  can be found in  $O(n)$  time
  - linear to the input size

# The Complete Divide-and-Conquer Algorithm

*MCS*( $A, s, t$ )

**Input:**  $A[s \dots t]$  with  $s \leq t$

**Output:** MCS of  $A[s \dots t]$

**begin**

**if**  $s = t$  **then return**  $A[s]$ ;

**else**

$m \leftarrow \lfloor \frac{s+t}{2} \rfloor$ ;

        Find  $MCS(A, s, m)$ ;

        Find  $MCS(A, m + 1, t)$ ;

        Find MCS that contains **both**  $A[m]$  and  $A[m + 1]$ ;


**return** maximum of the three sequences found

**end**

**end**

First Call:  $MCS(A, 1, n)$

# A Full Illustration of the D&C Algorithm



# Outline

---

- Introduction to Part I
- **Maximum Contiguous Subarray Problem**
  - Problem definition
  - A brute force algorithm
  - A data-reuse algorithm
  - A divide-and-conquer algorithm
  - **Analysis of the divide-and-conquer algorithm**

# Analysis of the D&C Algorithm

- $n$ : problem size ( $n = t - s + 1$ )
- $T(n)$ : time needed to run  $MCS(A, s, t)$

```

begin
  if  $s = t$  then return  $A[s]$  //  $O(1)$ 
  else
     $m \leftarrow \lfloor \frac{s+t}{2} \rfloor$ ;
    Find  $MCS(A, s, m)$ ; //  $T(\lceil \frac{n}{2} \rceil)$ 
    Find  $MCS(A, m+1, t)$ ; //  $T(\lfloor \frac{n}{2} \rfloor)$ 
    Find MCS that contains both  $A[m]$  and  $A[m+1]$ ; //  $O(n)$ 
    return maximum of the three sequences found //  $O(1)$ 
  end
end

```


$$T(1) = O(1)$$

$$T(n) = T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor) + O(n) \quad \text{for } n > 1$$

# Analysis of the D&C Algorithm

To simplify the analysis, we assume that  $n$  is a power of 2

$$T(n) = \begin{cases} 2T(n/2) + n, & \text{if } n > 1, \\ 1, & \text{if } n = 1. \end{cases}$$



# Summary

---

In the MCS problem, we saw 3 different algorithms for solving the maximum contiguous subarray problem

- A  $O(n^3)$  **brute force** algorithm
- A  $O(n^2)$  algorithm that **reuses data**
- A  $O(n \log n)$  **divide-and-conquer** algorithm

Can you solve the problem in  $O(n)$  time?

# 谢谢

