Week 12
From LLM to MLLM

Hwanjun Song
KAIST, Dept. of ISE


Today's Contents

- From LLM to MLLM from Architecture View <<
- Existing Challenge and Solution
- Practical Use of MLLMs (a focus on VLLM)

What is Multimodality?


- A modality refers to distinct sensory channel/information. Hence, an Ideal AI model is expected to receive multimodality inputs, including:
  - **Discrete** Signal : Sparse, symbolic data governed by syntax and discrete token distributions (= Text)
  - **Spatial** Signal : Dense grid data governed by spatial locality and continuous intensity values (= Image)
  - **Temporal** Signal : Sequential waveforms or frame series where time-domain dependencies requires temporal modeling (=Audio, Video)


Multimodal AI?



Inherent LLM's Constraints

- Vanila LLMs are architecturally **locked to discrete linguistic tokens**, creating a barrier for direct sensory ingestion
  - **Discrete Vocab Head**: The embedding layer is optimized to look up indices in a fixed vocabulary, which cannot natively process raw pixel intensities or waveforms
  - **Manifold Mismatch**: Pre-trained weights can only define a world model based on text co-occurrence







Emerging Solution towards MLLMs

- The cost of training LLMs is prohibitively high, making repeated retraining undesirable.


  Then, What if we bring information from other modalities into the text space?



Independent Latent Space




Matching Pairs based on Similar Objects, Concepts, Semantic, etc



Uniformly Aligned Space

- Before MLLM, there are lots of efforts… [Representative one is CLIP]



Key idea is using the set of images with their text description

Making the two embeddings to be similar while others dissimilar, refer to as "**contrastive learning**"

KAIST

Emerging Solution towards MLLMs: Connector Module


- But, it still needs additional training of text encoder (= LMMs)… but I said I don't want to do this!
- Smart Solution to Save Cost: **LLaVA [NeurIPS Oral 2023]**

Visual Instruction Tuning

Haotian Liu[1*], **Chunyuan Li**[2*], **Qingyang Wu**[3], **Yong Jae Lee**[1]
[1]University of Wisconsin–Madison [2]Microsoft Research [3]Columbia University
https://llava-vl.github.io

Emerging Solution towards MLLMs: Connector Module


- First, there already exist pre-trained vision (or other modality) encoders, such as CLIP, that align visual representations with text. So, instead of training from scratch, we reuse them even though their embedding space is not exactly the same as our LLM's text representation space.
- Second, we add a projection layer (or multiple layers) to map the visual representations into the LLM representation space, enabling the LLM to process visual inputs as token-like embeddings.



More Studies for Modality Alignment before LLaVA


They shared the similar key idea with LLaVA in that which learns a set of query tokens to extract and compress visual information before feeding it into the LLM

- **BLIP-2 [2023; Salesforce]** proposed the Q-Former, a trainable transformer module with learnable query tokens that selectively extracts relevant information from the frozen vision encoder and maps it into the input space of the frozen LLM.
- Here, the Q-Former is the connector module to form the original visual features to be aligned with our text representation space



More Studies for Modality Alignment

- **Flamingo [NeurIPS 2022; Deepmind]** proposed Perceiver Resampler, a trainable resampling module that compresses original visual features into a fixed number of visual tokens aligned with the target LLM before inserting them
- Here, the Perceiver Resampler acts as the connector module, but differs in that it feeds the visual features into intermediate cross-attention layers of the LLM rather than directly inserting them into the input embedding sequence.



Common Goal of LLaVA, BLIP-2, and Flamingo

- Reuse powerful pretrained encoders and LLMs, and efficiently align heterogeneous modalities without training everything from scratch
- Shared Architecture Pattern (applicable to any modality)
  - MLLM: Modality Encoder -> Connector Module -> LLM


Era	Representative Models	Main Idea
Early	Flamingo	Cross-attention injection
Middle	BLIP-2	Query-based compression
Practical Open-source	LLaVA	Simple projector alignment
Recent [~2026]	LLaVA-NeXT, LLaViT, Gemini-3, Qwen3-VL	Dynamic fusion & unified multimodal reasoning [Skip]

The architecture remains similar, but modern MLLMs increasingly focus on more efficient and expressive modality alignment rather than simple feature projection.


Other Modalities: Video Modality

- Video-perceiving MLLM: Extend image-based VLLMs by enabling temporal understanding by sampling multiple video frames and aggregating the frame features into a unified representation

Video-ChatGPT




Video-LLaVa



[1] Video-ChatGPT, Towards Detailed Video Understanding via Large Vision and Language Models, 2023
[2] Video-LLaVA: Learning United Visual Representation by Alignment before Projection, 2023
… and more including Qwen-3-VL, Gemma-4

Other Modalities: 3D Scene

- 3D-perceiving MLLM:




Encode input 3D information with external encoders, generating LLM-understandable 3D feature, feeding into LLM, which then interprets the input 3D/points based on the input text instructions and produces a textual response.

[1] 3D-LLM: Injecting the 3D World into Large Language Models, 2023
[2] LL3DA: Visual Interactive Instruction Tuning for Omni-3D Understanding, Reasoning, and Planning, 2023
[3] SpatialVLM: Endowing Vision-Language Models with Spatial Reasoning Capabilities, 2024,
…

KAIST

Other Modalities: Audio

- Audio-perceiving MLLM



Encode input audio signals with external encoders, generating LLM-understandable signal features, feeding into LLM, which then interprets the audio based on the input text instructions and produces a textual response.


[1] AudioGPT: Understanding and Generating Speech, Music, Sound, and Talking Head, 2023
[2] AudioPaLM: A Large Language Model that can Speak and Listen, 2023
[3] SALMONN: Towards Generic Hearing Abilities for Large Language Models, 2023
…

KAIST

Other Modalities: Domain Specialized Modality

Bio-/Medical & Healthcare

- BioGPT
- DrugGPT
- BioMedLM
- OphGLM
- GatorTron
- GatorTronGPT
- MEDITRON
- DoctorGLM
- BianQue
- ClinicalGPT
- Qilin-Med
- ChatDoctor
- BenTsao
- HuatuoGPT
- MedAlpaca
- AlpaCare
- Zhongjing
- PMC-LLaMA
- CPLLM
- MedPaLM 2
- BioMedGPT




Molecule & Chemistry

- ChemGPT
- SPT
- T5 Chem
- ChemLLM
- MolCA
- MolXPT
- MolSTM
- GIMLET
- ...

Graph

- StructGPT
- GPT4Graph
- GraphGPT
- LLaGA
- HiGPT
- ...



KAIST

Today's Contents

- From LLM to MLLM from Architecture View
- Existing Challenge and Solution <<
- Practical Use of MLLMs (a focus on VLLM)

Challenge 1: Hallucination

- Text-only LLMs: Hallucinations mainly arise from imperfect or outdated learned knowledge due to the knowledge boundary of LLMs – this is why we use RAG
- But MLLMs?
  - Hallucinations arise from **cross-modal** misalignment, visual misunderstanding, missing visual grounding; For example in visual large language models:



InstructBLIP:
The image shows a man in a yellow shirt standing on the back of a yellow SUV, ironing clothes on the roof of the vehicle. He is surrounded by various items, including a suitcase, a backpack, and a purse. The scene takes place on a busy city street, with multiple cars and a traffic light visible in the background. The man's presence on the roof of the SUV is a unique and creative way to iron clothes, ...

InstructBLIP:
The image captures a beautiful aerial view of a scenic coastline, … The mountain is situated on the left side of the image, while the ocean is visible on the right side. The coastline features a long stretch of sandy beach, with a few people scattered along the shoreline. There are several cars visible in the scene, with one car located near the top of the image and another near the bottom. The cars add to the sense of a bustling coastal community.

LLaVA-1.5:
The image displays a refrigerator filled with various food items and drinks, …, there are multiple bottles, including milk and juice, placed in different compartments. Some of the bottles are located on the top shelf, while others are placed on the middle and bottom shelves. In addition to the bottles, there are several carrots and a bowl of strawberries, … The carrots are scattered throughout the refrigerator, … The bowl of strawberries is placed on the bottom shelf, …

LLaVA-1.5:
The image features a tall, skinny building with a large antenna on top, towering over a city. The building is situated in the middle of a cityscape, surrounded by other buildings. In the background, there are several cars and a truck, indicating that the city is busy with traffic. The cars are scattered throughout the scene, with some closer to the foreground and others further away. The truck is located near the center of the image,…

Challenge 1: Hallucination Categories

- Common Hallucination Types in MLLMs
  - MLLM hallucinations often appear as incorrect object recognition, attribute prediction, counting, spatial reasoning, or OCR understanding, even when the visual evidence is clear.

Type	Image Context	Failure Mode Output
Object Existence	Desk with laptop **only**	There is **a cup of coffee** next to the laptop
Attribute Mismatch	Person in a **blue** shirt	The person is wearing a **red** shirt
Counter Error	Basket with **three** apples	I see **five** apples in the basket
Relation Error	Dog **beside** a chair	The dog is **sitting on top of** the chair
OCR Error	Sign saying **Open**	The sign says **Closed**


Challenge 1: Root Causes of Hallucination

- Multimodal hallucination are rooted in the conflict between internal language priors (LMMs) and external visual evidence (Vision Encoder)
  - **Language prior dominance**: LLMs "guess" based on text probability (e.g., kitchens usually have fridges) regardless of actual pixel evidence
  - **Manifold alignment mismatch**: The connector fails to translate critical visual details (e.g., small text or specific attributes) into linguistic tokens
  - **Attention sink**: Over long sequences, the model's self-attention may fade away from visual tokens, favoring the generated text history

Challenge 2: Failing at Spatial Grounding

- MLLMs frequently fail at precision tasks that require exact spatial awareness. There is a massive gap between identifying an object and pinpointing its exact location or reading small details

- Example: Document Visual QA (= traditional OCR but with MLLM)




SWANSON CENTER FOR NUTRITION
1979 Budget
Revised, July, 1979

Budget Analysis for September, 1979

	Annual $1,000	Monthly Budget $	Monthly Actual $	Monthly (Over) Under $	Year to Date Budget $	Year to Date Actual $	Year to Date (Over) Under $
INCOME:							
Swanson Interests	362.0	30,166	20,000	10,166	271,494	270,000	1,494
Consulting Fees	12.0	1,000	200	800	9,000	8,000	1,000
Grants, etc.	90.2	7,516	3,750	3,766	67,644	57,800	9,844
Other Contributions	5.0	416	-0-	416	3,744	250	3,494
Committed Funds Carried Over	44.7	3,730	-0-	3,730	33,570	44,765	(11,195)
GRAND TOTAL	513.9	42,828	23,950	18,878	385,452	380,815	4,637
EXPENDITURES:							
1) Projects							
SCN-1, Univ. of Neb. Medical Center	205.0	17,083	-0-*	17,083	153,747	133,333	20,414
UNMC Grants	26.2	2,183	-0-	2,183	19,647	4,750	14,897
SCN-2, International	1.0	83	-0-	83	747	32	715
SCN-3, Native Americans	20.0	1,667	1,903	(236)	15,003	15,734	(731)
SCN-4, Education	57.5	4,792	179	4,613	43,128	57,337	(14,209)
SCN-5, Nat. & Child Hlth (Creighton)	5.0	417	-0-	417	3,753	-0-	3,753
SCN-6, Collaborative Research	2.0	167	-0-	167	1,503	740	763
SCN-7, Elderly	22.0	1,833	1,009	824	16,497	11,845	4,652
SCN-8, Symposiums & Consultants	10.0	833	400	433	7,497	3,600	3,897
2) Center Support							
Salaries	121.0	10,083	10,043	40	90,747	90,812	(65)
Fringe Benefits	4.0	333	314	19	2,997	2,943	54
Office Expense	10.0	833	1,392	(559)	7,497	10,928	(3,431)
Office Rent	9.0	750	723	27	6,750	6,507	243
Travel	7.0	583	1,036**	(453)	5,247	5,472	(225)
Public Relations	5.0	417	77	340	3,753	1,317	2,436
Misc., Insurance, Audit	8.0	667	6	661	6,003	4,792	1,211
GRAND TOTAL	512.7	42,724	17,082	25,642	384,516	350,142	34,374

*October will show expenditure for two months (Sept. & Oct.)
**$450 will be reimbursed to SCN.

[Q] What is the year of the budget?
[G] 1979 [P] 1980



[Q] Which country is represented by brown color bar?
[G] Libya [P] united states

Challenge 2: Root Causes of Failing at Spatial Grounding

- The inability to resolve fine-grained details is a direct byproduct of the discretization loss during encoding and the fixed bottleneck of connector
  - **Fixed patch size:** ViT (vision encoder) partitions images into 16x16 patches. Any object smaller than this grid is effectively compressed into a single feature vector, losing its internal geometry
  - **Positional interpolation loss:** When scaling resolution (e.g., 224 to 672), positional embeddings must be interpolated. This leads to coordinate drifting and imprecise grounding
  - **Dataset granularity:** standard image-text pair lack dense spatial annotations, preventing the model from learning character-level or pixel level alignment

Data is Matter in Multimodal Alignment

- In the past, we focus on **global alignment** with text caption-image pairs
  - Global alignment refers to mapping the holistic visual representation of an entire image to the overall semantic meaning of its full text description within a shared embedding space.
  - So, the training input looks like:



Woman and man with dog having autumn walk on a path covered with foliage

Jennifer Lawrence in an embroidered Stella McCartney gown at the Orange British Academy Film Awards (BAFTA) held at the Royal Opera House in London, England, on February 13, 2011



KAIST

Data is Matter in Multimodal Alignment


- **Advantage** using Img-Caption pairs (Global Alignment):
  - **Exceptional Scalability at Web-Scale:** It allows for the use of massive, uncurated image-text pairs (e.g., LAION, CC12M) crawled from the internet, as it only requires holistic alt-text rather than dense manual annotations.
  - **Strong Zero-Shot Generalization:** By mapping images into a broad linguistic latent space, the model can generalize to unseen categories and diverse visual styles without task-specific fine-tuning.
  - **Highly Efficient Training and Inference:** Contrastive learning on global feature vectors is computationally less expensive than dense, pixel-level or region-based alignment, enabling the processing of billions of sample
  - **Broad Semantic Coverage**: It captures high-level concepts, artistic styles, and abstract themes effectively, which is beneficial for broad image-text retrieval tasks.

Data is Matter in Multimodal Alignment

- **Disadvantage** using Img-Caption pairs (Global Alignment):
  - **Lack of Fine-Grained Spatial Grounding:** Since the model compresses the entire image into a single vector, it often fails to pinpoint the exact location of objects (bounding boxes) or understand localized details.
  - **Weak Attribute and Relational Reasoning:** It struggles with tasks requiring precise logic, such as counting multiple objects, identifying relative positions (e.g., "left of"), or distinguishing specific color-object associations.
  - **Coarse-Grained Feature Representation:** Holistic alignment may miss subtle but critical visual nuances, leading to "CLIP-blind" instances where visually distinct scenes with similar global descriptions are incorrectly mapped together.

Data is Matter in Multimodal Alignment


- Surface-level alignment leads to weak spatial reasoning, attribute counting, and logical reasoning



That is, the use of global alignment is the main cause of hallucination and limited spatial grounding

Solution 1: Enhancing Caption Quality

- Recent work improves MLLMs by addressing the problem of **weak image understanding and inaccurate in the original text caption**
  - Adding: (1) containing detailed attributes, (2) object relations, (3) spatial layouts, scene context, and (4) reasoning-oriented descriptions.




(a) Comparison of Captions' Quality

(b) Comparison of Performance

Global alignment but with much fine-grained information

Solution 2: Instruction Tuning for MLLMs

- The field is shifting from passive descriptions to Query-Response data



The model is trained to generate not only the final answer but also the reasoning process behind it.

Response type 1: conversation
Question: What type of vehicle is featured in the image?
Answer: The image features a black sport utility vehicle (SUV) ...<omitted>
Response type 2: detailed description
The image is an underground parking area with a black sport utility vehicle (SUV) parked. There are three people in the scene, with one person standing closer to the left side of the vehicle, another person in the middle, and the third person on the right side. They are all working together to pack their luggage into the SUV for a trip. ...<omitted>
Response type 3: complex reasoning
Question: What challenges do these people face?
Answer: In the image, a group of people is standing outside a black SUV in a parking area, surrounded by various pieces of luggage, including suitcases and backpacks. They are facing the challenge of fitting all their luggage into the black SUV. There are multiple suitcases and backpacks to be packed, which suggests that the group has a significant amount of belongings ...<omitted>

Today's Contents

- From LLM to MLLM from Architecture View
- Existing Challenge and Solution
- Practical Use of MLLMs (a focus on VLLM) <<
  - Using the LLaVA model
  - Task 1: Visual Question Answering (VQA)
  - Task 2: Object Detection
  - Task 3: OCR-free Visual Document Understanding

Preparation with a HuggingFace Model

Practical Usage of MLLMs

This Colab provides a detailed guide for the Practical Use of MLLMs (VLLM).

Following the architectural patterns of Modality Encoder → Connector → LLM , we will use LLaVA-1.5-7B to bridge the gap between raw pixel intensities and discrete linguistic tokens.

It is designed to be self-contained, including environment setup, model quantization for T4 GPUs, and three distinct tasks.

```
import warnings
warnings.filterwarnings("ignore")
!pip install -q -U transformers accelerate bitsandbytes "pillow>=10.2.0" requests matplotlib
```

```
WARNING: Ignoring invalid distribution ~illow (/usr/local/lib/python3.12/dist-packages)
WARNING: Ignoring invalid distribution ~illow (/usr/local/lib/python3.12/dist-packages)
WARNING: Ignoring invalid distribution ~illow (/usr/local/lib/python3.12/dist-packages)
ERROR: pip's dependency resolver does not currently take into account all the packages that are installed. This beh
gradio 5.50.0 requires pillow<12.0,>=8.0, but you have pillow 12.2.0 which is incompatible.
```

```
import torch
from transformers import AutoProcessor, LlavaForConditionalGeneration
from PIL import Image, ImageDraw
import requests
import re
import json
import matplotlib.pyplot as plt
```

Preparation with a HuggingFace Model

```
# Load Model with 4-bit Quantization (BitsAndBytes)
# Can use any MLLM available from HuggingFace
model_id = "llava-hf/llava-1.5-7b-hf"
```

```
# The Processor handles both Image (Vision Encoder) and Text (Tokenizer)
processor = AutoProcessor.from_pretrained(model_id)
```

```
Warning: You are sending unauthenticated requests to the HF Hub. Please set a HF_TOKEN to enable higher rate limits
WARNING:huggingface_hub.utils._http:Warning: You are sending unauthenticated requests to the HF Hub. Please set a H
```

```
from transformers import BitsAndBytesConfig

# Configure 4-bit quantization
quantization_config = BitsAndBytesConfig(
    load_in_4bit=True,
    bnb_4bit_compute_dtype=torch.float16,
    bnb_4bit_use_double_quant=True,
    bnb_4bit_quant_type="nf4"
)

# Load the model with the quantization config
model = LlavaForConditionalGeneration.from_pretrained(
    model_id,
    torch_dtype=torch.float16,
    low_cpu_mem_usage=True,
    quantization_config=quantization_config,
    device_map="auto"
)
print("Model loaded with 4-bit quantization.")
```

```
Download complete:  0.00/0.00 [00:00<?, ?B/s]
Fetching 3 files: 100%  3/3 [00:00<00:00, 176.01it/s]
Loading weights: 100%  686/686 [01:01<00:00, 133.88it/s]
Model loaded with 4-bit quantization.
```


KAIST

Preparation with a HuggingFace Model

```
LlavaForConditionalGeneration(
  (model): LlavaModel(
    (vision_tower): CLIPVisionModel(
      (embeddings): CLIPVisionEmbeddings(
        (patch_embedding): Conv2d(3, 1024, kernel_size=(14, 14), stride=(14, 14), bias=False)
        (position_embedding): Embedding(577, 1024)
      )
      (pre_layrnorm): LayerNorm((1024,), eps=1e-05, elementwise_affine=True)
      (encoder): CLIPEncoder(
        (layers): ModuleList(
          (0-23): 24 x CLIPEncoderLayer(
            (self_attn): CLIPAttention(
              (k_proj): Linear4bit(in_features=1024, out_features=1024, bias=True)
              (v_proj): Linear4bit(in_features=1024, out_features=1024, bias=True)
              (q_proj): Linear4bit(in_features=1024, out_features=1024, bias=True)
              (out_proj): Linear4bit(in_features=1024, out_features=1024, bias=True)
            )
            (layer_norm1): LayerNorm((1024,), eps=1e-05, elementwise_affine=True)
            (mlp): CLIPMLP(
              (activation_fn): QuickGELUActivation()
              (fc1): Linear4bit(in_features=1024, out_features=4096, bias=True)
              (fc2): Linear4bit(in_features=4096, out_features=1024, bias=True)
            )
            (layer_norm2): LayerNorm((1024,), eps=1e-05, elementwise_affine=True)
          )
        )
      )
      (post_layernorm): LayerNorm((1024,), eps=1e-05, elementwise_affine=T
    )
    (multi_modal_projector): LlavaMultiModalProjector(
      (linear_1): Linear4bit(in_features=1024, out_features=4096, bias=Tru
      (act): GELUActivation()
      (linear_2): Linear4bit(in_features=4096, out_features=4096, bias=Tru
    )
```

Vision Encoder + Connector

LLM Backbone

```
    (language_model): LlamaModel(
      (embed_tokens): Embedding(32064, 4096)
      (layers): ModuleList(
        (0-31): 32 x LlamaDecoderLayer(
          (self_attn): LlamaAttention(
            (q_proj): Linear4bit(in_features=4096, out_features=4096, bias=False)
            (k_proj): Linear4bit(in_features=4096, out_features=4096, bias=False)
            (v_proj): Linear4bit(in_features=4096, out_features=4096, bias=False)
            (o_proj): Linear4bit(in_features=4096, out_features=4096, bias=False)
          )
          (mlp): LlamaMLP(
            (gate_proj): Linear4bit(in_features=4096, out_features=11008, bias=False)
            (up_proj): Linear4bit(in_features=4096, out_features=11008, bias=False)
            (down_proj): Linear4bit(in_features=11008, out_features=4096, bias=False)
            (act_fn): SiLUActivation()
          )
          (input_layernorm): LlamaRMSNorm((4096,), eps=1e-05)
          (post_attention_layernorm): LlamaRMSNorm((4096,), eps=1e-05)
        )
      )
      (norm): LlamaRMSNorm((4096,), eps=1e-05)
      (rotary_emb): LlamaRotaryEmbedding()
    )
  )
  (lm_head): Linear(in_features=4096, out_features=32064, bias=False)
)
```


KAIST

Task 1: Visual Question Answering (VQA)


- VQA is the task of answering natural language questions about an image by jointly understanding visual content and language.



What color are her eyes?
What is the mustache made of?



How many slices of pizza are there?
Is this a vegetarian pizza?



Is this person expecting company?
What is just under the tree?



Does it appear to be rainy?
Does this person have 20/20 vision?

KAIST

Task 1: Visual Question Answering (VQA)

Objective: Test the model's ability to perform Visual Reasoning by identifying anomalies or complex physical interactions.

- Logic: We wrap the input in a specific template:
  - USER: \n{prompt}\nASSISTANT:

This ensures the Connector Module maps the visual features to the correct position in the LLM's sequence.

```python
def run_vqa_task(image_obj, question):
    """
    Executes a VQA task using a pre-loaded PIL Image object.

    Args:
        image_obj (PIL.Image): The already opened image.
        question (str): The natural language query.
    """
    # Step 1: Prompt Engineering for MLLMs
    prompt = f"USER: <image>\n{question}\nASSISTANT:"

    # Step 2: Multimodal Input Encoding
    # We explicitly pass images=image_obj to the processor
    inputs = processor(text=prompt, images=image_obj, return_tensors='pt').to("cuda", torch.float16)

    # Step 3: Autoregressive Generation
    output = model.generate(
        **inputs,
        max_new_tokens=500,
        do_sample=False,
        use_cache=True
    )

    # Step 4: Output Parsing
    decoded_output = processor.decode(output[0], skip_special_tokens=True)

    # Extract only the model's final reasoning
    final_answer = decoded_output.split("ASSISTANT:")[-1].strip()

    return final_answer
```



Task 1: Visual Question Answering (VQA)

```
# Update question to match the dog image
print("--- Task 1: Reasoning ---")
answer_1 = run_vqa_task(image, "What breed of dog is in this image and what is it doing?")

# Use textwrap to format the output with line breaks for better readability
formatted_answer = textwrap.fill(answer_1, width=80)
print(f"Response:\n{formatted_answer}")
```

```
--- Task 1: Reasoning ---
Response:
The image features a white dog, likely a Samoyed, sitting on a grassy field. The
dog appears to be enjoying the outdoors and is possibly posing for a picture.
```



```
# More complex spatial reasoning question for Task 2
print("\n--- Task 2: Advanced Spatial Reasoning ---")

# This question requires the model to identify the dog's position relative to the camera
# and its orientation within the 3D space of the grass field.
spatial_query = "Describe the spatial arrangement: Where is the dog positioned in the frame what is it sitting on,
       + " and in which direction (left, right, or center) is its head tilted?"


answer_2 = run_vqa_task(image, spatial_query)
formatted_answer = textwrap.fill(answer_2, width=80)
print(f"Response:\n{formatted_answer}")
```

```
--- Task 2: Advanced Spatial Reasoning ---
Response:
The dog is positioned in the center of the frame, sitting on a grassy area. Its
head is tilted to the left.
```


KAIST

Task 2: Object Detection

- Object detection is the task of identifying and localizing objects within an image or video, typically by predicting both the object category and its bounding box coordinates.



Task 2: Object Detection

Objective: Extract precise coordinates. MLLMs represent space by discretizing coordinates into a [0, 1000] range.

- The Challenge: Models often suffer from Coordinate Drifting due to the fixed patch size (16×16) of the Vision Encoder

```python
def detect_and_visualize(image_obj, target_object):
    # Prompting for normalized coordinates [ymin, xmin, ymax, xmax]
    query = f"Please detect the {target_object} and provide the bounding box in [ymin, xmin, ymax, xmax] format."

    # run_vqa_task returns only the text answer string
    raw_res = run_vqa_task(image_obj, query)

    print(f"Raw Model Output: {raw_res}")

    # Updated regex to handle both integers and floats
    match = re.search(r"\[([\d\.]+),\s*([\d\.]+),\s*([\d\.]+),\s*([\d\.]+)\]", raw_res)

    if match:
        # Convert to float first
        coords = [float(g) for g in match.groups()]

        # If the model outputs normalized 0-1 instead of 0-1000, scale it up
        if all(0 <= c <= 1.05 for c in coords):
            coords = [c * 1000 for c in coords]

        w, h = image_obj.size

        # Scaling normalized [0-1000] coordinates back to actual pixel dimensions
        ymin, xmin, ymax, xmax = coords
        left = xmin * w / 1000
        top = ymin * h / 1000
        right = xmax * w / 1000
        bottom = ymax * h / 1000

        # Draw the Bounding Box (create a copy to avoid modifying original)
        display_img = image_obj.copy()
        draw = ImageDraw.Draw(display_img)
        draw.rectangle([left, top, right, bottom], outline="red", width=5)

        print(f"Object detected (normalized 0-1000): {[int(c) for c in coords]}")
        plt.figure(figsize=(8, 5))
        plt.imshow(display_img); plt.axis('off'); plt.show()
    else:
        print("Detection failed. The model may have failed to ground the object spatially.")
```

Task 2: Object Detection

```
# Prompting for normalized coordinates [ymin, xmin, ymax, xmax]
query = f"Please detect the {target_object} and provide the bounding box in [ymin, xmin, ymax, xmax] format."
```

```
# Update detection target to match the new image
detect_and_visualize(image, "dog")
```

```
Raw Model Output: [0.0, 0.0, 0.99, 0.99]
Object detected (normalized 0-1000): [0, 0, 990, 990]
```



```
# Update detection target to match the new image
detect_and_visualize(multi_dogs, "dogs")
```

```
Raw Model Output: [0.0, 0.49, 0.12, 0.78]
Object detected (normalized 0-1000): [0, 490, 120, 780]
```




LLaVA model is not able to detect multiple dogs in an image, but further prompt tuning may resolve this (Try on your own)

Task 3: OCR-free Document Understanding

- OCR-free Document Understanding is the task of directly understanding and processing document images without relying on an explicit Optical Character Recognition (OCR) system to extract text first.

Query: Look at this chart. Extract the names of the countries and their values. Return the result as a valid JSON object.



Task 2: OCR-free Document Understanding (one of the VQAs)

Objective: Directly extract data from images of tables or charts, bypassing traditional OCR. This is a "Practical Use" focus for Industrial Systems Engineering.


- Risk: We must watch for Hallucinations where the LLM's language prior overrides the actual visual evidence in the document.

```python
def extract_document_data(doc_img, query):
    # Industrial Document Analysis prompt
    # Targeting the Human Development Index chart as seen in slides

    results = run_vqa_task(doc_img, query)
    print(results)
```

```python
# Testing with the 'Our World in Data' HDI chart [cite: 319, 320]
query = "Look at this chart. Extract the names of the countries and their values. Return the result as a valid JSO
extract_document_data(doc_image, query)
```


```
{
"Afghanistan": 0.42,
"Albania": 0.42,
"Algeria": 0.42,
"Andorra": 0.42,
"Angola": 0.42,
"Antigua and Barbados": 0.42,
"Argentina": 0.42,
"Armenia": 0.42,
"Australia": 0.42,
"Austria": 0.42,
"Azerbaijan": 0.42,
"Bahrain": 0.42,
"Bangladesh": 0.42,
"Barbados": 0.42,
"Belarus": 0.42,
"Belgium": 0.42,
"Belize": 0.42,
"Benin": 0.42,
```

Summary

- Contents
  - From LLM to MLLM – Architecture Perspective: {Vision Encoder, Connector}
  - Existing Challenges (Hallucination; Lack of Spatial Grounding) and Solutions (From Global Alignment to Detailed Visual Instruction Tuning)
  - Three Practical Use cases using MLLMs (a focus on VLLM)
    - VQA, Object Detection, Document Understanding
- Practice using Colab
  - https://drive.google.com/file/d/1wM_0pRTFanRVQrnx-dy7ZMZ5WLY6NCAa/view?usp=sharing

Q & A