Sparse & Explainable Bayesian Neural Networks for Official Statistics

Unit-Weighted Pseudo-Posteriors, Formal Differential Privacy, and Non-Probability Propensity Estimation in LBBNN

Aliaksandr Hubin & Lars Skaaret-Lund (NMBU & UiO Integreat)

In collaboration with Terrance D. Savitsky, Matthew R. Williams, Vladislav Beresovsky, and Julie Gershunskaya (U.S. Bureau of Labor Statistics)

October 2026

Section 1

PART I: Foundations of LBBNN & Input-Skip Architecture (ISLaB)

Motivation — Why Sparse & Explainable BNNs in Official Statistics?

The Black-Box & Over-Parameterization Dilemma:

- Modern deep neural networks capture complex multi-way interactions, but lack calibrated uncertainty quantification and interpretable feature attributions.
- Standard dense BNNs quantify parameter uncertainty, but retain all noise covariates, inflating variance in downstream survey estimators.

What Official Statistics Requires:

- **Structural Sparsity**: Combine model selection (spike-and-slab edge pruning) and parameter uncertainty in a single variational framework.
- **Explainable Depth**: Automatically adapt between simple linear GLMs (Depth $= 1$) and deep non-linear interaction surfaces (Depth > 1).
- **Survey & Privacy Rigor**: Rigorous integration with informative sampling weights, differential privacy (ϵ, δ), and non-probability samples.

From Dense BNNs to Latent Binary BNNs (Hubin & Storvik, 2024)


Spike-and-Slab Edge Selection:

- Latent binary inclusion indicator $\gamma_{k,p}^{(j)} \in \{0, 1\}$:

$$p\big(w_{k,p}^{(j)} \mid \gamma_{k,p}^{(j)}\big) = \gamma_{k,p}^{(j)} \mathcal{N}\big(0, (\tau_{k,p}^{(j)})^2\big) + \big(1 - \gamma_{k,p}^{(j)}\big)\delta_0$$

$$p\big(\gamma_{k,p}^{(j)}\big) = \text{Bernoulli}\big(\psi_{k,p}^{(j)}\big)$$

- **Bayesian Model Averaging (BMA)**: Ensembles across posterior draws $\Gamma \sim q(\Gamma)$ and $W \sim q(W \mid \Gamma)$ for optimal uncertainty quantification.
- **Median Probability Model (MPM)**: Hard-prunes edges with posterior inclusion probability $a_{k,p}^{(j)} \leq 0.5$ (Barbieri & Berger, 2004 optimal predictive submodel).




Input-Skip LBBNNs (ISLaB) & Structural Depth Metrics (Høyheim et al., 2026)

The ISLaB Architecture (*JAIR*, 2026):

- Direct skips route inputs $\mathbf{x} \in \mathbb{R}^p$ to every hidden layer: $\mathbf{a}^{(j-1)} = [a_1^{(j-1)}, \ldots, a_K^{(j-1)}, \mathbf{x}^\top]^\top$.
- **Active Path (AP)**: Connects input x_k to output ζ via edges with $a_{k,p}^{(j)} > 0.5$.

Contribution Depth Classification:

- **Depth = 1**: Direct skip $\implies$ linear GLM effect.
- **Depth $\geq$ 2**: Hidden layers $\implies$ non-linear interaction.
- **Paths = 0**: Noise covariate pruned from graph.



Local Explainability via Polyhedral ReLU Activation Regions


Local GLM Theorem (JSM 2026):

- Piecewise-linear activations partition $\mathbb{R}^p$ into polyhedral activation regions $\mathcal{P}_1, \ldots, \mathcal{P}_M$.
- Within each local region $\mathcal{P}_m$, the active network reduces to an exact **local GLM**:

$$\zeta(\mathbf{x}) = \beta_0(\mathbf{x}_i) + \sum_{j=1}^{p} \beta_j(\mathbf{x}_i) x_j$$

$$\boldsymbol{\beta}(\mathbf{x}_i) = \nabla_{\mathbf{x}} \zeta(\mathbf{x})\big|_{\mathbf{x}=\mathbf{x}_i}$$

- **Exact Gradients**: Evaluated via analytical backpropagation (zero perturbation error).
- **Credible Intervals**: Draws $W \sim q(W \mid \Gamma^*)$ yield exact posterior intervals for respondent sensitivities.




Variational Inference & Protection Against Cold Posteriors

Variational ELBO at True $T = 1.0$:

$$\text{ELBO}(q) = \sum_{i=1}^{n} \mathbb{E}_q[\log f(y_i \mid \mathbf{x}_i, \theta)] - \text{KL}(q \parallel p)$$

Why Explicit Error Scale σ^2 Matters (Wenzel et al., 2020):

- Omitting residual noise scale σ^2 artificially rescales likelihood ($T = \sigma^2 \neq 1$), mis-calibrating spike-and-slab KL shrinkage.
- In `lbbnn_net(sigma = ...)`, calibrated σ^2 grounds log-likelihood sensitivities on the true Bayesian scale.
- Calibrates both feature inclusion probabilities a_k and DP sensitivities f_i.



The LBBNN Open-Source Software Ecosystem

R Package LBBNN (CRAN v0.1.6):

- Pure C++ LibTorch backend via `torch` for R (zero Python dependencies or overhead).
- Mean-field spike-and-slab with Local Reparameterization Trick (LRT) and Normalizing Flows (*TMLR*, 2024).
- Automated model selection, predictive ensembling (BMA), and sparse median probability models (MPM).

Joint BLS Collaboration Modules:

- **Unit Weighting**: `get_dataloaders()` supports non-trainable weights $u_i \geq 0$ with optional sample-size normalization.
- **Residual Calibration**: `lbbnn_net(sigma = ...)` incorporates observation noise scale.
- **Differential Privacy**: `loglik_contributions()` and `fit_dp_lbbnn()` for two-pass (ϵ, δ)-PDP synthesis.
- **Composite Propensities**: Native losses for `STACK`, `LINK1`, `LINK2`, and `MIP`.

Section 2

PART II: Track 1 — Unit-Weighted Pseudo-Posteriors & Formal Differential Privacy

Unit-Weighted Variational Pseudo-Posteriors (Savitsky & Toth, 2016)

Equipping each unit $i \in \{1, \ldots, n\}$ with a non-negative weight $u_i \geq 0$ defines the pseudo-posterior:

$$p_{\mathbf{u}}(\theta \mid \mathbf{y}) \propto p(\theta) \prod_{i=1}^{n} f(y_i \mid \mathbf{x}_i, \theta)^{u_i}$$

$$\text{ELBO}(q; \mathbf{u}) = \sum_{i=1}^{n} u_i \, \mathbb{E}_{q(\theta)}[\log f(y_i \mid \mathbf{x}_i, \theta)] - \text{KL}\big(q(\theta) \parallel p(\theta)\big)$$

1. Survey Sampling Weights ($u_i = \tilde{w}_i$):

- Normalized to sample size n: $\tilde{w}_i = w_i \frac{n}{\sum w_j}$.
- Setting `normalize_weights = TRUE` ensures $\sum \tilde{w}_i = n$ does not overpower spike-and-slab KL shrinkage.
- Corrects informative sampling selection bias.

2. Differential Privacy Weights ($u_i = \alpha_i$):

- Unnormalized weights: $\alpha_i \in [0, 1]$.
- Setting `normalize_weights = FALSE` ensures $\sum \alpha_i \leq n$.
- Downweights high-sensitivity tail outliers and contracts the pseudo-posterior toward the prior.

Track 1A — Informative Survey Sampling Setup & Automated Noise Pruning

Simulation Setup ($N = 2,000, p = 4$):

- **True Non-Linear DGP**:

  $$Y_i = 2X_{1i} + 1.5\sin(\pi X_{2i}) + 0.8X_{1i}X_{2i} + \varepsilon_i$$


  where $\varepsilon_i \sim \mathcal{N}(0, 0.4^2)$, and $X_3, X_4 \sim \mathcal{N}(0, 1)$ are pure noise.

- **Informative Selection Mechanism**:


  $$\pi_i = \text{logit}^{-1}(-1.0 + 1.2Y_i)$$

  Draws $n = 737$ units favoring high Y_i.

- Unweighted sample mean is **+2.009** (True population mean: **0.000**).




Track 1A — Population Mean & Imputation RMSE Recovery (Visual Benchmark)



Key Takeaways:

- Classical **Hájek mean** reduces bias ($+0.27$) but only provides a single scalar estimate (Pop RMSE $= 2.32$).
- **Survey-Weighted LBBNN** learns the conditional surface, reducing Pop RMSE to **0.46** (approaching $\sigma = 0.40$ noise floor).

Track 1A — Full Population Distribution Recovery



Distributional Recovery: Survey-weighted LBBNN models (green/blue curves) accurately reconstruct the full population density (black solid curve) across all 2,000 units, completely correcting the severe rightward shift of the observed sample (red dotted curve).

Track 1B — Why Unweighted Neural Networks Fail Differential Privacy

Probabilistic Differential Privacy (Savitsky, Williams & Hu, 2022):

$$\sup_{\theta \in \Theta_\delta} \left| \log \frac{q_{\boldsymbol{\alpha}}(\theta \mid \mathbf{y})}{q_{\boldsymbol{\alpha}}(\theta \mid \mathbf{y}')} \right| \leq \epsilon_{\mathbf{y}} = 2\Delta_{\alpha,\mathbf{y}}, \qquad \Delta_{\alpha,\mathbf{y}} = \max_{s,i} |\alpha_i \log f(y_i \mid \mathbf{x}_i, \theta^{(s)})|$$


The Quadratic Exposure Dilemma in Gaussian Regression:

- Pointwise Gaussian log-likelihood grows quadratically with the residual:

$$|\log f(y_i \mid \mathbf{x}_i, \theta)| \propto \frac{(y_i - \mu_\theta(\mathbf{x}_i))^2}{2\sigma^2}$$

- In skewed survey microdata (wages, financial expenditures), extreme outliers drive unweighted sensitivity $\Delta \to \infty$ and privacy budget $\epsilon_{\mathbf{y}} \to \infty$.
- Naive gradient clipping distorts the mean and destroys the variance structure of official statistics.

Track 1B — The Two-Pass Surgical Downweighting Pipeline (`fit_dp_lbbnn`)




Monotone Surgical Truncation Formula:

$$\alpha_i = \min\left(\alpha_i^{\text{raw}}, \frac{M_{\text{thresh}}}{f_i}\right), \qquad \alpha_i = 0 \quad \text{if } f_i > 3M_{\text{thresh}}$$

Guarantees local Lipschitz bound $\Delta_{\alpha,\mathbf{y}} = \max_{s,i} |\alpha_i L_{s,i}^{(2)}| \leq M_{\text{thresh}}$ and bounded privacy $\epsilon_{\mathbf{y}} = 2\Delta_{\alpha,\mathbf{y}}$.


Track 1B — Monotone Surgical Downweighting Diagnostic



Empirical DP Metrics:

- **Sample**: $n = 300$, median $\$4.16$, 3 extreme outliers ($\$400$–$\$530$).
- **Standard Records**: Retain high weights $\alpha_i \in [0.34, 0.85]$ (median 0.81).
- **Tail Outliers**: All 3 outliers ($f_i > 26 > 3M$) surgically zeroed ($\alpha_i = 0.0$).
- **Privacy Guarantee**: $\Delta_{\alpha,\mathbf{y}} = 4.32 \leq 5.50 \implies \boldsymbol{\epsilon_{\mathbf{y}} = 8.63}$.

Track 1B — Synthetic Microdata Utility vs. Outlier Protection



Distributional Utility vs. Disclosure Protection:

- 3 extreme outliers distort raw sample mean ($\$11.30$ vs. $\$6.70$) and explode standard deviation to $\$46.75$.
- **DP-Private Synthetic** microdata recovers the true distribution body (Mean $\$7.99$, Median $\$4.13$) while safely truncating disclosure risk on extreme tail outliers.

Section 3

PART III: Track 2 — Combining Probability & Non-Probability Samples

The Big Data Paradox in Convenience Samples (Meng, 2018)

The Non-Probability Selection Dilemma:

- Let $U = \{1, \ldots, N\}$ denote the finite target population of size N.
- In convenience/opt-in samples $S_c \subset U$, sample inclusion $I_{ci} \in \{0, 1\}$ is non-random and driven by unobserved self-selection mechanisms.
- **Meng's Law of Large Populations (2018)**:

$$\text{Bias}(\bar{y}_c) = \frac{\text{Cov}_U(I_c, Y)}{\bar{\pi}_c} = \rho_{I_c,Y} \cdot \sigma_Y \cdot \sqrt{\frac{N - n_c}{n_c}}$$

  where Cov_U denotes finite-population covariance across all units in U.
- A tiny correlation $\rho_{I_c,Y} \neq 0$ creates selection bias that scales with $\sqrt{N}$.
- Merely increasing convenience sample size n_c shrinks variance around a severely biased estimate (the Big Data Paradox).

The Identification Barrier & The Conditioning Trick (Beresovsky et al., 2026)

The Identification Barrier:

- Covariates $\mathbf{x}_i$ are observed only on convenience sample S_c (unknown π_{ci}) and reference survey S_r (known design probability π_{ri}).
- Units in the unobserved population remainder $U \setminus (S_c \cup S_r)$ are never observed (where $U = \{1, \ldots, N\}$ is the finite target population).

The Conditioning Trick:

- Pool S_c and S_r into a combined sample S, and model membership indicator $D_i = \mathbb{I}(i \in S_c)$:

$$\pi_{zi}^{\mathsf{STACK}} = \mathbb{P}(D_i = 1 \mid \mathbf{x}_i, i \in S) = \frac{\pi_{ci}}{\pi_{ci} + \pi_{ri}}$$

- The known reference probability π_{ri} acts as an **exact structural offset**, anchoring neural network logits $\eta_\theta(\mathbf{x}_i)$ to the true population scale.

The Five Sample Combination Formulations (Beresovsky et al., 2026)

Estimator	Sample Domain	Target Indicator	Composite Probability π_{zi}
`STACK`	$S_c \oplus S_r$ (Unlinked)	$I_{zi} = D_i$ (sample source)	$\frac{\pi_{ci}}{\pi_{ci}+\pi_{ri}}$
`LINK1`	$S_c \cup (S_r \setminus S_c)$	$I_{zi} = I_{ci}$ (deduplicated)	$\frac{\pi_{ci}}{\pi_{ci}+\pi_{ri}-\pi_{ci}\pi_{ri}}$
`LINK2`	$S_c \oplus S_r$ (Linked Stacked)	$I_{zi} = D_i + (1-D_i)I_{ci}$	$\frac{\pi_{ci}(1+\pi_{ri})}{\pi_{ci}+\pi_{ri}}$
`MIP`	Missing Information	$\tilde{I}_{zi}^{\text{MIP}} = D_i + (1-D_i)\tilde{p}_i$	Bridges `STACK` and `LINK2`
`PSEUDO`	Survey Weighted	Score: $\nabla \ell_{\text{pseudo}} = 0$	Design-weighted: $\sum_{S_r} \pi_{ri}^{-1}\text{softplus}(\eta_i)$

How MIP Bridges STACK and LINK2 vs. Why PSEUDO Explodes

Louis's (1982) Missing Information Principle (MIP):

- Imputes linkage expectations on unlinked reference units:


$$\tilde{p}_i = p_{\text{link}} I_{ci} + (1 - p_{\text{link}})\text{sg}(\pi_{ci}), \qquad \tilde{I}_{zi}^{\text{MIP}} = D_i + (1 - D_i)\tilde{p}_i$$

- Continuously bridges unlinked STACK ($p_{\text{link}} = 0$) and deterministically linked LINK2 ($p_{\text{link}} = 1$).

The Pseudo-Likelihood (PSEUDO) Breakdown:

- PSEUDO scores reference units with inverse design weights π_{ri}^{-1}.
- Under low common support (where $\pi_{ci} \gg 0$ but $\pi_{ri} \approx 0$), weights $\pi_{ri}^{-1} \to \infty$, causing loss gradients and parameter variance to explode.

Study 0 — Exact Linear Baseline Monte Carlo ($R = 20$, Visual Benchmark)



Empirical Findings Across Methods & Propensity Formulations:

- **Efficiency Hierarchy**: LINK2 $\succ$ LINK1 $\succ$ STACK $\succ$ PSEUDO across both GLM and LBBNN.
- **Pseudo-Likelihood Breakdown**: Under low common support, `GLM-PSEUDO` explodes to RMSE $= 1.015$, while all composite formulations remain bounded (RMSE ≈ 0.16–0.33).
- **LBBNN Agreement**: On linear truth, `LBBNN` matches GLM efficiency across all 5 formulations (e.g., `LINK2` RMSE: 0.23 vs. 0.24 High Support; 0.17 vs. 0.14 Low Support).


Study 1 — Automated Confounder Selection & Noise Pruning ($p = 6$)

Simulation Setup ($N = 5,000, p = 6$):


- **Confounders**: X_1, X_2 drive both propensity π_{ci} and outcome Y_i.
- **Outcome-Only**: X_3 drives Y_i but uncorrelated with selection I_c.
- **Pure Noise**: $X_4, X_5, X_6 \sim \mathcal{N}(0, 1)$.

Why Variable Selection Matters:

- Including non-propensity predictors X_3–X_6 inflates Hájek weight variance without reducing confounding bias.
- `LBBNN` automatically prunes them.




Study 2 — High Common Support with Non-Linear Propensity & Interaction



Non-Linear Recovery Across Formulations:

- Linear GLMs are structurally misspecified on the interaction surface ($|\text{Bias}| = 0.19$–0.39 across formulations).
- `LBBNN` (BMA and MPM) captures non-linear interactions, reducing bias across all 5 formulations (lowest on `STACK`: $|\text{Bias}| = 0.086$ vs GLM 0.187; `MIP50`: 0.198 vs 0.229; `PSEUDO`: 0.237 vs 0.347).


Study 3 — Low Common Support + Non-Linearity: Bias vs. Kish's ESS



Catastrophic Breakdown of Pseudo-Likelihood vs. Composite LBBNN:

- `PSEUDO` collapses Kish ESS (≤ 8.3 of $n_c = 521$) and explodes bias ($|\text{Bias}| = 4.82$–5.44) across all methods.
- Composite formulations remain stable; `LBBNN-LINK2 (MPM)` achieves the **lowest bias (+0.61)** and **highest effective sample size (Kish ESS = 136.0)**.
- On `MIP50`, LBBNN restores ESS from 45.1 to 129.4 and cuts bias from 1.90 to 0.71.

Study 3 — Propensity Recovery Diagnostic (2x2 Scatterplot Grid)



Panels: (A) GLM-STACK bias from missing interactions; (B) GLM-PSEUDO severe weight explosion and scatter collapse; (C) LBBNN-STACK Bayesian Model Averaging calibration; (D) LBBNN-LINK2 Median Probability Model point recovery.

Section 4

PART IV: Practical Pipelines, Software Architecture & Synthesis

Unified LBBNN Architecture Across Track 1 & Track 2

Function / Module	Operational Track	Description & Statistical Role
`get_dataloaders()`	Track 1 & 2	Handles non-trainable weights $u_i \geq 0$, normalization, and multi-targets.
`lbbnn_net(sigma, ...)`	Track 1 & 2	ELBO likelihood scaling by error variance σ^2 (cold-posterior protection).
`loglik_contributions()`	Track 1B (Privacy)	Computes $S \times n$ record-level log-likelihood contributions $L_{s,i}$.
`fit_dp_lbbnn()`	Track 1B (Privacy)	Two-pass monotone surgical downweighting with Lipschitz bound Δ_α.
`sample_synthetic_lbbnn()`	Track 1B (Privacy)	Generates (ϵ, δ)-DP synthetic microdata via post-processing theorem.
`nll_link1()` / `nll_link2()`	Track 2 (Propensity)	Composite Bernoulli NLL on singly matched and matched-pair samples.
`make_nll_mip(p_link)`	Track 2 (Propensity)	Factory producing composite NLL under Missing Information Principle.
`nll_stack()` / `nll_pseudo()`	Track 2 (Propensity)	Stacked pooled sample NLL and survey design-weighted pseudo-NLL.
`build_propensity_dataset()`	Track 2 (Propensity)	Formats covariates and targets for any of the 5 estimation methods.
`hajek_estimate()`	Track 2 (Propensity)	Computes self-normalizing Hájek estimator $\sum w_i y_i / \sum w_i$ with $w_i = \hat{\pi}_{ci}^{-1}$.

Pipeline Tutorial: Survey-Weighted Pseudo-Posteriors (Track 1A)

Goal: Estimate population regressions under informative survey sampling while selecting active features.

```
# 1. Package design weights; auto-normalize to sample size (sum w_i = n)
dl_train <- get_dataloaders(x = X_samp, y = y_samp, weights = w_design,
                            normalize_weights = TRUE, batch_size = 64)

# 2. Build LBBNN with calibrated residual noise scale sigma (protects T=1)
net <- lbbnn_net(problem_type = "regression", sizes = c(p, 16, 1),
                 sigma = 1.0, input_skip = TRUE)

# 3. Train unit-weighted ELBO across mini-batches
fit <- train_lbbnn(LBBNN = net, train_dl = dl_train, epochs = 100, lr = 0.01)

# 4. Predict via sparse Median Probability Model (hard-prunes noise a_k <= 0.5)
y_hat <- predict(net, newdata = dl_test, model_type = "mpm")
```

- `normalize_weights = TRUE` enforces $\sum \tilde{w}_i = n$ (Savitsky & Toth, 2016), preventing KL distortion.
- Grounding log-likelihood sensitivity via calibrated σ^2 avoids cold posteriors ($T \neq 1$).
- Direct input skips preserve linear parametric efficiency while pruning uninformative noise.

Pipeline Tutorial: Two-Pass (ϵ, δ)-DP Synthesis (Track 1B)

Goal: Generate synthetic microdata under finite-sample (ϵ, δ)-differential privacy guarantees.

```
# 1. Automated two-pass DP estimation with monotone surgical downweighting
dp_fit <- fit_dp_lbbnn(
  model_spec = list(sizes = c(p, 16, 1), problem_type = "regression"),
  X = x_micro, y = y_sensitive, M_thresh = 5.5, epochs = 100, lr = 0.01
)

# 2. Inspect record risk weights alpha_i and guaranteed privacy budget
cat(sprintf("Zeroed outliers: %d (alpha_i = 0)\n", sum(dp_fit$alpha == 0)))
cat(sprintf("Guaranteed Budget: eps = %.2f (Delta = %.2f)\n",
            dp_fit$epsilon_local, dp_fit$delta_alpha))

# 3. Generate private synthetic microdata via post-processing theorem
synth_micro <- sample_synthetic_lbbnn(dp_fit$model, n_syn = 2000, draws = 50)
```

- `fit_dp_lbbnn()` encapsulates Pass 1 fit $\rightarrow$ sensitivity extraction $(L_{s,i})$ $\rightarrow$ surgical weight capping (α_i) $\rightarrow$ Pass 2 weighted fit in a single call.
- Surgically zeroes extreme outliers $(\alpha_i = 0.0)$ while retaining high utility on typical records $(\alpha_i \in [0.34, 0.85])$.
- Guarantees finite-sample local Lipschitz bound $\Delta_{\alpha,\mathbf{y}} \leq M_{\text{thresh}}$ and privacy budget $\epsilon_{\mathbf{y}} = 2\Delta_{\alpha,\mathbf{y}}$.

Pipeline Tutorial: Composite Non-Probability Propensity (Track 2)

Goal: Condition on pooled inclusion $S = S_c \cup S_r$ to debias non-probability sample means.

```
# 1. Format combined sample (S_c (+) S_r) & dataloader with composite targets
prep <- build_propensity_dataset(pop, method = "LINK2", covar_cols = paste0("X", 1:p))
dl_prop <- get_dataloaders(prep$data, target_cols = prep$target_cols, batch_size = 64)

# 2. Fit LBBNN with custom composite Bernoulli loss (pi_ri offset)
net_prop <- lbbnn_net(problem_type = "custom", sizes = c(p, 8, 1),
                      link = torch::torch_sigmoid, nll = nll_link2)
train_lbbnn(LBBNN = net_prop, train_dl = dl_prop, epochs = 150, lr = 0.02)

# 3. Predict convenience propensities pi_c_hat & compute debiased Hajek mean
pi_c_hat <- predict(net_prop, newdata = dl_prop, model_type = "mpm")[prep$Sc_indices]
y_bar_hajek <- hajek_estimate(y = pop$y[pop$I.c == 1], pi_hat = pi_c_hat)
```

- `build_propensity_dataset()` handles any of the 5 formulations (`LINK2`, `LINK1`, `STACK`, `MIP`, `PSEUDO`).
- Composite Bernoulli likelihood grounds unconstrained logits via the exact reference offset π_{ri}.
- `hajek_estimate()` computes $\hat{\bar{Y}}_{\text{Hajek}} = \sum w_i y_i / \sum w_i$, eliminating selection bias.

Key Takeaways & Synthesis for Official Statistics

1. **Survey-Weighted Pseudo-Posteriors (Track 1A)**:
   - Normalizing survey weights to sample size ($\sum \tilde{w}_i = n$) + calibrated observation noise σ^2 prevents likelihood mis-scaling ($T \neq 1$) and protects spike-and-slab KL shrinkage.
   - `LBBNN` achieves 5x lower population RMSE than classical Hájek weighting under informative sampling while pruning irrelevant covariates.
2. **Two-Pass (ϵ, δ)-PDP Microdata Synthesis (Track 1B)**:
   - Monotone surgical downweighting (`fit_dp_lbbnn`) eliminates disclosure risk from extreme tail outliers ($\alpha_i = 0$) while preserving high utility ($\alpha_i \in [0.34, 0.85]$) on normal records.
3. **Composite Non-Probability Sample Integration (Track 2)**:
   - Conditioning on pooled sample inclusion $S_c \cup S_r$ allows known design probabilities π_{ri} to anchor neural network logits to the true population scale.
   - Composite Bernoulli likelihoods (`LINK2`, `LINK1`, `MIP`, `STACK`) bound loss gradients and prevent the catastrophic effective sample size collapse (`Kish ESS` < 7) of pseudo-likelihood under low common support.

References & Collaborative Works

1. **Beresovsky, V., Gershunskaya, J., & Savitsky, T. D.** (2024). *Review of quasi-randomization approaches for estimation from non-probability samples*. Statistical Science (arXiv:2312.05383).
2. **Savitsky, T. D., Williams, M. R., & Hu, J.** (2022). *Bayesian pseudo posterior mechanism under asymptotic differential privacy*. Journal of Machine Learning Research, 23(232), 1–37.
3. **Savitsky, T. D., & Toth, D.** (2016). *Bayesian estimation under informative sampling*. Electronic Journal of Statistics, 10(1), 1677–1708.
4. **Meng, X.-L.** (2018). *Statistical paradises and paradoxes in big data (I): Law of large populations, big data paradox, and the 2016 US presidential election*. The Annals of Applied Statistics, 12(2), 685–726.
5. **Chen, Y., Li, P., & Wu, C.** (2020). *Doubly robust inference with nonprobability survey samples*. Journal of the American Statistical Association, 115(532), 2011–2021.
6. **Hubin, A., & Storvik, G.** (2024). *Sparse Bayesian neural networks: Bridging model and parameter uncertainty through scalable variational learning*. Mathematics, 12(6), 788.
7. **Skaaret-Lund, L., Storvik, G., & Hubin, A.** (2024). *Sparsifying Bayesian neural networks with latent binary variables and normalizing flows*. Transactions on Machine Learning Research, ISSN: 2835-8856.
8. **Høyheim, E., Skaaret-Lund, L., Sæbø, S., & Hubin, A.** (2026). *Explainable Bayesian deep learning through input-skip Latent Binary Bayesian Neural Networks*. Journal of Artificial Intelligence Research, 86 (arXiv:2503.10496).