

MCA:           Type: I2K                               Serial No.13001124  
MCA Hardware version: 2514276D

Stab.:   Type: I2K DSt.                               Serial No.0  
Zero correct: -1  
Gain centroid: 7680 ch  
Gain window: 8 chs  
Gain spacing: 64 chs  
Gain rate div: 1  
Correction rng: Ge  
Gain mode: Off  
Gain correct: 0  
Gain overrange: Clear  
Gain ratio: 1.000

HVPS:    Type: I2K HiV                               Serial No.0  
Voltage: 3000.0v  
Inh. signal: Positive  
Polarity: Positive  
Status: On  
Range: 5000  
Fault: Clear

PwrMgr:   Type: I2K PwM                               Serial No.0  
Power mode: A/C  
Bat A voltage: 10  
Standby delay: 10min

Gain:    Type: I2K Gain                               Serial No.0  
Coarse gain: 5  
Fine gain: 1.7601x  
S-fine gain: 0.999998x  
Amp gain: 8.80035  
Conv. gain: 8192  
LLD: 0.1%  
FDisc Mode: Auto  
FDisc Setting: 1.0%  
Inp. Polarity: Positive  
Inh. polarity: Positive  
LTC mode: On  
PUR Guard: 1.10x  
Inhibit Mode: Manual  
LT Trim: 500  
ICR (cps): 30  
LLD Mode: Auto  
Gain Attenuator: Off  
Inh. setting: 0

Filter:   Type: I2K Fltr                               Serial No.0  
Rise Time: 5.6  
Flat Top: 0.8  
BLR mode: Auto  
Preamp type: RC  
Pole zero: 3494  
FDisc shaping: Normal