

MCA: Type: I2K Serial No.13001124
MCA Hardware version: 2514276D

Stab.: Type: I2K DSt. Serial No.0
Zero correct: -1
Gain centroid: 7680 ch
Gain window: 8 chs
Gain spacing: 64 chs
Gain rate div: 1
Correction rng: Ge
Gain mode: Off
Gain correct: 0
Gain overrange: Clear
Gain ratio: 1.000

HVPS: Type: I2K HiV Serial No.0
Voltage: 3000.0v
Inh. signal: Positive
Polarity: Positive
Status: On
Range: 5000
Fault: Clear

PwrMgr: Type: I2K PwM Serial No.0
Power mode: A/C
Bat A voltage: 10
Standby delay: 10min

Gain: Type: I2K Gain Serial No.0
Coarse gain: 5
Fine gain: 1.7601x
S-fine gain: 0.999998x
Amp gain: 8.80035
Conv. gain: 8192
LLD: 0.1%
FDisc Mode: Auto
FDisc Setting: 1.0%
Inp. Polarity: Positive
Inh. polarity: Positive
LTC mode: On
PUR Guard: 1.10x
Inhibit Mode: Manual
LT Trim: 500
ICR (cps): 1300
LLD Mode: Auto
Gain Attenuator: Off
Inh. setting: 0

Filter: Type: I2K Fltr Serial No.0
Rise Time: 5.6
Flat Top: 0.8
BLR mode: Auto
Preamp type: RC
Pole zero: 3494
FDisc shaping: Normal