```
MCA:    Type: Lynx              Serial No.13007374

Stab.:  Type: Internal          Serial No.13007374
        Gain centroid: 10 ch
        Gain window: 4 chs
        Gain spacing: 10 chs
        Gain rate div: 1
        Corr. Range: Ge
        Gain mode: Off
        Gain correct: 0
        Gain ratio: 1.000
        Ratio Mode: Manual

HVPS:   Type: Internal          Serial No.13007374
        Voltage: -3000.0v
        Inh. signal: Positive
        Polarity: Negative
        Status: On
        Voltage limit: -3011.0v
        Range: -5000
        Fault: clear
        HVPS inhibit enabled: yes

Gain:   Type: Internal          Serial No.13007374
        Coarse gain: 4
        Fine gain: 0.87062x
        Offset: 0
        LLD: 0.1%
        FDisc Mode: Auto
        FDisc Setting: 1.0%
        Inp. Polarity: Negative
        LTC mode: On
        PUR Guard: 1.10x
        TRP Inh. Mode: Auto
        LT Trim: 500
        ICR (cps): 5
        LLD Mode: Auto
        Gain Attn.: On
        TRP Inhibit: 10us
        ULD: 100.0%
        TRP Gate Pol.: Positive
        SDisc Mode: Auto
        SDisc Setting: 1.0%

Filter: Type: I2K Fltr          Serial No.0
        Rise Time: 5.6
        Flat Top: 0.8
        BLR mode: Auto
        Preamp type: RC
        Pole zero: 2491
        FDisc shaping: Normal
```