Revision 295

Added by Lars van Duijnhoven 7 days ago

refs: #13546
Werkende code die meerdere stopberichten kan ontvangen (van meerdere meetkasten) en onderscheid kan maken tussen 29 bit en 11 bit identifiers, gecombineerd met wat bug fixes.

Related issues

- Feature #13546: Configuratie code aanpassen op de CU zodat deze meerdere meetkasten kan configureren

View differences: ○ inline ⦿ side by side

canConfigRead.cpp

```
2  #include "debug.h"

3

4  bool configComplete = false;




5

6  struct can_frame CanStopMsg;

7

8  bool checkCompletion() {

9    if (mcp2515.readMessage(&CanStopMsg) == MCP2515::ERROR_OK) {

10     if (CanStopMsg.can_id == 0) {

11       configComplete = true;

12       if(debug){

13        Serial.println(CanStopMsg.data[0]);

14        Serial.println("STOP SENDING");

15       }

16     }

17   }







18   return configComplete;

19 }

20
```

```
2  #include "debug.h"

3

4  bool configComplete = false;

5  uint8_t amountOfStopMessagesReceived = 0;

6

7  // struct can_frame CanStopMsg;

8

9  bool checkCompletion(const struct can_frame *frame) {

10   if(debug){

11     Serial.println("RECEIVED A STOP MESSAGE WITH ID: ");

12     Serial.println(frame->can_id & ~CAN_EFF_FLAG);








13   }

14   amountOfStopMessagesReceived++;

15   if(amountOfStopMessagesReceived == AMOUNTOFMODULES){

16     configComplete = true;

17   }

18   return configComplete;

19 }

20
```