## Memo-rap-check CTF Writeup

#### Task descriptions

- Browse the application. Make note of any endpoints which might process user input.
- · You can find the flag within the route "/flag". Within the source code, find the reason why you can't access it.
- · Within the source, find out how and by whom your inputs are processed.
- · Exploit the application to retrieve the flag remotely. For debuggin purposes you might want to temporarily patch the source, for example by commenting out parts of the code.

As always we go to the main page of the application and act as an innocent user

# Haters delight


networth of rapper vero case the rapper sea back full swing.

According to a recent interview the rapper plans to invest the money into the community funding supplying crack dealers with the latest and newest scales.

amet,

Due to some risky et dolore magna aliquyam erat, sed "investments" the diam voluptua. At eos 50 Cent is once accusam et justo again higher then duo dolores et ea 50 cent. After a rebum. Stet clita recent bancruptcy kasd gubergren, no takimata managed to come sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit consetetur sadipscing sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At eos Lorem ipsum dolor accusam et justo

duo dolores et ea



Rapper 50 cent back on track..

## Hot this month



### Tekashi69 sues Takeshi's Castle for copiright infringement.

Rapper allegedly states: I'm clearly in \*heavy mubmling\* and therefore this is a clear and shut case.

Main page of Memo rap, the first thing we notice is the dude sure is stoned  $\stackrel{\smile}{=}$ 



Let's not judge the funny guy and nmap the application

```
└-$ <u>sudo</u> nmap -sV 172.17.0.2
Starting Nmap 7.93 ( https://nmap.org ) at 2023-01-13 10:56 CET
Nmap scan report for 172.17.0.2
Host is up (0.0000040s latency).
Not shown: 999 closed tcp ports (reset)
PORT
            STATE SERVICE VERSION
80/tcp open http
1 service unrecognized despite returning data. If you know the service/version,
ollowing fingerprint at https://nmap.org/cgi-bin/submit.cgi?new-service :
SF-Port80-TCP:V=7.93%I=7%D=1/13%Time=63C12AE6%P=x86_64-pc-linux-gnu%r(GetR
SF:equest, E81, "HTTP/1\.1\x20200\x200K\r\nX-DNS-Prefetch-Control:\x20off\r\
SF:nExpect-CT:\x20max-age=0\r\nX-Frame-Options:\x20SAMEORIGIN\r\nStrict-Tr
SF:ansport-Security:\x20max-age=15552000;\x20includeSubDomains\r\nX-Downlo
SF:ad-Options:\x20noopen\r\nX-Content-Type-Options:\x20nosniff\r\nX-Permit
SF:ted-Cross-Domain-Policies:\x20none\r\nReferrer-Policy:\x20no-referrer\r
SF:\nX-XSS-Protection:\x200\r\ncontent-type:\x20text/html\r\ncontent-lengt
SF:h:\x203294\r\nDate:\x20Fri,\x2013\x20Jan\x202023\x2009:56:54\x20GMT\r\n
SF:Connection:\x20close\r\n\r\n<html\x20lang=\"en\">\n\x20\x20\x20<head>\n
SF:\x20\x20\x20\x20\x20\x20<meta\x20charset=\"UTF-8\">\n\x20\x20\x20\x20\x
SF:20\x20<title>Memo\x20Rap\x20Check</title>\n\x20\x20\x20\x20\x20\x20<met
SF:a\x20 name = \"viewport\"\x20 content = \"width = device - width, \x20 initial - scaller = \x20 name = \x20 n
SF:e=1,\x20user-scalable=no\">\n\x20\x20\x20\x20\x20\x20<link\x20rel=\"ico
SF:n\"\x20href=\"/static/images/favicon\.png\">\n\x20\x20\x20\x20\x20\x20<
SF:link\x20rel=\"stylesheet\"\x20href=\"/static/css/bootstrap\.min\.css\">
SF:0\x20\x20\x20<div\x20class='clouds'>\n\x20\x20\x20\x20\x20\x20\x20\x20\x20\x
SF:x20<div\x20class=\"main__wrapper\">\n\x20\x20\x20\x20\x20\x20\x20\x20\x
SF:ons,20A,"HTTP/1\.1\x20404\x20Not\x20Found\r\nX-DNS-Prefetch-Control:\x2
SF:0off\r\nExpect-CT:\x20max-age=0\r\nX-Frame-Options:\x20SAMEORIGIN\r\nSt
SF:rict-Transport-Security:\x20max-age=15552000;\x20includeSubDomains\r\nX
SF:-Download-Options:\x20noopen\r\nX-Content-Type-Options:\x20nosniff\r\nX
SF:-Permitted-Cross-Domain-Policies:\x20none\r\nReferrer-Policy:\x20no-ref
SF:errer\r\nX-XSS-Protection:\x200\r\ncontent-type:\x20application/json;\x
```

we see there is a http server running on port 80, which is common, and the other output, which is uncommon


now let's try to dirb it to find hidden directories, maybe we find something interesting

```
—— Scanning URL: http://172.17.0.2/ ——
+ http://172.17.0.2/feedback (CODE:200|SIZE:2690)
+ http://172.17.0.2/flag (CODE:401|SIZE:39)
+ http://172.17.0.2/list (CODE:401|SIZE:39)
```


we see 3 direcotries, 1 of them has to contain the flag



Feedback directory: the text field might be exploitable, but let's check other directories first



The list directory is only allowed to be accessed with localhost, so only if I am the one who runs the server



Same thing with /flag directory Let's get back to our /feedback page and see if we can inject some code in that chat box

```
</aside>
▼<article id="article">
▼ <section class="container"> overflo vsubmit http://172.17.0.2/static/js/main.js:15:36 ♂=
  ▼ <div class="row"> flex
                                     ▶ <div class="col-12 d-flex justing"
                                       e.preventDefault();
    </div>
                                        alerts.innerHTML = '';
  ▶ <div class="row"> ··· </div> flex
  ▼ <div class="row"> [flex]
                                       fetch('/api/submit', {
    ▼ <div class="container">
                                            method: 'POST',
      ▼<div class="row col-12 d-flex just /-content-center"> Tiex
   ▼<form id="form" method="POST"> event
```

from what I see the submit button creates POST request

amazing ana original you u **NOT SURE IF THEY DIDN'T READ OUR** OR THEY JUST <script>alert("ez xss")</script> Submit .....

First thing that comes to mind is to try and easily exploit the comment box with XSS to output an alert on the site, which didn't work

```
eturn reply.type('text/ntml').sena(Ts.readFlleSync('Vlews/TeedD
                    ack.html',{encoding:'utf8', flag:'r'}));
                            fastify.post('/api/submit', async (request, reply) => {
                                     let { feedback } = request.body;
                                    if (feedback) {
                                             return db.addFeedback(feedback)
                                                     .then(() => {
                                                             bot.purgeData(db);
                                                             reply.send({ message: 'Our intern has wo
                    rked tirelessly to process your feedback.' });
                                                     })
.catch(() => reply.send({ message: 'Ooops, could
                    n\'t process your feedback.', error: 1}));
Q. Search HTML
       ▼<div class="ro
        ▼ <div class="d
                                     return reply.send({ message: 'Missing parameters.', error: 1 });
          ▼<div class=
                            });
           ▼<form id=
             <div id=
                            fastify.get('/list', async (request, reply) => {
    if (request.ip != '127.0.0.1') {
        return reply.code(401).send({ message: 'Only localhost i
            ▼ <div id=
             </div>
            ▼<div cla
                    s allowed'});
              <butto
             </div>
                                     return await db.getFeedback()
            </form>
                                             .then(feedback => {
           </div>
         </div>
                                                     if (feedback) {
        </div>
                                                             return reply.view('views/list.pug', { fe
       </section>
                    edback: feedback });
      </article>
    </div>
   e/divs
```

In the container we can encounter the source code

We can notice what addFeedback() function is called when we press the button

We could have commented out the function and check /list in the browser, but what for if we already got the flag: flag\_you\_w0uldn't\_copy\_paste\_content\_Would\_u?