

C introduction

## Control structures 2

# Contents


Motivation

Loops

Miscellaneous

# THE FRIENDSHIP ALGORITHM

DR. SHELDON COOPER, Ph.D



Take a look at the right part. It is executed up to seven times.

# Loops

To repeat statements as long as a certain condition is met, C offers 3 different loops.

```
while (condition)  
    statement;
```

```
do  
    statement;  
while (condition);
```

```
for (initialization; condition; statement)  
    statement;
```

For multiple statements again, use braces.

# while

The execution of a loop is a continuous alternation between checking if the condition is still met and executing the statement(s).

```
1 int i = 2;  
2 while (i > 0)  
3     - -i;  
4 printf("done\n");
```

# while

The execution of a loop is a continuous alternation between checking if the condition is still met and executing the statement(s).

```
1 int i = 2;  
2 while (i > 0)  
3     - -i;  
4 printf("done\n");
```

1. Check ( $i > 0$ ) → true → go to line 3

# while

The execution of a loop is a continuous alternation between checking if the condition is still met and executing the statement(s).

```
1 int i = 2;  
2 while (i > 0)  
3     --i;  
4 printf("done\n");
```

1. Check ( $i > 0$ )  $\rightarrow$  true  $\rightarrow$  go to line 3
2. Decrement  $i \rightarrow i$  now is 1, go back to line 2

# while

The execution of a loop is a continuous alternation between checking if the condition is still met and executing the statement(s).

```
1 int i = 2;  
2 while (i > 0)  
3     --i;  
4 printf("done\n");
```

1. Check ( $i > 0$ )  $\rightarrow$  true  $\rightarrow$  go to line 3
2. Decrement  $i \rightarrow i$  now is 1, go back to line 2
3. Check ( $i > 0$ )  $\rightarrow$  true  $\rightarrow$  go to line 3



# while

The execution of a loop is a continuous alternation between checking if the condition is still met and executing the statement(s).

```
1 int i = 2;  
2 while (i > 0)  
3     --i;  
4 printf("done\n");
```

1. Check  $(i > 0) \rightarrow \text{true} \rightarrow$  go to line 3
2. Decrement  $i \rightarrow i$  now is 1, go back to line 2
3. Check  $(i > 0) \rightarrow \text{true} \rightarrow$  go to line 3
4. Decrement  $i \rightarrow i$  now is 0, go back to line 2

# while

The execution of a loop is a continuous alternation between checking if the condition is still met and executing the statement(s).

```
1 int i = 2;  
2 while (i > 0)  
3     - -i;  
4 printf("done\n");
```

1. Check ( $i > 0$ )  $\rightarrow$  true  $\rightarrow$  go to line 3
2. Decrement  $i \rightarrow$   $i$  now is 1, go back to line 2
3. Check ( $i > 0$ )  $\rightarrow$  true  $\rightarrow$  go to line 3
4. Decrement  $i \rightarrow$   $i$  now is 0, go back to line 2
5. Check ( $i > 0$ )  $\rightarrow$  false  $\rightarrow$  go to line 4

# while

The execution of a loop is a continuous alternation between checking if the condition is still met and executing the statement(s).

```
1 int i = 2;  
2 while (i > 0)  
3     - -i;  
4 printf("done\n");
```

1. Check  $(i > 0) \rightarrow \text{true} \rightarrow$  go to line 3
2. Decrement  $i \rightarrow i$  now is 1, go back to line 2
3. Check  $(i > 0) \rightarrow \text{true} \rightarrow$  go to line 3
4. Decrement  $i \rightarrow i$  now is 0, go back to line 2
5. Check  $(i > 0) \rightarrow \text{false} \rightarrow$  go to line 4
6. Print done

## do...while

The difference between *do...while* and *while* is the order of executing the statement(s) and checking the condition.

The *while* loop begins with checking, while the *do...while* loop begins with executing the statement(s).

```
int i = 3;  
do  
    - -i;  
while (i < 1);
```

The Statement(s) in a *do ... while* loop are executed at least once.

# for

The For-Loop is comfortable for iterating. It takes three arguments.

- ▶ Initialization
- ▶ Condition
- ▶ Iteration statement

For illustration, consider a program printing the numbers 1 to 10:

```
int i;  
for (i = 1; i <= 10; ++i)  
    printf("%d\n", i);
```

- ▶  $i$  is called an *index* iterating from the given start to a given end value
- ▶  $i, j, k$  are commonly used identifiers for the index

## Meanwhile...

Be careful, this

```
while (1 > 0)
    printf("Did you miss me?\n");
```

runs till the end of all days.

∞ loops are common mistakes, and you will experience many of them.  
Check for conditions that are always true.

## for ever

The arguments for the *for loop* are optional. E.g. if you already have defined your iterating variable:

```
int i = 1;
for (; i <= 10; ++i)
    printf("%d\n", i);
```

Or if you have the iteration statement in your loop body:

```
for (i = 1; i <= 10;)
    printf("%d\n", ++i);    /* seems more like a while loop
*/
```

And if you're not passing anything, it runs forever:

```
for (;;)
    printf("I'm still here\n");
```

Note: the semicolons are still there.

# Cancelling loops

## *break*

- ▶ Ends loop execution
- ▶ Moves forward to first statement after loop

## *continue*

- ▶ Ends current loop iteration
- ▶ Moves forward to next step of loop iteration
  - ▶ *while*: Jumps to condition
  - ▶ *for*: Jumps to iteration statement



## Saving code lines

You can define variables inside the initialization part of a for loop.

```
for (int i = 1; i <= 10; ++i)
    printf("%d\n", i);
```

In that case, the variable is only available inside the for loop (as if it was declared in the body).

```
1 int guess = 0;
2 int solution = 42;
3 for (int i = 1; guess != solution; ++i)
4     scanf("%d", &guess);
5 printf("Tries: %d\n", i);    /* invalid! */
```

This feature was added in the C99 standard.

## Compiler options

When calling `gcc`, you can pass several options to it:

option	description
<code>-std=c99</code>	Use C99 as the standard
<code>-o &lt;name&gt;</code>	output file is <i>name</i> instead of <i>a.out</i>
<code>-Wall</code>	Enable all compiler warnings
<code>-Wextra</code>	Enable even more compiler warnings
<code>-Werror</code>	Treat warnings as errors

Example:

```
$ gcc -std=c99 -o main main.c
```

## A few words on style

- ▶ Stay consistent after deciding whether to use or not to use braces on a single statement
- ▶ If you skip the loop body
  - ▶ Leave a comment in your code
  - ▶ Use an extra line for the empty statement

```
for (i = 1; i < 9; printf("%d\n", ++i));    /* confusing */  
  
for (i = 1; i < 9; printf("%d\n", ++i))    /* clear */  
;    /* do nothing */
```