

North Data API

Programmatic access to the North Data DB.

More information: <https://github.com/northdata/api/blob/master/doc/data-api-userguide/data-api-userguide.md>

Contact Info: support@northdata.de

Version: 1.232.11

BasePath: /_api

All rights reserved

<http://apache.org/licenses/LICENSE-2.0.html>

Access

Methods

[[Jump to Models](#)]

Table of Contents

[Default](#)

- [GET /billing/v1/requests](#)
- [GET /company/v1/company](#)
- [GET /company/v1/publications](#)
- [GET /person/v1/person](#)
- [GET /person/v1/publications](#)
- [GET /pub/v1/publications](#)
- [GET /search/v1/power](#)
- [GET /search/v1/suggest](#)
- [GET /search/v1/universal](#)

Default

[Up](#)

GET /billing/v1/requests

(billingV1RequestsGet)

number of unique requests

Query parameters

year (optional)

Query Parameter – year of the billing period (>= 2024) format: int32

month (optional)

Query Parameter – month of the billing period between 1 (January) and 12 (December) format: int32

output (optional)

Query Parameter – response format default: json

Return type

[Billing](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses**200**A successful response [Billing](#)[Up](#)**GET /company/v1/company****(companyV1CompanyGet)**

Retrieve a company.

Query parameters**name (optional)***Query Parameter* – company name**address (optional)***Query Parameter* – company address (you only need to specify the city)**registerId (optional)***Query Parameter* – the ID of under which the company is registered, for example HRB 12345**registerCity (optional)***Query Parameter* – the city of the court where the company is registered, for example Hamburg**companyId (optional)***Query Parameter* – internal company id (do not store this id in an external database, it may change over time)**fuzzyMatch (optional)***Query Parameter* – true to find best match (similar name and nearby address)**registerKey (optional)***Query Parameter* – key that has been provided via the register uniqueKey field**history (optional)***Query Parameter* – true to include historical data**financials (optional)***Query Parameter* – true to include financial data**events (optional)***Query Parameter* – true to include event data**eventTypes (optional)***Query Parameter* – restrict which event types will be returned if events equals true**maxEvents (optional)***Query Parameter* – maximum number of events to return format: int32**relations (optional)***Query Parameter* – true to include related company and person data**alwaysResolve (optional)***Query Parameter* – true to lookup current state of related company from database**sheets (optional)***Query Parameter* – true to include company financial sheets (balance, earnings)**extras (optional)***Query Parameter* – true to include extra company data provided by 3rd parties**output (optional)***Query Parameter* – response format default: json**Return type**[Company](#)**Example data**

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [Company](#).

[Up](#)

GET /company/v1/publications

(companyV1PublicationsGet)

Retrieve the publications associated with a company.

Query parameters

name (optional)

Query Parameter — company name

address (optional)

Query Parameter — company address (you only need to specify the city)

registerId (optional)

Query Parameter — the ID of under which the company is registered, for example HRB 12345

registerCity (optional)

Query Parameter — the city of the court where the company is registered, for example Hamburg

companyId (optional)

Query Parameter — internal company id (do not store this id in an external database, it may change over time)

fuzzyMatch (optional)

Query Parameter — true to find best match (similar name and nearby address)

registerKey (optional)

Query Parameter — key that has been provided via the register uniqueKey field

minTimestamp (optional)

Query Parameter — minimum datetime publication was added to the database format: date-time

maxTimestamp (optional)

Query Parameter — maximum datetime publication was added to the database format: date-time

minPublicationDate (optional)

Query Parameter — minimum date publication was published on (by the source) format: date

maxPublicationDate (optional)

Query Parameter — maximum date publication was published on (by the source) format: date

sources (optional)

Query Parameter — DEPRECATED (will be removed at some point of time)

source (required)

Query Parameter — only publications with this source will be returned

content (optional)

Query Parameter — whether to include publication text / html (may significantly slow down response)

attachments (optional)

Query Parameter — whether to include publication attachments (binary, such as images or PDF)

censor (optional)

Query Parameter — should be set when presenting the content on a public website

offset (optional)

Query Parameter — offset of first item to return format: int32

limit (optional)

Query Parameter — maximum number of items to return format: int32

output (optional)

Query Parameter — response format default: json

Return type

[GenericResponse](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [GenericResponse](#)

[Up](#)

GET /person/v1/person

(personV1PersonGet)

Retrieve a person.

Query parameters

firstName (optional)

Query Parameter — first name(s) of a person

lastName (optional)

Query Parameter — last name of a person

address (optional)

Query Parameter — person address (you only need to specify the city)

birthDate (optional)

Query Parameter — birth date format: date

personId (optional)

Query Parameter — internal person id (do not store this id in an external database, it may change over time)

history (optional)

Query Parameter — true to include historical data

relations (optional)

Query Parameter — true to include related company and person data

alwaysResolve (optional)

Query Parameter — true to lookup current state of related company from database

output (optional)

Query Parameter — response format default: json

Return type

[Person](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [Person](#)

[Up](#)

GET /person/v1/publications

(personV1PublicationsGet)

Retrieve the publications associated with a person.

Query parameters

firstName (optional)

Query Parameter — first name(s) of a person

lastName (optional)

Query Parameter — last name of a person

address (optional)

Query Parameter — person address (you only need to specify the city)

birthDate (optional)

Query Parameter — birth date format: date

personId (optional)

Query Parameter — internal person id (do not store this id in an external database, it may change over time)

minTimestamp (optional)

Query Parameter — minimum datetime publication was added to the database format: date-time

maxTimestamp (optional)

Query Parameter — maximum datetime publication was added to the database format: date-time

minPublicationDate (optional)

Query Parameter — minimum date publication was published on (by the source) format: date

maxPublicationDate (optional)

Query Parameter — maximum date publication was published on (by the source) format: date

sources (optional)

Query Parameter — DEPRECATED (will be removed at some point of time)

source (required)

Query Parameter — only publications with this source will be returned

content (optional)

Query Parameter — whether to include publication text / html (may significantly slow down response)

attachments (optional)

Query Parameter — whether to include publication attachments (binary, such as images or PDF)

censor (optional)

Query Parameter — should be set when presenting the content on a public website

offset (optional)

Query Parameter — offset of first item to return format: int32

limit (optional)

Query Parameter — maximum number of items to return format: int32

output (optional)

Query Parameter — response format default: json

Return type

[GenericResponse](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [GenericResponse](#)

GET /pub/v1/publications

[Up](#)

(pubV1PublicationsGet)

Retrieve publications. At most 10 publications are returned with each call. For more, repeat the call setting the pos parameter to the newPos attribute value of the response.

Query parameters

id (optional)

Query Parameter — publication id to get a single publication

minDate (optional)

Query Parameter — DEPRECATED - please use minTimestamp or minPublicationDate instead format: date

maxDate (optional)

Query Parameter — DEPRECATED - please use maxTimestamp or maxPublicationDate instead format: date

minTimestamp (optional)

Query Parameter — minimum datetime publication was added to the database format: date-time

maxTimestamp (optional)

Query Parameter — maximum datetime publication was added to the database format: date-time

minPublicationDate (optional)

Query Parameter — minimum date publication was published on (by the source) format: date

maxPublicationDate (optional)

Query Parameter — maximum date publication was published on (by the source) format: date

sources (optional)

Query Parameter — DEPRECATED (will be removed at some point of time)

source (required)

Query Parameter — only publications with this source will be returned

content (optional)

Query Parameter — whether to include publication text / html (may significantly slow down response)

attachments (optional)

Query Parameter — whether to include publication attachments (binary, such as images or PDF)

publisherHistory (optional)

Query Parameter — true to include historical data for the publisher

publisherFinancials (optional)

Query Parameter — true to include financial data for the publisher

publisherRelations (optional)

Query Parameter — true to include related company and person data for the publisher

publisherEvents (optional)

Query Parameter — true to include event data for the publisher

publisherExtras (optional)

Query Parameter — true to include extra publisher data provided by 3rd parties

publisherSheets (optional)

Query Parameter — true to include publisher sheets (balance, earnings)

pos (optional)

Query Parameter – if additional results shall be downloaded, set this to the value of the newPos attribute of the previous response

censor (optional)

Query Parameter – should be set when presenting the content on a public website

output (optional)

Query Parameter – response format default: json

Return type

[GenericResponse](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [GenericResponse](#)

[Up](#)

GET /search/v1/power

(searchV1PowerGet)

power search: supports geo and financial criteria

Query parameters**keywords (optional)**

Query Parameter – keywords to match in the company's subject

address (optional)

Query Parameter – address or geo coordinates

maxDistanceKm (optional)

Query Parameter – maximum distance from given address format: double

legalForm (optional)

Query Parameter – list of legal forms

segmentCodeStandard (optional)

Query Parameter – name of the segment code standard to use

segmentCodes (optional)

Query Parameter – list of segment codes

indicatorId (optional)

Query Parameter – list of indicator ids for performance filtering (see user guide)

lowerBound (optional)

Query Parameter – list of lower bounds for performance filterings (see user guide) format: double

upperBound (optional)

Query Parameter – list of upper bounds for performance filterings (see user guide) format: double

lowerBoundUnit (optional)

Query Parameter – list of lower bound units. Only required for currencies different from EUR

upperBoundUnit (optional)

Query Parameter – list of upper bound units. Only required for currencies different from EUR

eventType (optional)

Query Parameter – list of event types for event filtering (see user guide)

minDate (optional)

Query Parameter – list of minimum dates for event filterings (see user guide) format: date

maxDate (optional)

Query Parameter – list of maximum dates for event filterings (see user guide) format: date

countries (optional)

Query Parameter – list of country ISO codes to restrict result set (empty to retrieve all countries)

status (optional)

Query Parameter – list of valid statuses (active, terminated, liquidation)

history (optional)

Query Parameter – true to include historical data

financials (optional)

Query Parameter – true to include financial data

events (optional)

Query Parameter – true to include event data

eventTypes (optional)

Query Parameter – restrict which event types will be returned if events equals true

maxEvents (optional)

Query Parameter – maximum number of events to return format: int32

relations (optional)

Query Parameter – true to include related company and person data

alwaysResolve (optional)

Query Parameter – true to lookup current state of related company from database

sheets (optional)

Query Parameter – true to include company financial sheets (balance, earnings)

extras (optional)

Query Parameter – true to include extra company data provided by 3rd parties

pos (optional)

Query Parameter – if additional results shall be downloaded, set this to the value of the nextPos attribute of the previous response

censor (optional)

Query Parameter – should be set when presenting the content on a public website

limit (optional)

Query Parameter – maximum number of items to return format: int32

output (optional)

Query Parameter – response format default: json

Return type

[SearchResults](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [SearchResults](#)

GET /search/v1/suggest

(searchV1SuggestGet)

auto complete: provides quick company and person suggestions for given input query

Query parameters

query (required)

Query Parameter — the query string

domain (optional)

Query Parameter — "company" to match companies only, "person" to match persons only, empty to match all

history (optional)

Query Parameter — true to include former company names

censor (optional)

Query Parameter — should be set when presenting the content on a public website

offset (optional)

Query Parameter — offset of first item to return format: int32

limit (optional)

Query Parameter — maximum number of items to return format: int32

output (optional)

Query Parameter — response format default: json

countries (optional)

Query Parameter — list of country ISO codes to restrict result set (empty to retrieve all countries)

status (optional)

Query Parameter — list of valid statuses (active, terminated, liquidation)

Return type

[SearchResults](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [SearchResults](#)

GET /search/v1/universal

(searchV1UniversalGet)

universal search: provides best company and person matches for given input query

Query parameters

query (required)

Query Parameter — the query string

domain (optional)

Query Parameter — set to "company" for companies only, "person" for persons only, otherwise leave empty

pos (optional)

Query Parameter – if additional results shall be downloaded, set this to the value of the nextPos attribute of the previous response

censor (optional)

Query Parameter – should be set when presenting the content on a public website

offset (optional)

Query Parameter – offset of first item to return format: int32

limit (optional)

Query Parameter – maximum number of items to return format: int32

output (optional)

Query Parameter – response format default: json

countries (optional)

Query Parameter – list of country ISO codes to restrict result set (empty to retrieve all countries)

status (optional)

Query Parameter – list of valid statuses (active, terminated, liquidation)

history (optional)

Query Parameter – true to include historical data

financials (optional)

Query Parameter – true to include financial data

events (optional)

Query Parameter – true to include event data

eventTypes (optional)

Query Parameter – restrict which event types will be returned if events equals true

maxEvents (optional)

Query Parameter – maximum number of events to return format: int32

relations (optional)

Query Parameter – true to include related company and person data

alwaysResolve (optional)

Query Parameter – true to lookup current state of related company from database

sheets (optional)

Query Parameter – true to include company financial sheets (balance, earnings)

extras (optional)

Query Parameter – true to include extra company data provided by 3rd parties

Return type

[SearchResults](#)

Example data

Content-Type: application/json

```
{"empty": false}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- application/xml

Responses

200

A successful response [SearchResults](#)

Models

[[Jump to Methods](#)]

Table of Contents

1. [Address -](#)
2. [AddressHistoryItem -](#)
3. [Attachment -](#)
4. [Billing -](#)
5. [Company - Company](#)
6. [CompanyHistory -](#)
7. [CompanyName -](#)
8. [CompanyNameHistoryItem -](#)
9. [Event -](#)
10. [EventType -](#)
11. [Events -](#)
12. [Extra -](#)
13. [Extras -](#)
14. [Filing -](#)
15. [Financial -](#)
16. [Financials -](#)
17. [FinancialsNote -](#)
18. [FinancialsSource -](#)
19. [GenericResponse -](#)
20. [Money -](#)
21. [Order -](#)
22. [OrderItem -](#)
23. [Person -](#)
24. [PersonName -](#)
25. [Product -](#)
26. [Publication -](#)
27. [PublicationSource -](#)
28. [PublicationStructure -](#)
29. [Register -](#)
30. [RegisterHistoryItem -](#)
31. [Relation -](#)
32. [Relations -](#)
33. [Role -](#)
34. [Role_sharesNominal -](#)
35. [SearchResult -](#)
36. [SearchResults -](#)
37. [Sheet -](#)
38. [SheetCell -](#)
39. [SheetColumnHeader -](#)
40. [SheetRow -](#)
41. [SourceSnippet -](#)
42. [Topic -](#)

Address -

[Up](#)

street (optional)

[String](#) street and house number

extra (optional)

[String](#) extra address information (such as c/o)

postalCode (optional)

[String](#) postal code

city

[String](#) city

state (optional)

[String](#) state

country

[String](#) two-letter ISO country code

lat (optional)

[Double](#) geo coordinates, latitude part format: double

lng (optional)

[Double](#) geo coordinates, longitude part format: double

formattedValue (optional)

[String](#) the whole address in one human readable string

AddressHistoryItem -

[Up](#)

address

[Address](#)

date (optional)

[date](#) since when the referred address is (known to be) in use format: date

Attachment -

[Up](#)

binary content related to a publication

name

[String](#) name of attachment

url

[String](#) url to download from (link will be valid for 3 days)

contentType

[String](#) mime type

Billing -

[Up](#)

number of requests in billing period

periodStart (optional)

[date](#) begin of the billing period format: date

periodEnd (optional)

[date](#) end of the billing period format: date

numberOfRequests (optional)

[Integer](#) number of unique requests format: int32

Company - Company

[Up](#)

All data for a particular company

id

[String](#) internal company id (do not store this id in an external database, it may change over time)

name

[CompanyName](#) name of the company

rawName (optional)

[String](#) May provide the raw name found in register sources before applying normalizations and spelling fixes

address

[Address](#) current address

register (optional)

[Register](#) register information

lei (optional)

[String](#) International Legal Entity Identifier (LEI)

euld (optional)

[String](#) European Unique Identifier (EUID)

elfCode (optional)

[String](#) current entity legal form code according to ISO 20275

subject (optional)

[String](#) subject according to register filing (also called corporate object, purpose, Unternehmensgegenstand), possibly translated

originalSubject (optional)

[*String*](#) subject according to register filing (also called corporate object, purpose, Unternehmensgegenstand), in the original language

originalSubjectLang (optional)

[*String*](#) original language of the subject

proxyPolicy (optional)

[*String*](#) rules for representation by legal representatives (e.g., signatory authority)

segmentCodes (optional)

[*map\[String, array\[String\]\]*](#) each property (naics, isic, nace, wz, uksic) contains a list of segment codes in respective standard classification

northDataUrl (optional)

[*String*](#) North data web page for this company

terminated (optional)

[*Boolean*](#) company has been terminated

status (optional)

[*String*](#) current status of the company, where liquidation is the intermediate state before the final removal from the register (=terminated)

Enum:

active

liquidation

terminated

history (optional)

[*CompanyHistory*](#) earlier names, addresses, and register entries

capital (optional)

[*Financials*](#) base respectively share capital

financials (optional)

[*Financials*](#) financial performance indicators

mktgTechIndicators (optional)

[*Financials*](#) Marketing and technology indicators (structure same as with financials)

events (optional)

[*Events*](#) relevant events in the history of the company

extras (optional)

[*array\[Extras\]*](#) extra data provided by 3rd parties

sheets (optional)

[*array\[Sheet\]*](#) company's financial sheets (such as balance and earnings sheets)

relatedCompanies (optional)

[*Relations*](#) related companies

relatedPersons (optional)

[*Relations*](#) related persons

filings (optional)

[*array\[Filing\]*](#) external source-specific IDs

blocked (optional)

[*Boolean*](#) company data should not be publicly on the Internet because of a request for privacy protection

lastUpdateTime (optional)

[*Date*](#) last time this company was updated format: date-time

CompanyHistory -

[Up](#)

names (optional)

[*array\[CompanyNameHistoryItem\]*](#) name history of a company

addresses (optional)

[*array\[AddressHistoryItem\]*](#) address history of a company

registers (optional)

[*array\[RegisterHistoryItem\]*](#) register entry history of a company

financials (optional)

[array\[Financials\]](#) historical financial data

mktgTechIndicators (optional)

[array\[Financials\]](#) historical financial data

CompanyName -

[Up](#)

name

[String](#) name of a company

legalForm (optional)

[String](#) legal form (for example: A/S, AG, AG & Co. KG, AöR, Co. KG, d.o.o., e. K., e. V., eG, EWIV, gAG, GbR, gGmbH, GmbH, GmbH & Co. KG, gSE, gUG, Inh., InvAG, KG, KGaA, KGaA & Co. KG, Ltd., Ltd. & Co. KG, OHG, PartGG, plc, REITG, S.L., SCE, SCE, SCE mbH, SE, SE & Co. KG, Stiftung & Co. KG, UG, UG & Co. KG, VVaG)

CompanyNameHistoryItem -

[Up](#)

name

[CompanyName](#)

date (optional)

[date](#) since when the referred company name is (known to be) in use format: date

Event -

[Up](#)

event

type (optional)

[String](#) one of ...

date (optional)

[date](#) when it happened format: date

description (optional)

[String](#) human-readable description of what happend

EventType -

[Up](#)

event type (for possible values, see Appendix G of the user's guide)

Events -

[Up](#)

list of events

items

[array\[Event\]](#) the list of events

Extra -

[Up](#)

extra data item, typically provided by a 3rd party.

id

[String](#) common ids are: email, url, phone, fax, vatId, wz

name

[String](#) describing name (for example, "Email" with English language settings, "E-Mail" with German language settigns)

value

[String](#) actual value

formattedHtmlValue

[String](#) value formatted as an HTML string

Extras -

[Up](#)

set of additional data, typically provided by 3rd parties.

sourceName (optional)

[*String*](#) name of the source

sourceUrl (optional)

[*String*](#) url of the source

items (optional)

[*array\[Extra\]*](#) extra data items in this set

Filing -

[Up](#)

Filings are external IDs that are used by an external source (for example the insolvency filing ID for the Ins source)

type (optional)

[*String*](#) filing type

name (optional)

[*String*](#) complete string

source (optional)

[*PublicationSource*](#)

city (optional)

[*String*](#) city (only for German insolvency filings)

id

[*String*](#) external ID (e.g., 36w IN 3284/16 for insolvency filings)

Financial -

[Up](#)

single financial number

id

[*String*](#) type of number (for example, revenue). Please see the [indicator reference](#) for a complete list

name

[*String*](#) name in current language (for example, Umsatz in German or Revenue in English)

value

[*Double*](#) actual value format: double

unit (optional)

[*String*](#) unit or currency (EUR, % or empty)

estimate (optional)

[*Boolean*](#) true if the value is not exact (because it relies on an estimate or an unsafe determination method)

note (optional)

[*String*](#) optional note or comment with respect to the calculation of the financial

formattedValue

[*String*](#) value formatted as a string (depending on the language settings)

Financials -

[Up](#)

financial data

date

[*date*](#) reference date format: date

formattedDate

[*String*](#) date formatted as a string (depending on the language settings)

consolidated

[*Boolean*](#) true if the financial data refer to a consolidated balance (Konzernabschluss)

source (optional)

[*FinancialsSource*](#) source of financial data

items

[array\[Financial\]](#) list of financial numbers (maybe empty. If empty, see note for the reason)

note (optional)

[FinancialsNote](#) explaining numbers (or their absence)

FinancialsNote -

[Up](#)

additional explanation of financials (or of their absence)

text

[String](#) explanation as plain text

html

[String](#) explanation as html

FinancialsSource -

[Up](#)

source of financial data

publicationId (optional)

[String](#) internal publication ID

publicationTitle

[String](#) publication title such as "Jahresabschluss 2015"

publicationDate

[date](#) date the publication was published format: date

auditorName (optional)

[String](#) name of auditing company

snippets (optional)

[array\[SourceSnippet\]](#) excerpts from the original publication containing the financial data

GenericResponse -

[Up](#)

newPos (optional)

[String](#)

publications (optional)

[array\[Publication\]](#)

Money -

[Up](#)

amount and currency

currency

[String](#) currency (three-letter code)

amount

[Double](#) amount as a number format: double

formattedValue

[String](#) amount and currency formatted as a human-readable string

Order -

[Up](#)

result of an order

id (optional)

[String](#) string to identify the order

items (optional)

[array\[OrderItem\]](#)

OrderItem -

[Up](#)

information whether and where a product maybe downloaded

product (optional)
[Product](#) product bought

status
[String](#) whether the publication is ready for download
Enum:
 waiting
 ready
 unavailable

url (optional)
[String](#) url to download from (when the status is 'ready')

contentType (optional)
[String](#) mime type

Person -

[Up](#)

id
[String](#) internal person id (do not store this id in an external database, it may change over time)

name
[PersonName](#)

address (optional)
[Address](#)

birthDate (optional)
[date](#) Birth date format: date

birthYear (optional)
[Integer](#) Sometimes only the birth years is known, but not the exact date format: int32

birthMonth (optional)
[Integer](#) Sometimes only birth year and month are known, but not the exact date format: int32

deceased (optional)
[Boolean](#) person is known to be dead

northDataUrl (optional)
[String](#) North data web page for this person

relatedCompanies (optional)
[Relations](#) Related companies

filings (optional)
[array\[Filing\]](#) external source-specific IDs

blocked (optional)
[Boolean](#) person data should not be publicly on the Internet because of a request for privacy protection

lastUpdateTime (optional)
[Date](#) last time this person was updated format: date-time

PersonName -

[Up](#)

firstName (optional)
[String](#) first name(s)

lastName
[String](#) last name

title (optional)
[String](#) title

Product -

[Up](#)

a publication that can be bought and downloaded

id
[String](#) string to identify a product when ordering for download

name
[String](#) name of the product

date (optional)
[date](#) publishing date format: date

price
[Money](#) cost of the product

Publication -

[Up](#)

id
[String](#) interne ID

date (optional)
[date](#) publishing date format: date

effectiveDate (optional)
[date](#) date when published changes became effective (e.g., appointment of new director) format: date

creationTime (optional)
[Date](#) database creation time (which is right after the initial publication download) format: date-time

source
[PublicationSource](#)

sourceName (optional)
[String](#) full name of source

category (optional)
[String](#) category under which publication was filed in the original source

originalLanguage (optional)
[String](#) ISO language code

language (optional)
[String](#) ISO language code. This is different from the original language, for translations only.

title
[String](#) title of publication

northDataUrl (optional)
[String](#) North data web page for this publication

text (optional)
[String](#) raw text of the publication

html (optional)
[String](#) text of publication in HTML format

publisher (optional)
[Company](#) company that published this publication

structure (optional)
[PublicationStructure](#) result of structural analysis

mentionedCompanies (optional)
[Relations](#) list of companies mentioned in this publication

mentionedPersons (optional)
[Relations](#) list of persons mentioned in this publication

filings (optional)
[array\[Filing\]](#) external filing IDs (e.g. insolvency filing IDs)

attachments (optional)
[array\[Attachment\]](#) additional binary content such as images or PDF

blocked (optional)
[Boolean](#) publication data should not be publicly on the Internet because of a request for privacy protection

internal (optional)
[Object](#) additional data used for internal purposes

PublicationSource -

[Up](#)

Source identifier, for a complete list see [Source reference](#)

PublicationStructure -

[Up](#)

result of the structural analysis of a publication

topics (optional)

[array\[Topic\]](#) topics of the publication

Register -

[Up](#)

register entry information (e.g., Amtsgericht Hamburg HRB 9999)

country (optional)

[String](#) register country (two-letter ISO code)

city (optional)

[String](#) city of the register court (e.g. Hamburg). Empty for most countries.

id

[String](#) ID of the register filing (e.g. HRB 9999)

uniqueKey (optional)

[String](#) unique numerical key for repeatably unique identification of the register entry

RegisterHistoryItem -

[Up](#)

register

[Register](#)

date (optional)

[date](#) since when this registry entry is valid format: date

Relation -

[Up](#)

relation of a company or person to another company or person

company (optional)

[Company](#) Related company (only base data - id, name, address, register)

person (optional)

[Person](#) Related person (only base data - id, first and last name, address, birth date)

description (optional)

[String](#) human readable short summary

roles

[array\[Role\]](#) description of the type of the relation

Relations -

[Up](#)

list of related companies / persons

items

[array\[Relation\]](#)

Role -

[Up](#)

description of the type of a relation

date (optional)

[date](#) date format: date

name

[String](#) description (depending on the current language settings)

detail (optional)

[*String*](#) depending on role and country

demotion (optional)

[*Boolean*](#) true if the relation ends at the given date

announce (optional)

[*Boolean*](#) true if the relation might be preliminary

type

[*String*](#) internal identifier (for possible values, see Appendix F of the User's Guide)

group

[*String*](#) internal group identifier

Enum:

Succession

Control

Merger

Personal

Other

Interest

dir (optional)

[*String*](#) Direction. The exact interpretation depends of the value of the field "group". Case "succession" - older company is "Source". Case "merger" - Sold company is "Source", Buyer is target "Target". Case "control" - controlling company is "Source".

Enum:

None

Source

Target

Bi

sharesPercent (optional)

[*Double*](#) shares in percent format: double

sharesNominal (optional)

[*Role*](#) [*sharesNominal*](#)

Role_sharesNominal -

[Up](#)

nominal shares

value

[*Double*](#) actual value format: double

unit

[*String*](#) unit or currency (EUR, % or empty)

SearchResult -

[Up](#)

company, person or publication that is result of a search

company (optional)

[*Company*](#) company found

person (optional)

[*Person*](#) person found

publication (optional)

[*Publication*](#) publication found

matchedName (optional)

[*String*](#) the matched name (useful if a company has been renamed)

SearchResults -

[Up](#)

search results

results (optional)

[*array\[SearchResult\]*](#) list of results

censored (optional)

[*Boolean*](#) true if results have been omitted because of censoring

offset (optional)

[Integer](#) offset of result array in all results format: int32

nextOffset (optional)

[Integer](#) offset to retrieve next batch of results format: int32

nextPos (optional)

[String](#) position to retrieve next batch of results

total (optional)

[Integer](#) total number of results (usually, this number is not available, unfortunately) format: int32

Sheet -

[Up](#)

represents balance sheets, profit and loss statements, and similar structures

columnHeaders

[array\[SheetColumnHeader\]](#) list of column headers

rows

[array\[SheetRow\]](#) list of rows

type

[String](#) the kind of financial data reported in this sheet

Enum:

balance

earnings

cashflow

consolidated

[Boolean](#) true if the financial is consolidated (including dependent companies) or not (excluding)

reporting (optional)

[String](#) the reporting standard used

Enum:

HGB

IFRS

GAAP

unit (optional)

[String](#) unit or currency (EUR, % or empty)

SheetCell -

[Up](#)

cell of a sheet

value (optional)

[Double](#) numeric value format: double

SheetColumnHeader -

[Up](#)

column header of a sheet

date

[date](#) the date of entries in this column format: date

source (optional)

[FinancialsSource](#) source of entries in this column

SheetRow -

[Up](#)

row of a sheet

name

[String](#) name of row

level (optional)

[Integer](#) if the sheet is structured as a tree, indicates the depth of the nesting of this row. format: int32

cells

[array\[SheetCell\]](#) list of cells

SourceSnippet -

[Up](#)

excerpts from an original publication

title

[String](#) title

content

[String](#) text

contentType (optional)

[String](#) content format, usually "text/html"

Topic -

[Up](#)

topic of a publication

name

[String](#) textual description

value (optional)

[String](#) accompanying value (e.g., €100.000,-)

type

[String](#) internal identifier for the topic (for possible values, see Appendix E of the user's guide)