Packet Dissection Using Python.

PACKET STRUCTURE





3

PACKET STRUCTURE







PACKET DISSECTION USING PYTHON

SCAPY LIBRARY – SHOW()

```
from scapy.all import *

packet_dump_file = "tcp_dump.pcap"
packets = rdpcap(packet_dump_file)

for i, packet in enumerate(packets[:20]):
    print(f"Packet {i + 1}:")
    packet.show()
```

```
###[ Ethernet ]###
  dst       = 54:b1:21:3a:a3:cc
  src       = 64:6c:80:18:5d:03
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 52
     id        = 1078
     flags     = DF
     flags     = DF
     frag      = 0
     ttl       = 64
     proto     = tcp
     chksum    = 0xf975
     src       = 192.168.8.105
     dst       = 34.95.81.168
     \options   \
###[ TCP ]###
        sport     = 40548
        dport     = https
        seq       = 1607385021
        ack       = 1363999823
        dataofs   = 8
        reserved  = 0
        flags     = A
        window    = 501
        chksum    = 0x3d3f
        urgptr    = 0
        options   = [('NOP', None), ('NOP', None), ('Timestamp', (4059643989, 960217662))]
```





2-dissection_extract.py - /home/madukajay/Desktop/network_programming/...
File Edit Format Run Options Window Help
from scapy.all import *
packet_dump_file = "tcp_dump.pcap"
packets = rdpcap(packet_dump_file)
def dissect_packet(packet):
#print(packet.summary())
packet.show()
if Ether in packet:
print("Source MAC:", packet[Ether].src)
print("Destination MAC:", packet[Ether].dst)
if IP in packet:
print("Source IP:", packet[IP].src)
print("Destination IP:", packet[IP].dst)
if TCP in packet:
print("Source Port:", packet[TCP].sport)
print("Destination Port:", packet[TCP].dport)
print("Window:", packet[TCP].window)
print("\n")
for i, packet in enumerate(packets[:20]):
print(f"Packet {i + 1}:")
#packet.show()
dissect_packet(packet)


2-dissection_extract.py - /home/madukajay/Desktop/network_programming/...
File Edit Format Run Options Window Help
Ln: 13 Col: 0
IDLE Shell 3.10.12
File Edit Shell Debug Options Window Help
Source IP: 192.168.8.105
Destination IP: 34.111.113.62
Proto: 6
Source Port: 56930
Destination Port: 443
Packet 20:
###[Ethernet]###
dst = 54:b1:21:3a:a3:cc
src = 64:6c:80:18:5d:03
type = IPv4
###[IP]###
version = 4
ihl = 5
tos = 0x0
len = 52
id = 1078
flags = DF
frag = 0
ttl = 64
proto = tcp
chksum = 0xf975
src = 192.168.8.105
dst = 34.95.81.168
\options \
###[TCP]###
sport = 40548
dport = https
seq = 1607385021
ack = 1363999823
dataofs = 8
reserved = 0
flags = A
window = 501
chksum = 0x3d3f
urgptr = 0
options = [('NOP', None), ('NOP', None), ('Timestamp', (4059643989, 960217662))]
Source IP: 192.168.8.105
Destination IP: 34.95.81.168
Proto: 6
Source Port: 40548
Destination Port: 443
Session


IDLE Shell 3.10.12
File Edit Shell Debug Options Window Help
Source IP: 192.168.8.105
Destination IP: 34.111.113.62
Proto: 6
Source Port: 56930
Destination Port: 443
Packet 20:
###[Ethernet]###
dst = 54:b1:21:3a:a3:cc
src = 64:6c:80:18:5d:03
type = IPv4
###[IP]###
version = 4
ihl = 5
tos = 0x0
len = 52
id = 1078
flags = DF
frag = 0
ttl = 64
proto = tcp
chksum = 0xf975
src = 192.168.8.105
dst = 34.95.81.168
\options \
###[TCP]###
sport = 40548
dport = https
seq = 1607385021
ack = 1363999823
dataofs = 8
reserved = 0
flags = A
window = 501
chksum = 0x3d3f
urgptr = 0
options = [('NOP', None), ('NOP', None), ('Timestamp', (4059643989, 960217662))]
Source IP: 192.168.8.105
Destination IP: 34.95.81.168
Proto: 6
Source Port: 40548
Destination Port: 443
>>>
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
Apply a display filter ... <Ctrl-/>
No. Time Source Destination Protocol Length Info
1 0.000000 192.168.8.105 35.186.232.68 TCP 66 47918 → 443 [ACK] Seq=1 Ack
2 0.068140 35.186.232.68 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
3 0.171988 192.168.8.105 3.230.74.156 TCP 66 47758 → 443 [ACK] Seq=1 Ack
4 0.479347 3.230.74.156 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
5 1.988033 192.168.8.105 35.208.249.213 TCP 66 40298 → 443 [ACK] Seq=1 Ack
6 2.040013 192.168.8.105 35.244.159.8 TCP 66 50286 → 443 [ACK] Seq=1 Ack
7 2.040049 192.168.8.105 35.244.154.8 TCP 66 44444 → 443 [ACK] Seq=1 Ack
8 2.040083 192.168.8.105 34.120.11.34 TCP 66 43194 → 443 [ACK] Seq=1 Ack
9 2.063993 192.168.8.105 69.173.158.64 TCP 66 37144 → 443 [ACK] Seq=1 Ack
10 2.103529 35.244.159.8 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
11 2.103840 34.120.11.34 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
12 2.104445 35.244.154.8 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
13 2.143637 69.173.158.64 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
14 2.322836 35.208.249.213 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
15 4.036021 192.168.8.105 23.52.114.50 TCP 66 36338 → 443 [ACK] Seq=1 Ack
16 4.038572 192.168.8.105 69.173.158.64 TCP 66 37142 → 443 [ACK] Seq=1 Ack
17 4.068010 192.168.8.105 35.186.253.211 TCP 66 42442 → 443 [ACK] Seq=1 Ack
18 4.091964 192.168.8.105 34.160.19.107 TCP 66 33178 → 443 [ACK] Seq=1 Ack
19 4.092000 192.168.8.105 34.111.113.62 TCP 66 56930 → 443 [ACK] Seq=1 Ack
20 4.092028 192.168.8.105 34.95.81.168 TCP 66 40548 → 443 [ACK] Seq=1 Ack
Ethernet II, Src: Chongqin_18:5d:03 (64:6c:80:18:5d:03), Dst: HuaweiTe_3a:a3:cc (54:b1:21:3a:a3:cc)
Internet Protocol Version 4, Src: 192.168.8.105, Dst: 34.95.81.168
Transmission Control Protocol, Src Port: 40548, Dst Port: 443, Seq: 1, Ack: 1, Len: 0
Source Port: 40548
Destination Port: 443
[Stream index: 12]
[Conversation completeness: Incomplete (4)]
[TCP Segment Len: 0]
Sequence Number: 1 (relative sequence number)
Sequence Number (raw): 1607385021
[Next Sequence Number: 1 (relative sequence number)]
Acknowledgment Number: 1 (relative ack number)
Acknowledgment number (raw): 1363999823
1000 .... = Header Length: 32 bytes (8)
Flags: 0x010 (ACK)
Window: 501
[Calculated window size: 501]
[Window size scaling factor: -1 (unknown)]
Checksum: 0x3d3f [unverified]
[Checksum Status: Unverified]
Urgent Pointer: 0
Options: (12 bytes), No-Operation (NOP), No-Operation (NOP), Timestamps
[Timestamps]
0000 54 b1 21 3a a3 cc 64 6c 80 18 5d 03 08 00 45 00


File Edit Shell Debug Options Window Help
Source IP: 192.168.8.105
Destination IP: 34.111.113.62
Proto: 6
Source Port: 56930
Destination Port: 443
Packet 20:
###[Ethernet]###
dst = 54:b1:21:3a:a3:cc
src = 64:6c:80:18:5d:03
type = IPv4
###[IP]###
version = 4
ihl = 5
tos = 0x0
len = 52
id = 1078
flags = DF
frag = 0
ttl = 64
proto = tcp
chksum = 0xf975
src = 192.168.8.105
dst = 34.95.81.168
\options \
###[TCP]###
sport = 40548
dport = https
seq = 1607385021
ack = 1363999823
dataofs = 8
reserved = 0
flags = A
window = 501
chksum = 0x3d3f
urgptr = 0
options = [('NOP', None), ('NOP', None), ('Timestamp', (4059643989, 960217662))]
Source IP: 192.168.8.105
Destination IP: 34.95.81.168
Proto: 6
Source Port: 40548
Destination Port: 443
>>>
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help
Apply a display filter ... <Ctrl-/>
No. Time Source Destination Protocol Length Info
1 0.000000 192.168.8.105 35.186.232.68 TCP 66 47918 → 443 [ACK] Seq=1 Ack
2 0.068140 35.186.232.68 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
3 0.171988 192.168.8.105 3.230.74.156 TCP 66 47758 → 443 [ACK] Seq=1 Ack
4 0.479347 3.230.74.156 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
5 1.988033 192.168.8.105 35.208.249.213 TCP 66 40298 → 443 [ACK] Seq=1 Ack
6 2.040013 192.168.8.105 35.244.159.8 TCP 66 50286 → 443 [ACK] Seq=1 Ack
7 2.040049 192.168.8.105 35.244.154.8 TCP 66 44444 → 443 [ACK] Seq=1 Ack
8 2.040083 192.168.8.105 34.120.11.34 TCP 66 43194 → 443 [ACK] Seq=1 Ack
9 2.063993 192.168.8.105 69.173.158.64 TCP 66 37144 → 443 [ACK] Seq=1 Ack
10 2.103529 35.244.159.8 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
11 2.103840 34.120.11.34 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
12 2.104445 35.244.154.8 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
13 2.143637 69.173.158.64 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
14 2.322836 35.208.249.213 192.168.8.105 TCP 66 [TCP ACKed unseen segment]
15 4.036021 192.168.8.105 23.52.114.50 TCP 66 36338 → 443 [ACK] Seq=1 Ack
16 4.038572 192.168.8.105 69.173.158.64 TCP 66 37142 → 443 [ACK] Seq=1 Ack
17 4.068010 192.168.8.105 35.186.253.211 TCP 66 42442 → 443 [ACK] Seq=1 Ack
18 4.091964 192.168.8.105 34.160.19.107 TCP 66 33178 → 443 [ACK] Seq=1 Ack
19 4.092000 192.168.8.105 34.111.113.62 TCP 66 56930 → 443 [ACK] Seq=1 Ack
20 4.092028 192.168.8.105 34.95.81.168 TCP 66 40548 → 443 [ACK] Seq=1 Ack
Frame 20: 66 bytes on wire (528 bits), 66 bytes captured (528 bits)
Ethernet II, Src: Chongqin_18:5d:03 (64:6c:80:18:5d:03), Dst: HuaweiTe_3a:a3:cc (54:b1:21:3a:a3:cc)
Internet Protocol Version 4, Src: 192.168.8.105, Dst: 34.95.81.168
0100 .... = Version: 4
.... 0101 = Header Length: 20 bytes (5)
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 52
Identification: 0x0436 (1078)
Flags: 0x40, Don't fragment
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 64
Protocol: TCP (6)
Header Checksum: 0xf975 [validation disabled]
[Header checksum status: Unverified]
Source Address: 192.168.8.105
Destination Address: 34.95.81.168
Transmission Control Protocol, Src Port: 40548, Dst Port: 443, Seq: 1, Ack: 1, Len: 0


Network_Programming
Fwd: In21-S4-EN2150
Maduka Jayasinghe
PACKET DISSECTION USING PYTHON
SCAPY LIBRARY – EXTRACTING HEADER INFORMATION
from scapy.all import *
packet_dump_file = "tcp_dump.pcap"
packets = rdpcap(packet_dump_file)
def dissect_packet(packet):
print(packet.summary())
if Ether in packet:
print("Source MAC:", packet[Ether].src)
print("Destination MAC:", packet[Ether].dst)
if IP in packet:
print("Source IP:", packet[IP].src)
print("Destination IP:", packet[IP].dst)
if TCP in packet:
print("Source Port:", packet[TCP].sport)
print("Destination Port:", packet[TCP].dport)
print("\n")
for i, packet in enumerate(packets[:20]):
print(f"Packet {i + 1}:")
packet.show()
dissect_packet(packet)
Packet 1:
Ether / IP / TCP 192.168.8.105:47918 > 35.186.232.68:https A
Source MAC: 64:6c:80:18:5d:03
Destination MAC: 54:b1:21:3a:a3:cc
Source IP: 192.168.8.105
Destination IP: 35.186.232.68
Source Port: 47918
Destination Port: 443
Packet 2:
Ether / IP / TCP 35.186.232.68:https > 192.168.8.105:47918 A
Source MAC: 54:b1:21:3a:a3:cc
Destination MAC: 64:6c:80:18:5d:03
Source IP: 35.186.232.68
Destination IP: 192.168.8.105
Source Port: 443
Destination Port: 47918
Packet 3:
Ether / IP / TCP 192.168.8.105:47758 > 3.230.74.156:https A
Source MAC: 64:6c:80:18:5d:03
Destination MAC: 54:b1:21:3a:a3:cc
Source IP: 192.168.8.105
Destination IP: 3.230.74.156
Source Port: 47758
Destination Port: 443


PACKET
DISSECTION-
LIVE TRAFFIC

3-live_traffic.py - /home/madukajay/Desktop/network_programming/3-live_t...

File Edit Format Run Options Window Help

```
import socket
from scapy.all import *

def process_packet(packet):
    print(packet.summary())
    #packet.show()
    print("\n")

def capture_live_traffic():
    sniff(prn=process_packet, store=0)

if __name__ == "__main__":
    capture_live_traffic()
```

Ln: 10 Col:


3-live_traffic.py - /home/madukajay/Desktop/network_programming/3-live_t...
File Edit Format Run Options Window Help
from scapy.all import *
def process_packet(packet):
print(packet.summary())
#packet.show()
print("\n")
def capture_live_traffic():
sniff(prn=process_packet, store=0)
if __name__ == "__main__":
capture_live_traffic()
Ln: 13 Col: 0
madukajay@dnm-pc: ~/Desktop/network_programming
Ether / IP / UDP 192.168.8.105:59285 > 170.114.166.175:8801 / Raw
Ether / IPv6 / UDP 2404:6800:4009:823::200a:https > 2402:4000:b282:3017:f8cc:34df:a3a9:3eec:38713 / Raw
Ether / IPv6 / UDP 2404:6800:4009:823::200a:https > 2402:4000:b282:3017:f8cc:34df:a3a9:3eec:38713 / Raw
Ether / IPv6 / UDP 2402:4000:b282:3017:f8cc:34df:a3a9:3eec:38713 > 2404:6800:4009:823::200a:https / Raw
Ether / IP / UDP 192.168.8.105:59285 > 170.114.166.175:8801 / Raw
Ether / IP / UDP 170.114.166.175:8801 > 192.168.8.105:44298 / Raw
Src, dst ip
Src, dst port


3-live_traffic.py - /home/madukajay/Desktop/network_programming/3-live_t...
File Edit Format Run Options Window Help
from scapy.all import *
def process_packet(packet):
#print(packet.summary())
packet.show()
print("\n")
def capture_live_traffic():
sniff(prn=process_packet, store=0)
if __name__ == "__main__":
capture_live_traffic()
madukajay@dnm-pc: ~/Desktop/network_programming
###[Ethernet]###
dst = 54:b1:21:3a:a3:cc
src = 64:6c:80:18:5d:03
type = IPv4
###[IP]###
version = 4
ihl = 5
tos = 0x0
len = 1094
id = 3970
flags =
frag = 0
ttl = 64
proto = udp
chksum = 0x4cf2
src = 192.168.8.105
dst = 170.114.166.175
\options \
###[UDP]###
sport = 44298
dport = 8801


*4-live_traffic_filter.py - /home/madukajay/Desktop/network_programming/4...
File Edit Format Run Options Window Help
from scapy.all import *
def capture_live_traffic():
sniff(filter="tcp", prn=process_packet, store=0)
if __name__ == "__main__":
capture_live_traffic()


*4-live_traffic_filter.py - /home/madukajay/Desktop/network_programming/4...
File Edit Format Run Options Window Help
from scapy.all import *
def capture_live_traffic():
sniff(filter="host ip]", prn=process_packet, store=0)
if __name__ == "__main__":
capture_live_traffic()



- 6-TCP and 17-UDP


5-live_traffic_dump.py - /home/madukajay/Desktop/network_programming/5-...
File Edit Format Run Options Window Help
import socket
from scapy.all import *
def process_packet(packet):
print(packet.summary())
#packet.show()
print("\n")
if __name__ == "__main__":
packets = sniff(filter="tcp", prn=process_packet, store=20)
wrpcap('captured_packets.pcap', packets)





We will look at the socket programming part in the network programming.....



SERVER AND CLIENT



Run the client.py in cmd after running the server.py in the shell.

We can observe this in loopback traffic capture in wireshark.
Also filter by : ip.addr == 192.168.8.160 || tcp.port == 12345

We have to log into the server using our cmd and run the server code in that.

Let us see for remote server.....





Let us see for remote server using udp.....