

Adatbázisrendszerek II

12. gyakorlat

László Andrea
DJ7PNE

```
create table vasarlas(sorszam number(38,0), idopont timestamp(6), tkod char(3), darab
number(38,0), vid char(3));
```

```
begin
```

```
    insert into vasarlas values(5, sysdate , 't06', 2, 'v03');
```

```
    insert into vasarlas values(2, sysdate , 't15', 4, 'v06');
```

```
    insert into vasarlas values(3, sysdate , 't03', 1, 'v01');
```

```
    insert into vasarlas values(4, sysdate , 't04', 2, 'v02');
```

```
end;
```

```
create or replace procedure VDbKiir is
```

```
cursor cur is select * from vasarlas;
```

```
cv cur%rowtype;
```

```
begin
```

```
    open cur;
```

```
    loop
```

```
        fetch cur into cv;
```

```
        exit when cur%notfound;
```

```
    end loop;
```

```
    dbms_output.put_line(cur%rowcount);
```

```
    close cur;
```

```
end;
```

```
5
```

```
PL/SQL procedure successfully completed.
```

```
BEGIN
```

```
DBMS_SCHEDULER.CREATE_JOB (
```

```
    job_name => 'vasarlas_job',
```

```
    job_type => 'STORED_PROCEDURE',
```

```
job_action => 'VDbKiir', --a tárolt eljárás neve
start_date => SYSTIMESTAMP,
repeat_interval => 'FREQ=MINUTELY; INTERVAL=1',
end_date => SYSTIMESTAMP + INTERVAL '30' day,
comments => 'Vasarlas');
END;
```

```
SELECT * FROM ALL_SCHEDULER_RUNNING_JOBS;
```

```
begin
    dbms_scheduler.drop_job(job_name => 'vasarlas_job');
end;
```