

Standing Instruction API

The SI API is available for testing now. It is an S2S call. Please use the below key/salt and API format:

key - ghTqsH
salt- QY8vR4PA

Test env URL : <https://test.payu.in/merchant/postservice.php?form=2>

Live env URL : <https://info.payu.in/merchant/postservice.php?form=2>

Please try the flow on Test URL at the moment.

Variables Formation:

a) **hashString** = <key> + "|" + <command> + "|" + <var1> + "|" + <salt>

Here,

<key> - ghTqsH
<salt> - QY8vR4PA
<command> - si_transaction
<var1> - As calculated below

**Please note that URL and key/salt will have to be changed while going live.*

b) **var1** = {amount:<amount>,txnid:<txnid>,cardno:<card number>,expmon:<2 digit expiry month>,expyr:<4 digit expiry year>}

Example:

var1 =
{amount:11,txnid:1asdhahsdh,cardno:5123456789012346,expmon:05,expyr:2020}

**You can use the same card details on test setup as above.*

Transaction Post Data:

```
postData['key'] = <key>
postData['hash'] = hashlib.sha512(hashString).hexdigest()
postData['command'] = si_transaction
postData['var1'] = var1
```

API Response Format

```
{
  "status": 1,
  "message": "Transaction Processed successfully",
  "details": {
    "1addddsdhhahsdh": {
      "transactionid": "1addddsdhhahsdh",
      "amount": "1112",
      "user_credentials": "IKSof8:1addddsdhhahsdh",
      "card_token": "28f89cbc84d14163bf38d4",
      "payuid": "70001000595570",
      "status": "captured",
      "udf1": null,
      "field9": "Transaction Completed Successfully"
    }
  }
}
```

Please mark the transaction only when the '**status**' parameter in the inner response array is '**captured**' or '**auth**'

Otherwise, mark it as a failure.