



LATTICE · DISCREET BRAND MARK IN ONE LINE OF FRONT MATTER

# Custom Logo

A grayscale watermark in the top-right corner — brightness adapts to dark and light canvases without per-author variants.



#### HOW IT WORKS

## **A filter, not a fork.**

CSS desaturates the injected image to a faint grayscale watermark and inverts the brightness on dark-canvas layouts so the mark stays legible on every theme.



# How it lands in the DOM.

---

A build-stage rewriter injects an `img` element with class `deck-logo` as the first child of every selected section — same shape Marp uses for `header` and `footer`. CSS positions it absolutely top-right and applies the filter chain. A real DOM element rather than a `::before` pseudo is what lets the logo compose with `::before`-based chrome like the SVG-mark backgrounds.

```
logo: ./acme-logo.svg
logo-style: auto | brand      # optional, default `auto`
logo-on: all | title          # optional, default `all`
```

---

Build-time only. The directive does not render in the marp-vscode preview pane because the extension does not run the engine's plugins.



# When to use which style.

---

## AUTO • DEFAULT

A faint grayscale watermark, brightness inverted on dark-canvas layouts so the mark stays legible on every theme. Best for marks you want present but not loud — a watermark, not a statement.



## BRAND

Original colors preserved on a soft surface plate. Best for logos whose colors carry meaning — government insignia, university crests, marks that *are* the brand.



# Layered gradient background, logo on top.

---

`tint-corner at-tl` adds a top-left radial glow; `tint-edge at-right` adds a right-edge linear wash; both compose into the section's `background-image` slot. The watermark sits on top, darkened automatically because the canvas is light — same SVG, same rule, the filter just inverts brightness based on the layout class.



# SVG-mark background and logo coexist.

---

`mark-orbit` draws its concentric-ring accent through `section::before`. Earlier iterations of this feature put the logo on `::before` too — and the two collided. The current implementation injects the logo as a real `img` element, so it sits on a different render layer. Every treatment — `tint-*` or `mark-*` — composes with the logo.





LATTICE · CUSTOM LOGO

One line of front matter.  
One CSS rule. Every theme.