Release audit · November 2026

Every slide you write, as you wrote it

Three engine fixes: a split title that leaked bold, a close tag that merged two slides, and a nested key that took over the footer.

FIX 1 · SPLIT TITLES

A bold number in a point title stays inside its point.

At this size the panel splits into a cover and one page per point. Each point below starts with its own bold number.

The supporting detail →

A bold number in a point title stays inside its point.

15 stable types

Flowchart, sequence, class and state draw with full theme control.

11 experimental types →

A bold number in a point title stays inside its point.

---

11 experimental types

Sankey, block and packet may still change their syntax.

6 with named variables →

A bold number in a point title stays inside its point.

> **6 with named variables**
>
> The rest inherit their colors from these six.

Fix 1 · the slide after

This slide is set in the regular weight.

Before the fix, the split page emitted `<strong>6</span>`, an open bold tag the browser carried into every later slide. This paragraph rendered bold, and the export counted fewer slides than the deck held.

Fix 2 · a close tag with a space

A legal close tag ends the block.

The block below closes as `</pre >`, with a space before the bracket. Browsers accept that, and the slide separator after it now starts a new slide.

```
revenue   $26M
margin    44%
```

Fix 2 · the next slide

This slide used to vanish into the one before.

Before the fix, the parser read the separator above as text inside the block, so this heading and paragraph printed on the previous page.

FIX 3 · FRONT MATTER

The footer below is the deck's own.

Fix 3 · front matter

The footer below is the deck's own.

This deck's front matter names a reader view called `footer` under `lenses:`.

continues →

Fix 3 · front matter

The footer below is the deck's own. (cont.)

The engine used to read that nested key as the deck's `footer:` directive.

continues →

Fix 3 · front matter

The footer below is the deck's own. (cont.)

Every page then printed the view's settings where the footer belongs.

continues →

Fix 3 · front matter

The footer below is the deck's own. (cont.)

Only **top-level** keys are directives now, so the footer reads as written.

Spaces beside inline marks are kept.

In a list card →

Spaces beside inline marks are kept.

In a list card

A `lenses:` block names each view, and the **class** is the contract.

In a grid card →

Spaces beside inline marks are kept. (cont.)

In a grid card

Inline code such as `paginate` keeps its space on both sides.

In bold →

Spaces beside inline marks are kept. (cont.)

In bold

So the **class** is the contract, not the register.

In italics →

Spaces beside inline marks are kept. (cont.)

In italics

Unknown values fall to the *running* default, never to silence.

Check a deck after these fixes.

Check a deck after these fixes.

STEP 01

Render it at a tall size such as `story` and count the pages.

continues →

Check a deck after these fixes. (cont.)

STEP 02

Look at the slide after any bold split title.

continues →

Check a deck after these fixes. (cont.)

STEP 03

Search the HTML for `data-footer` and read what it holds.

The deck renders as written.

Release audit · fixes 1 to 3