Base layer · the default table

Universal table

A plain GFM pipe table used to render at raw browser defaults on every slide that was not one of the table-owning components. It now inherits a house treatment from the base layer — palette-blind, and standing off the six components that still style their own table.

No class at all

UNIVERSAL TABLE · BASE LAYER

The gap this closes

Every table rule in the engine was scoped to a component. A markdown table on an un-classed slide, on `_class: content`, or under a base modifier got no borders, no cell padding, no header weight — the columns simply scattered across the slide.

REGION	Q3 REVENUE	Q4 REVENUE	CHANGE
North America	$4.2M	$5.1M	+21%
EMEA	$3.8M	$3.9M	+3%
APAC	$1.9M	$2.6M	+37%

✦ *The slide above declares no `_class` — this is the base treatment alone.*

Inside a component

It reaches `content` too

The treatment is scoped to the stage's own child, so it lands wherever an author writes a table: an un-classed slide, a base-modifier slide, or a component that has no table opinion of its own.

CONTROL	OWNER	STATUS
Access review	Security	Complete
Vendor attestation	Legal	In flight
Key rotation	Platform	Not started

Alignment

UNIVERSAL TABLE · BASE LAYER

Column alignment still comes from the source

Markdown's `:---`, `:---:` and `---:` alignment survives untouched — the treatment sets type, rules and padding, never the author's alignment.

METRIC	TARGET	ACTUAL	VARIANCE
Gross margin	62%	64.1%	+2.1pt
Net retention	110%	118%	+8pt
Payback	18mo	21mo	-3mo

✦ *Left, centered, right, right — as written in the pipe table.*

Two switches

UNIVERSAL TABLE · BASE LAYER

Striping off, vertical fill on

`table-plain` clears the row wash; `table-fill` lets the table take the leftover stage height so its rows spread instead of stacking at the top. Both are custom properties underneath — `--table-zebra` and `--table-grow` — so a theme or a deck's `style:` block can set them without touching a slide.

WORKSTREAM	OWNER	Q3	Q4
Migration	Platform	Complete	—
Attestation	Legal	In flight	Complete
Key rotation	Security	Not started	In flight

The first column

UNIVERSAL TABLE · BASE LAYER

The row label is measured, not assumed

The first column reads as a label — 600 weight, heading ink — when it actually is one. The engine decides per table from the header cell and the column itself.

CRITERION	OPTION A	OPTION B
Speed	Fast	Slow
Cost	Low	High

✦ *Measured ON: a named header over a textual column.*

The first column

UNIVERSAL TABLE · BASE LAYER

A year column is not a set of labels

The same slide class, a numeric first column, and the emphasis declines itself — no author opt-out needed. It also declines on an index header (`#`, `No.`, `Ref`), a column of bare state markers, and a single-column table.

YEAR	REVENUE	GROWTH
2024	$4.2M	+21%
2025	$5.1M	+3%

✦ *Measured OFF: every cell in column one is a number.*

with-row-label

UNIVERSAL TABLE · BASE LAYER

`with-row-label` forces it on — even here

A plain table, no component class, and the measurement would have declined this column. `with-row-label` overrules it. `no-row-label` overrules the other way, and
wins if a slide somehow carries both.

YEAR	REVENUE	GROWTH
2024	$4.2M	+21%
2025	$5.1M	+3%

✦ *The author always has the last word.*

Riding it

UNIVERSAL TABLE · BASE LAYER

The `table` component IS this treatment

`table` styles no `<table>` element of its own — it rides the rules above and adds what only a manifest can declare: a row capacity, autosplit, the portrait card reshape, and the focus axes. That is why the switches reach it.

DIMENSION	OWNED ENGINE	MARP
Layout source	lattice.css	marp-core
Overflow	Fit Spine	none
Themes	32	3

✦ *Same rules as the un-classed slide above — plus a contract.*

Standing off

UNIVERSAL TABLE · BASE LAYER

A specialist IS untouched — `glossary`

TERM	MEANING
Stage	The bounded content box a slide's body flows into
Deny guard	The `:where(:not(…))` list that holds base off a specialist
Subject	The last compound of a selector — what the rule actually styles

Gated, not remembered

The deny list cannot rot

An ownership gate fails the build three ways: on a component that styles a table with no deny entry, on a stale entry, and on an entry broader than the claim it names — which would silently withhold the default from every slide missing the variant.