

FEATURE DEMO · DEBUG OVERLAY

See the boxes your layout is made of.

Set `debug: on-hover` in the front matter and every preview — Playground, Drawing Board, Studio — outlines each box by its **layout mode; hover** one to read its label. It travels with the deck, and it is **stripped from every export**, so a boardroom PDF is byte-identical whether debug is on or off.

Read the grid at a glance.

Each box is outlined by how it lays out its children: **grid** (blue), **flex** (vermillion), **flow** (gray). **Hover** a box to read its label.

Tool A · Chorus

✓ Speed

– Auditability

✓ Adoption

✗ Calibration

Strong call recording and summarization. No decision logging or calibration loop.

Tool B · Productboard

✗ Speed

✓ Auditability

✓ Adoption

✗ Calibration

Solid intake and prioritization. Decision logging is manual and rarely used.

Tool C · Notion

✓ Speed

✓ Auditability

– Adoption

✗ Calibration

Flexible enough to build the whole system — but the result is fragile to maintain.

Tool D · Sprig + Decision Log

✓ Speed

✓ Auditability

✓ Adoption

✓ Calibration

Meets all four criteria within the weekly budget. Recommended.

★

Pull every lever on one slide.

`<!-- _debug: on-hover verbose -->` turns on the full set — `identity · layout · size · class · box` — for **this slide only**. The deck-wide `debug: on-hover` stays the

default everywhere else; a spot directive just overrides the box it sits on.

- Sizes are the **intrinsic** pixel box, read straight off the layout — not the scaled-down thumbnail you see in the filmstrip.
- `class` shows the raw CSS classes; `box` shows padding + gap. Both are opt-in, because on a dense slide they are more than you usually want to read.

Mute a slide you have already checked.

`<!-- _debug: off -->` silences the overlay on one slide even while the deck is debugging — handy once a layout is settled and the boxes are just noise. `off` is also the default everywhere: with no `debug:` key at all, the preview is clean.

Because labels are summoned by default, a busy grid never becomes a wall of chips:

you pull detail in only where you look — **hover** on desktop, **press and hold** on touch — one box (and its containers) at a time.

Debug in the preview. Ship it clean.

`debug: on-hover` is an authoring aid, not
a deck style — the engine strips it from
the PDF, PPTX, and HTML exports, so it can never end up
in front of a board.