

BASE LAYER • THE DEFAULT TABLE

Universal table

A plain GFM pipe table used to render at raw browser defaults on every slide that was not one of the table-owning components. It now inherits a house treatment from the base layer — palette-blind, and standing off the six components that still style their own table.

The gap this closes

Every table rule in the engine was scoped to a component. A markdown table on an un-classed slide, on `_class: content`, or under a base modifier got no borders, no cell padding, no header weight — the columns simply scattered across the slide.

REGION	Q3 REVENUE	Q4 REVENUE	CHANGE
North America	\$4.2M	\$5.1M	+21%
EMEA	\$3.8M	\$3.9M	+3%
APAC	\$1.9M	\$2.6M	+37%

✦ The slide above declares no `_class` — this is the base treatment alone.

It reaches content too

The treatment is scoped to the stage's own child, so it lands wherever an author writes a table: an un-classed slide, a base-modifier slide, or a component that has no table opinion of its own.

CONTROL	OWNER	STATUS
Access review	Security	Complete
Vendor attestation	Legal	In flight
Key rotation	Platform	Not started

Column alignment still comes from the source

Markdown's `:---`, `:---:` and `---:` alignment survives untouched — the treatment sets type, rules and padding, never the author's alignment.

METRIC	TARGET	ACTUAL	VARIANCE
Gross margin	62%	64.1%	+2.1pt
Net retention	110%	118%	+8pt
Payback	18mo	21mo	-3mo

✦ *Left, centered, right, right — as written in the pipe table.*

Striping off, vertical fill on

`table-plain` clears the row wash; `table-fill` lets the table take the leftover stage height so its rows spread instead of stacking at the top. Both are custom properties underneath — `--table-zebra` and `--table-grow` — so a theme or a deck's `style:` block can set them without touching a slide.

WORKSTREAM	OWNER	Q3	Q4
Migration	Platform	Complete	—
Attestation	Legal	In flight	Complete
Key rotation	Security	Not started	In flight

The row label is measured, not assumed

The first column reads as a label — 600 weight, heading ink — when it actually is one. The engine decides per table from the header cell and the column itself.

CRITERION	OPTION A	OPTION B
Speed	Fast	Slow
Cost	Low	High

+ Measured ON: a named header over a textual column.

A year column is not a set of labels

The same slide class, a numeric first column, and the emphasis declines itself — no author opt-out needed. It also declines on an index header (`#`, `No.`, `Ref`), a column of bare state markers, and a single-column table.

YEAR	REVENUE	GROWTH
2024	\$4.2M	+21%
2025	\$5.1M	+3%

✦ Measured OFF: every cell in column one is a number.

row-label forces it on — even here

A plain table, no component class, and the measurement would have declined this column. **row-label** overrules it. **no-row-label** overrules the other way, and wins if a slide somehow carries both.

YEAR	REVENUE	GROWTH
2024	\$4.2M	+21%
2025	\$5.1M	+3%

✦ The author always has the last word.

The `table` component IS this treatment

`table` styles no `<table>` element of its own — it rides the rules above and adds what only a manifest can declare: a row capacity, autosplit, the portrait card reshape, and the focus axes. That is why the switches reach it.

DIMENSION	OWNED ENGINE	MARP
Layout source	lattice.css	marp-core
Overflow	Fit Spine	none
Themes	32	3

✦ Same rules as the un-classed slide above — plus a contract.

A specialist IS untouched —

glossary

TERM	MEANING
Stage	The bounded content box a slide's body flows into
Deny guard	The <code>:where(:not(...))</code> list that holds base off a specialist
Subject	The last compound of a selector — what the rule actually styles

GATED, NOT REMEMBERED

The deny list cannot rot

An ownership gate fails the build three ways: on a component that styles a table with no deny entry, on a stale entry, and on an entry broader than the claim it names — which would silently withhold the default from every slide missing the variant.