AUTO-SPLIT · STRUCTURE DECIDES THE CUT

One thing per slide

A slide holding six things becomes six slides. The markup says how many, so every machine cuts the same deck the same way.

What changed

What changed

The trigger is **structure**, not a measured overflow — no render decides the page count

continues →

What changed (cont.)

A page carries **one** structural element; nothing packs to an authoring budget

continues →

What changed (cont.)

Every run opens on a **cover** and closes on the section's **note and key insight**

continues →

What changed (cont.)

Each page **names the next one**, so an atomized run still reads as one thing

the key insight →

What changed

KEY INSIGHT

A deck is authored once. What it becomes should not depend on which machine renders it.

What a split page owes the reader

The one thing it holds, set at full size



What a split page owes the reader

The one thing it holds, set

01 at full size — not shrunk to share

continues →

What a split page owes the reader (cont.)

02

A heading that says which run it belongs to

A pointer to what comes next →

What a split page owes the reader (cont.)

03

A pointer to what comes next

A way back to the whole →

What a split page owes the reader (cont.)

A way back to the whole

04 — the k-of-N rail in the footer band

An ending that says what the run meant →

What a split page owes the reader (cont.)

05 An ending that says what the run meant

the note →

What a split page owes the reader

✦ *This numbered list — authored as the since-retired* `list-criteria` *then — could not split at all before this change.*

How the cut was decided, over time

Opt-in per deck

Authors who missed the flag got clipped slides

Default-on for portrait

Right direction; the directive itself had to go

Measured fit

The page count became the renderer's job

Structure

Read from the markup, so lint and export agree

Reading a split run

Arrive →

Reading a split run

Arrive
• Meet the cover 
• Learn what the run is about 

• reader

PAIN 1 2 3 4 5 DELIGHT

Move →

Reading a split run (cont.)

Move

- Take one element per page



- Follow the pointer to the next



- reader

PAIN 1 2 3 4 5 DELIGHT

Close →

Reading a split run (cont.)

Close

Read the note and the insight together



• reader

PAIN 1 2 3 4 5 DELIGHT

the note →

A chart splits when the splitter can reach its seam. On a tall deck journey stacks its stages, so each is a unit and this slide becomes three. On a wide deck the same list draws one grid over one shared axis, and the splitter declines.

Enrollment across the catalog

Enrolled →

Enrollment across the catalog

Enrolled — 31 of 61 components split, three of which could not before

Whole →

Enrollment across the catalog (cont.)

Whole — the other 30 ring on overflow, each for a reason recorded in the kernel

Packed →

Enrollment across the catalog (cont.)

Packed — none, at any count, on any component

Pointed →

Enrollment across the catalog (cont.)

Pointed — every run carries a forward pointer; four components did before

the note →

Enrollment across the catalog

✦ *A bold lead becomes the next page's pointer — unless it is a FIGURE, which yields to the name beneath it.*

More slides, one thing each

Structure decides, not the renderer