API documentation

get a preparator

by giving its id

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/getPreparator?
id=..
```

example :

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/getPreparator?
id=1
```

get a group of command according to a preparator's criterion

take as get inputs the preparators name and the max weight he can supports

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/getCommandPrep
Group?maxWeight=..&firstname=..&lastname=..
```

example :

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/getCommandPrep
Group?maxWeight=15&firstname=jon&lastname=doe
```

when a preparator scan a product command

you need to specify the product id and its related command id

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/scanProduct?pr
```

```
oductId=..&commandId=..
```

example :

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/scanProduct?pr
oductId=1&commandId=1
```

end of stock alert from a preparator

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/endOfStockAlte
rt?productId=..
```

example :

```
https://us-central1-huitneufdis-1e9f6.cloudfunctions.net/endOfStockAlte
rt?productId=2
```