

EasySave User Guide (Full)

Field	Value
Product	EasySave
Audience	End users (executable package)
Scope	EasySave.exe + Resources folder
Doc version	2.1
Last update	February 25, 2026

1. What your EasySave folder should contain

Your user package should include at least:

- EasySave.exe
- Resources\Languages\
- Resources\CryptoSoft.exe

This guide is written for that executable package (not for source repository usage).

2. Starting EasySave

2.1 Standard launch (GUI)

Double-click:

- EasySave.exe

The main window provides:

- jobs list
- action buttons (New job , Edit job , Run selection , Run all , Delete selection)
- job details panel
- Settings menu

2.2 Command launch (optional)

From a terminal opened in the application folder:

```
EasySave.exe "1-3"
```

EasySave.exe "1;3;5"

Accepted selection formats:

- 1-3 : range
- 1;3;5 : explicit IDs

3. User Workflow

1. Create a job (New job)
2. Fill name, source, destination, type
3. Save
4. Select one or more jobs
5. Run (Run selection or Run all)
6. Monitor and control (Start , Pause , Cancel)

For a visual illustrated walkthrough:

- EN HTML: docs/user-guide/en/EasySave_GUI_User_Guide.html
- EN PDF: docs/user-guide/en/EasySave_GUI_User_Guide.pdf

4. Job Management

4.1 Create

Required fields:

- Name (required, unique)
- Source folder (required)
- Destination folder (required)
- Type (Full or Differential)

4.2 Edit

- select exactly one job
- click Edit job
- modify values and save

4.3 Delete

- single or multi-selection
- confirm deletion

5. Backup Behavior

Type	Rule
Full	Copies all files from source
Differential	Copies only files missing or newer than destination

Execution:

- selected jobs run in parallel
- per-job runtime control is available
- live monitoring relies on `state.json`

Possible statuses:

- `Inactive`, `Active`, `Paused`, `Completed`, `Error`, `Cancelled`

6. Settings Reference

Settings are persisted in:

- `%APPDATA%\EasySave\userdata\userconfig.json`

Setting	Values	Effect
Language	<code>en</code> , <code>fr</code>	UI language
Log format	<code>Json</code> , <code>Xml</code>	Log format
Log storage mode	<code>Local</code> , <code>Docker</code> , <code>Both</code>	Log destination
Business software to block	process name (without <code>.exe</code>)	Auto-pause when process is detected
File extensions to encrypt	free list separated by commas	CryptoSoft encryption on matching files
Priority file extensions	free list separated by commas	Priority gate across parallel jobs
File size not to back up in parallel (KB)	integer ≥ 0	Files above threshold are serialized

Important note about extensions:

- this is not strict CSV formatting
- this is plain text list separated by commas, for example: `.txt, txt, .log`
- case-insensitive matching

7. CryptoSoft (User Package)

Path to verify:

- `Resources\CryptoSoft.exe`

Behavior:

1. if file extension matches, EasySave attempts encryption
2. otherwise, normal copy
3. if CryptoSoft is missing, EasySave falls back to normal copy

8. Important Runtime Files

Item	Default Windows path	Usage
User config	<code>%APPDATA%\EasySave\userdata\userconfig.json</code>	Persisted settings
Jobs	<code>%APPDATA%\EasySave\Jobs\jobs.json</code>	Job definitions
Live state	<code>%APPDATA%\EasyLog\Progress\state.json</code>	Execution monitoring
Local logs	<code>%APPDATA%\EasyLog\Logs\log-YYYY-MM-DD.json xml</code>	Execution history

9. Quick Troubleshooting

9.1 Encryption not applied

Check:

1. `Resources\CryptoSoft.exe` exists
2. encryption extensions are configured
3. logs (`WorkType` , `EncryptionTimeMs`)

9.2 Jobs remain paused

Check:

1. monitored business process still running
2. manual pause not cleared
3. restart with `Start`

9.3 No Docker logs

Check:

1. storage mode is `Docker` or `Both`
2. log server is reachable on `127.0.0.1:11000`

10. Best Practices

- Keep job names short and explicit.
- Test on a small dataset before large runs.
- Start with `Local` logs, then use `Both` if Docker logging is needed.
- Enable priority extensions only when needed.

11. Related Documentation

- Full FR guide: `docs/user-guide/fr/Guide_Utilisateur_EasySave_Complet.md`
- One-page FR summary: `docs/user-guide/fr/USER_GUIDE_ONE_PAGE.md`
- One-page EN summary: `docs/user-guide/en/USER_GUIDE_ONE_PAGE_EN.md`
- Debug guide: `docs/debug/DEBUG_GUIDE.md`
- Unit test guide: `docs/testing/UNIT_TESTS.md`