SteamJet

A New Age of Steam in Space

S J
S S

The Steam TunaCan Thruster

Steam Powered Propulsion Technologies for Small Satellites and CubeSats

The Steam TunaCan Thruster is a safe, high-performance, electrothermal propulsion system specifically designed for CubeSats. Its unique shape factor allows its installation in the tunacan volume available in many CubeSats deployers, located outside the main CubeSat structure. Using only low-pressure water as the main propellant, the Steam TunaCan Thruster can be easily integrated into any satellite, supporting all its propulsion needs

Optimization & Manoeuvres

Collision Avoidance

Constellation Management

Life Extension

De-Orbit

Thruster Head

Heat Exchanger

Electronics

Control Systems

Water Tank

High Thrust
50x More Than Electric Propulsion

Low Power Consumption

Safe
Low Pressure Water as The Main Propellant

Easy to Integrate

No RF interference

For more Info and Pre-Orders

Contact us Today to Receive a Free Engineering Model of the Steam Thruster

team@steamjet.space

https://steamjet.space

17 Moorfield, Canterbury, CT2 7AN

Specifications	Value
Nominal Thrust (mN)	6
Specific Impulse (s)	172
Total Impulse (Ns)	219
Minimum Impulse Bit [mNs]	10
Power consumption Thrusting / Idle [W]	<19.9 / 0.12
Wet Mass [g]	540
Propellant Mass [g]	130
Propellant	Water
Voltage [VDC]	9 - 14
Communication Protocol	RS 422, TTL UART
Dimensions [mm]	Ø 80 x 80

Dimensions

TunaCan



Power vs Isp



Space qualified according to ESA ECSS-E-ST-10-03C and NASA GSFC-STD-7000A

The Steam TunaCan Thruster can be operated with a power between 5W to 20W depending on the CubeSat availability

Typical Applications

3U (5KG) SATELLITE @ 400KM INITIAL ORBIT

Product	Total Impulse (Ns)	Life-time (Years)	Orbital Change (Km)	Orbit Phasing	Collision avoidance
No Propulsion	0	1.6	No	No	No
TunaCan	*219*	*4.3*	*± 70*	*0° to 360°*	*Yes*

6U (10KG) SATELLITE @ 400KM INITIAL ORBIT

Product	Total Impulse (Ns)	Life-time (Years)	Orbital Change (Km)	Orbit Phasing	Collision avoidance
No Propulsion	0	1.6	No	No	No
TunaCan	*219*	*3*	*± 35*	*0° to 360°*	*Yes*