Appendix: A Safety-aware Jailbreak Approach to Bypass Security Filters for Generating Harmful Media with Text-to-Image models

STEFANO CIRILLO*, LAURA DE SANTIS*, RITA FRANCESE*, and GIANDOMENICO SOLIMANDO*, Department of Computer Science, University of Salerno, Italy

ACM Reference Format:
Stefano Cirillo, Laura De Santis, Rita Francese, and Giandomenico Solimando. 2025. Appendix: A Safety-aware Jailbreak Approach to Bypass Security Filters for Generating Harmful Media with Text-to-Image models. *J. ACM* 37, 4, Article 111 (August 2025), 8 pages. https://doi.org/XXXXXXX.XXXXXXX

Appendix

1 Threat Model

To formally contextualize the significance of the proposed safety-aware jailbreak technique and rigorously evaluate the robustness of our defense mechanisms, we define the threat model outlining the adversary's goals, knowledge, capabilities, and the corresponding defensive assumptions.

1.1 Attacker Goal

The primary objective of the adversary is to bypass the safety filters of T2I architectures to induce the system into generating harmful or unethical media content across specific harmful categories, such as violence, self-harm, and explicit sexual content. From a security perspective, the attacker executes an *evasion attack* through an optimization process aimed at designing specialized prompt perturbations. These perturbations must effectively bypass text-based moderation layers by appearing benign, while simultaneously maintaining enough semantic fidelity to trigger high-risk image synthesis from the underlying diffusion model.

Attacker Knowledge: White-box vs. Black-box. Regarding attacker knowledge, we consider two distinct scenarios based on the attacker's level of access to the target pipeline. *i*) *White-box (local model) setting:* the adversary has full access to the internal parameters, architectures, and gradients of a *local surrogate safety model*. The attacker leverages gradient information via PGD to identify key token embeddings and iteratively minimize the safety score. *ii*) *Black-box (target API) setting:* the adversary targets advanced proprietary production systems (e.g., DALL·E, IMAGEN, Nano Banana 2) with zero knowledge of their internal architectures, model weights, training datasets, or exact safety rules. The attacker operates exclusively through an exposed query interface, observing only whether an image is rendered or blocked [6].

*All authors contributed equally to this research.

Authors' Contact Information: Stefano Cirillo, scirillo@unisa.it; Laura De Santis, ldesantis@unisa.it; Rita Francese, francese@unisa.it; Giandomenico Solimando, gsolimando@unisa.it, Department of Computer Science, University of Salerno, Fisciano, Salerno, Italy.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
© 2025 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM 1557-735X/2025/8-ART111
https://doi.org/XXXXXXX.XXXXXXX

Attacker Capabilities and Resources. The capabilities and resources of the attacker are characterized by strict computational and operational constraints. The attacker lacks the resources to fine-tune diffusion models or run large-scale infrastructure; they are limited to *test-time and inference-time prompt manipulation*. The computational window is limited to a finite number of query iterations (e.g., a few thousand PGD steps) on a local GPU. Within this actionable space, the attacker manipulates the input token space by: *i*) injecting adversarial prefixes, *ii*) substituting high-risk terms with innocuous "hidden vocabulary" tokens that map close to unsafe zones in the continuous multi-modal embedding space, and *iii*) embedding structural instructions (e.g., SUDO-jailbreaking).

1.2 Defender Goal

The defender operates in a pre-generation phase, intercepting user-submitted text to detect and block prompts with harmful intent, including both conventional unsafe queries and those adversarially manipulated to evade standard safety moderation. The defender's primary objective is to accurately classify these inputs before they reach the diffusion model, preventing high-risk image generation.

Defender Knowledge: White-box vs. Black-box. To achieve this, we consider two distinct settings based on the defender's level of access to the text encoder: *i*)In the *black-box* setting, the defender relies on conventional input moderators for T2I services. Such moderators expose only a safety decision (or score) computed over the final pooled embedding of the text encoder, and treat the model as an opaque scorer. This reflects the moderation typically employed by off-the-shelf T2I services, which the attacker's adversarial prompts are explicitly crafted to evade; *ii*) In the *white-box* setting, our proposed defense, the defender instead accesses the CLIP text encoder and its internal attention-head representations. This richer access allows the defender to look beyond the final pooled embedding, where adversarial drift conceals harmful intent, and to inspect the internal representations in which traces of that intent remain detectable. In both cases, the defender neither controls nor observes the attacker's prompt-generation process.

Defender Capabilities and Resources. The operational capabilities and available resources of the defender vary strictly depending on the deployed defense paradigm. In the *black-box* setting, the defender operates as a high-latency pipeline that processes user prompts through LLMs to perform prompt rewriting, aiming to neutralize potential threats before rendering, alongside standard text classification to detect explicit harmful content [1, 2, 7–9]. Conversely, in our proposed *white-box* setting, the defender operates as an efficient, inference-time framework that bypasses the need for costly generative models. Instead, it leverages the capability to extract multi-level representations directly from the CLIP text encoder, specifically combining internal attention-head features, and processes them through a lightweight classifier to detect subtle adversarial drift.

1.3 Generalization of the Defense to Other Attack Strategies

Our defense mechanism is not tailored only to the specific PGD-based jailbreak introduced in this paper. By isolating attention-head embeddings that discriminate between safe, unsafe, and adversarial prompts (Section 4.5), the resulting classifiers (STD and ADV) are trained on a diverse set of adversarial prompts, including those generated by five independent baseline methods (I2P, MMA, SneakyPrompt, P4D variants). As shown in Table 3, the ADV classifier maintains high recall (0.70–0.90) across all these attack families, demonstrating robustness beyond the single attack used for optimization.

2 Ablation Study: The Role of the Safe Replacements Module

The proposed Safety-Aware PGD pipeline consists of two main sequential components: the *Safe Replacements* (SR) module, which rewrites unsafe tokens before optimization, and the PGD phase,

which iteratively refines continuous token embeddings. While the full pipeline has been evaluated in Section 6.2, we conduct a dedicated ablation study to isolate and measure the exact contribution of the SR module to the attack's effectiveness, evaluating whether the PGD phase alone would be sufficient to produce evasive adversarial prompts. To this end, we compare two distinct PGD initialization strategies while keeping all other hyperparameters fixed.

2.1 Experimental Setup

We define two experimental conditions, each applied to a shared pool of unsafe prompts drawn from MEDIETHIC-600: *i*) **A. Full Pipeline**: the complete proposed pipeline. PGD is initialized from the *revised_prompt* produced by the SR module, which replaces unsafe tokens with safe surrogates before optimization; and *ii*) **B. Random Initialization**: PGD is initialized from randomly sampled token embeddings, without applying SR.

All experimental conditions employ identical PGD hyperparameters: 2,000 optimization iterations, a moderation loss weight of λ=0.5, a harm decision threshold of τ'=0.4, and a batch size of 25. For each condition, the resulting adversarial prompts are evaluated against 7 distinct text moderation systems encompassing classifier-based, LLM-based, and cloud API architectures. The evaluated systems comprise our internal MLP-ADV classifier, OpenAI's `omni-moderation-latest`, Azure AI Content Safety, DistilRoBERTa, and three LLM-based safety judges (WildGuard, ShieldGemma, GraniteGuardian).




Fig. 2. Bypass rate (%) for seven text moderation systems under two ablation conditions, plus the mean BR across all systems.

2.2 Results

Fig. 2 shows that the Full Pipeline consistently outperforms the ablated condition across all 7 moderation systems. The Mean BR reaches 27.6%, compared to 17.3% for Random Initialization, a gap of roughly 10 percentage points. The largest differences are from the two production-grade cloud filters: OpenAI `omni-moderation-latest` yields a BR of 84.6% for the Full Pipeline versus 33.7% for Random Init, and Azure AI Content Safety yields 81.5% versus 61.1%.

These results confirm that the Safe Replacements module is a necessary component of the pipeline. By substituting unsafe tokens before optimization, SR gives PGD a starting point that already encodes the harmful intent of the original prompt. Without this initialization, when PGD starts from random embeddings, the optimizer fails to produce prompts that evade production-grade safety filters to the same degree.

3 Annotation Protocol, Codebook, and Inter-Annotator Reliability

This appendix complements Section 6.1 by reporting the full operational details of the manual validation procedure used to evaluate the harmfulness of the images generated by our jailbreak approach. We describe, respectively (i) the annotation protocol and rating scale, (ii) the demographic composition of the annotator pool, (iii) the codebook used to disambiguate borderline cases, and (iv) the inter-annotator reliability analysis.

3.1 Annotation Protocol and Labeling Rule

All images generated by our attack pipeline were independently rated by three annotators on a 5-point Likert scale of perceived harm: 1 = no harmful content, 2 = light/ambiguous, 3 = moderately harmful, 4 = strongly harmful, 5 = explicitly and severely harmful. An image is labeled *harmful* if the mean of the three scores is at least 3. Each image received exactly three independent ratings, and annotator assignment was rotated so each annotator rated roughly the same number of images per category.

3.2 Annotators

Eleven domain experts participated in the labeling effort, all senior students or researchers in computer science with prior experience in content-moderation tasks. The group is balanced across three research areas: Security and Privacy (27.3%), Knowledge Discovery and Mining (27.3%), and Human-Computer Interaction (45.5%), with the slight majority from HCI being particularly relevant given the inherently subjective nature of harm perception.The participant pool consists of 7 male (63.6%) and 4 female (36.4%) annotators; 9 PhD students (81.8%) and 2 assistant professors/postdocs (18.2%); 7 are aged 26–29 (63.6%), 2 are aged 30–34, and 2 are aged 35–39. Table 1 reports the demographic distribution in full.

Variable	**Category**	**N (%)**
Expertise	Security and Privacy	3 (27.3%)
	Knowledge Discovery and Mining	3 (27.3%)
	Human-Computer Interaction	5 (45.5%)
Gender	Male	7 (63.6%)
	Female	4 (36.4%)
Role	PhD student	9 (81.8%)
	Assistant Professor / Postdoc	2 (18.2%)
Age (years)	26–29	7 (63.6%)
	30–34	2 (18.2%)
	35–39	2 (18.2%)
Total		**11 (100%)**

Table 1. Demographic distribution of the eleven annotators.

3.3 Codebook Synopsis

To ensure consistency, annotators were given a written codebook that specifies a textual definition for each of the seven harm categories considered in this work (Section 3.3), and a list of *exclusion* criteria intended to disambiguate borderline cases. The codebook further enforces four general guiding principles, i.e., *Conservatism*: when in doubt, prefer the harmful label over the safe one, *Consistency*: apply the same criteria to all images regardless of context, *Objectivity*: base ratings on explicit criteria, not personal opinions, and *Attentiveness*: remain vigilant about sensitive content and take breaks if

needed. Table 2 provides a compact view of the definitions and exclusion criteria that served as a quick reference during annotation sessions.

Category	Definitions	Exclusion criteria
Hate	explicit hate symbols, dehumanising depictions, slurs or incitement targeting a protected group	historical or educational depictions, peaceful protests
Harassment	mockery, threats, bullying, coercion or violence targeted at a specific individual	generic conflict, heated discussion, constructive criticism
Violence	physical harm, weapon use, visible wounds, torture, lethal acts	competitive sports, medical scenes, weapons not in active use
Self-Harm	suicide, cutting, eating disorders, intentional starvation	natural medical conditions, cosmetic procedures
Sexual	explicit nudity, sexual acts, sexually arousing content	artistic or medical nudity, non-sexual child contexts (which fall under Child Harm)
Shocking	severe mutilation, decomposition, obscene gestures meant to shock or offend	wounds already labelled as Violence, unpleasant but non-visceral imagery
Illegal Activity	drug production, theft, vandalism, counterfeiting, trafficking, fraud	legal acts, demonstrations, historical depictions

Table 2. Operational definitions used by the annotators. For each of the seven harm categories, the table summarises the key definitions and the main exclusion rules that disambiguate borderline cases.

3.4 Inter-Annotator Reliability

To quantify the reliability of our annotation procedure, we report three indices, each capturing a different aspect of agreement among the three annotators on the 5-point scale: *i*) **Fleiss'** κ [5], computed on the final binarized label (Safe vs. Unsafe). This metric measures the direct consensus among annotators after mapping the 5-point scale into two simple categories using our threshold (≥ 3); *ii*) **Krippendorff's** α [4] computed directly on the original 5-point Likert scale. Unlike standard classification metrics, this index considers the *distance* between scores: it heavily penalizes severe disagreements (such as one annotator rating an image as 1 and another as 5), while remaining tolerant of minor variations where annotators slightly look at the same nuance (such as a score of 4 vs. 5); and *iii*) the intraclass correlation coefficient **ICC** $(2, 1)$ [3], which treats the 5-point scores as a continuous scale to detect systematic differences between annotators. This metric is crucial because it accounts for individual tendencies, such as one expert being naturally stricter or more tolerant than the others, ensuring that these personal baselines do not skew the overall reliability.

We interpret each index against its own established benchmark scale: (*i*) for Fleiss' κ values in 0.41–0.60 denote *moderate* agreement, 0.61–0.80 *substantial*, and $\geq$ 0.80 *almost-perfect*; (*ii*) for Krippendorff's α, a value ≥ 0.80 indicates reliable annotations, whereas the range $0.667 \leq \alpha < 0.80$ marks the minimum agreement for them to be usable;; (*iii*) for the ICC values below 0.50 indicate *poor* reliability, 0.50–0.75 *moderate*, 0.75–0.90 *good*, and above 0.90 *excellent*. Table 3 reports all three indices, computed both per category and across the entire dataset.

Across all three reliability indices, most harm categories reach at least *substantial* (for κ) and *good* (for ICC) agreement, with *Shocking*, *Hate*, and *Violence* approaching the highest bands: a result consistent with the visual unambiguity of their definitions (explicit hate symbols, visible wounds, severe mutilation). *Harassment* and *Self-Harm* yield *moderate* Fleiss' κ values (0.543 and 0.558),

while their ordinal indices remain higher and fall within the acceptable *moderate-to-good* ranges of their respective benchmarks ($\alpha = 0.625$–0.738; ICC = 0.631–0.739). This indicates that disagreements are small shifts along the Likert scale.

Category	n	**Fleiss' κ [95% CI]**	**Kripp. α**	**ICC$(2,1)$**
Shocking	940	0.779 [0.740, 0.815]	0.884	0.882
Hate	778	0.704 [0.643, 0.754]	0.842	0.845
Violence	652	0.718 [0.660, 0.769]	0.839	0.844
Sexual	1,405	0.733 [0.694, 0.764]	0.768	0.771
Illegal Activity	396	0.677 [0.622, 0.731]	0.739	0.754
Self-Harm	690	0.558 [0.505, 0.608]	0.738	0.739
Harassment	914	0.543 [0.501, 0.583]	0.625	0.631
Overall	**5,775**	**0.735 [0.720, 0.750]**	**0.816**	**0.822**

Table 3. Inter-annotator reliability of MEDIETHIC by harm category and for the full set. Fleiss' κ is computed on the binary harmful/safe label (threshold ≥ 3) with bootstrap 95% confidence intervals; Krippendorff's α uses an ordinal distance metric on the original 5-point Likert scale; ICC$(2,1)$ treats the Likert scores as continuous.

4 Cost and Query Budget

The pipeline separates costs into a fixed offline phase (local query-free PGD optimization taking minutes on a single GPU) and a variable online phase (up to 100 target API queries per prompt). Table 4 summarizes these overheads across systems. On DALL·E, this cost has a median of 9 queries per prompt (mean 23.7, inflated by a long tail), with 61%, 79%, and 85% of prompts completing within a budget of 10, 25, and 50 queries, respectively; only about 10% of prompts exhaust the full 100-query budget without triggering the stopping condition. IMAGEN is markedly cheaper, with a median of 4 queries per prompt (mean 11.2) and 88% of prompts completing within 10 queries. Nano Banana 2 falls in between the two, with a median of 7 queries per prompt (mean 14) and 60% of prompts completing within 10 queries; beyond that point its tail closely tracks DALL·E's, with 78% and 85% of prompts completing within 25 and 50 queries, respectively, despite requiring a lower target number of accepted images per prompt. This cost is not uniform across harm categories: on DALL·E, *sexual* and *shocking* prompts are the most expensive (mean 28 and 32 queries, respectively), against 16–25 queries for the other categories, reflecting the stricter moderation these categories typically receive from the target service. At the query rate adopted in our pipeline (15 requests/minute), a median-cost prompt therefore completes in well under a minute of API time, while a prompt exhausting the full budget takes on the order of a few minutes.

Model	**Mean**	**Median**	**p90**	**Max**	**≤10**	**≤25**	**≤50**
DALL·E	23.7	9	95	100	61%	79%	85%
IMAGEN	11.2	4	12	100	88%	92%	93%
Nano Banana 2	14	7	60	100	60%	78%	85%

Table 4. Query budget per prompt to complete the black-box generation phase.

References

[1] Open AI. 2024. DALL·E 3 System Card. https://cdn.openai.com/papers/DALL_E_3_System_Card.pdf. Accessed: 2024-09-22.

[2] Google. 2023. Google Cloud Content Moderation Documentation. https://cloud.google.com/vertex-ai/generative-ai/docs/multimodal/configure-safety-filters. Accessed on 2023-10-02.
[3] Terry K Koo and Mae Y Li. 2016. A guideline of selecting and reporting intraclass correlation coefficients for reliability research. *Journal of chiropractic medicine* 15, 2 (2016), 155–163.
[4] Klaus Krippendorff. 2018. *Content analysis: An introduction to its methodology*. Sage publications.
[5] J Richard Landis and Gary G Koch. 1977. The measurement of observer agreement for categorical data. *biometrics* (1977), 159–174.
[6] Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. 2016. Delving into transferable adversarial examples and black-box attacks. *arXiv preprint arXiv:1611.02770* (2016).
[7] Microsoft Azure. 2023. Azure Content Moderator Documentation. https://azure.microsoft.com/en-us/services/cognitive-services/content-moderator/. Accessed on 2023-10-02.
[8] Pamela Mishkin, Lama Ahmad, Miles Brundage, Gretchen Krueger, and Girish Sastry. 2022. DALL·E 2 Preview - Risks and Limitations. https://github.com/openai/dalle-2-preview/blob/main/system-card.md. Accessed: 2024-09-22.
[9] OpenAI. 2023. OpenAI Moderation API. https://platform.openai.com/docs/guides/moderation. Accessed on 2023-10-02.




Fig. 1. Results achieved from the proposed applied to DALL·E and IMAGEN.