

Pricing Financial Derivatives Project 1

Angus McKay, Laura Roman, Euan Dowers, Veronika Kyuchukova

February 2, 2017

Exercise 1

Consider a binomial model with $r = 0.04$, $T = 4$, $d = 0.98$, $S_0 = 20$ and a European call with maturity $T = 4$ and strike price $K = 20$. In the lecture notes we are given that in the binomial model the no-arbitrage condition is satisfied if and only if

$$d < 1 + r < u$$


Furthermore, we are given that the risk-neutral probability is given by

$$q = \frac{1 + r - d}{u - d} = 0.75$$

So the risk-neutral probability is 0.75.

Since $0.98 < 1.04 < 1.06$, the no-arbitrage condition is satisfied.

The following tree represents the binomial tree of S_n for $n \in \{0, 1, 2, 3, 4\}$. Note that prices are rounded to 1 decimal place for presentation, but rounding is done after evaluation to avoid numerical errors.



Exercise 2


```
rm(list=ls())
library(ggplot2)
#####
```

```
### QUESTION 2 ###  
#####
```


```
# Part 1
```

```
Sn <- function(n,T = 5){  
  # Create function that produces random walk with step size sqrt(T/n)  
  stepsize <- sqrt(T/n)  
  Z <- rbinom(n+1,1,0.5)  
  Z[Z==1] <- stepsize  
  Z[Z==0] <- -stepsize  
  X <- rep(0,n+1)  
  for ( i in 2:n+1) {  
    X[i] = X[i-1] + Z[i] }  
  return(X)  
}
```


```
# Now plot the process Sn(t) for n = 10,50,100,1000  
y <- Sn(10)  
x <- seq(0,5,length.out = length(y))  
plot(y=y,x=x,type = 'l')
```




```
y <- Sn(50)  
x <- seq(0,5,length.out = length(y))  
plot(y=y,x=x,type = 'l')
```



```
y <- Sn(100)
x <- seq(0,5,length.out = length(y))
plot(y=y,x=x,type = 'l')
```



```
y <- Sn(10000)
x <- seq(0,5,length.out = length(y))
plot(y=y,x=x,type = 'l')
```



```
#####
# PART 2
#####

geometric.brownian <- function(n,T,sigma,mu){
  B <- Sn(n,T)
  t <- seq(0,T,length.out = n)
  X <- sigma * B + mu * t
  return(exp(X))
}

brownian.drift <- function(n,T,sigma,mu){
  B <- Sn(n,T)
  t <- seq(0,T,length.out = n)
  X <- sigma * B + mu * t
  return(X)
}

brownian.bridge <- function(n,T){
  B <- Sn(n,T)
  t <- seq(0,1,length.out = n)
  X <- B - t * B[n]
}

martingale <- function(n,T) {
  B <- Sn(n,T)
  t <- seq(0,T,length.out = n)
  return(B^2 - t)
}

n <- 1000
T <- 1
```

```

t <- seq(0,T,length.out = n)

simulations <- as.data.frame(
  cbind(
    t,
    geometric.brownian(n,T,sigma = 1, mu = -0.5),
    geometric.brownian(n,T,sigma = 1, mu = 0.5),
    brownian.drift(n,T,sigma = 0.1, mu = 1),
    brownian.drift(n,T,sigma = 1, mu = 0.1),
    brownian.bridge(n,T),
    martingale(n,T)
  )
)

## Warning in sigma * B + mu * t: longer object length is not a multiple of
## shorter object length

## Warning in sigma * B + mu * t: longer object length is not a multiple of
## shorter object length

## Warning in sigma * B + mu * t: longer object length is not a multiple of
## shorter object length

## Warning in sigma * B + mu * t: longer object length is not a multiple of
## shorter object length

## Warning in B - t * B[n]: longer object length is not a multiple of shorter
## object length

## Warning in B^2 - t: longer object length is not a multiple of shorter
## object length

## Warning in cbind(t, geometric.brownian(n, T, sigma = 1, mu = -0.5),
## geometric.brownian(n, : number of rows of result is not a multiple of
## vector length (arg 1)

ggplot(data = simulations,aes(x=t,y=V2)) +
  labs(x='t', y='Value of process', title = 'Processes related to Brownian motion') +
  geom_line(aes(x=t,y=V2,colour='Geometric mu = -.5, sigma=1')) +
  geom_line(aes(x=t,y=V3,colour='Geometric mu = .5, sigma=1')) +
  geom_line(aes(x=t,y=V4,colour='Drift mu = 1, sigma = 0.1')) +
  geom_line(aes(x=t,y=V5,colour='Drift mu = 0.1, sigma = 1')) +
  geom_line(aes(x=t,y=V6,colour='Brownian Bridge')) +
  geom_line(aes(x=t,y=V7,colour='Martingale'))

```

Processes related to Brownian motion

