

HyMITATOR

Parametric Analysis of Hybrid Systems

Étienne André¹ and Ulrich Kühne²

¹LIPN, CNRS UMR 7030, Université Paris 13, France



²Group for Computer Architecture, University of Bremen, Germany



An Example of Hybrid System: The Bouncing Ball


Hybrid systems combine

- Discrete behavior
- Continuous behavior





Parameterized Hybrid Automata

- Hybrid Automata (HA): Sets of variables, actions, locations, and discrete transitions
- Parameterized Hybrid Automata: HA augmented with a set of timing parameters (unknown constants)
- Example: Water Tank



The Parameter Synthesis Problem



- How to choose \min , \max , m , M and delay , such that always $\min < w < \max$?


Synthesis problem: “find values for the timing parameters such that the system behaves well”.

We will synthesize here a constraint, viz., a convex and dense set of values.

Parameter Synthesis for Hybrid Automata

- Inverse Method [Fribourg and Kühne, 2011]


- Given an HA and a reference valuation π_0 for the parameters, synthesize a constraint K_0 guaranteeing the same time-abstract behavior as for π_0



- K_0 obtained by iterative removal of states incompatible with π_0

- Behavioral Cartography [André and Fribourg, 2010]

- Performs a tiling of the parametric space, and partition it between good and bad tiles w.r.t. a given property



Example of “good” constraint for the water tank:

$$M + \text{delay} \geq m \wedge m \geq \min + 2 \cdot \text{delay} \wedge \max \geq M + \text{delay}$$



Features of HyMITATOR

- Algorithms of Parameter Synthesis for Hybrid Systems

- Implements the inverse method and the behavioral cartography
- Includes local partitioning with linear over-approximations
- Makes use of predicate abstraction techniques
- Features an efficient merging technique [André et al., 2012]

- User-friendly Features

- Numerous options for analysis
- Graphical output



- Implementation [André and Kühne, 2012]

- Implemented in OCaml, using the Parma Polyhedra Library

Try it!

- Distributed under the GNU General Public License
- www.lsv.ens-cachan.fr/Software/hymitator/

References

- André, É. and Fribourg, L. (2010). Behavioral cartography of timed automata. In *RP'10*, volume 6227 of *LNCS*, pages 76–90. Springer.
- André, É., Fribourg, L., and Soulat, R. (2012). Enhancing the inverse method with state merging. In *NFM'12*, volume 7226 of *LNCS*, pages 100–105. Springer.
- André, É. and Kühne, U. (2012). Parametric analysis of hybrid systems using HyMITATOR. In *Posters & Tool demos Session of iFM'12*, pages 16–19. CNR and ISTI.
- Fribourg, L. and Kühne, U. (2011). Parametric verification and test coverage for hybrid automata using the inverse method. In *RP'11*, volume 6945 of *LNCS*, pages 191–204. Springer.
- Halbwachs, N., Proy, Y.-E., and Roumanoff, P. (1997). Verification of real-time systems using linear relation analysis. *Formal Methods In System Design*, 11(2):157–185.