

Package ‘FeatureExtraction’

July 26, 2021

Type Package

Title Generating Features for a Cohort

Version 3.1.1

Date 2021-04-19

Maintainer Anthony Sena <sena@ohdsi.org>

Description An R package for generating features (covariates) for a cohort using data in the Common Data Model.

License Apache License 2.0

VignetteBuilder knitr

URL <https://github.com/OHDSI/FeatureExtraction>

BugReports <https://github.com/OHDSI/FeatureExtraction/issues>

Depends R (>= 3.2.2),
DatabaseConnector (>= 3.0.0),
Andromeda

Imports methods,
dplyr,
rJava,
jsonlite,
SqlRender (>= 1.6.0),
ParallelLogger (>= 2.0.2),
cli,
pillar,
readr,
rlang,
RSQLite,
DBI

Suggests testthat,
knitr,
rmarkdown,
Eunomia,
withr

NeedsCompilation no

RoxygenNote 7.1.1

Encoding UTF-8

R topics documented:

aggregateCovariates	2
computeStandardizedDifference	3
convertPrespecSettingsToDetailedSettings	3
CovariateData-class	4
createAnalysisDetails	4
createCohortAttrCovariateSettings	6
createCovariateSettings	7
createDefaultCovariateSettings	18
createDefaultTemporalCovariateSettings	19
createDetailedCovariateSettings	19
createDetailedTemporalCovariateSettings	20
createTable1	21
createTable1CovariateSettings	22
createTemporalCovariateSettings	23
createTemporalSequenceCovariateSettings	27
filterByCohortDefinitionId	30
filterByRowId	31
getDbCohortAttrCovariatesData	31
getDbCovariateData	33
getDbDefaultCovariateData	34
getDefaultTable1Specifications	36
isAggregatedCovariateData	36
isCovariateData	37
isTemporalCovariateData	37
loadCovariateData	38
saveCovariateData	38
tidyCovariateData	39
Index	40

aggregateCovariates	<i>Aggregate covariate data</i>
---------------------	---------------------------------

Description

Aggregate covariate data

Usage

```
aggregateCovariates(covariateData)
```

Arguments

`covariateData` An object of type `covariateData` as generated using `getDbCovariateData`.

Value

An object of class `covariateData`.

`computeStandardizedDifference`*Compute standardized difference of mean for all covariates.*

Description

Computes the standardized difference for all covariates between two cohorts. The standardized difference is defined as the difference between the mean divided by the overall standard deviation.

Usage

```
computeStandardizedDifference(  
  covariateData1,  
  covariateData2,  
  cohortId1 = NULL,  
  cohortId2 = NULL  
)
```

Arguments

<code>covariateData1</code>	The covariate data of the first cohort. Needs to be in aggregated format.
<code>covariateData2</code>	The covariate data of the second cohort. Needs to be in aggregated format.
<code>cohortId1</code>	If provided, <code>covariateData1</code> will be restricted to this cohort. If not provided, <code>covariateData1</code> is assumed to contain data on only 1 cohort.
<code>cohortId2</code>	If provided, <code>covariateData2</code> will be restricted to this cohort. If not provided, <code>covariateData2</code> is assumed to contain data on only 1 cohort.

Value

A data frame with means and standard deviations per cohort as well as the standardized difference of mean.

`convertPrespecSettingsToDetailedSettings`*Convert prespecified covariate settings into detailed covariate settings*

Description

Convert prespecified covariate settings into detailed covariate settings

Usage

```
convertPrespecSettingsToDetailedSettings(covariateSettings)
```

Arguments

<code>covariateSettings</code>	An object of type <code>covariateSettings</code> as created for example by the createCovariateSettings function.
--------------------------------	--

Details

For advanced users only.

Value

An object of type covariateSettings, to be used in other functions.

CovariateData-class	<i>Covariate Data</i>
---------------------	-----------------------

Description

CovariateData is an S4 class that inherits from [Andromeda](#). It contains information on covariates, which can be either captured on a per-person basis, or aggregated across the cohort(s).

By default covariates refer to a specific time period, with for example different covariate IDs for whether a diagnosis code was observed in the year before and month before index date. However, a CovariateData can also be temporal, meaning that next to a covariate ID there is also a time ID, which identifies the (user specified) time window the covariate was captured.

A CovariateData object is typically created using [getDbCovariateData](#), can only be saved using [saveCovariateData](#), and loaded using [loadCovariateData](#).

Usage

```
## S4 method for signature 'CovariateData'
show(object)

## S4 method for signature 'CovariateData'
summary(object)
```

Arguments

object An object of class ‘CovariateData’.

See Also

[isCovariateData](#), [isAggregatedCovariateData](#), [isTemporalCovariateData](#)

createAnalysisDetails	<i>Create detailed covariate settings</i>
-----------------------	---

Description

Create detailed covariate settings

Usage

```
createAnalysisDetails(
  analysisId,
  sqlFileName,
  parameters,
  includedCovariateConceptIds = c(),
  addDescendantsToInclude = FALSE,
  excludedCovariateConceptIds = c(),
  addDescendantsToExclude = FALSE,
  includedCovariateIds = c()
)
```

Arguments

analysisId	An integer between 0 and 999 that uniquely identifies this analysis.
sqlFileName	The name of the parameterized SQL file embedded in the featureExtraction package.
parameters	The list of parameter values used to render the template SQL.
includedCovariateConceptIds	A list of concept IDs that should be used to construct covariates.
addDescendantsToInclude	Should descendant concept IDs be added to the list of concepts to include?
excludedCovariateConceptIds	A list of concept IDs that should NOT be used to construct covariates.
addDescendantsToExclude	Should descendant concept IDs be added to the list of concepts to exclude?
includedCovariateIds	A list of covariate IDs that should be restricted to.

Details

creates an object specifying in detail how covariates should be constructed from data in the CDM model. Warning: this function is for advanced users only.

Value

An object of type analysisDetail, to be used in [createDetailedCovariateSettings](#) or [createDetailedTemporalC](#)

Examples

```
analysisDetails <- createAnalysisDetails(analysisId = 1,
  sqlFileName = "DemographicsGender.sql",
  parameters = list(analysisId = 1,
    analysisName = "Gender",
    domainId = "Demographics"),
  includedCovariateConceptIds = c(),
  addDescendantsToInclude = FALSE,
  excludedCovariateConceptIds = c(),
  addDescendantsToExclude = FALSE,
  includedCovariateIds = c())
```

```
createCohortAttrCovariateSettings
```

Create cohort attribute covariate settings

Description

Create cohort attribute covariate settings

Usage

```
createCohortAttrCovariateSettings(  
  analysisId = -1,  
  attrDatabaseSchema,  
  attrDefinitionTable = "attribute_definition",  
  cohortAttrTable = "cohort_attribute",  
  includeAttrIds = c(),  
  isBinary = FALSE,  
  missingMeansZero = FALSE  
)
```

Arguments

<code>analysisId</code>	A unique identifier for this analysis.
<code>attrDatabaseSchema</code>	The database schema where the attribute definition and cohort attribute table can be found.
<code>attrDefinitionTable</code>	The name of the attribute definition table.
<code>cohortAttrTable</code>	The name of the cohort attribute table.
<code>includeAttrIds</code>	(optional) A list of attribute definition IDs to restrict to.
<code>isBinary</code>	Needed for aggregation: Are these binary variables? Binary variables should only have the values 0 or 1.
<code>missingMeansZero</code>	Needed for aggregation: For continuous values, should missing values be interpreted as 0?

Details

Creates an object specifying where the cohort attributes can be found to construct covariates. The attributes should be defined in a table with the same structure as the `attribute_definition` table in the Common Data Model. It should at least have these columns:

attribute_definition_id A unique identifier of type integer.

attribute_name A short description of the attribute.

The cohort attributes themselves should be stored in a table with the same format as the `cohort_attribute` table in the Common Data Model. It should at least have these columns:

cohort_definition_id A key to link to the cohort table.

subject_id A key to link to the cohort table.
cohort_start_date A key to link to the cohort table.
attribute_definition_id An foreign key linking to the attribute definition table.
value_as_number A real number.

Value

An object of type covariateSettings, to be used in other functions.

```
createCovariateSettings
      Create covariate settings
```

Description

Create covariate settings

Usage

```
createCovariateSettings(
  useDemographicsGender = FALSE,
  useDemographicsAge = FALSE,
  useDemographicsAgeGroup = FALSE,
  useDemographicsRace = FALSE,
  useDemographicsEthnicity = FALSE,
  useDemographicsIndexYear = FALSE,
  useDemographicsIndexMonth = FALSE,
  useDemographicsPriorObservationTime = FALSE,
  useDemographicsPostObservationTime = FALSE,
  useDemographicsTimeInCohort = FALSE,
  useDemographicsIndexYearMonth = FALSE,
  useConditionOccurrenceAnyTimePrior = FALSE,
  useConditionOccurrenceLongTerm = FALSE,
  useConditionOccurrenceMediumTerm = FALSE,
  useConditionOccurrenceShortTerm = FALSE,
  useConditionOccurrencePrimaryInpatientAnyTimePrior = FALSE,
  useConditionOccurrencePrimaryInpatientLongTerm = FALSE,
  useConditionOccurrencePrimaryInpatientMediumTerm = FALSE,
  useConditionOccurrencePrimaryInpatientShortTerm = FALSE,
  useConditionEraAnyTimePrior = FALSE,
  useConditionEraLongTerm = FALSE,
  useConditionEraMediumTerm = FALSE,
  useConditionEraShortTerm = FALSE,
  useConditionEraOverlapping = FALSE,
  useConditionEraStartLongTerm = FALSE,
  useConditionEraStartMediumTerm = FALSE,
  useConditionEraStartShortTerm = FALSE,
  useConditionGroupEraAnyTimePrior = FALSE,
  useConditionGroupEraLongTerm = FALSE,
  useConditionGroupEraMediumTerm = FALSE,
```

```
useConditionGroupEraShortTerm = FALSE,
useConditionGroupEraOverlapping = FALSE,
useConditionGroupEraStartLongTerm = FALSE,
useConditionGroupEraStartMediumTerm = FALSE,
useConditionGroupEraStartShortTerm = FALSE,
useDrugExposureAnyTimePrior = FALSE,
useDrugExposureLongTerm = FALSE,
useDrugExposureMediumTerm = FALSE,
useDrugExposureShortTerm = FALSE,
useDrugEraAnyTimePrior = FALSE,
useDrugEraLongTerm = FALSE,
useDrugEraMediumTerm = FALSE,
useDrugEraShortTerm = FALSE,
useDrugEraOverlapping = FALSE,
useDrugEraStartLongTerm = FALSE,
useDrugEraStartMediumTerm = FALSE,
useDrugEraStartShortTerm = FALSE,
useDrugGroupEraAnyTimePrior = FALSE,
useDrugGroupEraLongTerm = FALSE,
useDrugGroupEraMediumTerm = FALSE,
useDrugGroupEraShortTerm = FALSE,
useDrugGroupEraOverlapping = FALSE,
useDrugGroupEraStartLongTerm = FALSE,
useDrugGroupEraStartMediumTerm = FALSE,
useDrugGroupEraStartShortTerm = FALSE,
useProcedureOccurrenceAnyTimePrior = FALSE,
useProcedureOccurrenceLongTerm = FALSE,
useProcedureOccurrenceMediumTerm = FALSE,
useProcedureOccurrenceShortTerm = FALSE,
useDeviceExposureAnyTimePrior = FALSE,
useDeviceExposureLongTerm = FALSE,
useDeviceExposureMediumTerm = FALSE,
useDeviceExposureShortTerm = FALSE,
useMeasurementAnyTimePrior = FALSE,
useMeasurementLongTerm = FALSE,
useMeasurementMediumTerm = FALSE,
useMeasurementShortTerm = FALSE,
useMeasurementValueAnyTimePrior = FALSE,
useMeasurementValueLongTerm = FALSE,
useMeasurementValueMediumTerm = FALSE,
useMeasurementValueShortTerm = FALSE,
useMeasurementRangeGroupAnyTimePrior = FALSE,
useMeasurementRangeGroupLongTerm = FALSE,
useMeasurementRangeGroupMediumTerm = FALSE,
useMeasurementRangeGroupShortTerm = FALSE,
useObservationAnyTimePrior = FALSE,
useObservationLongTerm = FALSE,
useObservationMediumTerm = FALSE,
useObservationShortTerm = FALSE,
useCharlsonIndex = FALSE,
useDcsi = FALSE,
useChads2 = FALSE,
```



```

useChads2Vasc = FALSE,
useHfrs = FALSE,
useDistinctConditionCountLongTerm = FALSE,
useDistinctConditionCountMediumTerm = FALSE,
useDistinctConditionCountShortTerm = FALSE,
useDistinctIngredientCountLongTerm = FALSE,
useDistinctIngredientCountMediumTerm = FALSE,
useDistinctIngredientCountShortTerm = FALSE,
useDistinctProcedureCountLongTerm = FALSE,
useDistinctProcedureCountMediumTerm = FALSE,
useDistinctProcedureCountShortTerm = FALSE,
useDistinctMeasurementCountLongTerm = FALSE,
useDistinctMeasurementCountMediumTerm = FALSE,
useDistinctMeasurementCountShortTerm = FALSE,
useDistinctObservationCountLongTerm = FALSE,
useDistinctObservationCountMediumTerm = FALSE,
useDistinctObservationCountShortTerm = FALSE,
useVisitCountLongTerm = FALSE,
useVisitCountMediumTerm = FALSE,
useVisitCountShortTerm = FALSE,
useVisitConceptCountLongTerm = FALSE,
useVisitConceptCountMediumTerm = FALSE,
useVisitConceptCountShortTerm = FALSE,
longTermStartDays = -365,
mediumTermStartDays = -180,
shortTermStartDays = -30,
endDays = 0,
includedCovariateConceptIds = c(),
addDescendantsToInclude = FALSE,
excludedCovariateConceptIds = c(),
addDescendantsToExclude = FALSE,
includedCovariateIds = c()
)

```

Arguments

```

useDemographicsGender
  Gender of the subject. (analysis ID 1)

useDemographicsAge
  Age of the subject on the index date (in years). (analysis ID 2)

useDemographicsAgeGroup
  Age of the subject on the index date (in 5 year age groups) (analysis ID 3)

useDemographicsRace
  Race of the subject. (analysis ID 4)

useDemographicsEthnicity
  Ethnicity of the subject. (analysis ID 5)

useDemographicsIndexYear
  Year of the index date. (analysis ID 6)

useDemographicsIndexMonth
  Month of the index date. (analysis ID 7)

```

`useDemographicsPriorObservationTime`
 Number of continuous days of observation time preceding the index date. (analysis ID 8)

`useDemographicsPostObservationTime`
 Number of continuous days of observation time following the index date. (analysis ID 9)

`useDemographicsTimeInCohort`
 Number of days of observation time during cohort period. (analysis ID 10)

`useDemographicsIndexYearMonth`
 Both calendar year and month of the index date in a single variable. (analysis ID 11)

`useConditionOccurrenceAnyTimePrior`
 One covariate per condition in the `condition_occurrence` table starting any time prior to index. (analysis ID 101)

`useConditionOccurrenceLongTerm`
 One covariate per condition in the `condition_occurrence` table starting in the long term window. (analysis ID 102)

`useConditionOccurrenceMediumTerm`
 One covariate per condition in the `condition_occurrence` table starting in the medium term window. (analysis ID 103)

`useConditionOccurrenceShortTerm`
 One covariate per condition in the `condition_occurrence` table starting in the short term window. (analysis ID 104)

`useConditionOccurrencePrimaryInpatientAnyTimePrior`
 One covariate per condition observed as a primary diagnosis in an inpatient setting in the `condition_occurrence` table starting any time prior to index. (analysis ID 105)

`useConditionOccurrencePrimaryInpatientLongTerm`
 One covariate per condition observed as a primary diagnosis in an inpatient setting in the `condition_occurrence` table starting in the long term window. (analysis ID 106)

`useConditionOccurrencePrimaryInpatientMediumTerm`
 One covariate per condition observed as a primary diagnosis in an inpatient setting in the `condition_occurrence` table starting in the medium term window. (analysis ID 107)

`useConditionOccurrencePrimaryInpatientShortTerm`
 One covariate per condition observed as a primary diagnosis in an inpatient setting in the `condition_occurrence` table starting in the short term window. (analysis ID 108)

`useConditionEraAnyTimePrior`
 One covariate per condition in the `condition_era` table overlapping with any time prior to index. (analysis ID 201)

`useConditionEraLongTerm`
 One covariate per condition in the `condition_era` table overlapping with any part of the long term window. (analysis ID 202)

`useConditionEraMediumTerm`
 One covariate per condition in the `condition_era` table overlapping with any part of the medium term window. (analysis ID 203)

`useConditionEraShortTerm`
 One covariate per condition in the `condition_era` table overlapping with any part of the short term window. (analysis ID 204)

useConditionEraOverlapping	One covariate per condition in the condition_era table overlapping with the end of the risk window. (analysis ID 205)
useConditionEraStartLongTerm	One covariate per condition in the condition_era table starting in the long term window. (analysis ID 206)
useConditionEraStartMediumTerm	One covariate per condition in the condition_era table starting in the medium term window. (analysis ID 207)
useConditionEraStartShortTerm	One covariate per condition in the condition_era table starting in the short term window. (analysis ID 208)
useConditionGroupEraAnyTimePrior	One covariate per condition era rolled up to groups in the condition_era table overlapping with any time prior to index. (analysis ID 209)
useConditionGroupEraLongTerm	One covariate per condition era rolled up to groups in the condition_era table overlapping with any part of the long term window. (analysis ID 210)
useConditionGroupEraMediumTerm	One covariate per condition era rolled up to groups in the condition_era table overlapping with any part of the medium term window. (analysis ID 211)
useConditionGroupEraShortTerm	One covariate per condition era rolled up to groups in the condition_era table overlapping with any part of the short term window. (analysis ID 212)
useConditionGroupEraOverlapping	One covariate per condition era rolled up to groups in the condition_era table overlapping with the end of the risk window. (analysis ID 213)
useConditionGroupEraStartLongTerm	One covariate per condition era rolled up to groups in the condition_era table starting in the long term window. (analysis ID 214)
useConditionGroupEraStartMediumTerm	One covariate per condition era rolled up to groups in the condition_era table starting in the medium term window. (analysis ID 215)
useConditionGroupEraStartShortTerm	One covariate per condition era rolled up to groups in the condition_era table starting in the short term window. (analysis ID 216)
useDrugExposureAnyTimePrior	One covariate per drug in the drug_exposure table starting any time prior to index. (analysis ID 301)
useDrugExposureLongTerm	One covariate per drug in the drug_exposure table starting in the long term window. (analysis ID 302)
useDrugExposureMediumTerm	One covariate per drug in the drug_exposure table starting in the medium term window. (analysis ID 303)
useDrugExposureShortTerm	One covariate per drug in the drug_exposure table starting in the short term window. (analysis ID 304)
useDrugEraAnyTimePrior	One covariate per drug in the drug_era table overlapping with any time prior to index. (analysis ID 401)

`useDrugEraLongTerm`
One covariate per drug in the `drug_era` table overlapping with any part of the long term window. (analysis ID 402)

`useDrugEraMediumTerm`
One covariate per drug in the `drug_era` table overlapping with any part of the medium term window. (analysis ID 403)

`useDrugEraShortTerm`
One covariate per drug in the `drug_era` table overlapping with any part of the short window. (analysis ID 404)

`useDrugEraOverlapping`
One covariate per drug in the `drug_era` table overlapping with the end of the risk window. (analysis ID 405)

`useDrugEraStartLongTerm`
One covariate per drug in the `drug_era` table starting in the long term window. (analysis ID 406)

`useDrugEraStartMediumTerm`
One covariate per drug in the `drug_era` table starting in the medium term window. (analysis ID 407)

`useDrugEraStartShortTerm`
One covariate per drug in the `drug_era` table starting in the long short window. (analysis ID 408)

`useDrugGroupEraAnyTimePrior`
One covariate per drug rolled up to ATC groups in the `drug_era` table overlapping with any time prior to index. (analysis ID 409)

`useDrugGroupEraLongTerm`
One covariate per drug rolled up to ATC groups in the `drug_era` table overlapping with any part of the long term window. (analysis ID 410)

`useDrugGroupEraMediumTerm`
One covariate per drug rolled up to ATC groups in the `drug_era` table overlapping with any part of the medium term window. (analysis ID 411)

`useDrugGroupEraShortTerm`
One covariate per drug rolled up to ATC groups in the `drug_era` table overlapping with any part of the short term window. (analysis ID 412)

`useDrugGroupEraOverlapping`
One covariate per drug rolled up to ATC groups in the `drug_era` table overlapping with the end of the risk window. (analysis ID 413)

`useDrugGroupEraStartLongTerm`
One covariate per drug rolled up to ATC groups in the `drug_era` table starting in the long term window. (analysis ID 414)

`useDrugGroupEraStartMediumTerm`
One covariate per drug rolled up to ATC groups in the `drug_era` table starting in the medium term window. (analysis ID 415)

`useDrugGroupEraStartShortTerm`
One covariate per drug rolled up to ATC groups in the `drug_era` table starting in the short term window. (analysis ID 416)

`useProcedureOccurrenceAnyTimePrior`
One covariate per procedure in the `procedure_occurrence` table any time prior to index. (analysis ID 501)

`useProcedureOccurrenceLongTerm`
One covariate per procedure in the `procedure_occurrence` table in the long term window. (analysis ID 502)

useProcedureOccurrenceMediumTerm	One covariate per procedure in the procedure_occurrence table in the medium term window. (analysis ID 503)
useProcedureOccurrenceShortTerm	One covariate per procedure in the procedure_occurrence table in the short term window. (analysis ID 504)
useDeviceExposureAnyTimePrior	One covariate per device in the device exposure table starting any time prior to index. (analysis ID 601)
useDeviceExposureLongTerm	One covariate per device in the device exposure table starting in the long term window. (analysis ID 602)
useDeviceExposureMediumTerm	One covariate per device in the device exposure table starting in the medium term window. (analysis ID 603)
useDeviceExposureShortTerm	One covariate per device in the device exposure table starting in the short term window. (analysis ID 604)
useMeasurementAnyTimePrior	One covariate per measurement in the measurement table any time prior to index. (analysis ID 701)
useMeasurementLongTerm	One covariate per measurement in the measurement table in the long term window. (analysis ID 702)
useMeasurementMediumTerm	One covariate per measurement in the measurement table in the medium term window. (analysis ID 703)
useMeasurementShortTerm	One covariate per measurement in the measurement table in the short term window. (analysis ID 704)
useMeasurementValueAnyTimePrior	One covariate containing the value per measurement-unit combination any time prior to index. (analysis ID 705)
useMeasurementValueLongTerm	One covariate containing the value per measurement-unit combination in the long term window. (analysis ID 706)
useMeasurementValueMediumTerm	One covariate containing the value per measurement-unit combination in the medium term window. (analysis ID 707)
useMeasurementValueShortTerm	One covariate containing the value per measurement-unit combination in the short term window. (analysis ID 708)
useMeasurementRangeGroupAnyTimePrior	Covariates indicating whether measurements are below, within, or above normal range any time prior to index. (analysis ID 709)
useMeasurementRangeGroupLongTerm	Covariates indicating whether measurements are below, within, or above normal range in the long term window. (analysis ID 710)
useMeasurementRangeGroupMediumTerm	Covariates indicating whether measurements are below, within, or above normal range in the medium term window. (analysis ID 711)

<code>useMeasurementRangeGroupShortTerm</code>	Covariates indicating whether measurements are below, within, or above normal range in the short term window. (analysis ID 712)
<code>useObservationAnyTimePrior</code>	One covariate per observation in the observation table any time prior to index. (analysis ID 801)
<code>useObservationLongTerm</code>	One covariate per observation in the observation table in the long term window. (analysis ID 802)
<code>useObservationMediumTerm</code>	One covariate per observation in the observation table in the medium term window. (analysis ID 803)
<code>useObservationShortTerm</code>	One covariate per observation in the observation table in the short term window. (analysis ID 804)
<code>useCharlsonIndex</code>	The Charlson comorbidity index (Romano adaptation) using all conditions prior to the window end. (analysis ID 901)
<code>useDcsi</code>	The Diabetes Comorbidity Severity Index (DCSI) using all conditions prior to the window end. (analysis ID 902)
<code>useChads2</code>	The CHADS2 score using all conditions prior to the window end. (analysis ID 903)
<code>useChads2Vasc</code>	The CHADS2VASc score using all conditions prior to the window end. (analysis ID 904)
<code>useHfrs</code>	The Hospital Frailty Risk Score score using all conditions prior to the window end. (analysis ID 926)
<code>useDistinctConditionCountLongTerm</code>	The number of distinct condition concepts observed in the long term window. (analysis ID 905)
<code>useDistinctConditionCountMediumTerm</code>	The number of distinct condition concepts observed in the medium term window. (analysis ID 906)
<code>useDistinctConditionCountShortTerm</code>	The number of distinct condition concepts observed in the short term window. (analysis ID 907)
<code>useDistinctIngredientCountLongTerm</code>	The number of distinct ingredients observed in the long term window. (analysis ID 908)
<code>useDistinctIngredientCountMediumTerm</code>	The number of distinct ingredients observed in the medium term window. (analysis ID 909)
<code>useDistinctIngredientCountShortTerm</code>	The number of distinct ingredients observed in the short term window. (analysis ID 910)
<code>useDistinctProcedureCountLongTerm</code>	The number of distinct procedures observed in the long term window. (analysis ID 911)
<code>useDistinctProcedureCountMediumTerm</code>	The number of distinct procedures observed in the medium term window. (analysis ID 912)

useDistinctProcedureCountShortTerm
 The number of distinct procedures observed in the short term window. (analysis ID 913)

useDistinctMeasurementCountLongTerm
 The number of distinct measurements observed in the long term window. (analysis ID 914)

useDistinctMeasurementCountMediumTerm
 The number of distinct measurements observed in the medium term window. (analysis ID 915)

useDistinctMeasurementCountShortTerm
 The number of distinct measurements observed in the short term window. (analysis ID 916)

useDistinctObservationCountLongTerm
 The number of distinct observations observed in the long term window. (analysis ID 917)

useDistinctObservationCountMediumTerm
 The number of distinct observations observed in the medium term window. (analysis ID 918)

useDistinctObservationCountShortTerm
 The number of distinct observations observed in the short term window. (analysis ID 919)

useVisitCountLongTerm
 The number of visits observed in the long term window. (analysis ID 920)

useVisitCountMediumTerm
 The number of visits observed in the medium term window. (analysis ID 921)

useVisitCountShortTerm
 The number of visits observed in the short term window. (analysis ID 922)

useVisitConceptCountLongTerm
 The number of visits observed in the long term window, stratified by visit concept ID. (analysis ID 923)

useVisitConceptCountMediumTerm
 The number of visits observed in the medium term window, stratified by visit concept ID. (analysis ID 924)

useVisitConceptCountShortTerm
 The number of visits observed in the short term window, stratified by visit concept ID. (analysis ID 925)

longTermStartDays
 What is the start day (relative to the index date) of the long-term window?

mediumTermStartDays
 What is the start day (relative to the index date) of the medium-term window?

shortTermStartDays
 What is the start day (relative to the index date) of the short-term window?

endDays
 What is the end day (relative to the index date) of the window?

includedCovariateConceptIds
 A list of concept IDs that should be used to construct covariates.

addDescendantsToInclude
 Should descendant concept IDs be added to the list of concepts to include?

excludedCovariateConceptIds
 A list of concept IDs that should NOT be used to construct covariates.


```
useDrugEraShortTerm = FALSE,
useDrugEraOverlapping = FALSE,
useDrugEraStartLongTerm = FALSE,
useDrugEraStartMediumTerm = FALSE,
useDrugEraStartShortTerm = FALSE,
useDrugGroupEraAnyTimePrior = FALSE,
useDrugGroupEraLongTerm = TRUE,
useDrugGroupEraMediumTerm = FALSE,
useDrugGroupEraShortTerm = TRUE,
useDrugGroupEraOverlapping = TRUE,
useDrugGroupEraStartLongTerm = FALSE,
useDrugGroupEraStartMediumTerm = FALSE,
useDrugGroupEraStartShortTerm = FALSE,
useProcedureOccurrenceAnyTimePrior = FALSE,
useProcedureOccurrenceLongTerm = TRUE,
useProcedureOccurrenceMediumTerm = FALSE,
useProcedureOccurrenceShortTerm = TRUE,
useDeviceExposureAnyTimePrior = FALSE,
useDeviceExposureLongTerm = TRUE,
useDeviceExposureMediumTerm = FALSE,
useDeviceExposureShortTerm = TRUE,
useMeasurementAnyTimePrior = FALSE,
useMeasurementLongTerm = TRUE,
useMeasurementMediumTerm = FALSE,
useMeasurementShortTerm = TRUE,
useMeasurementValueAnyTimePrior = FALSE,
useMeasurementValueLongTerm = FALSE,
useMeasurementValueMediumTerm = FALSE,
useMeasurementValueShortTerm = FALSE,
useMeasurementRangeGroupAnyTimePrior = FALSE,
useMeasurementRangeGroupLongTerm = TRUE,
useMeasurementRangeGroupMediumTerm = FALSE,
useMeasurementRangeGroupShortTerm = FALSE,
useObservationAnyTimePrior = FALSE,
useObservationLongTerm = TRUE,
useObservationMediumTerm = FALSE,
useObservationShortTerm = TRUE,
useCharlsonIndex = TRUE,
useDcsi = TRUE,
useChads2 = TRUE,
useChads2Vasc = TRUE,
useHfrs = FALSE,
useDistinctConditionCountLongTerm = FALSE,
useDistinctConditionCountMediumTerm = FALSE,
useDistinctConditionCountShortTerm = FALSE,
useDistinctIngredientCountLongTerm = FALSE,
useDistinctIngredientCountMediumTerm = FALSE,
useDistinctIngredientCountShortTerm = FALSE,
useDistinctProcedureCountLongTerm = FALSE,
useDistinctProcedureCountMediumTerm = FALSE,
useDistinctProcedureCountShortTerm = FALSE,
useDistinctMeasurementCountLongTerm = FALSE,
useDistinctMeasurementCountMediumTerm = FALSE,
useDistinctMeasurementCountShortTerm = FALSE,
useDistinctObservationCountLongTerm = FALSE,
useDistinctObservationCountMediumTerm = FALSE,
useDistinctObservationCountShortTerm = FALSE,
```

```

useVisitCountLongTerm = FALSE,
useVisitCountMediumTerm = FALSE,
useVisitCountShortTerm = FALSE,
useVisitConceptCountLongTerm = FALSE,
useVisitConceptCountMediumTerm = FALSE,
useVisitConceptCountShortTerm = FALSE,
longTermStartDays = -365,
mediumTermStartDays = -180,
shortTermStartDays = -30,
endDays = 0,
includedCovariateConceptIds = c(),
addDescendantsToInclude = FALSE,
excludedCovariateConceptIds = c(),
addDescendantsToExclude = FALSE,
includedCovariateIds = c())

```

createDefaultCovariateSettings

Create default covariate settings

Description

Create default covariate settings

Usage

```

createDefaultCovariateSettings(
  includedCovariateConceptIds = c(),
  addDescendantsToInclude = FALSE,
  excludedCovariateConceptIds = c(),
  addDescendantsToExclude = FALSE,
  includedCovariateIds = c()
)

```

Arguments

includedCovariateConceptIds
A list of concept IDs that should be used to construct covariates.

addDescendantsToInclude
Should descendant concept IDs be added to the list of concepts to include?

excludedCovariateConceptIds
A list of concept IDs that should NOT be used to construct covariates.

addDescendantsToExclude
Should descendant concept IDs be added to the list of concepts to exclude?

includedCovariateIds
A list of covariate IDs that should be restricted to.

Value

An object of type covariateSettings, to be used in other functions.

```
createDefaultTemporalCovariateSettings
```

Create default covariate settings

Description

Create default covariate settings

Usage

```
createDefaultTemporalCovariateSettings(
  includedCovariateConceptIds = c(),
  addDescendantsToInclude = FALSE,
  excludedCovariateConceptIds = c(),
  addDescendantsToExclude = FALSE,
  includedCovariateIds = c()
)
```

Arguments

`includedCovariateConceptIds`
A list of concept IDs that should be used to construct covariates.

`addDescendantsToInclude`
Should descendant concept IDs be added to the list of concepts to include?

`excludedCovariateConceptIds`
A list of concept IDs that should NOT be used to construct covariates.

`addDescendantsToExclude`
Should descendant concept IDs be added to the list of concepts to exclude?

`includedCovariateIds`
A list of covariate IDs that should be restricted to.

Value

An object of type `covariateSettings`, to be used in other functions.

```
createDetailedCovariateSettings
```

Create detailed covariate settings

Description

Create detailed covariate settings

Usage

```
createDetailedCovariateSettings(analyses = list())
```

Arguments

`analyses` A list of `analysisDetail` objects as created using [createAnalysisDetails](#).

Details

creates an object specifying in detail how covariates should be constructed from data in the CDM model. Warning: this function is for advanced users only.

Value

An object of type covariateSettings, to be used in other functions.

```
createDetailedTemporalCovariateSettings
```

Create detailed temporal covariate settings

Description

Create detailed temporal covariate settings

Usage

```
createDetailedTemporalCovariateSettings(
  analyses = list(),
  temporalStartDays = -365:-1,
  temporalEndDays = -365:-1
)
```

Arguments

analyses	A list of analysis detail objects as created using createAnalysisDetails .
temporalStartDays	A list of integers representing the start of a time period, relative to the index date. 0 indicates the index date, -1 indicates the day before the index date, etc. The start day is included in the time period.
temporalEndDays	A list of integers representing the end of a time period, relative to the index date. 0 indicates the index date, -1 indicates the day before the index date, etc. The end day is included in the time period.

Details

creates an object specifying in detail how temporal covariates should be constructed from data in the CDM model. Warning: this function is for advanced users only.

Value

An object of type covariateSettings, to be used in other functions.

createTable1

Create a table 1

Description

Creates a formatted table of cohort characteristics, to be included in publications or reports. Allows for creating a table describing a single cohort, or a table comparing two cohorts.

Usage

```
createTable1(
  covariateData1,
  covariateData2 = NULL,
  cohortId1 = NULL,
  cohortId2 = NULL,
  specifications = getDefaultTable1Specifications(),
  output = "two columns",
  showCounts = FALSE,
  showPercent = TRUE,
  percentDigits = 1,
  valueDigits = 1,
  stdDiffDigits = 2
)
```

Arguments

covariateData1	The covariate data of the cohort to be included in the table.
covariateData2	The covariate data of the cohort to also be included, when comparing two cohorts.
cohortId1	If provided, covariateData1 will be restricted to this cohort. If not provided, covariateData1 is assumed to contain data on only 1 cohort.
cohortId2	If provided, covariateData2 will be restricted to this cohort. If not provided, covariateData2 is assumed to contain data on only 1 cohort.
specifications	Specifications of which covariates to display, and how.
output	The output format for the table. Options are output = "two columns", output = "one column", or output = "list".
showCounts	Show the number of cohort entries having the binary covariate?
showPercent	Show the percentage of cohort entries having the binary covariate?
percentDigits	Number of digits to be used for percentages.
valueDigits	Number of digits to be used for the values of continuous variables.
stdDiffDigits	Number of digits to be used for the standardized differences.

Value

A data frame, or, when output = "list" a list of two data frames.

```
createTable1CovariateSettings
```

Create covariate settings for a table 1

Description

Creates a covariate settings object for generating only those covariates that will be included in a table 1. This function works by filtering the covariateSettings object for the covariates in the specifications object.

Usage

```
createTable1CovariateSettings(
  specifications = getDefaultTable1Specifications(),
  covariateSettings = createDefaultCovariateSettings(),
  includedCovariateConceptIds = c(),
  addDescendantsToInclude = FALSE,
  excludedCovariateConceptIds = c(),
  addDescendantsToExclude = FALSE,
  includedCovariateIds = c()
)
```

Arguments

specifications A specifications object for generating a table using the [createTable1](#) function.

covariateSettings The covariate settings object to use as the basis for the filtered covariate settings.

includedCovariateConceptIds A list of concept IDs that should be used to construct covariates.

addDescendantsToInclude Should descendant concept IDs be added to the list of concepts to include?

excludedCovariateConceptIds A list of concept IDs that should NOT be used to construct covariates.

addDescendantsToExclude Should descendant concept IDs be added to the list of concepts to exclude?

includedCovariateIds A list of covariate IDs that should be restricted to.

Value

A covariate settings object, for example to be used when calling the [getDbCovariateData](#) function.

createTemporalCovariateSettings
Create covariate settings

Description

Create covariate settings

Usage

```
createTemporalCovariateSettings(  
  useDemographicsGender = FALSE,  
  useDemographicsAge = FALSE,  
  useDemographicsAgeGroup = FALSE,  
  useDemographicsRace = FALSE,  
  useDemographicsEthnicity = FALSE,  
  useDemographicsIndexYear = FALSE,  
  useDemographicsIndexMonth = FALSE,  
  useDemographicsPriorObservationTime = FALSE,  
  useDemographicsPostObservationTime = FALSE,  
  useDemographicsTimeInCohort = FALSE,  
  useDemographicsIndexYearMonth = FALSE,  
  useConditionOccurrence = FALSE,  
  useConditionOccurrencePrimaryInpatient = FALSE,  
  useConditionEraStart = FALSE,  
  useConditionEraOverlap = FALSE,  
  useConditionEraGroupStart = FALSE,  
  useConditionEraGroupOverlap = FALSE,  
  useDrugExposure = FALSE,  
  useDrugEraStart = FALSE,  
  useDrugEraOverlap = FALSE,  
  useDrugEraGroupStart = FALSE,  
  useDrugEraGroupOverlap = FALSE,  
  useProcedureOccurrence = FALSE,  
  useDeviceExposure = FALSE,  
  useMeasurement = FALSE,  
  useMeasurementValue = FALSE,  
  useMeasurementRangeGroup = FALSE,  
  useObservation = FALSE,  
  useCharlsonIndex = FALSE,  
  useDcsi = FALSE,  
  useChads2 = FALSE,  
  useChads2Vasc = FALSE,  
  useHfrs = FALSE,  
  useDistinctConditionCount = FALSE,  
  useDistinctIngredientCount = FALSE,  
  useDistinctProcedureCount = FALSE,  
  useDistinctMeasurementCount = FALSE,  
  useDistinctObservationCount = FALSE,  
  useVisitCount = FALSE,  
  useVisitConceptCount = FALSE,
```

```

temporalStartDays = -365:-1,
temporalEndDays = -365:-1,
includedCovariateConceptIds = c(),
addDescendantsToInclude = FALSE,
excludedCovariateConceptIds = c(),
addDescendantsToExclude = FALSE,
includedCovariateIds = c()
)

```

Arguments

```

useDemographicsGender
    Gender of the subject. (analysis ID 1)
useDemographicsAge
    Age of the subject on the index date (in years). (analysis ID 2)
useDemographicsAgeGroup
    Age of the subject on the index date (in 5 year age groups) (analysis ID 3)
useDemographicsRace
    Race of the subject. (analysis ID 4)
useDemographicsEthnicity
    Ethnicity of the subject. (analysis ID 5)
useDemographicsIndexYear
    Year of the index date. (analysis ID 6)
useDemographicsIndexMonth
    Month of the index date. (analysis ID 7)
useDemographicsPriorObservationTime
    Number of days of observation time preceding the index date. (analysis ID 8)
useDemographicsPostObservationTime
    Number of days of observation time preceding the index date. (analysis ID 9)
useDemographicsTimeInCohort
    Number of days of observation time preceding the index date. (analysis ID 10)
useDemographicsIndexYearMonth
    Calendar month of the index date. (analysis ID 11)
useConditionOccurrence
    One covariate per condition in the condition_occurrence table starting in the
    time window. (analysis ID 101)
useConditionOccurrencePrimaryInpatient
    One covariate per condition observed as a primary diagnosis in an inpatient set-
    ting in the condition_occurrence table starting in the time window. (analysis ID
    102)
useConditionEraStart
    One covariate per condition in the condition_era table starting in the time win-
    dow. (analysis ID 201)
useConditionEraOverlap
    One covariate per condition in the condition_era table overlapping with any part
    of the time window. (analysis ID 202)
useConditionEraGroupStart
    One covariate per condition era rolled up to SNOMED groups in the condi-
    tion_era table starting in the time window. (analysis ID 203)

```


useConditionEraGroupOverlap	One covariate per condition era rolled up to SNOMED groups in the condition_era table overlapping with any part of the time window. (analysis ID 203)
useDrugExposure	One covariate per drug in the drug_exposure table starting in the time window. (analysis ID 301)
useDrugEraStart	One covariate per drug in the drug_era table starting in the time window. (analysis ID 401)
useDrugEraOverlap	One covariate per drug in the drug_era table overlapping with any part of the time window. (analysis ID 402)
useDrugEraGroupStart	One covariate per drug rolled up to ATC groups in the drug_era table starting in the time window. (analysis ID 403)
useDrugEraGroupOverlap	One covariate per drug rolled up to ATC groups in the drug_era table overlapping with any part of the time window. (analysis ID 403)
useProcedureOccurrence	One covariate per procedure in the procedure_occurrence table in the time window. (analysis ID 501)
useDeviceExposure	One covariate per device in the device exposure table starting in the time window. (analysis ID 601)
useMeasurement	One covariate per measurement in the measurement table in the time window. (analysis ID 701)
useMeasurementValue	One covariate containing the value per measurement-unit combination in the time window. If multiple values are found, the last is taken. (analysis ID 702)
useMeasurementRangeGroup	Covariates indicating whether measurements are below, within, or above normal range within the time period. (analysis ID 703)
useObservation	One covariate per observation in the observation table in the time window. (analysis ID 801)
useCharlsonIndex	The Charlson comorbidity index (Romano adaptation) using all conditions prior to the window end. (analysis ID 901)
useDcsi	The Diabetes Comorbidity Severity Index (DCSI) using all conditions prior to the window end. (analysis ID 902)
useChads2	The CHADS2 score using all conditions prior to the window end. (analysis ID 903)
useChads2Vasc	The CHADS2VAsC score using all conditions prior to the window end. (analysis ID 904)
useHfrs	The Hospital Frailty Risk Score score using all conditions prior to the window end. (analysis ID 926)
useDistinctConditionCount	The number of distinct condition concepts observed in the time window. (analysis ID 905)

Details

Value

Examples

[illegible]

```

useDemographicsPriorObservationTime = FALSE,
useDemographicsPostObservationTime = FALSE,
useDemographicsTimeInCohort = FALSE,
useDemographicsIndexYearMonth = FALSE,
useConditionOccurrence = FALSE,
useConditionOccurrencePrimaryInpatient = FALSE,
useConditionEraStart = FALSE,
useConditionEraOverlap = FALSE,
useConditionEraGroupStart = FALSE,
useConditionEraGroupOverlap = TRUE,
useDrugExposure = FALSE,
useDrugEraStart = FALSE,
useDrugEraOverlap = FALSE,
useDrugEraGroupStart = FALSE,
useDrugEraGroupOverlap = TRUE,
useProcedureOccurrence = TRUE,
useDeviceExposure = TRUE,
useMeasurement = TRUE,
useMeasurementValue = FALSE,
useMeasurementRangeGroup = TRUE,
useObservation = TRUE,
useCharlsonIndex = TRUE,
useDcsi = TRUE,
useChads2 = TRUE,
useChads2Vasc = TRUE,
useHfrs = FALSE,
useDistinctConditionCount = FALSE,
useDistinctIngredientCount = FALSE,
useDistinctProcedureCount = FALSE,
useDistinctMeasurementCount = FALSE,
useDistinctObservationCount = FALSE,
useVisitCount = FALSE,
useVisitConceptCount = FALSE,
temporalStartDays = -365:-1,
temporalEndDays = -365:-1,
includedCovariateConceptIds = c(),
addDescendantsToInclude = FALSE,
excludedCovariateConceptIds = c(),
addDescendantsToExclude = FALSE,
includedCovariateIds = c())

```

```
createTemporalSequenceCovariateSettings
```

Create covariate settings

Description

Create covariate settings

Usage

```

createTemporalSequenceCovariateSettings(
  useDemographicsGender = FALSE,

```

```

useDemographicsAge = FALSE,
useDemographicsAgeGroup = FALSE,
useDemographicsRace = FALSE,
useDemographicsEthnicity = FALSE,
useDemographicsIndexYear = FALSE,
useDemographicsIndexMonth = FALSE,
useConditionOccurrence = FALSE,
useConditionOccurrencePrimaryInpatient = FALSE,
useConditionEraStart = FALSE,
useConditionEraGroupStart = FALSE,
useDrugExposure = FALSE,
useDrugEraStart = FALSE,
useDrugEraGroupStart = FALSE,
useProcedureOccurrence = FALSE,
useDeviceExposure = FALSE,
useMeasurement = FALSE,
useMeasurementValue = FALSE,
useObservation = FALSE,
timePart = "month",
timeInterval = 1,
sequenceEndDay = -1,
sequenceStartDay = -730,
includedCovariateConceptIds = c(),
addDescendantsToInclude = FALSE,
excludedCovariateConceptIds = c(),
addDescendantsToExclude = FALSE,
includedCovariateIds = c()
)

```

Arguments

```

useDemographicsGender
    Gender of the subject. (analysis ID 1)
useDemographicsAge
    Age of the subject on the index date (in years). (analysis ID 2)
useDemographicsAgeGroup
    Age of the subject on the index date (in 5 year age groups) (analysis ID 3)
useDemographicsRace
    Race of the subject. (analysis ID 4)
useDemographicsEthnicity
    Ethnicity of the subject. (analysis ID 5)
useDemographicsIndexYear
    Year of the index date. (analysis ID 6)
useDemographicsIndexMonth
    Month of the index date. (analysis ID 7)
useConditionOccurrence
    One covariate per condition in the condition_occurrence table starting in the
    time window. (analysis ID 101)
useConditionOccurrencePrimaryInpatient
    One covariate per condition observed as a primary diagnosis in an inpatient set-
    ting in the condition_occurrence table starting in the time window. (analysis ID
    102)

```

useConditionEraStart	One covariate per condition in the condition_era table starting in the time window. (analysis ID 201)
useConditionEraGroupStart	One covariate per condition era rolled up to SNOMED groups in the condition_era table starting in the time window. (analysis ID 203)
useDrugExposure	One covariate per drug in the drug_exposure table starting in the time window. (analysis ID 301)
useDrugEraStart	One covariate per drug in the drug_era table starting in the time window. (analysis ID 401)
useDrugEraGroupStart	One covariate per drug rolled up to ATC groups in the drug_era table starting in the time window. (analysis ID 403)
useProcedureOccurrence	One covariate per procedure in the procedure_occurrence table in the time window. (analysis ID 501)
useDeviceExposure	One covariate per device in the device exposure table starting in the time window. (analysis ID 601)
useMeasurement	One covariate per measurement in the measurement table in the time window. (analysis ID 701)
useMeasurementValue	One covariate containing the value per measurement-unit combination in the time window. If multiple values are found, the last is taken. (analysis ID 702)
useObservation	One covariate per observation in the observation table in the time window. (analysis ID 801)
timePart	The interval scale ('DAY', 'MONTH', 'YEAR')
timeInterval	Fixed interval length for timeId using the 'timePart' scale. For example, a 'timePart' of DAY with 'timeInterval' 30 has timeIds where timeId 1 is day 0 to day 29, timeId 2 is day 30 to day 59, etc.
sequenceEndDay	What is the end day (relative to the index date) of the data extraction?
sequenceStartDay	What is the start day (relative to the index date) of the data extraction?
includedCovariateConceptIds	A list of concept IDs that should be used to construct covariates.
addDescendantsToInclude	Should descendant concept IDs be added to the list of concepts to include?
excludedCovariateConceptIds	A list of concept IDs that should NOT be used to construct covariates.
addDescendantsToExclude	Should descendant concept IDs be added to the list of concepts to exclude?
includedCovariateIds	A list of covariate IDs that should be restricted to.

Details

creates an object specifying how covariates should be constructed from data in the CDM model.

Value

An object of type covariateSettings, to be used in other functions.

Examples

```
settings <- createTemporalSequenceCovariateSettings(useDemographicsGender = TRUE,
                                                    useDemographicsAge = FALSE,
                                                    useDemographicsAgeGroup = TRUE,
                                                    useDemographicsRace = TRUE,
                                                    useDemographicsEthnicity = TRUE,
                                                    useDemographicsIndexYear = TRUE,
                                                    useDemographicsIndexMonth = TRUE,
                                                    useConditionOccurrence = FALSE,
                                                    useConditionOccurrencePrimaryInpatient = FALSE,
                                                    useConditionEraStart = FALSE,
                                                    useConditionEraGroupStart = FALSE,
                                                    useDrugExposure = FALSE,
                                                    useDrugEraStart = FALSE,
                                                    useDrugEraGroupStart = FALSE,
                                                    useProcedureOccurrence = TRUE,
                                                    useDeviceExposure = TRUE,
                                                    useMeasurement = TRUE,
                                                    useMeasurementValue = FALSE,
                                                    useObservation = TRUE,
                                                    timePart = 'DAY',
                                                    timeInterval = 1,
                                                    sequenceEndDay = -1,
                                                    sequenceStartDay = -730,
                                                    includedCovariateConceptIds = c(),
                                                    addDescendantsToInclude = FALSE,
                                                    excludedCovariateConceptIds = c(),
                                                    addDescendantsToExclude = FALSE,
                                                    includedCovariateIds = c())
```

filterByCohortDefinitionId

Filter covariates by cohort definition ID

Description

Filter covariates by cohort definition ID

Usage

```
filterByCohortDefinitionId(covariateData, cohortId)
```

Arguments

covariateData An object of type CovariateData
 cohortId The cohort definition ID to keep.

Value

An object of type covariateData.

filterByRowId	<i>Filter covariates by row ID</i>
---------------	------------------------------------

Description

Filter covariates by row ID

Usage

```
filterByRowId(covariateData, rowIds)
```

Arguments

covariateData	An object of type CovariateData
rowIds	A vector containing the rowIds to keep.

Value

An object of type covariateData.

getDbCohortAttrCovariatesData	<i>Getcovariate information from the database through the cohort_attribute table</i>
-------------------------------	--

Description

Constructs covariates using the cohort_attribute table.

Usage

```
getDbCohortAttrCovariatesData(
  connection,
  oracleTempSchema = NULL,
  cdmDatabaseSchema,
  cohortTable = "#cohort_person",
  cohortId = -1,
  cdmVersion = "5",
  rowIdField = "subject_id",
  covariateSettings,
  aggregated = FALSE
)
```

Arguments

connection	A connection to the server containing the schema as created using the connect function in the DatabaseConnector package.
oracleTempSchema	A schema where temp tables can be created in Oracle.
cdmDatabaseSchema	The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm_instance.dbo'.
cohortTable	Name of the table holding the cohort for which we want to construct covariates. If it is a temp table, the name should have a hash prefix, e.g. '#temp_table'. If it is a non-temp table, it should include the database schema, e.g. 'cdm_database.cohort'.
cohortId	For which cohort ID should covariates be constructed? If set to -1, covariates will be constructed for all cohorts in the specified cohort table.
cdmVersion	The version of the Common Data Model used. Currently only cdmVersion = "5" is supported.
rowIdField	The name of the field in the cohort temp table that is to be used as the row_id field in the output table. This can be especially usefull if there is more than one period per person.
covariateSettings	An object of type covariateSettings as created using the createCohortAttrCovariateSettings function.
aggregated	Should aggregate statistics be computed instead of covariates per cohort entry?

Details

This function uses the data in the CDM to construct a large set of covariates for the provided cohort. The cohort is assumed to be in an existing temp table with these fields: 'subject_id', 'cohort_definition_id', 'cohort_start_date'. Optionally, an extra field can be added containing the unique identifier that will be used as rowID in the output. Typically, users don't call this function directly but rather use the [getDbCovariateData](#) function instead.

Value

Returns an object of type CovariateData, which is an Andromeda object containing information on the baseline covariates. Information about multiple outcomes can be captured at once for efficiency reasons. This object is a list with the following components:

covariates An ffdF object listing the baseline covariates per person in the cohorts. This is done using a sparse representation: covariates with a value of 0 are omitted to save space. The covariates object will have three columns: rowId, covariateId, and covariateValue. The rowId is usually equal to the person_id, unless specified otherwise in the rowIdField argument.

covariateRef A table describing the covariates that have been extracted.

. The CovariateData object will also have a metaData attribute, a list of objects with information on how the covariateData object was constructed.

getDbCovariateData	<i>Get covariate information from the database</i>
--------------------	--

Description

Uses one or several covariate builder functions to construct covariates.

Usage

```
getDbCovariateData(
  connectionDetails = NULL,
  connection = NULL,
  oracleTempSchema = NULL,
  cdmDatabaseSchema,
  cdmVersion = "5",
  cohortTable = "cohort",
  cohortDatabaseSchema = cdmDatabaseSchema,
  cohortTableIsTemp = FALSE,
  cohortId = -1,
  rowIdField = "subject_id",
  covariateSettings,
  aggregated = FALSE
)
```

Arguments

connectionDetails	An R object of type connectionDetails created using the function createConnectionDetails in the DatabaseConnector package. Either the connection or connectionDetails argument should be specified.
connection	A connection to the server containing the schema as created using the connect function in the DatabaseConnector package. Either the connection or connectionDetails argument should be specified.
oracleTempSchema	A schema where temp tables can be created in Oracle.
cdmDatabaseSchema	The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm_instance.dbo'.
cdmVersion	Define the OMOP CDM version used: currently supported is "5".
cohortTable	Name of the (temp) table holding the cohort for which we want to construct covariates
cohortDatabaseSchema	If the cohort table is not a temp table, specify the database schema where the cohort table can be found. On SQL Server, this should specify both the database and the schema, so for example 'cdm_instance.dbo'.
cohortTableIsTemp	Is the cohort table a temp table?
cohortId	For which cohort ID(s) should covariates be constructed? If set to -1, covariates will be constructed for all cohorts in the specified cohort table.

rowIdField	The name of the field in the cohort table that is to be used as the row_id field in the output table. This can be especially usefull if there is more than one period per person.
covariateSettings	Either an object of type covariateSettings as created using one of the create-Covariate functions, or a list of such objects.
aggregated	Should aggregate statistics be computed instead of covariates per cohort entry?

Details

This function uses the data in the CDM to construct a large set of covariates for the provided cohort. The cohort is assumed to be in an existing table with these fields: 'subject_id', 'cohort_definition_id', 'cohort_start_date'. Optionally, an extra field can be added containing the unique identifier that will be used as rowID in the output.

Value

Returns an object of type covariateData, containing information on the covariates.

getDbDefaultCovariateData

Get default covariate information from the database

Description

Constructs a large default set of covariates for one or more cohorts using data in the CDM schema. Includes covariates for all drugs, drug classes, condition, condition classes, procedures, observations, etc.

Usage

```
getDbDefaultCovariateData(
  connection,
  oracleTempSchema = NULL,
  cdmDatabaseSchema,
  cohortTable = "#cohort_person",
  cohortId = -1,
  cdmVersion = "5",
  rowIdField = "subject_id",
  covariateSettings,
  targetDatabaseSchema,
  targetCovariateTable,
  targetCovariateRefTable,
  targetAnalysisRefTable,
  aggregated = FALSE
)
```

Arguments

connection	A connection to the server containing the schema as created using the connect function in the DatabaseConnector package.
oracleTempSchema	A schema where temp tables can be created in Oracle.
cdmDatabaseSchema	The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm_instance.dbo'.
cohortTable	Name of the table holding the cohort for which we want to construct covariates. If it is a temp table, the name should have a hash prefix, e.g. '#temp_table'. If it is a non-temp table, it should include the database schema, e.g. 'cdm_database.cohort'.
cohortId	For which cohort ID should covariates be constructed? If set to -1, covariates will be constructed for all cohorts in the specified cohort table.
cdmVersion	The version of the Common Data Model used. Currently only cdmVersion = "5" is supported.
rowIdField	The name of the field in the cohort temp table that is to be used as the row_id field in the output table. This can be especially useful if there is more than one period per person.
covariateSettings	Either an object of type covariateSettings as created using one of the createCovariate functions, or a list of such objects.
targetDatabaseSchema	(Optional) The name of the database schema where the resulting covariates should be stored.
targetCovariateTable	(Optional) The name of the table where the resulting covariates will be stored. If not provided, results will be fetched to R. The table can be a permanent table in the targetDatabaseSchema or a temp table. If it is a temp table, do not specify targetDatabaseSchema.
targetCovariateRefTable	(Optional) The name of the table where the covariate reference will be stored.
targetAnalysisRefTable	(Optional) The name of the table where the analysis reference will be stored.
aggregated	Should aggregate statistics be computed instead of covariates per cohort entry?

Details

This function uses the data in the CDM to construct a large set of covariates for the provided cohort. The cohort is assumed to be in an existing temp table with these fields: 'subject_id', 'cohort_definition_id', 'cohort_start_date'. Optionally, an extra field can be added containing the unique identifier that will be used as rowID in the output. Typically, users don't call this function directly but rather use the [getDbCovariateData](#) function instead.

Value

Returns an object of type CovariateData, which is an Andromeda object containing information on the baseline covariates. Information about multiple outcomes can be captured at once for efficiency reasons. This object is a list with the following components:

covariates An ffdF object listing the baseline covariates per person in the cohorts. This is done using a sparse representation: covariates with a value of 0 are omitted to save space. The covariates object will have three columns: rowId, covariateId, and covariateValue. The rowId is usually equal to the person_id, unless specified otherwise in the rowIdField argument.

covariateRef A table describing the covariates that have been extracted.

. The CovariateData object will also have a metaData attribute, a list of objects with information on how the covariateData object was constructed.

```
getDefaultTable1Specifications
```

Get the default table 1 specifications

Description

Loads the default specifications for a table 1, to be used with the [createTable1](#) function.

Usage

```
getDefaultTable1Specifications()
```

Value

A specifications objects.

```
isAggregatedCovariateData
```

Check whether covariate data is aggregated

Description

Check whether covariate data is aggregated

Usage

```
isAggregatedCovariateData(x)
```

Arguments

x The covariate data object to check.

Value

A logical value.

isCovariateData	<i>Check whether an object is a CovariateData object</i>
-----------------	--

Description

Check whether an object is a CovariateData object

Usage

```
isCovariateData(x)
```

Arguments

x	The object to check.
---	----------------------

Value

A logical value.

isTemporalCovariateData	<i>Check whether covariate data is temporal</i>
-------------------------	---

Description

Check whether covariate data is temporal

Usage

```
isTemporalCovariateData(x)
```

Arguments

x	The covariate data object to check.
---	-------------------------------------

Value

A logical value.

loadCovariateData	<i>Load the covariate data from a folder</i>
-------------------	--

Description

loadCovariateData loads an object of type covariateData from a folder in the file system.

Usage

```
loadCovariateData(file, readOnly)
```

Arguments

file	The name of the folder containing the data.
readOnly	DEPRECATED: If true, the data is opened read only.

Details

The data will be written to a set of files in the folder specified by the user.

Value

An object of class CovariateData.

Examples

```
# todo
```

saveCovariateData	<i>Save the covariate data to folder</i>
-------------------	--

Description

saveCovariateData saves an object of type covariateData to folder.

Usage

```
saveCovariateData(covariateData, file)
```

Arguments

covariateData	An object of type covariateData as generated using getDbCovariateData.
file	The name of the folder where the data will be written. The folder should not yet exist.

Details

The data will be written to a set of files in the folder specified by the user.

Examples

```
# todo
```

tidyCovariateData	<i>Tidy covariate data</i>
-------------------	----------------------------

Description

Tidy covariate data

Usage

```
tidyCovariateData(  
  covariateData,  
  minFraction = 0.001,  
  normalize = TRUE,  
  removeRedundancy = TRUE  
)
```

Arguments

covariateData	An object as generated using the getDbCovariateData function.
minFraction	Minimum fraction of the population that should have a non-zero value for a covariate for that covariate to be kept. Set to 0 to don't filter on frequency.
normalize	Normalize the covariates? (dividing by the max).
removeRedundancy	Should redundant covariates be removed?

Details

Normalize covariate values by dividing by the max and/or remove redundant covariates and/or remove infrequent covariates. For temporal covariates, redundancy is evaluated per time ID.

Index

aggregateCovariates, [2](#)
Andromeda, [4](#)

computeStandardizedDifference, [3](#)
convertPrespecSettingsToDetailedSettings,
[3](#)
CovariateData (CovariateData-class), [4](#)
CovariateData-class, [4](#)
createAnalysisDetails, [4](#), [19](#), [20](#)
createCohortAttrCovariateSettings, [6](#),
[32](#)
createCovariateSettings, [3](#), [7](#)
createDefaultCovariateSettings, [18](#)
createDefaultTemporalCovariateSettings,
[19](#)
createDetailedCovariateSettings, [5](#), [19](#)
createDetailedTemporalCovariateSettings,
[5](#), [20](#)
createTable1, [21](#), [22](#), [36](#)
createTable1CovariateSettings, [22](#)
createTemporalCovariateSettings, [23](#)
createTemporalSequenceCovariateSettings,
[27](#)

filterByCohortDefinitionId, [30](#)
filterByRowId, [31](#)

getDbCohortAttrCovariatesData, [31](#)
getDbCovariateData, [4](#), [22](#), [32](#), [33](#), [35](#), [39](#)
getDbDefaultCovariateData, [34](#)
getDefaultTable1Specifications, [36](#)

isAggregatedCovariateData, [4](#), [36](#)
isCovariateData, [4](#), [37](#)
isTemporalCovariateData, [4](#), [37](#)

loadCovariateData, [4](#), [38](#)

saveCovariateData, [4](#), [38](#)
show, CovariateData-method
(CovariateData-class), [4](#)
summary, CovariateData-method
(CovariateData-class), [4](#)

tidyCovariateData, [39](#)