

Contents

1	Exercise 1	1
2	Exercise 2	2
3	Exercise 3	4
4	Exercise 4	6
5	Exercise 5	8

1 Exercise 1

Objective: Find sales made in specific locations with certain conditions on customers and items.

```
db.sales.find(
{
  // Filtros
  storeLocation: {
    // Condition: sales made in "London", "Austin" or "San Diego"
    $in: ['London', 'Austin', 'San Diego']
  },
  'customer.age': {
    // Condition: customer age greater than or equal to 18
    $gte: 18
  },
  items: {
    // Condition: items must have a price of at least 1000 and be tagged as "school" or "kids"
    $elemMatch: {
      price: {
        $type: 'number',
        $gte: 1000
      },
      $or: [
        {
          tags: 'school'
        },
        {
          tags: 'kids'
        }
      ]
    }
  }
})
```

```

    }
  }
},
{
  // Proyección
  _id: 0,
  sale: '$_id',
  saleDate: 1,
  storeLocation: 1,
  customer_email: '$customer.email',
  age: '$customer.age',
  items: '$items'
}
);

```

Explanation:

- `db.sales.find(...)`: This is a MongoDB query to find documents in the `sales` collection.
- The first argument is the query filter:
 - `storeLocation: { $in: [...] }`: Filters sales to only include those made in “London”, “Austin”, or “San Diego”.
 - `'customer.age': { $gte: 18 }`: Filters to include only customers who are 18 years old or older.
 - `items: { $elemMatch: {...} }`: This checks that at least one item in the `items` array meets the specified conditions:
 - * `price: { $type: 'number', $gte: 1000 }`: The item’s price must be a number and at least 1000.
 - * `$or: [...]`: The item must have a tag of either “school” or “kids”.
- The second argument is the projection:
 - `_id: 0`: Excludes the default `_id` field from the results.
 - `sale: '$_id'`: Renames the `_id` field to `sale`.
 - `saleDate: 1`: Includes the `saleDate` field.
 - `storeLocation: 1`: Includes the `storeLocation` field.
 - `customer_email: '$customer.email'`: Renames the customer’s email field.
 - `age: '$customer.age'`: Includes the customer’s age.
 - `items: '$items'`: Includes the `items` array.

2 Exercise 2

Objective: Find sales in Seattle with specific purchase methods and date range, and calculate total amounts.

```

db.sales.aggregate([
  {
    // Filtros
    $match: {
      // Condition: sales from stores located in Seattle
      storeLocation: 'Seattle',
      // Condition: purchase method is 'In store' or 'Phone'
      purchaseMethod: {
        $in: ['In store', 'Phone']
      },
      // Condition: sales made between 1st February 2014 and 31st January 2015
      saleDate: {
        $gte: new Date('2014-02-01'),
        $lte: new Date('2015-01-31')
      }
    }
  },
  {
    // Unwind items to process each item individually
    $unwind: '$items'
  },
  {
    // Grouping to calculate total sales
    $group: {
      _id: {
        sale_id: '$_id',
        email: '$customer.email',
        satisfaction: '$customer.satisfaction'
      },
      total: {
        // Calculate total price * quantity for each item
        $sum: {
          $multiply: [
            { $toDouble: '$items.price' },
            { $toDouble: '$items.quantity' }
          ]
        }
      }
    }
  },
  {
    // Proyección
    $project: {
      _id: 0,

```

```

        email: '$_id.email',
        satisfaction: '$_id.satisfaction',
        total: 1
    }
},
{
    // Sort by satisfaction (descending) and email (alphabetical)
    $sort: {
        satisfaction: -1,
        email: 1
    }
}
]);

```

Explanation:

- `db.sales.aggregate([...])`: This is a MongoDB aggregation pipeline to process documents in the `sales` collection.
- `$match`: Filters documents based on specified conditions.
- `$unwind`: Deconstructs the `items` array, creating a separate document for each item.
- `$group`: Groups documents by sale ID, email, and satisfaction, calculating the total amount for each sale.
- `$project`: Restructures the output documents to include only the specified fields.
- `$sort`: Sorts the results first by satisfaction in descending order and then by email in ascending order.

3 Exercise 3

Objective: Create a view that calculates sales statistics by year and month.

```

salesInvoicedPipeline = [
    {
        // Unwind items to process each item individually
        $unwind: '$items'
    },
    {
        // Grouping to calculate total sales
        $group: {
            _id: {
                sale_id: '$_id',
                year: { $year: '$saleDate' },
                month: { $month: '$saleDate' }
            }
        }
    }
];

```

```

    },
    total: {
      $sum: {
        $multiply: [
          { $toDouble: '$items.price' },
          { $toDouble: '$items.quantity' }
        ]
      }
    }
  }
},
{
  // Grouping by year and month to calculate statistics
  $group: {
    _id: {
      year: '$_id.year',
      month: '$_id.month'
    },
    min: { $min: '$total' },
    max: { $max: '$total' },
    total: { $sum: '$total' },
    average: { $avg: '$total' }
  }
},
{
  // Proyección
  $project: {
    _id: 0,
    year: '$_id.year',
    month: '$_id.month',
    min: 1,
    max: 1,
    total: 1,
    average: 1
  }
},
{
  // Sort by chronological order
  $sort: {
    year: 1,
    month: 1
  }
}
];

```

```
// Create the view
db.createView('salesInvoiced', 'sales', salesInvoicedPipeline);
```

Explanation:

- `salesInvoicedPipeline`: Defines the aggregation pipeline for creating the view.
- `$unwind`: Deconstructs the `items` array.
- `$group`: First groups by sale ID, year, and month to calculate total sales for each sale.
- The second `$group` aggregates the results by year and month, calculating minimum, maximum, total, and average sales.
- `$project`: Restructures the output to include only the relevant fields.
- `$sort`: Sorts the results chronologically.
- `db.createView(...)`: Creates a view named `salesInvoiced` based on the defined pipeline.

4 Exercise 4

Objective: Show store location, average sales, objectives, and differences.

```
db.storeObjectives.aggregate(
{
  // Join with sales data
  $lookup: {
    from: 'sales',
    localField: '_id',
    foreignField: 'storeLocation',
    as: 'store_info',
    pipeline: [
      {
        // Unwind items
        $unwind: '$items'
      },
      {
        // Group to calculate total sales
        $group: {
          _id: {
            sale_id: '$_id',
            storeLocation: '$storeLocation'
          },
          total: {
            $sum: {
              $multiply: [
```

```

        { $toDouble: '$items.price' },
        { $toDouble: '$items.quantity' }
      ]
    }
  }
},
{
  // Calculate average sales per store
  $group: {
    _id: '$storeLocation',
    average: { $avg: '$total' }
  }
}
]
}
},
{
  // Set to get the first element of store_info
  $set: {
    store_info: {
      $first: '$store_info'
    }
  }
},
{
  // Proyección
  $project: {
    _id: 0,
    storeLocation: '$_id',
    average_sales: '$store_info.average',
    objective: 1,
    difference: {
      // Calculate difference between average and objective
      $subtract: [
        { $toDouble: '$store_info.average' },
        { $toDouble: '$objective' }
      ]
    }
  }
}
}
);

```

Explanation:

- `db.storeObjectives.aggregate(...)`: Aggregates data from the `storeObjectives` collection.
- `$lookup`: Joins the `sales` collection based on store location.
- The inner pipeline unwinds the `items`, groups by store location, and calculates total sales.
- The outer pipeline sets the first element of `store_info` and projects the desired fields.
- The `difference` field calculates the difference between average sales and the objective.

5 Exercise 5

Objective: Specify validation rules for the `sales` collection using JSON Schema.

```
db.runCommand({
  collMod: 'sales',
  validator: {
    $jsonSchema: {
      bsonType: 'object',
      required: [
        'saleDate',
        'storeLocation',
        'purchaseMethod',
        'customer',
        'items'
      ],
      properties: {
        saleDate: {
          bsonType: 'date'
        },
        storeLocation: {
          bsonType: 'string',
          enum: [
            'London',
            'New York',
            'Denver',
            'San Diego',
            'Austin',
            'Seattle'
          ]
        },
        purchaseMethod: {
          bsonType: 'string',
```



```

    enum: [
      'Online',
      'Phone',
      'In store'
    ]
  },
  customer: {
    bsonType: 'object',
    required: [
      'gender',
      'age',
      'email',
      'satisfaction'
    ],
    properties: {
      gender: {
        bsonType: 'string',
        enum: [
          'M',
          'F'
        ]
      },
      age: {
        bsonType: 'int',
        minimum: 0,
        maximum: 200
      },
      email: {
        bsonType: 'string',
        pattern: '^(.*)@(.*)\\.(.{2,4})$'
      },
      satisfaction: {
        bsonType: 'int',
        minimum: 1,
        maximum: 5
      }
    }
  },
  items: {
    bsonType: 'array',
    minLength: 1,
    required: [
      'name',
      'price',

```

```

        'quantity'
    ],
    properties: {
        name: {
            bsonType: 'string'
        },
        tags: {
            bsonType: ['string'],
        },
        price: {
            bsonType: 'double',
            minimum: 0
        },
        quantity: {
            bsonType: 'int',
            minimum: 1
        }
    }
},
couponUsed: {
    bsonType: 'bool'
}
}
}
});

```

Explanation:

- `db.runCommand(...)`: Executes a command to modify the `sales` collection.
- `validator`: Specifies the validation rules using JSON Schema.
- `bsonType`: Defines the expected data type for each field.
- `required`: Lists fields that must be present in each document.
- `enum`: Restricts the values for certain fields to a predefined list.
- `pattern`: Uses a regex pattern to validate the format of the email.
- `minimum` and `maximum`: Sets constraints on numerical fields.
- `minLength`: Ensures that the `items` array contains at least one item. `### Test Cases for Validation Case A: Successful insertion`

```

db.sales.insertOne({
    saleDate: new Date('2023-11-17'),
    items: [
        {
            name: "printer paper",

```

```

        tags: [
            "office",
            "stationary"
        ],
        price: 40.01,
        quantity: 2
    }
],
storeLocation: 'London',
customer: {
    gender: "M",
    age: 20,
    email: "emanuelherrador2@gmail.com",
    satisfaction: 5
},
couponUsed: false,
purchaseMethod: 'Online'
});

```

Case B: Failed insertion (missing items)

```

db.sales.insertOne({
    saleDate: new Date('2023-11-17'),
    storeLocation: 'London',
    customer: {
        gender: "M",
        age: 20,
        email: "emanuelherrador2@gmail.com",
        satisfaction: 5
    },
    couponUsed: false,
    purchaseMethod: 'Online'
});

```

Explanation:

- The first case is successful because it meets all validation criteria.
- The second case fails because it does not include any items, violating the `minLength` requirement for the `items` array. This detailed breakdown covers the purpose and functionality of each part of the code, providing a comprehensive understanding of the MongoDB operations involved.